



FCC TEST REPORT

(15.407)

REPORT NO.: RF150123C26

MODEL NO.: CPA-57020-V1

FCC ID: Q5A-SMAC-CPA57020

RECEIVED: Jan. 23, 2015

TESTED: Jan. 27 ~ Jan. 28, 2015

ISSUED: Feb. 05, 2015

APPLICANT: Sify Technologies Ltd.

ADDRESS: II floor, TIDEL Park, 4, Rajiv Gandhi Salai,
Tharamani, Chennai – 600113

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3 DUTY CYCLE OF TEST SIGNAL	11
3.4 DESCRIPTION OF SUPPORT UNITS	12
3.4.1 CONFIGURATION OF SYSTEM UNDER TEST	12
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	13
4. TEST TYPES AND RESULTS	14
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT	14
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	14
4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS	14
4.1.3 TEST INSTRUMENTS	15
4.1.4 TEST PROCEDURES	16
4.1.5 DEVIATION FROM TEST STANDARD	16
4.1.6 TEST SETUP	17
4.1.7 EUT OPERATING CONDITION	18
4.1.8 TEST RESULTS	19
4.2 CONDUCTED EMISSION MEASUREMENT	28
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	28
4.2.2 TEST INSTRUMENTS	28
4.2.3 TEST PROCEDURES	29
4.2.4 DEVIATION FROM TEST STANDARD	29
4.2.5 TEST SETUP	29
4.2.6 EUT OPERATING CONDITIONS	29
4.2.7 TEST RESULTS	30
4.3 TRANSMIT POWER MEASUREMENT	32
4.3.1 LIMITS OF TRANSMIT POWER MEASUREMENT	32
4.3.2 TEST SETUP	32
4.3.3 TEST INSTRUMENTS	32
4.3.4 TEST PROCEDURE	33
4.3.5 DEVIATION FROM TEST STANDARD	33
4.3.6 EUT OPERATING CONDITIONS	33
4.3.7 TEST RESULTS	34
4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT	35
4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT	35
4.4.2 TEST SETUP	35
4.4.3 TEST INSTRUMENTS	35
4.4.4 TEST PROCEDURES	35
4.4.5 DEVIATION FROM TEST STANDARD	36
4.4.6 EUT OPERATING CONDITIONS	36
4.4.7 TEST RESULTS	37
4.5 FREQUENCY STABILITY	39
4.5.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	39
4.5.2 TEST SETUP	39
4.5.3 TEST INSTRUMENTS	39



A D T

4.5.4	TEST PROCEDURE.....	40
4.5.5	DEVIATION FROM TEST STANDARD	40
4.5.6	EUT OPERATING CONDITION.....	40
4.5.7	TEST RESULTS	41
4.6	6dB BANDWIDTH MEASUREMENT.....	42
4.6.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	42
4.6.2	TEST SETUP.....	42
4.6.3	TEST INSTRUMENTS.....	42
4.6.4	TEST PROCEDURE.....	42
4.6.5	DEVIATION FROM TEST STANDARD	42
4.6.6	EUT OPERATING CONDITIONS	42
4.6.7	TEST RESULTS	43
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	45
6.	INFORMATION ON THE TESTING LABORATORIES	46
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	47



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150123C26	Original release	Feb. 05, 2015



A D T

1. CERTIFICATION

PRODUCT: Wireless device

MODEL: CPA-57020-V1

BRAND: Sify

APPLICANT: Sify Technologies Ltd.

TESTED: Jan. 27 ~ Jan. 28, 2015

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart E (Section 15.407)

The above equipment (model: CPA-57020-V1) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chou , **DATE :** Feb. 05, 2015
Celine Chou / Specialist

APPROVED BY : Ken Liu , **DATE :** Feb. 05, 2015
Ken Liu / Senior Manager



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E (SECTION 15.407 UNDER NEW RULE)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.407(b)(6)	AC Power Conducted Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -12.63dB at 0.38047MHz.
15.407(b) (1/2/3/4/6)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -1.2dB at 5440.00MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(1/2/3)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(e)	6dB bandwidth	PASS	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is MMCX not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.63 dB
	200MHz ~1000MHz	3.64 dB
	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Wireless device
MODEL NO.	CPA-57020-V1
POWER SUPPLY	24Vdc (POE)
MODULATION TYPE	64QAM, 16QAM, QPSK, BPSK
MODULATION TECHNOLOGY	OFDM
TRANSFER RATE	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 150Mbps
OPERATING FREQUENCY	5745 ~ 5825MHz
NUMBER OF CHANNEL	5 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz)
OUTPUT POWER	35.975mW
ANTENNA TYPE	Patch antenna with 18dBi gain
ANTENNA CONNECTOR	MMCX
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	POE, 1.8m non-shielded ground cable without core

NOTE:

1. The EUT provides 1 completed transmitter and 1 receiver.

MODULATION MODE	TX FUNCTION
802.11a	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

2. The EUT uses following POE.

BRAND:	Powertron
MODEL:	PA1022-3T3
INPUT:	100-240Vac, 50-60Hz, 0.6A
OUTPUT:	24Vdc, 1.0A
POWER LINE:	1.8m non-shielded cable without core

3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

5 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz



A D T

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6.0
-	802.11n (20MHz)		149 to 165	149, 157, 165	OFDM	BPSK	6.5
-	802.11n (40MHz)		151 to 159	151, 159	OFDM	BPSK	13.5

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	5745-5825	149 to 165	149	OFDM	BPSK	6.0

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	5745-5825	149 to 165	149	OFDM	BPSK	6.0



A D T

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6.0
-	802.11n (20MHz)		149 to 165	149, 157, 165	OFDM	BPSK	6.5
-	802.11n (40MHz)		151 to 159	151, 159	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE \geq 1G	25deg. C, 65%RH	120Vac, 60Hz	Ted Chang
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Ted Chang
PLC	25deg. C, 65%RH	120Vac, 60Hz	Ted Chang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Ted Chang


3.3 DUTY CYCLE OF TEST SIGNAL

Duty cycle of test signal is < 98%, duty factor shall be considered.

802.11a: Duty cycle = $1.348/1.403 = 0.961$, Duty factor = $10 * \log(1/0.961) = 0.17$

802.11n (20MHz): Duty cycle = $1.268/1.320 = 0.961$, Duty factor = $10 * \log(1/0.961) = 0.17$

802.11n (40MHz): Duty cycle = $0.630/0.664 = 0.949$, Duty factor = $10 * \log(1/0.949) = 0.23$



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.



NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	E5420	BPQ8MQ1	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	3m RJ45 Cable and 1.8m RJ45 Cable

NOTE:

1. All power cords of the above support units are non-shielded (1.8 m).
2. Item 1 acted as a communication partner to transfer data.

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST





A D T

3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

789033 D02 General UNII Test Procedures New Rules v01

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

APPLICABLE TO	LIMIT	
789033 D02 General UNII Test Procedures New Rules v01	FIELD STRENGTH AT 3m	
	PK: 74 (dB μ V/m)	AV: 54 (dB μ V/m)
APPLICABLE TO	EIRP LIMIT	EQUIVALENT FIELD STRENGTH AT 3m
15.407(b)(1)	PK: -27 (dBm/MHz)	PK: 68.2 (dB μ V/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)	PK: -27 (dBm/MHz) ^{*1} PK: -17 (dBm/MHz) ^{*2}	PK: 68.2 (dB μ V/m) ^{*1} PK: 78.2 (dB μ V/m) ^{*2}

NOTE: ^{*1} beyond 10MHz of the band edge ^{*2} within 10 MHz of band edge

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts).}$$



4.1.3 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Dec. 01, 2014	Nov. 30, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Feb. 11, 2014	Feb. 10, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-156	Feb. 25, 2014	Feb. 24, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-209	Aug. 25, 2014	Aug. 24, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Feb. 17, 2014	Feb. 16, 2015
Preamplifier Agilent	8449B	3008A01911	Aug. 09, 2014	Aug. 08, 2015
Preamplifier Agilent	8447D	2944A10638	Aug. 09, 2014	Aug. 08, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	248780/4 309222/4 274092/4	Aug. 09, 2014	Aug. 08, 2015
RF signal cable Worken	8D-FB	Cable-CH9-01	Aug. 11, 2014	Aug. 10, 2015
Software BV ADT	ADT_Radiated_V7.6.15.9.4	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn Table Controller EMCO	2090	NA	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 18, 2014	Oct. 17, 2015
High Speed Peak Power Meter	ML2495A	0824011	Jul. 26, 2014	Jul. 25, 2015
Power Sensor	MA2411B	0738171	Jul. 26, 2014	Jul. 25, 2015
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 09, 2014	Jun. 08, 2015

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 9.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 215374.
5. The IC Site Registration No. is IC 7450F-9.



4.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz(Duty cycle $> 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.5 DEVIATION FROM TEST STANDARD


No deviation.

4.1.6 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

4.1.7 EUT OPERATING CONDITION

- a. Placed the EUT on the testing table.
- b. Prepared the notebook to act as a communication partner and placed it outside of testing area.
- c. The communication partner connected with EUT via a RJ45 cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- d. The communication partner sent data to EUT by command "PING".



A D T

4.1.8 TEST RESULTS

ABOVE 1GHz DATA

802.11a

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 40GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	57.5 PK	74.0	-16.5	1.20 H	40	55.40	2.10
2	5440.00	43.5 AV	54.0	-10.5	1.20 H	40	41.40	2.10
3	#5665.00	57.0 PK	74.0	-17.0	1.20 H	40	54.60	2.40
4	#5665.00	43.3 AV	54.0	-10.7	1.20 H	40	40.90	2.40
5	#5714.90	56.7 PK	74.0	-17.3	1.20 H	40	54.10	2.60
6	#5714.90	42.9 AV	54.0	-11.1	1.20 H	40	40.30	2.60
7	#5722.90	59.4 PK	78.2	-18.8	1.20 H	40	56.80	2.60
8	#5725.00	47.6 PK	78.2	-30.6	1.20 H	40	45.00	2.60
9	*5745.00	101.7 PK			1.20 H	40	60.70	41.00
10	*5745.00	91.0 AV			1.20 H	40	50.00	41.00
11	11490.00	61.1 PK	74.0	-12.9	1.02 H	95	45.20	15.90
12	11490.00	48.1 AV	54.0	-5.9	1.02 H	95	32.20	15.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	65.3 PK	74.0	-8.7	1.04 V	11	63.20	2.10
2	5440.00	52.7 AV	54.0	-1.3	1.04 V	11	50.60	2.10
3	#5665.00	63.7 PK	74.0	-10.3	1.00 V	11	61.30	2.40
4	#5665.00	50.7 AV	54.0	-3.3	1.00 V	11	48.30	2.40
5	#5714.90	65.5 PK	74.0	-8.5	1.07 V	10	62.90	2.60
6	#5714.90	49.2 AV	54.0	-4.8	1.07 V	10	46.60	2.60
7	#5722.90	74.1 PK	78.2	-4.1	1.07 V	10	71.50	2.60
8	#5725.00	61.8 PK	78.2	-16.4	1.00 V	10	59.20	2.60
9	*5745.00	116.7 PK			1.06 V	10	75.70	41.00
10	*5745.00	105.9 AV			1.06 V	10	64.90	41.00
11	11490.00	61.1 PK	74.0	-12.9	1.05 V	64	45.20	15.90
12	11490.00	48.4 AV	54.0	-5.6	1.05 V	64	32.50	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	55.9 PK	74.0	-18.1	1.01 H	81	53.80	2.10
2	5440.00	43.5 AV	54.0	-10.5	1.01 H	81	41.40	2.10
3	#5705.00	57.5 PK	74.0	-16.5	1.02 H	82	54.90	2.60
4	#5705.00	43.9 AV	54.0	-10.1	1.02 H	82	41.30	2.60
5	*5785.00	100.0 PK			1.02 H	81	58.90	41.10
6	*5785.00	89.5 AV			1.02 H	81	48.40	41.10
7	11570.00	60.9 PK	74.0	-13.1	1.03 H	65	45.30	15.60
8	11570.00	46.7 AV	54.0	-7.3	1.03 H	65	31.10	15.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	65.9 PK	74.0	-8.1	1.14 V	12	63.80	2.10
2	5440.00	52.8 AV	54.0	-1.2	1.14 V	12	50.70	2.10
3	#5705.00	63.6 PK	74.0	-10.4	1.00 V	12	61.00	2.60
4	#5705.00	50.6 AV	54.0	-3.4	1.00 V	12	48.00	2.60
5	*5785.00	117.1 PK			1.07 V	12	76.00	41.10
6	*5785.00	106.2 AV			1.07 V	12	65.10	41.10
7	11570.00	59.2 PK	74.0	-14.8	1.02 V	51	43.60	15.60
8	11570.00	47.2 AV	54.0	-6.8	1.02 V	51	31.60	15.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	56.7 PK	74.0	-17.3	1.01 H	85	54.60	2.10
2	5440.00	43.7 AV	54.0	-10.3	1.01 H	85	41.60	2.10
3	*5825.00	98.9 PK			1.01 H	85	57.80	41.10
4	*5825.00	87.8 AV			1.01 H	85	46.70	41.10
5	#5850.00	45.7 PK	78.2	-32.5	1.02 H	85	42.70	3.00
6	#5852.10	61.0 PK	78.2	-17.2	1.01 H	85	58.00	3.00
7	#5860.10	57.9 PK	74.0	-16.1	1.01 H	86	54.90	3.00
8	#5860.10	44.2 AV	54.0	-9.8	1.01 H	86	41.20	3.00
9	11650.00	59.3 PK	74.0	-14.7	1.02 H	11	43.70	15.60
10	11650.00	46.8 AV	54.0	-7.2	1.02 H	11	31.20	15.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	64.9 PK	74.0	-9.1	1.05 V	12	62.80	2.10
2	5440.00	52.5 AV	54.0	-1.5	1.05 V	12	50.40	2.10
3	*5825.00	115.7 PK			1.05 V	12	74.60	41.10
4	*5825.00	105.0 AV			1.05 V	12	63.90	41.10
5	#5850.00	49.3 PK	78.2	-28.9	1.05 V	12	46.30	3.00
6	#5852.10	65.4 PK	78.2	-12.8	1.05 V	12	62.40	3.00
7	#5860.10	59.2 PK	74.0	-14.8	1.05 V	12	56.20	3.00
8	#5860.10	45.9 AV	54.0	-8.1	1.05 V	12	42.90	3.00
9	11650.00	61.6 PK	74.0	-12.4	1.05 V	34	46.00	15.60
10	11650.00	47.8 AV	54.0	-6.2	1.05 V	34	32.20	15.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

802.11n (20MHz)

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	57.4 PK	74.0	-16.6	1.20 H	41	55.30	2.10
2	5440.00	43.4 AV	54.0	-10.6	1.20 H	41	41.30	2.10
3	#5665.00	57.6 PK	74.0	-16.4	1.20 H	40	55.20	2.40
4	#5665.00	43.5 AV	54.0	-10.5	1.20 H	40	41.10	2.40
5	#5714.90	56.5 PK	74.0	-17.5	1.21 H	41	53.90	2.60
6	#5714.90	43.1 AV	54.0	-10.9	1.21 H	41	40.50	2.60
7	#5722.90	58.5 PK	78.2	-19.7	1.21 H	42	55.90	2.60
8	#5725.00	47.9 PK	78.2	-30.3	1.21 H	40	45.30	2.60
9	*5745.00	101.2 PK			1.21 H	41	60.20	41.00
10	*5745.00	90.5 AV			1.21 H	41	49.50	41.00
11	11490.00	61.2 PK	74.0	-12.8	1.02 H	34	45.30	15.90
12	11490.00	47.2 AV	54.0	-6.8	1.02 H	34	31.30	15.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	65.0 PK	74.0	-9.0	1.04 V	11	62.90	2.10
2	5440.00	52.6 AV	54.0	-1.4	1.04 V	11	50.50	2.10
3	#5665.00	63.2 PK	74.0	-10.8	1.00 V	11	60.80	2.40
4	#5665.00	50.2 AV	54.0	-3.8	1.00 V	11	47.80	2.40
5	#5714.90	64.9 PK	74.0	-9.1	1.00 V	11	62.30	2.60
6	#5714.90	48.8 AV	54.0	-5.2	1.00 V	11	46.20	2.60
7	#5722.90	73.7 PK	78.2	-4.5	1.01 V	11	71.10	2.60
8	#5725.00	61.2 PK	78.2	-17.0	1.02 V	12	58.60	2.60
9	*5745.00	116.1 PK			1.04 V	11	75.10	41.00
10	*5745.00	105.4 AV			1.04 V	11	64.40	41.00
11	11490.00	61.2 PK	74.0	-12.8	1.02 V	3	45.30	15.90
12	11490.00	47.1 AV	54.0	-6.9	1.02 V	3	31.20	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	55.6 PK	74.0	-18.4	1.01 H	82	53.50	2.10
2	5440.00	43.1 AV	54.0	-10.9	1.01 H	82	41.00	2.10
3	#5705.00	56.8 PK	74.0	-17.2	1.02 H	83	54.20	2.60
4	#5705.00	43.6 AV	54.0	-10.4	1.02 H	83	41.00	2.60
5	*5785.00	99.6 PK			1.02 H	81	58.50	41.10
6	*5785.00	89.1 AV			1.02 H	81	48.00	41.10
7	11570.00	60.6 PK	74.0	-13.4	1.02 H	33	45.00	15.60
8	11570.00	46.6 AV	54.0	-7.4	1.02 H	33	31.00	15.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	65.6 PK	74.0	-8.4	1.15 V	13	63.50	2.10
2	5440.00	52.6 AV	54.0	-1.4	1.15 V	13	50.50	2.10
3	#5705.00	63.1 PK	74.0	-10.9	1.01 V	12	60.50	2.60
4	#5705.00	50.1 AV	54.0	-3.9	1.01 V	12	47.50	2.60
5	*5785.00	116.7 PK			1.01 V	13	75.60	41.10
6	*5785.00	105.4 AV			1.01 V	13	64.30	41.10
7	11570.00	59.2 PK	74.0	-14.8	1.02 V	55	43.60	15.60
8	11570.00	46.8 AV	54.0	-7.2	1.02 V	55	31.20	15.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	56.2 PK	74.0	-17.8	1.01 H	86	54.10	2.10
2	5440.00	43.1 AV	54.0	-10.9	1.01 H	86	41.00	2.10
3	*5825.00	98.3 PK			1.01 H	84	57.20	41.10
4	*5825.00	87.3 AV			1.01 H	84	46.20	41.10
5	#5850.00	45.1 PK	78.2	-33.1	1.01 H	86	42.10	3.00
6	#5852.10	60.6 PK	78.2	-17.6	1.01 H	86	57.60	3.00
7	#5860.10	57.2 PK	74.0	-16.8	1.02 H	88	54.20	3.00
8	#5860.10	43.9 AV	54.0	-10.1	1.02 H	88	40.90	3.00
9	11650.00	59.8 PK	74.0	-14.2	1.02 H	18	44.20	15.60
10	11650.00	46.6 AV	54.0	-7.4	1.02 H	18	31.00	15.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	65.2 PK	74.0	-8.8	1.05 V	13	63.10	2.10
2	5440.00	52.6 AV	54.0	-1.4	1.05 V	13	50.50	2.10
3	*5825.00	115.1 PK			1.05 V	11	74.00	41.10
4	*5825.00	104.4 AV			1.05 V	11	63.30	41.10
5	#5850.00	49.1 PK	78.2	-29.1	1.02 V	13	46.10	3.00
6	#5852.10	64.9 PK	78.2	-13.3	1.02 V	12	61.90	3.00
7	#5860.10	58.8 PK	74.0	-15.2	1.01 V	11	55.80	3.00
8	#5860.10	45.5 AV	54.0	-8.5	1.01 V	11	42.50	3.00
9	11650.00	61.4 PK	74.0	-12.6	1.05 V	33	45.80	15.60
10	11650.00	47.1 AV	54.0	-6.9	1.05 V	33	31.50	15.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

802.11n (40MHz)

CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	55.6 PK	74.0	-18.4	1.56 H	342	53.50	2.10
2	5440.00	43.4 AV	54.0	-10.6	1.56 H	342	41.30	2.10
3	#5714.90	56.9 PK	74.0	-17.1	1.56 H	342	54.30	2.60
4	#5714.90	43.9 AV	54.0	-10.1	1.56 H	342	41.30	2.60
5	#5722.90	60.2 PK	78.2	-18.0	1.56 H	343	57.60	2.60
6	#5725.00	51.6 PK	78.2	-26.6	1.57 H	342	49.00	2.60
7	*5755.00	93.2 PK			1.56 H	342	52.20	41.00
8	*5755.00	82.5 AV			1.56 H	342	41.50	41.00
9	11510.00	59.3 PK	74.0	-14.7	1.23 H	33	43.60	15.70
10	11510.00	46.9 AV	54.0	-7.1	1.23 H	33	31.20	15.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	63.0 PK	74.0	-11.0	1.03 V	12	60.90	2.10
2	5440.00	52.3 AV	54.0	-1.7	1.03 V	12	50.20	2.10
3	#5714.90	66.7 PK	74.0	-7.3	1.04 V	12	64.10	2.60
4	#5714.90	51.8 AV	54.0	-2.2	1.04 V	12	49.20	2.60
5	#5722.90	73.4 PK	78.2	-4.8	1.06 V	12	70.80	2.60
6	#5725.00	59.0 PK	78.2	-19.2	1.06 V	13	56.40	2.60
7	*5755.00	108.7 PK			1.07 V	13	67.70	41.00
8	*5755.00	97.8 AV			1.07 V	13	56.80	41.00
9	11510.00	62.2 PK	74.0	-11.8	1.02 V	6	46.50	15.70
10	11510.00	47.9 AV	54.0	-6.1	1.02 V	6	32.20	15.70

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	56.7 PK	74.0	-17.3	1.30 H	41	54.60	2.10
2	5440.00	43.4 AV	54.0	-10.6	1.30 H	41	41.30	2.10
3	*5795.00	97.7 PK			1.30 H	41	56.60	41.10
4	*5795.00	87.0 AV			1.30 H	41	45.90	41.10
5	#5850.00	48.3 PK	78.2	-29.9	1.03 H	12	45.30	3.00
6	#5852.10	58.4 PK	78.2	-19.8	1.03 H	42	55.40	3.00
7	#5860.10	58.0 PK	74.0	-16.0	1.31 H	42	55.00	3.00
8	#5860.10	44.2 AV	54.0	-9.8	1.31 H	42	41.20	3.00
9	11590.00	60.6 PK	74.0	-13.4	1.02 H	34	45.00	15.60
10	11590.00	46.9 AV	54.0	-7.1	1.02 H	34	31.30	15.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	66.4 PK	74.0	-7.6	1.14 V	12	64.30	2.10
2	5440.00	52.6 AV	54.0	-1.4	1.14 V	12	50.50	2.10
3	*5795.00	113.0 PK			1.04 V	11	71.90	41.10
4	*5795.00	102.1 AV			1.04 V	11	61.00	41.10
5	#5850.00	49.2 PK	78.2	-29.0	1.04 V	11	46.20	3.00
6	#5852.10	63.2 PK	78.2	-15.0	1.04 V	11	60.20	3.00
7	#5860.10	62.8 PK	74.0	-11.2	1.04 V	11	59.80	3.00
8	#5860.10	47.4 AV	54.0	-6.6	1.04 V	11	44.40	3.00
9	11590.00	61.1 PK	74.0	-12.9	1.02 V	64	45.50	15.60
10	11590.00	47.8 AV	54.0	-6.2	1.02 V	64	32.20	15.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

BELOW 1GHZ WORST-CASE DATA**802.11a**

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	76.56	30.2 QP	40.0	-9.8	1.49 H	139	48.00	-17.80
2	142.52	34.4 QP	43.5	-9.1	1.99 H	69	48.80	-14.40
3	249.22	31.4 QP	46.0	-14.6	1.24 H	62	45.80	-14.40
4	336.52	28.5 QP	46.0	-17.5	1.00 H	225	40.20	-11.70
5	450.98	27.7 QP	46.0	-18.3	1.49 H	10	36.90	-9.20
6	625.58	27.0 QP	46.0	-19.0	1.00 H	95	32.70	-5.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.40	36.1 QP	40.0	-3.9	1.24 V	15	50.30	-14.20
2	142.52	36.5 QP	43.5	-7.0	1.24 V	86	50.90	-14.40
3	249.22	27.8 QP	46.0	-18.2	1.00 V	54	42.20	-14.40
4	336.52	27.2 QP	46.0	-18.8	1.24 V	33	38.90	-11.70
5	450.98	27.8 QP	46.0	-18.2	1.24 V	42	37.00	-9.20
6	676.02	29.2 QP	46.0	-16.8	1.49 V	342	34.40	-5.20

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Apr. 24, 2014	Apr. 23, 2015
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2014	Dec. 29, 2015
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 10, 2014	Jul. 09, 2015
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.
3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.7.

4.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA : 802.11a

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.38047	0.18	39.11	35.46	39.29	35.64	58.27	48.27	-18.98	-12.63
2	0.71250	0.21	36.69	32.26	36.90	32.47	56.00	46.00	-19.10	-13.53
3	1.32031	0.24	34.65	30.26	34.89	30.50	56.00	46.00	-21.11	-15.50
4	2.85156	0.30	35.31	30.84	35.61	31.14	56.00	46.00	-20.39	-14.86
5	10.25000	0.45	26.90	22.70	27.35	23.15	60.00	50.00	-32.65	-26.85
6	22.86719	0.56	40.60	32.22	41.16	32.78	60.00	50.00	-18.84	-17.22

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.37266	0.20	34.75	28.65	34.95	28.85	58.44	48.44	-23.49	-19.59
2	0.69688	0.22	31.11	26.79	31.33	27.01	56.00	46.00	-24.67	-18.99
3	1.85938	0.28	29.50	25.44	29.78	25.72	56.00	46.00	-26.22	-20.28
4	2.90234	0.33	29.00	25.13	29.33	25.46	56.00	46.00	-26.67	-20.54
5	10.44141	0.54	31.34	26.67	31.88	27.21	60.00	50.00	-28.12	-22.79
6	22.96875	0.72	35.95	27.39	36.67	28.11	60.00	50.00	-23.33	-21.89

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 TRANSMIT POWER MEASUREMENT

4.3.1 LIMITS OF TRANSMIT POWER MEASUREMENT

Operation Band	EUT Category	LIMIT
U-NII-1	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p \leq 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	Fixed point-to-point Access Point	1 Watt (30 dBm)
	Indoor Access Point	1 Watt (30 dBm)
	Mobile and Portable client device	250mW (24 dBm)
U-NII-2A	---	250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C	---	250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3	✓	1 Watt (30 dBm)

*B is the 26 dB emission bandwidth in megahertz

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.



A D T

4.3.4 TEST PROCEDURE

FOR AVERAGE POWER MEASUREMENT

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.



4.3.7 TEST RESULTS

POWER OUTPUT:

802.11a

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (mW)	MAXIMUM CONDUCTED POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
149	5745	35.975	15.56	18	PASS
157	5785	31.405	14.97	18	PASS
165	5825	20.654	13.15	18	PASS

NOTE: Gain = 18dBi > 6dBi, so the power limit shall be reduced to $30-(18-6) = 18$ dBm.

802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (mW)	MAXIMUM CONDUCTED POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
149	5745	33.574	15.26	18	PASS
157	5785	29.444	14.69	18	PASS
165	5825	20.606	13.14	18	PASS

NOTE: Gain = 18dBi > 6dBi, so the power limit shall be reduced to $30-(18-6) = 18$ dBm.

802.11n (40MHz)

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (mW)	MAXIMUM CONDUCTED POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
151	5755	10.280	10.12	18	PASS
159	5795	25.882	14.13	18	PASS

NOTE: Gain = 18dBi > 6dBi, so the power limit shall be reduced to $30-(18-6) = 18$ dBm.

4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT

4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

Operation Band	EUT Category		LIMIT	
U-NII-1	Outdoor Access Point		17dBm/ MHz	
	Fixed point-to-point Access Point			
	Indoor Access Point			
	Mobile and Portable client device		11dBm/ MHz	
U-NII-2A	---		11dBm/ MHz	
U-NII-2C	---		11dBm/ MHz	
U-NII-3	✓	---	30dBm/ 500 kHz	

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 500 kHz, Set VBW \geq 3 RBW, Detector = RMS
- 3) Sweep time = auto, trigger set to “free run”.
- 4) Trace average at least 100 traces in power averaging mode.
- 5) Record the max value.
- 6) Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500\text{ kHz}/300\text{ kHz})$



A D T

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as 4.3.6.



A D T

4.4.7 TEST RESULTS

802.11a

Channel	Freq. (MHz)	PSD (dBm/300 kHz)	PSD (dBm/500 kHz)	Duty Factor	PSD with Duty Factor (dBm/500kHz)	Limit (dBm/500 kHz)	PASS /FAIL
149	5745	-5.22	-3.00	0.17	-2.83	18	PASS
157	5785	-5.55	-3.33	0.17	-3.16	18	PASS
165	5825	-7.39	-5.17	0.17	-5.00	18	PASS

NOTE: 1. Gain = 18dBi > 6dBi, so the power density limit shall be reduced to 30-(18-6) = 18dBm.

2. Refer to section 3.3 for duty cycle spectrum plot.

802.11n (20MHz)

Channel	Freq. (MHz)	PSD (dBm/300 kHz)	PSD (dBm/500 kHz)	Duty Factor	PSD with Duty Factor (dBm/500kHz)	Limit (dBm/500 kHz)	PASS /FAIL
149	5745	-5.20	-2.98	0.17	-2.81	18	PASS
157	5785	-5.73	-3.51	0.17	-3.34	18	PASS
165	5825	-7.67	-5.45	0.17	-5.28	18	PASS

NOTE: 1. Gain = 18dBi > 6dBi, so the power density limit shall be reduced to 30-(18-6) = 18dBm.




2. Refer to section 3.3 for duty cycle spectrum plot.

802.11n (40MHz)

Channel	Freq. (MHz)	PSD (dBm/300 kHz)	PSD (dBm/500 kHz)	Duty Factor	PSD with Duty Factor (dBm/500kHz)	Limit (dBm/500 kHz)	PASS /FAIL
151	5755	-13.78	-11.56	0.23	-11.33	18	PASS
159	5795	-10.00	-7.78	0.23	-7.55	18	PASS

NOTE: 1. Gain = 18dBi > 6dBi, so the power density limit shall be reduced to 30-(18-6) = 18dBm.

2. Refer to section 3.3 for duty cycle spectrum plot.


SPECTRUM PLOT OF WORST VALUE
802.11a

802.11n (20MHz)

802.11n (40MHz)


4.5 FREQUENCY STABILITY

4.5.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency of the carrier signal shall be maintained within band of operation

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.



A D T

4.5.4 TEST PROCEDURE

- a. The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Set the EUT transmit at un-modulation mode to test frequency stability.



4.5.7 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5825MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
50	120	5824.9713	-0.00049	5824.9708	-0.00050	5824.9709	-0.00050	5824.9726	-0.00047
40	120	5825.0167	0.00029	5825.0174	0.00030	5825.0124	0.00021	5825.0127	0.00022
30	120	5825.0109	0.00019	5825.0085	0.00015	5825.014	0.00024	5825.0095	0.00016
20	120	5825.0175	0.00030	5825.0181	0.00031	5825.0172	0.00030	5825.0143	0.00025
10	120	5824.9923	-0.00013	5824.9932	-0.00012	5824.9924	-0.00013	5824.9929	-0.00012
0	120	5824.9717	-0.00049	5824.969	-0.00053	5824.9707	-0.00050	5824.973	-0.00046
-10	120	5825.0151	0.00026	5825.0146	0.00025	5825.0167	0.00029	5825.015	0.00026
-20	120	5824.9758	-0.00042	5824.9737	-0.00045	5824.9731	-0.00046	5824.975	-0.00043
-30	120	5824.9925	-0.00013	5824.9898	-0.00018	5824.9941	-0.00010	5824.9914	-0.00015

FREQUENCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5825MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
20	138	5825.0172	0.00030	5825.0185	0.00032	5825.0174	0.00030	5825.0135	0.00023
	120	5825.0175	0.00030	5825.0181	0.00031	5825.0172	0.00030	5825.0143	0.00025
	102	5825.0176	0.00030	5825.017	0.00029	5825.0165	0.00028	5825.0146	0.00025

4.6 6dB BANDWIDTH MEASUREMENT

4.6.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

4.6.7 TEST RESULTS

802.11a




CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	16.37	0.5	PASS
157	5785	16.39	0.5	PASS
165	5825	16.40	0.5	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	17.58	0.5	PASS
157	5785	17.37	0.5	PASS
165	5825	17.40	0.5	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
151	5755	35.91	0.5	PASS
159	5795	35.93	0.5	PASS

SPECTRUM PLOT OF WORST VALUE
802.11a

802.11n (20MHz)

802.11n (40MHz)




A D T

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab:

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab:

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---