



FCC PART 15.249
EMI MEASUREMENT AND TEST REPORT
For
Ray Wolf Technology Co., Ltd.

Le Sanalele Complex, Ground Floor, Vaea Street, Saleufi, P.O. Box 1868, Apia, Samoa

FCC ID: Q5HRWK-7200

September 19, 2012

This Report Concerns: Original Report	Equipment Type: RF 2.4GHz Wireless Trackball Keyboard
Test Engineer:	Eric Li 
Test Engineer of performing the tests:	Adam Yang 
Report No.:	BST12080430Y-1ER-3
Receive EUT Date/Test Date:	September 10, 2012/ September 11-18, 2012
Reviewed By:	Christina Deng 
Prepared By:	 <p>Shenzhen BST Technology Co.,Ltd. 3F,Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District,Shenzhen,Guangdong,China Tel: 0755-26747751 ~ 3 Fax: 0755-26747751 ~ 3 ext.826</p>

Note: The test report is specially limited to the above company and this particular sample only.
It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd.
This report must not be used by the client to claim product certification,approval,or
endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1.	Report information.....	3
1.2.	Measurement Uncertainty	3
2.	PRODUCT DESCRIPTION	4
2.1.	EUT Description	4
2.2.	Block Diagram of EUT Configuration.....	4
2.3.	Support Equipment List	5
2.4.	Test Conditions	5
3.	FCC ID LABEL.....	6
4.	TEST RESULTS SUMMARY	7
	Modifications	7
5.	TEST EQUIPMENT USED	8
6.	ANTENNA REQUIREMENT	9
6.1.	Standard Applicable	9
6.2.	Antenna Connected Construction	9
6.3.	Result	9
7.	CONDUCTED POWER LINE TEST.....	10
7.1.	Test Equipment	10
7.2.	Test Procedure	10
7.3.	Test Setup.....	10
7.4.	Conducted Power line Emission Limits.....	10
7.5.	Conducted Power Line Test Result.....	11
8.	RADIATED EMISSION TEST	13
8.1.	Test Equipment	13
8.2.	Test Procedure	13
8.3.	Radiated Test Setup	13
8.4.	Radiated Emission Limit.....	15
8.5.	Radiated Emission Test Result	16
9.	BAND EDGE	18
9.1.	Test Equipment	18
9.2.	Test Procedure	18
9.3.	Band Edge FCC 15.249(d) Limit.....	18
9.4.	Band Edge Test Result.....	19

1. GENERAL INFORMATION

1.1. Report information

1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.

1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of

Shenzhen Certification Technology Service Co., Ltd

(FCC Registered Test Site Number: 197647) on

2F, Building B, East Area of Nanchang Second Industrial Zone, Gushu 2nd Road,
Bao'an District, shenzhen 518126, China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

Available upon request.

2. PRODUCT DESCRIPTION

2.1. EUT Description

Description : RF 2.4GHz Wireless Trackball Keyboard

Applicant : Ray Wolf Technology Co., Ltd.
Le Sanalele Complex, Ground Floor, Vaea Street, Saleufi,
P.O. Box 1868, Apia, Samoa

Manufacturer : Shen Zhen Zhong Xin Kai Technology Co., Ltd.
3F, 5#, 302(Office) Xin Tian She Qu Bi Fu Xin Chun Zone,
FuYong Town, Bao'An District, ShenZhen, GuangDong, China

Model Number : RWK-7200

Trade Name : Ray Wolf

Frequency : 2403-2469MHz, 12 Channels

Power Supply : DC 2.8V (2 AA Batteries) or DC 5V Charging via USB port

2.2. Block Diagram of EUT Configuration



Figure 1 EUT Setup of TX mode




Figure 2 EUT Setup of Charging mode

2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used “ ”
PC system	AM1830	N/A	Acer	
Printer	HP1020	N/A	HP	
Router	PL-R860	N/A	TP-LINK	

2.4. Test Conditions

Temperature: 20~26

Relative Humidity: 50~63 %


3. FCC ID LABEL

FCC ID: Q5HRWK-7200

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation.

Label Location on EUT

EUT View/ FCC ID Label Location



4. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.249

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	Compliant
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

Remark: "N/A" means "Not applicable".

Statement: All testing was performed using the test procedures found in ANSI C63.4-2003.

Modifications

No modification was made.

5. TEST EQUIPMENT USED

Equipment/Facilities	Manufacturer	Model	Serial no.	Date of Cal.	Cal. Interval
3m Semi-Anechoic Chamber	Changzhou Chengyu	EC3048	N/A	May 5, 2012	1 Year
Broadband antenna	SCHWARZBECK	VULB 9168	VULB916 8-438	Aug. 14, 2012	1 Year
Horn antenna	R&S	HF906	10027	Aug. 14, 2012	1 Year
ETS Horn Antenna	ETS	3160	SEL0076	May 8, 2012	1 Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	Apr. 6, 2012	1 Year
Spectrum analyzer	Agilent	E4443A	MY461856 49	Apr. 6, 2012	1 Year
Spectrum analyzer	Agilent	E4440A	MY461873 35	Apr. 6, 2012	1 Year
Spectrum analyzer	Agilent	E4446A	MY453001 03	Apr. 6, 2012	1 Year
Test receiver	R&S	ESCI	100492	Apr. 6, 2012	1 Year
Test receiver	R&S	ESCI	101202	Apr. 6, 2012	1 Year
L.I.S.N.	SCHWARZBECK	NSLK8126	8126466	Apr. 6, 2012	1 Year
L.I.S.N.	SCHWARZBECK	NSLK8126	8126487	Apr. 6, 2012	1 Year
Cable	Resenberger	N/A	NO.1	Apr. 6, 2012	1 Year
Cable	SCHWARZBECK	N/A	NO.2	Apr. 6, 2012	1 Year
Cable	SCHWARZBECK	N/A	NO.3	Apr. 6, 2012	1 Year
Pre-amplifier	SCHWARZBECK	BBV9743	9743-019	Apr. 6, 2012	1 Year
Pre-amplifier	R&S	AFS33-1800 2650-30-8P-44	SEL0080	Apr. 6, 2012	1 Year

6. ANTENNA REQUIREMENT

6.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2. Antenna Connected Construction

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used for this product is a sheet metal soldered with PCB. The antenna is permanently attached. Refer to the product photo.

6.3. Result

Compliance

7. CONDUCTED POWER LINE TEST

7.1. Test Equipment


Please refer to section 5 this report.

7.2. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.).This provides a 50ohm/50uh coupling impedance for the measuring equipment.The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling impedance with 50ohm termination.

Both sides of A.C. Line are check for maximum conducted interference.In order to find the maximum emission,the relative positions of equipment and all of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement .Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

7.3. Test Setup



For the actual test configuration,Please refer to the related items-Photos of testing

7.4. Conducted Power line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHZ)	Class A QP/AV	Class B QP/AV
0.15-0.5	79/66	65-56/56-46
0.5-5.0	73/60	56-46
5.0-3.0	73/60	60-50


Note: In the above table, the tighter limit applies at the band edges.

7.5. Conducted Power Line Test Result

Pass.

Date of Test:	September 17, 2012	Temperature:	24°C
EUT:	RF 2.4Ghz Wireless Trackball Keyboard	Humidity:	55%
Model No.:	RWK-7200	Power Supply:	DC 5V power by PC USB port PC power: AC120V/60Hz
Test Mode:	Charging	Test Engineer:	Eric Li

L Line




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV)	Margin (dB)	Limit (dBuV)	Detector Type
1		0.263	9.600	27.670	37.270	-24.057	61.327	QUASIPEAK
2		0.263	9.600	15.250	24.850	-26.477	51.327	AVERAGE
3		0.408	9.610	23.400	33.010	-24.683	57.693	QUASIPEAK
4		0.408	9.610	9.020	18.630	-29.063	47.693	AVERAGE
5		0.791	9.630	24.810	34.440	-21.560	56.000	QUASIPEAK
6		0.791	9.630	11.370	21.000	-25.000	46.000	AVERAGE
7		1.728	9.782	25.890	35.672	-20.328	56.000	QUASIPEAK
8		1.728	9.782	15.530	25.312	-20.688	46.000	AVERAGE
9		3.744	9.834	35.640	45.474	-10.526	56.000	QUASIPEAK
10	*	3.744	9.834	25.710	35.544	-10.456	46.000	AVERAGE
11		10.763	10.093	20.770	30.863	-29.137	60.000	QUASIPEAK
12		10.763	10.093	9.860	19.953	-30.047	50.000	AVERAGE

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

N Line



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV)	Margin (dB)	Limit (dBuV)	Detector Type
1		0.189	9.600	24.310	33.910	-30.168	64.078	QUASIPEAK
2		0.189	9.600	8.530	18.130	-35.948	54.078	AVERAGE
3		0.259	9.600	24.570	34.170	-27.281	61.451	QUASIPEAK
4		0.259	9.600	11.530	21.130	-30.321	51.451	AVERAGE
5		0.627	9.602	19.820	29.422	-26.578	56.000	QUASIPEAK
6		0.627	9.602	6.550	16.152	-29.848	46.000	AVERAGE
7		1.459	9.752	19.530	29.281	-26.719	56.000	QUASIPEAK
8		1.459	9.752	9.650	19.401	-26.599	46.000	AVERAGE
9	*	3.279	9.825	32.670	42.495	-13.505	56.000	QUASIPEAK
10		3.279	9.825	21.750	31.575	-14.425	46.000	AVERAGE
11		13.884	10.284	11.890	22.173	-37.827	60.000	QUASIPEAK
12		13.884	10.284	4.500	14.783	-35.217	50.000	AVERAGE

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

8. RADIATED EMISSION TEST

8.1. Test Equipment

Please refer to section 5 this report.

8.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz, and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.


Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit.

8.3. Radiated Test Setup


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



8.4. Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below :

A . Fundamental and Harmonics Radiated Emissions 15.249(a) Limit

Fundamental Frequency (MHZ)	Field as strength of Fundamental(3m)			Field as strength of Harmonics(3m)		
	mV/m	dBuV/m		uV/m	dBuV/m	
902~928	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)
2400~2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(3) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

B. Spurious Radiated Emissions.

Frequency (MHz)	Limit			
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dB μ V/m)	Measurement distance (m)	The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mentioned above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
0.009 - 0.490	2400/F(kHz)	/	300	
0.490 - 1.705	24000/F(kHz)	/	30	
1.705-30	30	29.5	30	
30 - 88	100	40	3	
88 - 216	150	43.5	3	
216 - 960	200	46	3	
Above 960	500	54	3	

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) In the Above Table, the tighter limit applies at the band edges.

(3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

8.5. Radiated Emission Test Result

Pass

A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2403	64.87/ 76.32	VERT	94/114	29.13/37.68
2403	76.73/ 88.45	HORIZ	94/114	17.27/25.55

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2439	63.08/ 74.71	VERT	94/114	30.92/39.29
2439	79.13/ 90.87	HORIZ	94/114	14.87/23.13

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2469	62.52/ 74.14	VERT	94/114	31.48/39.86
2469	80.46/ 92.20	HORIZ	94/114	13.54/21.80

B. Harmonics Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4806.0	41.41/ 54.01	VERT	54.0/74.0	12.59/19.99
4806.0	42.72/ 54.86	HORIZ	54.0/74.0	11.28/19.14

Emissions attenuated more than 20 dB below the permissible value are not reported.

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4878.0	40.03/ 52.81	VERT	54.0/74.0	13.97/21.19
4878.0	41.60/ 53.98	HORIZ	54.0/74.0	12.40/20.02

Emissions attenuated more than 20 dB below the permissible value are not reported.

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4938.0	40.07/ 52.43	VERT	54.0/74.0	13.93/21.57
4938.0	41.12/ 53.11	HORIZ	54.0/74.0	12.88/20.89

Emissions attenuated more than 20 dB below the permissible value are not reported.

C. General Radiated Emissions Data

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	HORIZ	-	-
-	-	VERT	-	-

Emissions attenuated more than 20 dB below the permissible value are not reported.

9. BAND EDGE

9.1. Test Equipment

Please refer to Section 5 this report.

9.2. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement. The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz respectively.

9.3. Band Edge FCC 15.249(d) Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB below that in the 100kHz bandwidth within the band that contains the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.4. Band Edge Test Result

Pass

TX 2403Hz

Frequency (MHz)	Result(dB μ V/m)		Limit(dB μ V/m)		Margin(dB)		Polarization
	PEAK	AV	PEAK	AV	PEAK	AV	
2310.000	51.29	/	74	54	22.71	/	Vertical
2353.720	53.14	40.95	74	54	20.86	13.05	Vertical
2390.000	51.39	/	74	54	22.61	/	Vertical
2310.000	53.17	42.43	74	54	20.82	11.57	Horizontal
2341.750	54.99	42.40	74	54	19.01	11.60	Horizontal
2390.000	52.49	/	74	54	21.50	/	Horizontal

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.


TX 2469Hz

Frequency (MHz)	Result(dB μ V/m)		Limit(dB μ V/m)		Margin(dB)		Polarization
	PEAK	AV	PEAK	AV	PEAK	AV	
2481.220	52.07	/	74	54	21.93	/	Vertical
2489.000	50.96	/	74	54	23.04	/	Vertical
2480.860	55.02	42.82	74	54	18.98	11.18	Horizontal
2489.000	54.09	42.81	74	54	19.91	11.19	Horizontal


Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.


Vertical (PK) TX 2403MHz



Horizontal (PK) TX 2403MHz



Vertical (PK) TX 2469MHz



Horizontal (PK) TX 2469MHz

