



TEST REPORT

Report No. : AF009138-001 Date : 2005 May 05
Application No. : LF203161(2)
Applicant : K&B International Limited
406 Empire Centre,
67 Mody Road, TST East,
Hong Kong
Sample Description : One(1) submitted sample stated to be:
Thunder Spin RC 4x4 Road Rage Stunt Machine
of Model No. KR-930, KR-910A, KR-980, KR-990, KR-1006 and KR-1007
Rating : 1 x 9V battery
No. of submitted sample : One (1) piece***
Date Received : 2005 March 16
Test Period : 2005 March 16 – 2005 April 16
Test Requested : FCC Part 15 Certification
Test Method : FCC Rules and Regulations Part 15 – July 2004
ANSI C63.4 – 2003
Test Result : See attached sheet(s) from page 2 to 11.
Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.
Remark : All six models are the same in circuitry and components and construction, and
therefore model KR-930 was chosen to be the representative of the test sample.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Daimy Chui
EMC Engineer - EL. Division

Page 1 of 11

FCC ID : Q5K9307T



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

Table of Contents

| | | |
|-----|---|----|
| 1 | General Information | 3 |
| 1.1 | General Description | 3 |
| 1.2 | Location of the test site | 4 |
| 1.3 | List of measuring equipment | 5 |
| 2 | Description of the radiated emission test | 6 |
| 2.1 | Test Procedure | 6 |
| 2.2 | Test Result | 6 |
| 2.3 | Radiated Emission Measurement Data | 7 |
| 3 | Description of the Line-conducted Test | 8 |
| 3.1 | Test Procedure | 8 |
| 3.2 | Test Result | 8 |
| 3.3 | Graph and Table of Conducted Emission Measurement Data | 8 |
| 4 | Photograph | 9 |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conduction Emission | 9 |
| 4.2 | Photographs of the External and Internal Configurations of the EUT | 9 |
| 5 | Supplementary document | 10 |
| 5.1 | Bandwidth | 10 |
| 5.2 | Duty Cycle | 10 |
| 6 | Appendices | 11 |



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for Thunder Spin RC 4x4 Road Rage Stunt Machine operating at 27.145MHz and is controlled by a crystal. The EUT is powered by 1 x 9V battery. There are two trigger levers on the EUT. When the trigger levers are activated, it will transmit different radio signals for the receiver to move in forward, backward, left or right direction.

The brief circuit description is listed as follows :

- Y1, Q1 and associated circuit act as oscillator.
- ZD1 and associated circuit act as voltage regulator.
- IC1 and associated circuit act as encoder.
- Q2 and associated circuit act as amplifier.



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

1.3 List of measuring equipment

| Equipment | Manufacturer | Model No. | Serial No. | Calibration Certification No. |
|-------------------|--------------|-----------|------------|-------------------------------|
| EMI Test Receiver | R&S | ESCS30 | 100001 | S43284 |
| Broadband Antenna | Schaffner | CBL6112B | 2692 | CA3025 |
| Signal Generator | IFR | 2023B | 202302/938 | S43098 |
| LISN | R&S | ESH3-Z5 | 100038 | S43377 |
| LISN | R&S | ESH3-Z5 | 100010 | S43101 |
| Pulse Limiter | R&S | ESH3-Z2 | 100001 | S43325 |
| Biconical Antenna | R&S | HK116 | 837414/004 | 2GB05000535-001 |



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasi-peak detector.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart C**

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dB μ V/m) | Antenna and Cable factor (dB) | Average Factor (dB) | Field Strength (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|-----------------|----------------|------------------------------|-------------------------------|---------------------|-------------------------------|----------------------------|-------------|
| 27.145 | V | 54.9 | 20.0 | -4.8 | 70.1 | 80.0 | -9.9 |
| 54.286 | V | 22.8 | 8.1 | - | 30.9 | 40.0 | -9.1 |
| 81.592 | H | 16.4 | 7.2 | - | 23.6 | 40.0 | -16.4 |
| * 108.739 | V | 16.3 | 11.0 | - | 27.3 | 43.5 | -16.2 |
| * 135.878 | H | 13.6 | 12.4 | - | 26.0 | 43.5 | -17.5 |
| * 163.029 | H | 15.8 | 10.4 | - | 26.2 | 43.5 | -17.3 |
| 190.176 | H | 14.8 | 9.2 | - | 24.0 | 43.5 | -19.5 |
| 217.319 | H | 17.3 | 9.7 | - | 27.0 | 46.0 | -19.0 |
| * 244.466 | H | 18.3 | 9.7 | - | 28.0 | 46.0 | -18.0 |
| * 271.611 | H | 15.5 | 13.9 | - | 29.4 | 46.0 | -16.6 |



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document | Filename |
|-------------------------|--------------|
| ID Label/Location | LabelSmp.jpg |
| Block Diagram | BlkDia.pdf |
| Schematic Diagram | Schem.pdf |
| Users Manual | UserMan.pdf |
| Operational Description | OpDes.pdf |

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 Duty Cycle

The duty cycle is simply the on-time divided by the period:

$$\begin{aligned} \text{The duration of one cycle} &= 18.05 \text{ ms} \\ \text{Effective period of the cycle} &= (4 \times 1.46 + 10 \times 0.46) \text{ ms} \\ &= 10.44 \text{ ms} \\ \text{Duty Cycle} &= 10.44 / 18.05 \\ &= 0.578 \end{aligned}$$

Therefore, the average factor is found by $20 \log_{10} 0.578 = -4.8 \text{ dB}$



TEST REPORT

Report No. : AF009138-001

Date : 2005 May 05

6 Appendices

| | | |
|---|--|---------|
| A | Photos of the set-up of Radiated Emissions | 1 page |
| A | Photos of External Configurations | 1 page |
| A | Photos of Internal Configurations | 1 page |
| A | ID Label/Location | 1 page |
| A | Bandwidth Plot | 1 page |
| A | Average Factor | 2 pages |
| A | Block Diagram | 1 page |
| A | Schematics Diagram | 1 page |
| A | User Manual | 2 pages |
| A | Operation Description | 1 page |

***** End of Report *****