

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## Appendix D

### Contour Plots

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## CDMA835 (1013CH )

Test Laboratory: HCT  
 File Name: [001\\_1013ch.da4](#)

**DUT: A410; Type: Bar**  
**Program Name: HAC\_TCoil\_WD\_Emission**

Communication System: CDMA 835MHz FCC; Frequency: 824.7 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
 Phantom section: AMB with Coil Section

**DASY4 Configuration:**

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2009-09-18
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -34.3 dB A/m  
 Location: -10, -2.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 35.3 dB  
 ABM1 comp = 1.05 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -10, -2.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 1.05 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -10, -2.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -33.3 dB A/m  
 Location: 1.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 33.1 dB  
 ABM1 comp = -0.222 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 1.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = -0.222 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 1.5, -8, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.50 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -0.5, -1.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300–3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 Diff = 1.86 dB  
 BWC Factor = 10.8 dB  
 Location: 1.3, -3.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 ABM2 = -27.0 dB A/m  
 Location: -0.5, -1.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm


**Cursor:**  
 ABM1/ABM2 = 34.8 dB  
 ABM1 comp = 7.83 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -1.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 ABM1 comp = 7.83 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -1.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 ABM1 comp = 9.36 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## CDMA835 (384CH)

Test Laboratory: HCT  
 File Name: [002\\_384ch.da4](#)

**DUT: A410; Type: Bar**  
**Program Name: HAC\_TCoil\_WD\_Emission**

Communication System: CDMA 835MHz FCC; Frequency: 836.52 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
 Phantom section: AMB with Coil Section

**DASY4 Configuration:**

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2009-09-18
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -37.6 dB A/m  
 Location: -10, 0.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.4 dB  
 ABM1 comp = 1.84 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -10, 0.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 1.84 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -10, 0.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -34.4 dB A/m  
 Location: 1.5, -6, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 34.8 dB  
 ABM1 comp = 0.407 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 1.5, -6, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.407 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 1.5, -6, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 10.2 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -2.5, -1.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 2.00 dB  
 BWC Factor = 10.8 dB  
 Location: -0.8, -3.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -30.6 dB A/m  
 Location: -2.5, -1.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.3 dB  
 ABM1 comp = 8.65 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -2.5, -1.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**


ABM1 comp = 8.65 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -2.5, -1.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 10.2 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## CDMA800 (777CH)

Test Laboratory: HCT  
 File Name: [003\\_777ch.da4](#)

**DUT: A410; Type: Bar**  
**Program Name: HAC\_TCoil\_WD\_Emission**

Communication System: CDMA 835MHz FCC; Frequency: 848.31 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
 Phantom section: AMB with Coil Section

**DASY4 Configuration:**

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2009-09-18
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -36.0 dB A/m  
 Location: -8, 0.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 36.8 dB  
 ABM1 comp = 0.851 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -8, 0.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.851 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -8, 0.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -36.8 dB A/m  
 Location: -0.5, -7, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 37.0 dB  
 ABM1 comp = 0.233 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -7, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.233 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -7, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.65 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, 2.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 2.00 dB  
 BWC Factor = 10.8 dB  
 Location: 1.2, 0.8, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -29.9 dB A/m  
 Location: -0.5, 2.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 38.8 dB  
 ABM1 comp = 8.93 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, 2.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**


ABM1 comp = 8.93 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, 2.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 8.95 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010

## PCS1900 (25CH )

Test Laboratory: HCT  
File Name: [004\\_25ch.da4](#)

DUT: A410; Type: Bar  
Program Name: HAC\_TCoil\_WD\_Emission

Communication System: PCS 1900MHz FCC; Frequency: 1851.25 MHz; Duty Cycle: 1:1  
Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2009-09-18
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -38.0 dB A/m

Location: -8, 2.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.2 dB

ABM1 comp = 1.23 dB A/m

BWC Factor = 0.15103 dB

Location: -8, 2.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 1.23 dB A/m

BWC Factor = 0.15103 dB

Location: -8, 2.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -36.3 dB A/m

Location: 2.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 35.9 dB

ABM1 comp = -0.369 dB A/m

BWC Factor = 0.15103 dB

Location: 2.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = -0.369 dB A/m

BWC Factor = 0.15103 dB

Location: 2.5, -8, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 10.3 dB A/m

BWC Factor = 0.151969 dB

Location: -2.5, 0.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 Diff = 2.00 dB  
 BWC Factor = 10.8 dB  
 Location: -0.7, -1.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm  
 Signal Type: Audio File (.wav) 48k\_voice\_1kHz\_1s.wav

**Cursor:**  
 ABM2 = -31.9 dB A/m  
 Location: -2.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm


**Cursor:**  
 ABM1/ABM2 = 41.0 dB  
 ABM1 comp = 9.06 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -2.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 ABM1 comp = 9.06 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -2.5, 0.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**  
 Measurement grid: dx=10mm, dy=10mm

**Cursor:**  
 ABM1 comp = 9.22 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## PCS1900 (600CH)

Test Laboratory: HCT  
 File Name: [005\\_600ch.da4](#)

**DUT: A410; Type: Bar**  
**Program Name: HAC\_TCoil\_WD\_Emission**

Communication System: PCS 1900MHz FCC; Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
 Phantom section: AMB with Coil Section

DASY4 Configuration:  
 - Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18  
 - Sensor-Surface: 0mm (Fix Surface)  
 - Electronics: DAE4 Sn869; Calibrated: 2009-09-18  
 - Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA  
 - Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -36.2 dB A/m  
 Location: -8, -3.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 36.7 dB  
 ABM1 comp = 0.458 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -8, -3.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.458 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -8, -3.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -38.4 dB A/m  
 Location: -0.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.6 dB  
 ABM1 comp = 1.17 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -0.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 1.17 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -0.5, -8, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.21 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -2.5, 0.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 2.00 dB  
 BWC Factor = 10.8 dB  
 Location: -0.7, -1.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -31.9 dB A/m  
 Location: -2.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.9 dB  
 ABM1 comp = 7.98 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -2.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**


ABM1 comp = 7.98 dB A/m  
 BWC Factor = 0.15103 dB  
 Location: -2.5, 0.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.58 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010

## PCS1900 (1175CH )

Test Laboratory: HCT  
File Name: [006\\_1175ch.da4](#)

DUT: A410; Type: Bar  
Program Name: HAC\_TCoil\_WD\_Emission

Communication System: PCS 1900MHz FCC; Frequency: 1908.75 MHz; Duty Cycle: 1:1  
Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
Phantom section: AMB with Coil Section

### DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2009-09-18
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

### Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM2 = -36.9 dB A/m  
Location: -10, -2.5, 363.7 mm

### Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM1/ABM2 = 38.4 dB  
ABM1 comp = 1.46 dB A/m  
BWC Factor = 0.15103 dB  
Location: -10, -2.5, 363.7 mm

### Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM1 comp = 1.46 dB A/m  
BWC Factor = 0.15103 dB  
Location: -10, -2.5, 363.7 mm

### Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM2 = -39.6 dB A/m  
Location: -4.5, 8, 363.7 mm

### Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM1/ABM2 = 39.3 dB  
ABM1 comp = -0.261 dB A/m  
BWC Factor = 0.15103 dB  
Location: -4.5, 8, 363.7 mm

### Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM1 comp = -0.261 dB A/m  
BWC Factor = 0.15103 dB  
Location: -4.5, 8, 363.7 mm

### Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

#### Cursor:

ABM1 comp = 10.0 dB A/m  
BWC Factor = 0.15103 dB  
Location: -0.5, -1.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 2.00 dB

BWC Factor = 10.8 dB

Location: 1.3, -3.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -29.6 dB A/m

Location: -0.5, -1.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 38.6 dB

ABM1 comp = 8.96 dB A/m

BWC Factor = 0.15103 dB

Location: -0.5, -1.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 8.96 dB A/m

BWC Factor = 0.15103 dB

Location: -0.5, -1.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**


Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.27 dB A/m

BWC Factor = 0.15103 dB

Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010

## AWS1700 (25CH)

Test Laboratory: HCT  
File Name: [007\\_25ch.da4](#)

DUT: A410; Type: Bar  
Program Name: HAC\_TCoil\_WD\_Emission

Communication System: AWS 1700 MHz FCC; Frequency: 1711.25 MHz; Duty Cycle: 1:1  
Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2009-09-18
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -37.8 dB A/m

Location: -10, 1.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.7 dB

ABM1 comp = 1.90 dB A/m

BWC Factor = 0.15103 dB

Location: -10, 1.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 1.90 dB A/m

BWC Factor = 0.15103 dB

Location: -10, 1.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -39.7 dB A/m

Location: -2.5, -12, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.9 dB

ABM1 comp = 0.202 dB A/m

BWC Factor = 0.15103 dB

Location: -2.5, -12, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.202 dB A/m

BWC Factor = 0.15103 dB

Location: -2.5, -12, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.45 dB A/m

BWC Factor = 0.151969 dB

Location: -2.5, 2.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 2.00 dB

BWC Factor = 10.8 dB

Location: -0.8, 0.8, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -29.8 dB A/m

Location: -2.5, 2.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 37.5 dB

ABM1 comp = 7.70 dB A/m

BWC Factor = 0.15103 dB

Location: -2.5, 2.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 7.70 dB A/m

BWC Factor = 0.15103 dB

Location: -2.5, 2.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**


Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.58 dB A/m

BWC Factor = 0.151969 dB

Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## AWS1700 (450CH)

Test Laboratory: HCT  
 File Name: [008\\_450ch.da4](#)

**DUT: A410; Type: Bar**  
**Program Name: HAC\_TCoil\_WD\_Emission**

Communication System: AWS 1700 MHz FCC; Frequency: 1732.5 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
 Phantom section: AMB with Coil Section

DASY4 Configuration:  
 - Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18  
 - Sensor-Surface: 0mm (Fix Surface)  
 - Electronics: DAE4 Sn869; Calibrated: 2009-09-18  
 - Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA  
 - Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -41.4 dB A/m  
 Location: -12, -3.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 41.8 dB  
 ABM1 comp = 0.485 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -12, -3.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.485 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -12, -3.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -39.4 dB A/m  
 Location: -0.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.0 dB  
 ABM1 comp = -0.344 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -8, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = -0.344 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -8, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 10.7 dB A/m  
 BWC Factor = 0.152993 dB  
 Location: -2.5, 0.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 1.35 dB  
 BWC Factor = 10.8 dB  
 Location: -0.7, -1.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -32.9 dB A/m  
 Location: -2.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 41.7 dB  
 ABM1 comp = 8.82 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -2.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**


ABM1 comp = 8.82 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -2.5, 0.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 8.38 dB A/m  
 BWC Factor = 0.152993 dB  
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

## AWS1700 (875CH )

Test Laboratory: HCT  
 File Name: [009\\_875ch.da4](#)

**DUT: A410; Type: Bar**  
**Program Name: HAC\_TCoil\_WD\_Emission**

Communication System: AWS 1700 MHz FCC; Frequency: 1753.75 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1$  kg/m<sup>3</sup>  
 Phantom section: AMB with Coil Section

DASY4 Configuration:  
 - Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18  
 - Sensor-Surface: 0mm (Fix Surface)  
 - Electronics: DAE4 Sn869; Calibrated: 2009-09-18  
 - Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA  
 - Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

**Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -37.8 dB A/m  
 Location: -8, 0.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 40.0 dB  
 ABM1 comp = 2.27 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -8, 0.5, 363.7 mm

**Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 2.27 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -8, 0.5, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):**

**Cursor:**

ABM2 = -38.9 dB A/m  
 Location: -0.5, -10, 363.7 mm

**Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 39.1 dB  
 ABM1 comp = 0.154 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -10, 363.7 mm

**Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 0.154 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, -10, 363.7 mm

**Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 9.62 dB A/m  
 BWC Factor = 0.151969 dB  
 Location: -0.5, 0.5, 363.7 mm

<b>Report No.:</b>	HCTA1006FT02	<b>FCC ID:</b>	Q78-A410	<b>Date of Issue:</b>	Jun. 13, 2010
--------------------	--------------	----------------	----------	-----------------------	---------------

**Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

Diff = 2.00 dB

BWC Factor = 10.8 dB

Location: 1.2, -1.2, 365 mm

**Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM2 = -30.6 dB A/m

Location: -0.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1/ABM2 = 38.0 dB

ABM1 comp = 7.37 dB A/m

BWC Factor = 0.151969 dB

Location: -0.5, 0.5, 363.7 mm

**Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):**

Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 7.37 dB A/m

BWC Factor = 0.151969 dB

Location: -0.5, 0.5, 363.7 mm

**Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):**


Measurement grid: dx=10mm, dy=10mm

**Cursor:**

ABM1 comp = 8.63 dB A/m

BWC Factor = 0.151969 dB

Location: 0, 0, 363.7 mm



0 dB = 1.00A/m