

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	-----------------	----------------	--------------

Appendix D

Contour Plots

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

CDMA835 (1013CH)

Test Laboratory: HCT
 File Name: [001_1013ch.da4](#)

DUT: A415; Type: Bar
Program Name: HAC_TCoil_WD_Emission

Communication System: CDMA 835MHz FCC; Frequency: 824.7 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -36.6 dB A/m
 Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.0 dB
 ABM1 comp = 6.41 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.41 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 0.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -38.6 dB A/m
 Location: 1.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 44.0 dB
 ABM1 comp = 5.36 dB A/m
 BWC Factor = 0.151969 dB
 Location: 1.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.36 dB A/m
 BWC Factor = 0.151969 dB
 Location: 1.5, -7, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.4 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.05 dB
BWC Factor = 10.8 dB
Location: 1.2, -1.2, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -31.0 dB A/m
Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.9 dB
ABM1 comp = 12.9 dB A/m
BWC Factor = 0.151969 dB
Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 12.9 dB A/m
BWC Factor = 0.151969 dB
Location: -0.5, 0.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.3 dB A/m
BWC Factor = 0.151969 dB
Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	-----------------	----------------	--------------

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

CDMA835 (384CH)

Test Laboratory: HCT
 File Name: [002_384ch.da4](#)

DUT: A415; Type: Bar
 Program Name: HAC_TCoil_WD_Emission

Communication System: CDMA 835MHz FCC; Frequency: 836.52 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.2 dB A/m
 Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.8 dB
 ABM1 comp = 6.69 dB A/m
 BWC Factor = 0.152993 dB
 Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.69 dB A/m
 BWC Factor = 0.152993 dB
 Location: -7, 0.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -38.3 dB A/m
 Location: -0.5, 8, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.8 dB
 ABM1 comp = 5.49 dB A/m
 BWC Factor = 0.152993 dB
 Location: -0.5, 8, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.49 dB A/m
 BWC Factor = 0.152993 dB
 Location: -0.5, 8, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.8 dB A/m
 BWC Factor = 0.151969 dB
 Location: 1.5, 0.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300–3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.49 dB
 BWC Factor = 10.8 dB
 Location: 3.2, -1.2, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -31.3 dB A/m
 Location: 1.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 44.6 dB
 ABM1 comp = 13.3 dB A/m
 BWC Factor = 0.152993 dB
 Location: 1.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 13.3 dB A/m
 BWC Factor = 0.152993 dB
 Location: 1.5, 0.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.2 dB A/m
 BWC Factor = 0.151969 dB
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

CDMA800 (777CH)

Test Laboratory: HCT
File Name: [003_777ch.da4](#)

DUT: A415; Type: Bar
Program Name: HAC_TCoil_WD_Emission

Communication System: CDMA 835MHz FCC; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -36.7 dB A/m
Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.0 dB
ABM1 comp = 6.27 dB A/m
BWC Factor = 0.178983 dB
Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.27 dB A/m
BWC Factor = 0.178983 dB
Location: -7, 0.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.8 dB A/m
Location: -0.5, 10, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.2 dB
ABM1 comp = 5.34 dB A/m
BWC Factor = 0.178983 dB
Location: -0.5, 10, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.34 dB A/m
BWC Factor = 0.178983 dB
Location: -0.5, 10, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.5 dB A/m
BWC Factor = 0.15103 dB
Location: -0.5, 2.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.34 dB
 BWC Factor = 10.8 dB
 Location: 1.2, 0.8, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -29.9 dB A/m
 Location: -0.5, 2.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.0 dB
 ABM1 comp = 13.1 dB A/m
 BWC Factor = 0.178983 dB
 Location: -0.5, 2.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 13.1 dB A/m
 BWC Factor = 0.178983 dB
 Location: -0.5, 2.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.5 dB A/m
 BWC Factor = 0.15103 dB
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

PCS1900 (25CH)

Test Laboratory: HCT
 File Name: [004_25ch.da4](#)

DUT: A415; Type: Bar
Program Name: HAC_TCoil_WD_Emission

Communication System: PCS 1900MHz FCC; Frequency: 1851.25 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.0 dB A/m
 Location: -8, 2.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.6 dB
 ABM1 comp = 6.65 dB A/m
 BWC Factor = 0.151969 dB
 Location: -8, 2.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.65 dB A/m
 BWC Factor = 0.151969 dB
 Location: -8, 2.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.3 dB A/m
 Location: -0.5, 8, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 42.7 dB
 ABM1 comp = 5.46 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 8, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.46 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 8, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.6 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 2.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.32 dB
BWC Factor = 10.8 dB
Location: 1.2, 0.8, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -30.0 dB A/m
Location: -0.5, 2.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.4 dB
ABM1 comp = 13.3 dB A/m
BWC Factor = 0.151969 dB
Location: -0.5, 2.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 13.3 dB A/m
BWC Factor = 0.151969 dB
Location: -0.5, 2.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.7 dB A/m
BWC Factor = 0.151969 dB
Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

PCS1900 (600CH)

Test Laboratory: HCT
 File Name: [005_600ch.da4](#)

DUT: A415; Type: Bar
Program Name: HAC_TCoil_WD_Emission

Communication System: PCS 1900MHz FCC; Frequency: 1880 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -39.1 dB A/m
 Location: -8, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 45.4 dB
 ABM1 comp = 6.21 dB A/m
 BWC Factor = 0.151969 dB
 Location: -8, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.21 dB A/m
 BWC Factor = 0.151969 dB
 Location: -8, 0.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -40.0 dB A/m
 Location: -0.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 45.4 dB
 ABM1 comp = 5.40 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.40 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, -7, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 14.0 dB A/m
 BWC Factor = 0.151969 dB
 Location: 1.5, 0.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 0.806 dB

BWC Factor = 10.8 dB

Location: 3.2, -1.2, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -30.9 dB A/m

Location: 1.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 44.0 dB

ABM1 comp = 13.2 dB A/m

BWC Factor = 0.151969 dB

Location: 1.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.2 dB A/m

BWC Factor = 0.151969 dB

Location: 1.5, 0.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):


Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.2 dB A/m

BWC Factor = 0.151969 dB

Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

PCS1900 (1175CH)

Test Laboratory: HCT
 File Name: [006_1175ch.da4](#)

DUT: A415; Type: Bar
Program Name: HAC_TCoil_WD_Emission

Communication System: PCS 1900MHz FCC; Frequency: 1908.75 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.2 dB A/m
 Location: -8, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.5 dB
 ABM1 comp = 6.29 dB A/m
 BWC Factor = 0.152993 dB
 Location: -8, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.29 dB A/m
 BWC Factor = 0.152993 dB
 Location: -8, 0.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -39.0 dB A/m
 Location: -0.5, 10, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 44.4 dB
 ABM1 comp = 5.38 dB A/m
 BWC Factor = 0.152993 dB
 Location: -0.5, 10, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.38 dB A/m
 BWC Factor = 0.152993 dB
 Location: -0.5, 10, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.6 dB A/m
 BWC Factor = 0.152993 dB
 Location: -0.5, 0.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.49 dB

BWC Factor = 10.8 dB

Location: 1.2, -1.2, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -30.5 dB A/m

Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 43.3 dB

ABM1 comp = 12.8 dB A/m

BWC Factor = 0.152993 dB

Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 12.8 dB A/m

BWC Factor = 0.152993 dB

Location: -0.5, 0.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):


Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.5 dB A/m

BWC Factor = 0.152993 dB

Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

AWS1700 (25CH)

Test Laboratory: HCT
 File Name: [007_25ch.da4](#)

DUT: A415; Type: Bar
 Program Name: HAC_TCoil_WD_Emission

Communication System: AWS 1700 MHz FCC; Frequency: 1711.25 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -42.2 dB A/m
 Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 48.3 dB
 ABM1 comp = 6.17 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 0.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.17 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 0.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -47.9 dB A/m
 Location: 3.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 52.9 dB
 ABM1 comp = 5.04 dB A/m
 BWC Factor = 0.151969 dB
 Location: 3.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.04 dB A/m
 BWC Factor = 0.151969 dB
 Location: 3.5, -7, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 14.0 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 2.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300-3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.10 dB
 BWC Factor = 10.8 dB
 Location: 1.2, 0.8, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.9 dB A/m
 Location: -0.5, 2.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 51.1 dB
 ABM1 comp = 13.2 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 2.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 13.2 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 2.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.3 dB A/m
 BWC Factor = 0.151969 dB
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

AWS1700 (450CH)

Test Laboratory: HCT
 File Name: [008_450ch.da4](#)

DUT: A415; Type: Bar
 Program Name: HAC_TCoil_WD_Emission

Communication System: AWS 1700 MHz FCC; Frequency: 1732.5 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -44.6 dB A/m
 Location: -7, 2.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 50.7 dB
 ABM1 comp = 6.08 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 2.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 6.08 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 2.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -45.1 dB A/m
 Location: -0.5, 10, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 50.7 dB
 ABM1 comp = 5.59 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 10, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.59 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 10, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 14.1 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300–3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.07 dB
 BWC Factor = 10.8 dB
 Location: 1.2, -1.2, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -37.6 dB A/m
 Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 51.6 dB
 ABM1 comp = 14.0 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 14.0 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 12.9 dB A/m
 BWC Factor = 0.151969 dB
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

AWS1700 (875CH)

Test Laboratory: HCT
 File Name: [009_875ch.da4](#)

DUT: A415; Type: Bar
 Program Name: HAC_TCoil_WD_Emission

Communication System: AWS 1700 MHz FCC; Frequency: 1753.75 MHz; Duty Cycle: 1:1
 Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1$ kg/m³
 Phantom section: AMB with Coil Section

DASY4 Configuration:

- Probe: AM1DV2 - 1013; ; Calibrated: 2006-04-18
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn869; Calibrated: 2010-09-21
- Phantom: HAC Test Arch with Coil; Type: SD HAC P01 BA
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Point measurement/x (longitudinal) at max x/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -47.2 dB A/m
 Location: -7, 2.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 52.7 dB
 ABM1 comp = 5.49 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 2.5, 363.7 mm

Point measurement/x (longitudinal) at max x/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.49 dB A/m
 BWC Factor = 0.151969 dB
 Location: -7, 2.5, 363.7 mm

Point measurement/y (transversal) at max y/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -48.4 dB A/m
 Location: 3.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 53.7 dB
 ABM1 comp = 5.31 dB A/m
 BWC Factor = 0.151969 dB
 Location: 3.5, -7, 363.7 mm

Point measurement/y (transversal) at max y/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 5.31 dB A/m
 BWC Factor = 0.151969 dB
 Location: 3.5, -7, 363.7 mm

Scans/z (axial) 15 x 15/ABM Signal(x,y,z) (8x8x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 14.6 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Report No.:	HCTA1103FT01	FCC ID:	Q78-A415	Date of Issue:	Mar. 3, 2011
-------------	--------------	---------	----------	----------------	--------------

Point measurement/z (axial) 300–3k response at max/ABM Freq Resp(x,y,z,f) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

Diff = 1.57 dB
 BWC Factor = 10.8 dB
 Location: 1.2, -1.2, 365 mm

Point measurement/z (axial) at max z/ABM Noise(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM2 = -40.2 dB A/m
 Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM SNR(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1/ABM2 = 53.6 dB
 ABM1 comp = 13.4 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Point measurement/z (axial) at max z/ABM Signal(x,y,z) (1x1x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:


ABM1 comp = 13.4 dB A/m
 BWC Factor = 0.151969 dB
 Location: -0.5, 0.5, 363.7 mm

Scans/z (axial) rough 50 x 50/ABM Signal(x,y,z) (11x11x1):

Measurement grid: dx=10mm, dy=10mm

Cursor:

ABM1 comp = 13.4 dB A/m
 BWC Factor = 0.151969 dB
 Location: 0, 0, 363.7 mm



0 dB = 1.00A/m