

# TEST REPORT

**REPORT NUMBER: I08GE5792-FCC-EMC**

**ON**


**Type of Equipment:** GSM Dual-Band Digital Mobile Phone  
**Type of Designation:** ZTE A933+  
**Manufacturer:** ZTE CORPORATION

**ACCORDING TO**  
**FCC CFR Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS; e-CFR, March 23, 2006**  
**PART 22, PUBLIC MOBILE SERVICES (Oct 1, 02 Edition)**  
**PART 24, PERSONAL COMMUNICATIONS SERVICES (Oct 1, 97 Edition)**

**China Telecommunication Technology Labs.**

*Month date, year*  
*July, 11, 2008*

*Signature*



He Guili  
Director

**FCC ID:** Q78-A933PLUS

**Report Date:** 2008-07-11

**Test Firm Name:** China Telecommunication Technology Labs

**Registration Number:** 840587

#### Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, 22, and 24. The sample tested was found to comply with the requirements defined in the applied rules.

## CONTENTS

<b>1 GENERAL INFORMATION .....</b>	<b>4</b>
1.1 NOTES .....	4
1.2 TESTERS .....	5
1.3 TESTING LABORATORY INFORMATION .....	6
1.4 DETAILS OF APPLICANT OR MANUFACTURER .....	7
<b>2 TEST ITEM .....</b>	<b>8</b>
2.1 GENERAL INFORMATION .....	8
2.2 OUTLINE OF EUT .....	8
2.3 MODIFICATIONS INCORPORATED IN EUT .....	8
2.4 EQUIPMENT CONFIGURATION .....	8
2.5 OTHER INFORMATION .....	9
<b>3 SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>4 TEST RESULTS OF MODE .....</b>	<b>11</b>
4.1 RADIATED SPURIOUS EMISSION .....	11
4.2 RADIATED RF POWER OUTPUT AND ERP .....	17
4.3 OCCUPIED BANDWIDTH .....	19
4.4 FREQUENCY STABILITY OVER TEMPERATURE VARIATION .....	24
4.5 FREQUENCY STABILITY OVER VOLTAGE VARIATION .....	26
4.6 CONDUCTED RF POWER OUTPUT .....	28
4.7 CONDUCTED SPURIOUS EMISSION .....	30
4.8 BAND EDGE .....	33
<b>ANNEX A EXTERNAL PHOTOS .....</b>	<b>37</b>
<b>ANNEX B INTERNAL PHOTOS.....</b>	<b>40</b>
<b>ANNEX C DEVIATIONS FROM PRESCRIBED TEST METHODS.....</b>	<b>41</b>

## 1 General Information

### 1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, 22 and 24.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.


The following deviation from, additions to, or exclusions from the test specifications have been made. See Annex C.

China Telecommunication Technology Labs.(CTTL) authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTTL Mr. He Guili.


Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CTTL accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## 1.2 Testers


Name: Li Dongjin  
Position: Engineer  
Department: Department of EMC test  
Signature: 

Name: Yuan Yuan  
Position: Engineer  
Department: Department of EMC test  
Signature: 

### Editor of this test report:

Name: Li Guoqing  
Position: Engineer  
Department: Department of EMC test  
Date: 2008-07-11  
Signature: 

### Technical responsibility for area of testing:

Name: Zou Dongyi  
Position: Manager  
Department: Department of EMC test  
Date: 2008-07-11  
Signature: 

### 1.3 Testing Laboratory information

#### 1.3.1 Location

Name: China Telecommunication Technology Labs.  
Address: No. 11, Yue Tan Nan Jie, Xi Cheng District  
BEIJING  
P. R. CHINA, 100083  
Tel: +86 10 68094053  
Fax: +86 10 68011404  
Email: [emc@chinattl.com](mailto:emc@chinattl.com)

#### 1.3.2 Details of accreditation status

Accredited by: China National Accreditation Service for Conformity  
Assessment (CNAS)  
Registration number: CNAS Registration No. CNAS L0570  
Standard: ISO/IEC 17025:2005

#### 1.3.3 Test location, where different from section 1.3.1

Name: -----  
Street: -----  
City: -----  
Country: -----  
Telephone: -----  
Fax: -----  
Postcode: -----

## 1.4 Details of applicant or manufacturer

### 1.4.1 Applicant

Name: ZTE CORPORATION  
Address: ZTE Plaza, Keji Road South, Hi-Tech Industrial  
Park, Nanshan District, Shenzhen, Guangdong  
Country: China  
Telephone: +86-021-68896840  
Fax: +86-21-50701080  
Contact: Zhangmin  
Telephone: 021-68896835  
Email: Zhang.min13@zte.com.cn

### 1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name: --  
Address: --  
City: --  
Country: --

### 1.4.3 Manufactory (if different from applicant in section 1.4.1)

Name: --  
Address: --

## 2 Test Item

### 2.1 General Information

Manufacturer: ZTE CORPORATION

Name: GSM Dual-Band Digital Mobile Phone

Model Number: ZTE A933+

Serial Number: --

Production Status: Product

Receipt date of test item: 2008-07-04

### 2.2 Outline of EUT

E.U.T. is a GSM Dual-Band Digital Mobile Phone.

### 2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

### 2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	handset	ZTE CORPORATION	ZTE A933+	--	None
B	adapter	Shenzhen Ruide Electronic Industrial Co.,Ltd	STC-A22050U8 -A	--	None
C	battery	CosLight/Ruide/BYD/Li shen	Li3707T42P3h4 63848	--	None
D	Headset	Full-Sound (Dongguan) Electrical Products Ltd .	HMZ1-U8		

Cables:

Item	Cable Type	Manufacturer	Length	Shield	Quantity	Remarks
1	DC cable on Adapter	Unknown	1.0 m	No	1	None

## 2.5 Other Information

(a) Modulation is GMSK.

(b) Emission Designator is 246KGXW.

(c) Version of hardware and software

HW Version: g3yB

SW Version: EREA-GR-P108C1FM(U)V1.0.0B01

(d) Adaptor information:

Input: 100-240VAC 50-60Hz 200mA

Output: 5.0V 700mA

(e) Battery information:

3.7VDC

CITL Test Report

### 3 Summary of Test Results

A brief summary of the tests carried out is shown as following.

<b>GSM mode:</b>		
Specification Clause	Name of Test	Result
2.1051, 24.238, 2.1053,22.917	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
22.913(a)	Effective Radiated Power (ERP)	Pass
2.1049,22.917(b), 24.238(b)	Occupied Bandwidth	*Note 1
2.1055,22.355, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055,22.355, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,22.913(a), 24.232(c)	Conducted RF Power Output	Pass
2.1051,22.917,24. 238	Conducted spurious emissions	Pass
Note 1: No applicable performance criteria.		

TTL TEST REPORT

## 4 Test Results of mode

### 4.1 Radiated Spurious Emission

<b>Specifications:</b>	2.1051, 24.238, 2.1053, 22.917					
<b>Date of Tests</b>	2008-07-09					
<b>Test conditions:</b>	Ambient Temperature: 15°C -35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 190 and 661 for GSM					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Ultra Broadband Antenna	R/S	HL562	100013	2008-07-24	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3 m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

#### Limit Level Construction:

According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB, so the limit level is:  
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

#### Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

#### Test Setup:

The EUT was placed in an anechoic chamber, see figure SP. The Wireless Communications Test Set was used to set the TX channel and power level and modulate the TX signal with different bit patterns. The test was done using an automated test system, where all test equipments were controlled by a computer.




Figure SP

**Test Method:**


The measurement was performed accordance with section 2.2.12 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

- 1 The maximum spurious emissions were searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.
- 2 Levels of EUT's transmitter harmonics and suspicious signals were recorded.
- 3 The recorded levels were corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration was made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.
- 4 The corrected values of radiated spurious emissions indicated as EIRP are reported.


**Note:**

- 1 The investigated ARFCNs are 190 (836.6 MHz) and 661 (1880.0 MHz).
- 2 The investigated frequency range is 30 MHz ~ 18 GHz.


**Test Results for GSM mode:**




**S190VF for GSM mode**




**S190HF for GSM mode**




S190VT for GSM mode




S190HT for GSM mode




### S661VF for GSM mode



### S661HF for GSM mode



S661VT for GSM mode



S661HT for GSM mode

### 4.2 Radiated RF Power Output and ERP

<b>Specifications:</b>	2.1046,24.232,22.913(a)					
<b>Date of Tests</b>	2008-07-09					
<b>Test conditions:</b>	Ambient Temperature: 15°C -35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 128, 190, 251, 512, 661 and 810					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
7330	Ultra Broadband Antenna	R/S	HL562	100013	2008-07-24	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

**Limit Level Construction:**

(a) Radiated RF Power Output

According to Part 24.232(b), i.e., Mobile/portable stations are limited to 2 watts EIRP peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications, so the limit level is 2 W or 33 dBm.

(b) ERP

According to Part 22.913(a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

**Limits for Radiated RF Power Output**

Frequency range	Limit Level (EIRP)/Resolution Bandwidth
TX channel	33dBm/1MHz

**Limits for ERP**

Frequency range	Limit Level (ERP)
TX channel	7W

## Test Setup:

The EUT was set in an anechoic chamber, which is connected to the Wireless Communications Test Set located outside the chamber over the air. The test was done using an automated test system, where all test equipments were controlled by a computer.

## Test Method

The measurement was performed accordance with section 2.2.17 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

1 The maximum power was searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.

2 The measured levels are EIRP values corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration is made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.

3 The corrected maximum levels were reported for EIRP values, and ERP values can be calculated from EIRP values.

### Note:

ERP dBm = EIRP dBm – 2.15dB.

### ERP Value for GSM 850 band mode:

ARFCN	Frequency [MHz]	ERP [dBm]
128	824.228457	24.73
190	836.553106	24.91
251	848.777555	24.23

### EIRP Value for GSM 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.1002	24.67
661	1879.91984	24.92
810	1909.8998	24.95

### 4.3 Occupied bandwidth

<b>Specifications:</b>	2.1049,22.917(b),24.238(b)					
<b>Date of Test</b>	2008-07-09					
<b>Test conditions:</b>	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 128, 190, 251, 512, 661 and 810					
<b>Test Results:</b>	--					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Ultra Broadband Antenna	R/S	HL562	100013	2008-07-24	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3 m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

### Test Setup

The situation under which maximum EIRP values were found in the measurement of the radiated RF power output was used to determine the 99% occupied bandwidth. The Wireless Communications Test Set was used to set the TX channel, power level and modulation.

### Test Method


The 99% occupied bandwidth was calculated from the spectrum analyzer. Markers in the spectrum analyzer were then placed between the calculated frequencies to show the calculated 99% power band.

Note: --

Results data of GSM mode:

EUT channel	99% occupied bandwidth [kHz]
128	244
190	242
251	244
512	246
661	244
810	240


Graphical results for GSM mode:



Channel 128


FCC Parts 2, 22, 24  
Equipment: ZTE A933+

REPORT NO.: I08GE5792-FCC-EMC



Date: 9.JUL.2008 14:40:00

Channel 190




Date: 9.JUL.2008 14:41:19

Channel 251


FCC Parts 2, 22, 24  
Equipment: ZTE A933+

REPORT NO.: I08GE5792-FCC-EMC



Date: 9.JUL.2008 14:27:47

Channel 512




Date: 9.JUL.2008 14:30:08

Channel 661

FCC Parts 2, 22, 24  
Equipment: ZTE A933+

REPORT NO.: I08GE5792-FCC-EMC



Date: 9.JUL.2008 14:33:53

Channel 810

CHINA TELECOMMUNICATION TECHNOLOGY LABS

### 4.4 Frequency Stability over Temperature Variation

<b>Specifications:</b>	2.1055,22.355,24.235					
<b>Date of Test</b>	2008-07-10					
<b>Test conditions:</b>	Ambient Temperature: -30°C-50°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 190 and 661					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
561	Temperature Chamber	Terchy Environmental Technology LTD.	MHU-800SR	84121202	2009-05-06	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal
<b>Limit</b>						
Frequency deviation [ppm]	±2.5					

### Test Setup

The EUT was placed in a temperature chamber, demonstrated as figure T. The wireless communications test set (test simulator) was used to set the TX channel and power levels, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure T: setup for measurement of frequency stability over temperature variation

## Test Method

1. The EUT was turned off and placed in the temperature chamber.
2. The temperature of the chamber was set to -30°C and allowed to stabilize.
3. The EUT temperature was allowed to stabilize for 45 minutes.
4. The EUT was turned on and set to transmit with 8960.
5. The maximum transmit frequency deviation during one minute period was measured by Wireless Communications Test Set.
6. The steps 3-5 were repeated for -20°C, -10°C, 0°C, 10°C, 20°C, 30°C, 40°C and 50°C.

## Test results data for GSM mode:

Table T1: frequency deviation over temperature variation for channel 190

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	28	0.033	Pass
-20	28	0.033	Pass
-10	25	0.030	Pass
0	23	0.027	Pass
10	30	0.036	Pass
20	33	0.039	Pass
30	29	0.035	Pass
40	28	0.033	Pass
50	27	0.032	Pass

Table T2: frequency deviation over temperature variation for channel 661

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	30	0.016	Pass
-20	25	0.013	Pass
-10	27	0.014	Pass
0	26	0.014	Pass
10	31	0.016	Pass
20	30	0.016	Pass
30	27	0.014	Pass
40	29	0.015	Pass
50	30	0.016	Pass

### 4.5 Frequency Stability over Voltage Variation

<b>Specifications:</b>	2.1055,22.355,24.235					
<b>Date of Test</b>	2008-07-10					
<b>Test conditions:</b>	Ambient Temperature: 15°C -35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 190 and 661					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal
7982	DC Power Source	4NIC	DH1715A-3	004224	--	Normal
<b>Limit</b>						
Frequency deviation [ppm]	±2.5					

### Test Setup

The EUT was placed in a shielding chamber and powered by the dummy battery which is connected to a DC power source, demonstrated as figure V. The wireless communications test set was used to set the TX channel and power level, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure V: test setup for measurement of frequency stability over voltage variation

Test Results data for GSM mode:

Table V1: frequency deviation over voltage variation for channel 190

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	30	0.035	Pass
Cut-off point	3.3	36	0.043	Pass

Table V2: frequency deviation over voltage variation for channel 661

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	17	0.009	Pass
Cut-off point	3.3	34	0.018	Pass

TTL Test Report


### 4.6 Conducted RF Power Output

<b>Specifications:</b>	2.1046,22.913(a),24.232(c)					
<b>Date of Tests</b>	2008-07-09					
<b>Test conditions:</b>	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 128, 190, 251, 512, 661 and 810					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

<b>Limits for Radiated RF Power Output</b>	
Frequency range	Limit Level (EIRP)/Resolution Bandwidth
TX channel	33dBm/1MHz
<b>Limits for ERP</b>	
Frequency range	Limit Level (ERP)
TX channel	7W

### Test Setup:

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26).



### Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --

### Test Results for GSM mode:

ERP Value for GSM 850 band:

ARFCN	Peak output power [dBm]
128	28.79
190	28.97
251	29.23

EIRP Value for GSM 1900 band:

ARFCN	Peak output power [dBm]
512	29.29
661	29.22
810	29.02

### 4.7 Conducted Spurious Emission

<b>Specifications:</b>	2.1051,22.917,24.238					
<b>Date of Tests</b>	2008-07-09					
<b>Test conditions:</b>	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 190 and 661					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

**Limit Level Construction:**


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB, so the limit level is:  
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

**Limits for Radiated spurious emissions(UE)**

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

### Test Setup:

During the process of testing, the EUT was controlled via Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26)



### Test Method

The measurement was performed accordance with section 2.2.13 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment under test, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Note: --


#### Test Results for GSM mode:

Out of band emission	
Frequency [GHz]	Level (dBm)
--	--
--	--
--	--

#### Graphical results for GSM mode:


FCC Parts 2, 22, 24  
Equipment: ZTE A933+

REPORT NO.: I08GE5792-FCC-EMC



Date: 9.JUL.2008 16:10:47

Channel 190



Date: 9.JUL.2008 16:09:50

Channel 661

### 4.8 Band Edge

<b>Specifications:</b>	2.1051, 24.238, 2.1053, 22.917					
<b>Date of Tests</b>	2008-07-09					
<b>Test conditions:</b>	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
<b>Operation Mode</b>	TX on, channel 128, 251, 512 and 810					
<b>Test Results:</b>	Pass					
<b>Test equipment Used:</b>						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

**Limit Level Construction:**


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB, so the limit level is:  
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

**Limits for Radiated spurious emissions(UE)**

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

**Test Setup:**

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26).



### Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --


### Test Results for GSM mode:

Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
Channel 128 Left band edge	824.000	-13.23
Channel 251 Right band edge	849.000	-13.80
Channel 512 Left band edge	1850.000	-18.60
Channel 810 Right band edge	1910.000	-18.07

FCC Parts 2, 22, 24  
Equipment: ZTE A933+

REPORT NO.: I08GE5792-FCC-EMC


UNCAL Marker 1 [T1] RBW 3 kHz RF Att 50 dB  
Ref Lvl -13.54 dBm VBW 10 kHz  
30 dBm 824.00208417 MHz SWT 10 ms Unit dBm



Date: 27.MAY.2008 17:59:34

Channel 128 Left band edge

UNCAL Marker 1 [T1] RBW 3 kHz RF Att 50 dB  
Ref Lvl -15.42 dBm VBW 10 kHz  
30 dBm 849.06212425 MHz SWT 10 ms Unit dBm




Date: 27.MAY.2008 18:03:47

Channel 251 Right band edge


FCC Parts 2, 22, 24  
Equipment: ZTE A933+

REPORT NO.: I08GE5792-FCC-EMC



Date: 27.MAY.2008 17:23:16

Channel 512 Left band edge



Date: 27.MAY.2008 17:34:46

Channel 810 Right band edge

## Annex A External Photos



Front view with clip close




Front view with clip open



Back view



Adaptor




Battery




Earphone

## Annex B Internal Photos



Main board (face)



Main board (back)

## ANNEX C Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

————— **The End of this Report** —————

*ATTN Test Report*