

**#01 CDMA2000 BC0\_RTAP 153.6\_Horizontal Up\_0.5cm\_Ch384**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.977$  mho/m;  $\epsilon_r = 54.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch384/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.883 mW/g



**Ch384/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = 0.00193 dB

Peak SAR (extrapolated) = 2.38 W/kg

**SAR(1 g) = 0.856 mW/g; SAR(10 g) = 0.516 mW/g**

Maximum value of SAR (measured) = 0.894 mW/g



**#02 CDMA2000 BC0\_RTAP 153.6\_Horizontal Down\_0.5cm\_Ch384**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.977$  mho/m;  $\epsilon_r = 54.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch384/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.842 mW/g



**Ch384/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.6 V/m; Power Drift = 0.0160 dB

Peak SAR (extrapolated) = 2.11 W/kg

**SAR(1 g) = 0.825 mW/g; SAR(10 g) = 0.517 mW/g**

Maximum value of SAR (measured) = 0.856 mW/g



**#03 CDMA2000 BC0\_RTAP 153.6\_Vertical Front\_0.5cm\_Ch384**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.977$  mho/m;  $\epsilon_r = 54.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch384/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.386 mW/g



**Ch384/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.2 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 0.506 W/kg

**SAR(1 g) = 0.348 mW/g; SAR(10 g) = 0.230 mW/g**

Maximum value of SAR (measured) = 0.379 mW/g



**#04 CDMA2000 BC0\_RTAP 153.6\_Vertical Back\_0.5cm\_Ch384**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.977$  mho/m;  $\epsilon_r = 54.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch384/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.455 mW/g

**Ch384/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.8 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 1.8 W/kg

**SAR(1 g) = 0.403 mW/g; SAR(10 g) = 0.243 mW/g**

Maximum value of SAR (measured) = 0.408 mW/g



**Ch384/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.8 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 0.568 W/kg

**SAR(1 g) = 0.410 mW/g; SAR(10 g) = 0.277 mW/g**

Maximum value of SAR (measured) = 0.431 mW/g



**#05 CDMA2000 BC0\_RTAP 153.6\_Tip Mode\_0.5cm\_Ch384**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.977$  mho/m;  $\epsilon_r = 54.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch384/Area Scan (31x41x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.223 mW/g



**Ch384/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12 V/m; Power Drift = 0.0168 dB

Peak SAR (extrapolated) = 0.669 W/kg

**SAR(1 g) = 0.234 mW/g; SAR(10 g) = 0.104 mW/g**

Maximum value of SAR (measured) = 0.259 mW/g



**#06 CDMA2000 BC0\_RTAP 153.6\_Horizontal Up\_0.5cm\_Ch1013**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.965$  mho/m;  $\epsilon_r = 54.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.11 mW/g



**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.5 V/m; Power Drift = -0.0094 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.641 mW/g**

Maximum value of SAR (measured) = 1.11 mW/g



**#06 CDMA2000 BC0\_RTAP 153.6\_Horizontal Up\_0.5cm\_Ch1013\_2D**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.965$  mho/m;  $\epsilon_r = 54.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.11 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 11.5 V/m; Power Drift = -0.0094 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.641 mW/g**

Maximum value of SAR (measured) = 1.11 mW/g

# 1g/10g Averaged SAR



**#07 CDMA2000 BC0\_RTAP 153.6\_Horizontal Up\_0.5cm\_Ch777**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 848.31$  MHz;  $\sigma = 0.987$  mho/m;  $\epsilon_r =$

$54.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18

- Phantom: SAM1; Type: SAM; Serial: TP-1479

- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch777/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.826 mW/g



**Ch777/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.4 V/m; Power Drift = 0.077 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.788 mW/g; SAR(10 g) = 0.485 mW/g**

Maximum value of SAR (measured) = 0.835 mW/g



**#08 CDMA2000 BC0\_RTAP 153.6\_Horizontal Down\_0.5cm\_Ch1013**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.965$  mho/m;  $\epsilon_r = 54.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.11 mW/g



**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.5 V/m; Power Drift = 0.0078 dB

Peak SAR (extrapolated) = 1.55 W/kg

**SAR(1 g) = 0.989 mW/g; SAR(10 g) = 0.643 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g



**#09 CDMA2000 BC0\_RTAP 153.6\_Horizontal Down\_0.5cm\_Ch777**

**DUT: 151301**

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_110523 Medium parameters used:  $f = 848.31$  MHz;  $\sigma = 0.987$  mho/m;  $\epsilon_r =$

$54.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.4 °C

**DASY5 Configuration:**

- Probe: ET3DV6 - SN1788; ConvF(5.99, 5.99, 5.99); Calibrated: 2010-9-21

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1210; Calibrated: 2010-11-18

- Phantom: SAM1; Type: SAM; Serial: TP-1479

- Measurement SW: DASY5, V5.2 Build 157; SEMCAD X Version 14.0 Build 57

**Ch777/Area Scan (31x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.991 mW/g

**Ch777/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 1.31 W/kg

**SAR(1 g) = 0.911 mW/g; SAR(10 g) = 0.583 mW/g**

Maximum value of SAR (measured) = 0.991 mW/g

