



Specific Absorption Rate (SAR) Test Report
for
ZTE CORPORATION
on the
UMTS/EVDO Dual Mode Wireless Data Terminal

Report Number : FA8N2204
Trade Name : ZTE
Model Name : AD3700
FCC ID : Q78-AD3700
Date of Testing : Dec. 11, 2008 ~ Feb. 11, 2009
Date of Report : Feb. 12, 2009
Date of Review : Feb. 12, 2009

- The test results refer exclusively to the tested model/sample only.
- Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.
- Report Version: Rev. 03

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Table of Contents

- 1. **Statement of Compliance**3
- 2. **Administration Data**4
 - 2.1 Testing Laboratory4
 - 2.2 Applicant.....4
 - 2.3 Manufacturer4
 - 2.4 Application Details4
- 3. **General Information**5
 - 3.1 Description of Device Under Test (DUT).....5
 - 3.2 Product Photos5
 - 3.3 Applied Standards6
 - 3.4 Device Category and SAR Limits6
 - 3.5 Test Conditions6
 - 3.6.1 Ambient Condition6
 - 3.6.2 Test Configuration.....6
- 4. **Specific Absorption Rate (SAR)**.....7
 - 4.1 Introduction7
 - 4.2 SAR Definition7
- 5. **SAR Measurement Setup**8
 - 5.1 DASY4 E-Field Probe System.....9
 - 5.1.1 ET3DV6 E-Field Probe Specification9
 - 5.1.2 ET3DV6 E-Field Probe Calibration9
 - 5.2 DATA Acquisition Electronics (DAE)11
 - 5.3 Robot.....11
 - 5.4 Measurement Server11
 - 5.5 SAM Twin Phantom12
 - 5.6 Device Holder for SAM Twin Phantom13
 - 5.7 Data Storage and Evaluation14
 - 5.7.1 Data Storage.....14
 - 5.7.2 Data Evaluation14
 - 5.8 Test Equipment List16
- 6. **Tissue Simulating Liquids**.....17
- 7. **Uncertainty Assessment**19
- 8. **SAR Measurement Evaluation**21
 - 8.1 Purpose of System Performance check21
 - 8.2 System Setup21
 - 8.3 Validation Results23
- 9. **Description for DUT Testing Position**.....24
- 10. **Measurement Procedures**25
 - 10.1 Spatial Peak SAR Evaluation.....25
 - 10.2 Scan Procedures26
 - 10.3 SAR Averaged Methods26
- 11. **SAR Test Results**27
 - 11.1 Conducted Power27
 - 11.2 Test Records for Body SAR Test28
 - 11.3 Test Record for Back-Off SAR Test.....30
- 12. **References**.....31
- Appendix A - System Performance Check Data**
- Appendix B - SAR Measurement Data**
- Appendix C - Calibration Data**
- Appendix D - Product Photos**
- Appendix E - Test Setup Photos**
- Appendix F - FCC 3G SAR Measurement Procedures**



1. Statement of Compliance

The Specific Absorption Rate (SAR) maximum results found during testing for the **ZTE CORPORATION UMTS/EVDO Dual Mode Wireless Data Terminal ZTE AD3700** are as follows (with expanded uncertainty 21.9%):

SAR Position	GSM850 SAR (W/kg)	GSM1900 SAR (W/kg)	WCDMA Band V SAR (W/kg)	WCDMA Band II SAR (W/kg)	CDMA2000 Cellular (W/kg)	CDMA2000 PCS (W/kg)
Body	0.851	0.603	0.423	1.3	0.391	0.716

They are in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1999 and had been tested in accordance with the measurement methods and procedures specified in OET Bulletin 65 Supplement C (Edition 01-01).

Approved by

Roy Wu
Manager



2. Administration Data

2.1 Testing Laboratory

Company Name : Sporton International Inc.
Address : No.52, Hwa-Ya 1st RD., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Test Site : SAR01-HY
Telephone Number : 886-3-327-3456
Fax Number : 886-3-328-4978

2.2 Applicant

Company Name : ZTE CORPORATION
Address : ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

2.3 Manufacturer

Company Name : ZTE CORPORATION
Address : ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

2.4 Application Details

Date of reception of application: Nov. 22, 2008
Start of test : Dec. 11, 2008
End of test : Feb. 11, 2009



3. General Information

3.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type :	UMTS/EVDO Dual Mode Wireless Data Terminal
Trade Name :	ZTE
Model Name :	AD3700
FCC ID :	Q78-AD3700
Tx Frequency :	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz CDMA2000 Cellular : 824 MHz ~ 849 MHz CDMA2000 PCS : 1850 MHz ~ 1910 MHz
Rx Frequency :	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz CDMA2000 Cellular : 869 MHz ~ 894 MHz CDMA2000 PCS : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna :	GSM850 : 32.36 dBm GSM1900 : 28.34 dBm WCDMA Band V : 24.28 dBm WCDMA Band II : 20.90 dBm CDMA2000 Cellular (1xEV-DO) : 24.61 dBm CDMA2000 PCS (1xEV-DO) : 18.64 dBm
Antenna Type :	Fixed Internal Antenna
HW Version :	E
SW Version :	DS1050-SUUAASDA-2151
Type of Modulation :	GSM / GPRS : GMSK EDGE : 8PSK WCDMA / CDMA2000 : QPSK HSDPA : QPSK / 16QAM HSUPA : BPSK
DUT Stage :	Production Unit

3.2 Product Photos

Refer to Appendix D.



3.3 Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this UMTS/EVDO Dual Mode Wireless Data Terminal is in accordance with the following standards:

- 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- KDB 941225 D01 v02
- KDB 447498 D02 v01
- OET Bulletin 65 Supplement C (Edition 01-01)
- Preliminary Guidance for Reviewing Applications for Certification of 3G Device. May 2006.

3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

3.5 Test Conditions

3.6.1 Ambient Condition

Ambient Temperature	20-24
Humidity	<60 %

3.6.2 Test Configuration

The device was controlled by using a base station emulator R&S CMU200. Communication between the device and the emulator was established by air link. The distance between the DUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of DUT. The DUT was set from the emulator to radiate maximum output power during all tests.

Measurements were performed on the lowest, middle, and highest channel for each testing position. However, measurements were performed only on the middle channel if the SAR is below 3 dB of limit.

For SAR testing, EUT is in GPRS/EDGE or WCDMA/HSDPA/HSUPA or CDMA2000 link mode. In GPRS/EDGE link mode, its crest factor is 4, because EUT is set in GPRS/EDGE multi-slot class 10 with 2 uplink slots. In WCDMA/HSDPA/HSUPA or CDMA2000 link mode, its crest factor is 1.

4. Specific Absorption Rate (SAR)

4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density.). The equation description is as below:

$$\mathbf{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\mathbf{SAR} = C \frac{\delta T}{\delta t}$$

, where C is the specific heat capacity, δT is the temperature rise and δt the exposure duration,

or related to the electrical field in the tissue by

$$\mathbf{SAR} = \frac{\sigma |E|^2}{\rho}$$

, where σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the rms electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

5. SAR Measurement Setup




Fig. 5.1 DASY5 System

The DASY5 system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (ECO) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY5 software
- Remove control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Some of the components are described in details in the following sub-sections.

5.1 DASY4 E-Field Probe System

The SAR measurement is conducted with the dosimetric probe ET3DV6 (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

5.1.1 ET3DV6 E-Field Probe Specification

<ET3DV6>

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents)
Frequency	10 MHz to 3 GHz
Directivity	± 0.2 dB in brain tissue (rotation around probe axis) ± 0.4 dB in brain tissue (rotation perpendicular to probe axis)
Dynamic Range	5 μ W/g to > 100mW/g; Linearity: ±0.2dB
Surface Detection	± 0.2 mm repeatability in air and clear liquids on reflecting surface
Dimensions	Overall length: 330mm Tip length: 16mm Body diameter: 12mm Tip diameter: 6.8mm Distance from probe tip to dipole centers: 2.7mm
Application	General dosimetry up to 3GHz Compliance tests for mobile phones and Wireless LAN Fast automatic scanning in arbitrary phantoms



Fig. 5.2 Probe Setup on Robot

5.1.2 ET3DV6 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than ± 10%. The spherical isotropy shall be evaluated and within ± 0.25dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data are as below:

➤ ET3DV6 sn1787

Sensitivity	X axis : 1.73 μV	Y axis : 1.59 μV	Z axis : 1.72 μV	
Diode compression point	X axis : 95 mV	Y axis : 98 mV	Z axis : 91 mV	
Conversion factor (Body)	Frequency (MHz)	X axis	Y axis	Z axis
	800~1000	6.34	6.34	6.34
	1850~2050	4.73	4.73	4.73
Boundary effect (Body)	Frequency (MHz)	Alpha	Depth	
	800~1000	0.50	2.48	
	1850~2050	0.74	1.99	



➤ ET3DV6 sn1788

Sensitivity	X axis : 1.73 μ V	Y axis : 1.59 μ V	Z axis : 1.72 μ V	
Diode compression point	X axis : 95 mV	Y axis : 98 mV	Z axis : 91 mV	
Conversion factor (Body)	Frequency (MHz)	X axis	Y axis	Z axis
	800~1000	6.34	6.34	6.34
	1850~2050	4.73	4.73	4.73
Boundary effect (Body)	Frequency (MHz)	Alpha	Depth	
	800~1000	0.50	2.48	
	1850~2050	0.74	1.99	

NOTE: The probe parameters have been calibrated by the SPEAG.

5.2 DATA Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.

5.3 Robot

The DASY5 system uses the high precision robots TX90 XL type out of the newer series from Stäubli SA (France). For the 6-axis controller DASY5 system, the CS8C robot controller version from Stäubli is used. The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller

5.4 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with
400 MHz CPU
128 MB chipdisk and
128 MB RAM.

Communication with
the DAE4 electronic box
the 16-bit AD-converter system for optical detection and digital I/O interface.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.

5.5 SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- Right head
- Flat phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

The phantom can be used with the following tissue simulating liquids:

- *Water-sugar based liquid
- *Glycol based liquids



Fig. 5.3 Top View of Twin Phantom



Fig. 5.4 Bottom View of Twin Phantom

5.6 Device Holder for SAM Twin Phantom

The SAR in the Phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source in 5 mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. An accurate device position is therefore crucial for accurate and repeatable measurement. The position in which the devices must be measured, are defined by the standards.

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig. 5.5 Device Holder



5.7 Data Storage and Evaluation

5.7.1 Data Storage

The DASY5 software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-loss media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.7.2 Data Evaluation

The DASY5 post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

- Probe parameters :**
 - Sensitivity Norm_i, a_{i0}, a_{i1}, a_{i2}
 - Conversion factor ConvF_i
 - Diode compression point dcp_i
- Device parameters :**
 - Frequency f
 - Crest factor cf
- Media parameters :**
 - Conductivity
 - Density

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i ($i = x, y, z$)
 U_i = input signal of channel i ($i = x, y, z$)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated :

E-field probes : $E_i = \sqrt{\frac{V_i}{Norm_i ConvF}}$

H-field probes : $H_i = \sqrt{V_i} \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$

with V_i = compensated signal of channel i ($i = x, y, z$)
 $Norm_i$ = sensor sensitivity of channel i ($i = x, y, z$)
 $\mu V/(V/m)^2$ for E-field Probes
 $ConvF$ = sensitivity enhancement in solution
 a_{ij} = sensor sensitivity factors for H-field probes
 f = carrier frequency [GHz]
 E_i = electric field strength of channel i in V/m
 H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm³

* Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²
 E_{tot} = total electric field strength in V/m
 H_{tot} = total magnetic field strength in A/m



5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	Dosimetric E-Filed Probe	ET3DV6	1787	Aug. 26, 2008	Aug. 25, 2009
SPEAG	Dosimetric E-Filed Probe	ET3DV6	1788	Sep. 23, 2008	Sep. 22, 2009
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 17, 2008	Mar. 16, 2010
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Mar. 28, 2008	Mar. 27, 2010
SPEAG	Data Acquisition Electronics	DAE3	577	Nov. 12, 2008	Nov. 11, 2009
SPEAG	Data Acquisition Electronics	DAE4	679	May 21, 2008	May 20, 2009
SPEAG	Data Acquisition Electronics	DAE4	778	Sep. 22, 2008	Sep. 21, 2009
SPEAG	Device Holder	N/A	N/A	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1303	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1446	NCR	NCR
SPEAG	SAM Phantom	QD 000 P40 C	TP-1383	NCR	NCR
SPEAG	ELI4 Phantom	QD 0VA 001 BA	1029	NCR	NCR
Agilent	PNA Series Network Analyzer	E8358A	US40260131	Apr. 02, 2008	Apr. 01, 2009
Agilent	Wireless Communication Test Set	E5515C	GB46311322	Dec. 22, 2006	Dec. 21, 2008
R&S	Universal Radio Communication Tester	CMU200	105934	Nov. 11, 2008	Nov. 10, 2009
Agilent	Dielectric Probe Kit	85070D	US01440205	NCR	NCR
Agilent	Dual Directional Coupler	778D	50422	NCR	NCR
AR	Power Amplifier	5S1G4M2	0328767	NCR	NCR
R&S	Power Meter	NRVD	101394	Oct. 20, 2008	Oct. 19, 2009
R&S	Power Sensor	NRV-Z1	100130	Oct. 20, 2008	Oct. 19, 2009

Table 5.1 Test Equipment List

6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY5, the phantom must be filled with around 25 liters of homogeneous tissue simulating liquid. The liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is (head SAR) or from the flat phantom to the liquid top surface (body SAR) is 15.2cm.

The following ingredients for tissue simulating liquid are used:

- **Water:** deionized water (pure H₂O), resistivity $\geq 16\text{M}\Omega$ - as basis for the liquid
- **Sugar:** refined sugar in crystals, as available in food shops – to reduce relative permittivity
- **Salt:** pure NaCl – to increase conductivity
- **Cellulose:** Hydroxyethyl-cellulose, medium viscosity (75-125 mPa.s, 2% in water, 20°C), CAS#54290-to increase viscosity and to keep sugar in solution.
- **Preservative:** Preventol D-7 Bayer AG, D-51368 Leverkusen, CAS#55965-84-9- to prevent the spread of bacteria and molds.
- **DGMBE:** Deithlenglycol-monobuthyl ether (DGMBE), Fluka Chemie GmbH, CAS#112-34-5 – to reduce relative permittivity.

Table 6.1 gives the recipes for one liter of body tissue simulating liquid for frequency band 850MHz and 1900 MHz.

Ingredient	MSL-850	MSL-1900
Water	631.68 g	716.56 g
Cellulose	0 g	0 g
Salt	11.72 g	4.0 g
Preventol D-7	1.2 g	0 g
Sugar	600.0 g	0 g
DGMBE	0 g	300.67 g
Total amount	1 liter (1.3 kg)	1 liter (1.0 kg)
Dielectric Parameters at 22°	f=835 MHz $\epsilon_r = 55.2 \pm 5\%$, $\sigma = 0.97 \pm 5\%$ S/m	f= 1900 MHz $\epsilon_r = 53.3 \pm 5\%$, $\sigma = 1.52 \pm 5\%$ S/m

Table 6.1 Recipes for Tissue Simulating Liquid

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

Table 6.2 shows the measuring results for muscle simulating liquid.

Band	Temperature ()	Frequency (MHz)	Conductivity (σ)	Permittivity (ϵ_r)	Measurement Date
GSM850	21.5	824.2	0.942	52.7	Dec. 12, 2008
		836.4	0.954	52.6	
		848.8	0.967	52.5	
	21.4	824.2	0.943	52.8	Dec. 22, 2008
		836.4	0.956	52.7	
		848.8	0.969	52.6	
GSM1900	21.6	1850.2	1.480	51.1	Dec. 14, 2008
		1880.0	1.510	51.0	
		1909.8	1.540	50.9	
	21.5	1850.2	1.480	51.3	Dec. 22, 2008
		1880.0	1.510	51.1	
		1909.8	1.540	51.1	
WCDMA Band V	21.3	826.4	0.946	52.8	Dec. 11, 2008
		836.4	0.956	52.7	
		846.6	0.967	52.6	
	21.4	826.4	0.945	52.8	Dec. 22, 2008
		836.4	0.956	52.7	
		846.6	0.967	52.6	
WCDMA Band II	21.6	1852.4	1.460	50.9	Dec. 20, 2008
		1880.0	1.480	50.8	
		1907.6	1.510	50.7	
	21.5	1852.4	1.480	51.2	Dec. 22, 2008
		1880.0	1.510	51.1	
		1907.6	1.540	51.1	
	21.4	1852.4	1.480	51.8	Feb. 11, 2009
		1880.0	1.510	51.7	
		1907.6	1.540	51.6	
CDMA2000 Cellular	21.4	824.70	0.943	52.9	Dec. 11, 2008
		836.52	0.954	52.8	
		848.31	0.967	52.7	
	21.4	824.70	0.944	52.8	Dec. 22, 2008
		836.52	0.955	52.7	
		848.31	0.968	52.6	
CDMA2000 PCS	21.6	1851.25	1.460	50.9	Dec. 20, 2008
		1880.00	1.480	50.8	
		1908.75	1.510	50.7	
	21.5	1851.25	1.480	51.2	Dec. 22, 2008
		1880.00	1.510	51.1	
		1908.75	1.540	51.1	

Table 6.2 Measuring Results for Simulating Liquid

The measuring data are consistent with $\epsilon_r = 55.2 \pm 5\%$ and $\sigma = 0.97 \pm 5\%$ for body GSM850, WCDMA Band V, and CDMA2000 Cellular, and $\epsilon_r = 53.3 \pm 5\%$ and $\sigma = 1.52 \pm 5\%$ for body GSM1900, WCDMA Band II, and CDMA2000 PCS.

7. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 7.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-shape
Multiplying factor^(a)	1/k ^(b)	1/ 3	1/ 6	1/ 2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) is the coverage factor

Table 7.1 Multiplying Factions for Various Distributions

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASYS5 uncertainty Budget is showed in Table 7.2.



Error Description	Uncertainty Value ± %	Probability Distribution	Divisor	Ci (1g)	Standard Unc. (1g)	vi or Veff
Measurement Equipment						
Probe Calibration	±5.9 %	Normal	1	1	±5.9 %	∞
Axial Isotropy	±4.7 %	Rectangular	√3	0.7	±1.9 %	∞
Hemispherical Isotropy	±9.6 %	Rectangular	√3	0.7	±3.9 %	∞
Boundary Effects	±1.0 %	Rectangular	√3	1	±0.6 %	∞
Linearity	±4.7 %	Rectangular	√3	1	±2.7 %	∞
System Detection Limits	±1.0 %	Rectangular	√3	1	±0.6 %	∞
Readout Electronics	±0.3 %	Normal	1	1	±0.3 %	∞
Response Time	±0.8 %	Rectangular	√3	1	±0.5 %	∞
Integration Time	±2.6 %	Rectangular	√3	1	±1.5 %	∞
RF Ambient Noise	±3.0 %	Rectangular	√3	1	±1.7 %	∞
RF Ambient Reflections	±3.0 %	Rectangular	√3	1	±1.7 %	∞
Probe Positioner	±0.4 %	Rectangular	√3	1	±0.2 %	∞
Probe Positioning	±2.9 %	Rectangular	√3	1	±1.7 %	∞
Max. SAR Eval.	±1.0 %	Rectangular	√3	1	±0.6 %	∞
Test Sample Related						
Device Positioning	±2.9 %	Normal	1	1	±2.9	145
Device Holder	±3.6 %	Normal	1	1	±3.6	5
Power Drift	±5.0 %	Rectangular	√3	1	±2.9	∞
Phantom and Setup						
Phantom Uncertainty	±4.0 %	Rectangular	√3	1	±2.3	∞
Liquid Conductivity (target)	±5.0 %	Rectangular	√3	0.64	±1.8	∞
Liquid Conductivity (meas.)	±2.5 %	Normal	1	0.64	±1.6	∞
Liquid Permittivity (target)	±5.0 %	Rectangular	√3	0.6	±1.7	∞
Liquid Permittivity (meas.)	±2.5 %	Normal	1	0.6	±1.5	∞
Combined Standard Uncertainty					±10.9	387
Coverage Factor for 95 %		K=2				
Expanded uncertainty (Coverage factor = 2)					±21.9	

Table 7.2 Uncertainty Budget of DASY5

8. SAR Measurement Evaluation

Each DASY5 system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY5 software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

8.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

8.2 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835 MHz and 1900 MHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig. 8.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. 835 MHz or 1900 MHz Dipole

The output power on dipole port must be calibrated to 20dBm (100mW) before dipole is connected.



Fig 8.2 Dipole Setup

8.3 Validation Results

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 8.1 shows the target SAR and measured SAR after normalized to 1W input power.

Frequency (MHz)	SAR	Target (W/kg)	Measurement data (W/kg)	Variation	Measurement Date
835	SAR (1g)	9.52	9.65	1.4 %	Dec. 11, 2008
	SAR (10g)	6.37	6.4	0.5 %	
	SAR (1g)	9.52	9.63	1.2 %	Dec. 12, 2008
	SAR (10g)	6.37	6.38	0.2 %	
	SAR (1g)	9.52	9.56	0.4 %	Dec. 22, 2008
	SAR (10g)	6.37	6.3	-1.1 %	
1900	SAR (1g)	40.1	41.8	4.2 %	Dec. 14, 2008
	SAR (10g)	21.3	22.1	3.8 %	
	SAR (1g)	40.1	44	9.7 %	Dec. 20, 2008
	SAR (10g)	21.3	23.4	9.9 %	
	SAR (1g)	40.1	39.2	-2.2 %	Dec. 22, 2008
	SAR (10g)	21.3	20.8	-2.3 %	
	SAR (1g)	40.1	40.4	0.7 %	Feb. 11, 2009
	SAR (10g)	21.3	21.4	0.5 %	

Table 8.1 Target and Measurement Data Comparison

The table above indicates the system performance check can meet the variation criterion.



9. Description for DUT Testing Position

This DUT was tested in six different positions. They are “Horizontal Up in Straight Mode“, “Vertical Front in Straight Mode”, “Horizontal Down in Straight Mode”, “Vertical Back in Straight Mode”, “Vertical Back in Vertical Mode” and “Vertical Front in Vertical Mode”. The separation distance from DUT to phantom is 5 mm for all test position.

Remark: Please refer to Appendix E for the test setup photos.

10. Measurement Procedures

The measurement procedures are as follows:

- Linking DUT with base station emulator CMU200 in middle channel
- Setting CMU200 to allow DUT to radiate maximum output power
- Measuring output power through RF cable and power meter
- Placing the DUT in the positions described in the last section
- Setting scan area, grid size and other setting on the DASY5 software
- Taking data for the middle channel on each testing position
- Finding out the largest SAR result on these testing positions of each band
- Measuring output power and SAR results for the lowest and highest channels in this worst case testing position

According to the OET Bulletin 65 Supplement C standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power reference measurement

10.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the OET Bulletin 65 Supplement C standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY5 software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- extraction of the measured data (grid and values) from the Zoom Scan
- calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- generation of a high-resolution mesh within the measured volume
- interpolation of all measured values from the measurement grid to the high-resolution grid
- extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- calculation of the averaged SAR within masses of 1g and 10g



10.2 Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 1 g.

10.3 SAR Averaged Methods

In DASY5, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.



11. SAR Test Results

11.1 Conducted Power

Mode \ Channel	GSM 850 (dBm)			GSM 1900 (dBm)		
	128	189	251	512	661	810
GPRS 8 (1 uplink)	32.36	32.28	32.25	28.34	28.20	28.07
GPRS 10 (2 uplink)	32.29	32.20	32.18	25.29	25.17	25.07
EGPRS 8 (1 uplink)	26.78	26.61	26.51	25.29	25.16	24.04
EGPRS 10 (2 uplink)	26.75	26.62	26.50	25.27	25.13	25.02

Mode \ Channel	WCDMA Band V (dBm)			WCDMA Band II (dBm)			
	4132	4182	4233	9262	9400	9538	
12.2K	24.28	24.08	24.08	20.78	20.74	20.57	
12.2K+HSDPA	Subtest-1	24.15	24.07	23.98	20.90	20.76	20.78
	Subtest-2	23.59	23.33	23.44	20.88	20.71	20.73
	Subtest-3	23.60	23.45	23.36	20.43	20.27	20.24
	Subtest-4	23.45	23.27	23.20	20.38	20.24	20.26
12.2K+HSUPA	Subtest-1	23.88	23.78	23.70	20.49	20.52	20.24
	Subtest-2	21.53	21.46	21.36	18.45	18.54	18.18
	Subtest-3	22.58	22.38	22.33	19.43	19.51	19.26
	Subtest-4	22.16	21.85	21.82	18.49	18.58	18.24
	Subtest-5	23.81	23.75	23.74	20.48	20.50	20.18

Mode \ Channel	CDMA2000 Cellular (dBm)			CDMA2000 PCS (dBm)		
	1013	334	777	25	600	1175
1xRTT FCH+RC1	24.46	24.27	24.45	18.01	16.34	17.86
1xRTT FCH+RC3	24.47	24.22	24.44	17.86	16.16	17.83
1xRTT FCH+RC3+SCH	23.63	23.42	23.72	17.83	16.02	17.87
1xEV-DO RTAP 9.6K	24.41	24.24	24.35	18.37	16.32	18.42
1xEV-DO RTAP 38.4K	24.36	24.17	24.33	18.18	16.25	18.15
1xEV-DO RTAP 153.6K	24.33	24.07	24.14	17.74	16.02	17.73
1xEV-DO RETAP 128	24.57	24.44	24.58	18.59	16.53	18.64
1xEV-DO RETAP 2048	24.61	24.37	24.45	18.54	16.61	18.57
1xEV-DO RETAP 12288	24.42	24.48	24.55	18.31	16.27	18.47



11.2 Test Records for Body SAR Test

Test Position	Band	Separation	Chan.	Freq. (MHz)	Modulation Type	Measured 1g SAR (W/kg)	Limit (W/kg)	Result
Horizontal Up in Straight Mode	GSM850 (GPRS10)	5 mm	189	836.40	GMSK	0.321	1.6	Pass
Vertical Front in Straight Mode	GSM850 (GPRS 10)	5 mm	189	836.40	GMSK	0.164	1.6	Pass
Horizontal Down in Straight Mode	GSM850 (GPRS 10)	5 mm	189	836.40	GMSK	0.752	1.6	Pass
Vertical Back in Straight Mode	GSM850 (GPRS 10)	5 mm	189	836.40	GMSK	0.113	1.6	Pass
Vertical Back in Vertical Mode	GSM850 (GPRS 10)	5 mm	189	836.40	GMSK	0.194	1.6	Pass
Horizontal Down in Straight Mode	GSM850 (EGPRS 10)	5 mm	189	836.40	8PSK	0.184	1.6	Pass
Horizontal Down in Straight Mode	GSM850 (GPRS10)	5 mm	128	824.20	GMSK	0.616	1.6	Pass
Horizontal Down in Straight Mode	GSM850 (GPRS10)	5 mm	251	848.80	GMSK	0.851	1.6	Pass
Vertical Front in Vertical Mode	GSM850 (GPRS 10)	5 mm	251	848.80	GMSK	0.012	1.6	Pass
Horizontal Up in Straight Mode	GSM1900 (GPRS10)	5 mm	661	1880.00	GMSK	0.314	1.6	Pass
Vertical Front in Straight Mode	GSM1900 (GPRS10)	5 mm	661	1880.00	GMSK	0.127	1.6	Pass
Horizontal Down in Straight Mode	GSM1900 (GPRS10)	5 mm	661	1880.00	GMSK	0.603	1.6	Pass
Vertical Back in Straight Mode	GSM1900 (GPRS10)	5 mm	661	1880.00	GMSK	0.258	1.6	Pass
Vertical Back in Vertical Mode	GSM1900 (GPRS10)	5 mm	661	1880.00	GMSK	0.018	1.6	Pass
Horizontal Down in Straight Mode	GSM1900 (GPRS8)	5 mm	661	1880.00	GMSK	0.528	1.6	Pass
Horizontal Down in Straight Mode	GSM1900 (EGPRS10)	5 mm	661	1880.00	8PSK	0.565	1.6	Pass
Horizontal Down in Straight Mode	GSM1900 (GPRS10)	5 mm	512	1850.20	GMSK	0.539	1.6	Pass
Horizontal Down in Straight Mode	GSM1900 (GPRS10)	5 mm	810	1909.80	GMSK	0.511	1.6	Pass
Vertical Front in Vertical Mode	GSM1900 (GPRS10)	5 mm	661	1880.00	GMSK	0.02	1.6	Pass
Horizontal Up in Straight Mode	WCDMA Band V (RMC 12.2K)	5 mm	4182	836.60	QPSK	0.189	1.6	Pass
Vertical Front in Straight Mode	WCDMA Band V (RMC 12.2K)	5 mm	4182	836.60	QPSK	0.1	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band V (RMC 12.2K)	5 mm	4182	836.60	QPSK	0.387	1.6	Pass
Vertical Back in Straight Mode	WCDMA Band V (RMC 12.2K)	5 mm	4182	836.60	QPSK	0.076	1.6	Pass
Vertical Back in Vertical Mode	WCDMA Band V (RMC 12.2K)	5 mm	4182	836.60	QPSK	0.142	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band V (RMC 12.2K+HSDPA)	5 mm	4182	836.60	QPSK	0.377	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band V (RMC 12.2K+HSUPA)	5 mm	4182	836.60	QPSK	0.308	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band V (RMC 12.2K)	5 mm	4132	826.40	QPSK	0.385	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band V (RMC 12.2K)	5 mm	4233	846.60	QPSK	0.423	1.6	Pass
Vertical Front in Vertical Mode	WCDMA Band V (RMC 12.2K)	5 mm	4233	846.60	QPSK	0.00514	1.6	Pass



Test Position	Band	Separation	Chan.	Freq. (MHz)	Modulation Type	Measured 1g SAR (W/kg)	Limit (W/kg)	Result
Horizontal Up in Straight Mode	WCDMA Band II (RMC 12.2K)	5 mm	9400	1880.00	QPSK	0.69	1.6	Pass
Vertical Front in Straight Mode	WCDMA Band II (RMC 12.2K)	5 mm	9400	1880.00	QPSK	0.257	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K)	5 mm	9400	1880.00	QPSK	1.17	1.6	Pass
Vertical Back in Straight Mode	WCDMA Band II (RMC 12.2K)	5 mm	9400	1880.00	QPSK	0.531	1.6	Pass
Vertical Back in Vertical Mode	WCDMA Band II (RMC 12.2K)	5 mm	9400	1880.00	QPSK	0.039	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K+HSDPA)	5 mm	9400	1880.00	QPSK	1.14	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K+HSUPA)	5 mm	9400	1880.00	QPSK	1.03	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K)	5 mm	9262	1852.40	QPSK	1.3	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K)	5 mm	9538	1907.60	QPSK	1.14	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K+HSDPA)	5 mm	9262	1852.40	QPSK	1.11	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K+HSDPA)	5 mm	9538	1907.60	QPSK	0.889	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K+HSUPA)	5 mm	9262	1852.40	QPSK	1.1	1.6	Pass
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K+HSUPA)	5 mm	9538	1907.60	QPSK	0.664	1.6	Pass
Vertical Front in Vertical Mode	WCDMA Band II (RMC 12.2K)	5 mm	9262	1852.40	QPSK	0.043	1.6	Pass
Horizontal Up in Straight Mode	CDMA2000 Cellular (RC1)	5 mm	334	835.02	QPSK	0.199	1.6	Pass
Vertical Front in Straight Mode	CDMA2000 Cellular (RC1)	5 mm	334	835.02	QPSK	0.064	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 Cellular (RC1)	5 mm	334	835.02	QPSK	0.371	1.6	Pass
Vertical Back in Straight Mode	CDMA2000 Cellular (RC1)	5 mm	334	835.02	QPSK	0.084	1.6	Pass
Vertical Back in Vertical Mode	CDMA2000 Cellular (RC1)	5 mm	334	835.02	QPSK	0.141	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 Cellular (PTAP 38.4K)	5 mm	334	835.02	QPSK	0.391	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 Cellular (PETAP 2048)	5 mm	334	835.02	QPSK	0.373	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 Cellular (PTAP 38.4K)	5 mm	1013	824.70	QPSK	0.274	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 Cellular (PTAP 38.4K)	5 mm	777	848.31	QPSK	0.371	1.6	Pass
Vertical Front in Vertical Mode	CDMA2000 Cellular (PTAP 38.4K)	5 mm	334	835.02	QPSK	0.0052	1.6	Pass



Test Position	Band	Separation	Chan.	Freq. (MHz)	Modulation Type	Measured 1g SAR (W/kg)	Limit (W/kg)	Result
Horizontal Up in Straight Mode	CDMA2000 PCS (RC1)	5 mm	600	1880.00	QPSK	0.229	1.6	Pass
Vertical Front in Straight Mode	CDMA2000 PCS (RC1)	5 mm	600	1880.00	QPSK	0.087	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 PCS (RC1)	5 mm	600	1880.00	QPSK	0.465	1.6	Pass
Vertical Back in Straight Mode	CDMA2000 PCS (RC1)	5 mm	600	1880.00	QPSK	0.179	1.6	Pass
Vertical Back in Vertical Mode	CDMA2000 PCS (RC1)	5 mm	600	1880.00	QPSK	0.014	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 PCS (RTAP 9.6K)	5 mm	600	1880.00	QPSK	0.447	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 PCS (RETAP 128)	5 mm	600	1880.00	QPSK	0.48	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 PCS (RETAP 128)	5 mm	25	1851.25	QPSK	0.716	1.6	Pass
Horizontal Down in Straight Mode	CDMA2000 PCS (RETAP 128)	5 mm	1175	1908.75	QPSK	0.644	1.6	Pass
Vertical Front in Vertical Mode	CDMA2000 PCS (RETAP 128)	5 mm	25	1851.25	QPSK	0.021	1.6	Pass

11.3 Test Record for Back-Off SAR Test

Test Position	Band	Separation	Chan.	Freq. (MHz)	Modulation Type	Measured 1g SAR (W/kg)	Limit (W/kg)	Result
Horizontal Down in Straight Mode	WCDMA Band II (RMC 12.2K)	10 mm	9262	1852.40	QPSK	0.64	1.6	Pass

Test Engineer : Jason Wang, Gordon Lin, Eric Huang, and A-Rod Chen



12. References

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] IEEE Std. P1528-2003, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, April 21, 2003
- [3] Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01), “Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to RF Emissions”, June 2001
- [4] IEEE Std. C95.1-1999, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, 1999
- [5] Robert J. Renka, “Multivariate Interpolation Of Large Sets Of Scattered Data”, University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148
- [6] DASYS System Handbook



Appendix A - System Performance Check Data

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2005/12/11

System Check_Body_835MHz_081211

DUT: Dipole 835 MHz

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.955 \text{ mho/m}$; $\epsilon_r = 52.7$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 22.7 °C; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184


Pin=100mW/Area Scan (61x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 1.06 mW/g

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 34.5 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.965 mW/g; SAR(10 g) = 0.640 mW/g

Maximum value of SAR (measured) = 1.05 mW/g



0 dB = 1.05mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/12

System Check_Body_835MHz_081212

DUT: Dipole 835 MHz

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.953 \text{ mho/m}$; $\epsilon_r = 52.6$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin=100mW/Area Scan (61x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 1.06 mW/g


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.5 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.963 mW/g; SAR(10 g) = 0.638 mW/g

Maximum value of SAR (measured) = 1.04 mW/g



0 dB = 1.04mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

System Check_Body_835MHz_081222

DUT: Dipole 835 MHz


Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.955 \text{ mho/m}$; $\epsilon_r = 52.7$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 22.4 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin=100mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.05 mW/g

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 34.3 V/m; Power Drift = 0.027 dB
Peak SAR (extrapolated) = 1.34 W/kg
SAR(1 g) = 0.956 mW/g; SAR(10 g) = 0.630 mW/g
Maximum value of SAR (measured) = 1.04 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/14

System Check_Body_1900MHz_081214

DUT: Dipole 1900 MHz

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin=100mW/Area Scan (91x91x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 4.82 mW/g


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.2 V/m; Power Drift = 0.007 dB

Peak SAR (extrapolated) = 7.58 W/kg

SAR(1 g) = 4.18 mW/g; SAR(10 g) = 2.21 mW/g

Maximum value of SAR (measured) = 4.69 mW/g



0 dB = 4.69mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

System Check_Body_1900MHz_081220

DUT: Dipole 1900 MHz

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 50.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 °C; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin=100mW/Area Scan (91x91x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 5.07 mW/g


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 60.0 V/m; Power Drift = -0.022 dB

Peak SAR (extrapolated) = 7.96 W/kg

SAR(1 g) = 4.4 mW/g; SAR(10 g) = 2.34 mW/g

Maximum value of SAR (measured) = 4.93 mW/g



0 dB = 4.93mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

System Check_Body_1900MHz_081222

DUT: Dipole 1900 MHz


Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.1$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin=100mW/Area Scan (91x91x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 4.46 mW/g

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 56.0 V/m; Power Drift = 0.069 dB
Peak SAR (extrapolated) = 7.06 W/kg
SAR(1 g) = 3.92 mW/g; SAR(10 g) = 2.08 mW/g
Maximum value of SAR (measured) = 4.40 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2009/2/11

System Check_Body_1900MHz_090211

DUT: Dipole 1900 MHz

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.6$; $\rho = 1000$ kg/m³


Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin=100mW/Area Scan (91x91x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 4.63 mW/g

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 56.9 V/m; Power Drift = -0.008 dB
Peak SAR (extrapolated) = 7.28 W/kg
SAR(1 g) = 4.04 mW/g; SAR(10 g) = 2.14 mW/g
Maximum value of SAR (measured) = 4.53 mW/g





Appendix B - SAR Measurement Data

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/12

Body_GSM850 Ch189_Horizontal Up in Straight Mode_GPRS10

DUT: 8N2204


Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:4
Medium: MSL_850 Medium parameters used: f = 836.4 MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch189/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.350 mW/g

Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.5 V/m; Power Drift = -0.112 dB
Peak SAR (extrapolated) = 0.472 W/kg
SAR(1 g) = 0.321 mW/g; SAR(10 g) = 0.203 mW/g
Maximum value of SAR (measured) = 0.348 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/12

Body_GSM850 Ch189_Veritical Back in Vertical Mode_GPRS10

DUT: 8N2204


Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.224 mW/g

Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.0 V/m; Power Drift = -0.002 dB
Peak SAR (extrapolated) = 0.346 W/kg
SAR(1 g) = 0.194 mW/g; SAR(10 g) = 0.100 mW/g
Maximum value of SAR (measured) = 0.227 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/13

Body_GSM850 Ch189_Vertical Front in Straight Mode_GPRS10

DUT: 8N2204

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:4

Medium: MSL_850 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.954 \text{ mho/m}$; $\epsilon_r = 52.6$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch189/Area Scan (31x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.154 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.0 V/m; Power Drift = -0.021 dB

Peak SAR (extrapolated) = 0.438 W/kg

SAR(1 g) = 0.164 mW/g; SAR(10 g) = 0.093 mW/g

Maximum value of SAR (measured) = 0.181 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/12

Body_GSM850 Ch189_Vertical Back in Straight Mode_GPRS10

DUT: 8N2204

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:4

Medium: MSL_850 Medium parameters used: $f = 836.4 \text{ MHz}$; $\sigma = 0.954 \text{ mho/m}$; $\epsilon_r = 52.6$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch189/Area Scan (31x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.118 mW/g


Ch189/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.147 dB

Peak SAR (extrapolated) = 0.188 W/kg

SAR(1 g) = 0.113 mW/g; SAR(10 g) = 0.063 mW/g

Maximum value of SAR (measured) = 0.124 mW/g



0 dB = 0.124mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/12

Body_GSM850 Ch189_Vertical Back in Vertical Mode_GPRS10

DUT: 8N2204

Communication System: GSM850; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.6 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.276 mW/g


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.6 V/m; Power Drift = -0.174 dB

Peak SAR (extrapolated) = 0.322 W/kg

SAR(1 g) = 0.217 mW/g; SAR(10 g) = 0.109 mW/g

Maximum value of SAR (measured) = 0.252 mW/g



0 dB = 0.252mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/13

Body_GSM850 Ch251_Horizontal Down in Straight Mode_GPRS10

DUT: 8N2204


Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:4
Medium: MSL_850 Medium parameters used: $f = 849$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch251/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.896 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.6 V/m; Power Drift = -0.135 dB
Peak SAR (extrapolated) = 1.49 W/kg
SAR(1 g) = 0.851 mW/g; SAR(10 g) = 0.479 mW/g
Maximum value of SAR (measured) = 0.936 mW/g



0 dB = 0.936mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

Body_GSM850 Ch251_Vertical Front in Vertical Mode_GPRS10

DUT: 8N2204


Communication System: GSM850; Frequency: 848.8 MHz; Duty Cycle: 1:4
Medium: MSL_850 Medium parameters used: $f = 849$ MHz; $\sigma = 0.969$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch251/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.013 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.82 V/m; Power Drift = -0.197 dB
Peak SAR (extrapolated) = 0.026 W/kg
SAR(1 g) = 0.012 mW/g; SAR(10 g) = 0.00652 mW/g
Maximum value of SAR (measured) = 0.012 mW/g



0 dB = 0.012mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/14

Body_GSM1900 Ch661_Horizontal Up in Straight Mode_GPRS10

DUT: 8N2204


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 51$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.6 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (41x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.366 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 12.3 V/m; Power Drift = -0.195 dB
Peak SAR (extrapolated) = 0.482 W/kg
SAR(1 g) = 0.314 mW/g; SAR(10 g) = 0.191 mW/g
Maximum value of SAR (measured) = 0.332 mW/g



0 dB = 0.332mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_GSM1900 Ch661_Horizontal Down in Straight Mode_GPRS10

DUT: 8N2204


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 51$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (41x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 0.657 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 11.6 V/m; Power Drift = -0.010 dB
Peak SAR (extrapolated) = 0.952 W/kg
SAR(1 g) = 0.603 mW/g; SAR(10 g) = 0.358 mW/g
Maximum value of SAR (measured) = 0.627 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/14

Body_GSM1900 Ch661_Vertical Back in Vertical Mode_GPRS10

DUT: 8N2204

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 ; Liquid Temperature : 21.6


DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.020 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.13 V/m; Power Drift = -0.175 dB
Peak SAR (extrapolated) = 0.035 W/kg
SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.011 mW/g
Maximum value of SAR (measured) = 0.019 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.13 V/m; Power Drift = -0.175 dB
Peak SAR (extrapolated) = 0.020 W/kg
SAR(1 g) = 0.013 mW/g; SAR(10 g) = 0.0076 mW/g
Maximum value of SAR (measured) = 0.014 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/14

Body_GSM1900 Ch661_Vertical Front in Straight Mode_GPRS10

DUT: 8N2204


Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (31x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.145 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.75 V/m; Power Drift = -0.143 dB
Peak SAR (extrapolated) = 0.220 W/kg
SAR(1 g) = 0.127 mW/g; SAR(10 g) = 0.073 mW/g
Maximum value of SAR (measured) = 0.137 mW/g



0 dB = 0.137mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/14

Body_GSM1900 Ch661_Vertical Back in Straight Mode_GPRS10

DUT: 8N2204


Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (31x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.299 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.20 V/m; Power Drift = 0.123 dB
Peak SAR (extrapolated) = 0.441 W/kg
SAR(1 g) = 0.258 mW/g; SAR(10 g) = 0.144 mW/g
Maximum value of SAR (measured) = 0.282 mW/g



0 dB = 0.282mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/14

Body_GSM1900 Ch661_Vertical Back in Vertical Mode_GPRS10

DUT: 8N2204


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.021 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.95 V/m; Power Drift = -0.191 dB
Peak SAR (extrapolated) = 0.033 W/kg
SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.011 mW/g
Maximum value of SAR (measured) = 0.020 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

Body_GSM1900 Ch661_Vertical Front in Vertical Mode_GPRS10

DUT: 8N2204

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51.1$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C


DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.023 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.90 V/m; Power Drift = -0.124 dB
Peak SAR (extrapolated) = 0.037 W/kg
SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.013 mW/g
Maximum value of SAR (measured) = 0.021 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.90 V/m; Power Drift = -0.124 dB
Peak SAR (extrapolated) = 0.036 W/kg
SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.013 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4182_Horizontal Up in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.956$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 ; Liquid Temperature : 21.3

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.208 mW/g


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.0 V/m; Power Drift = -0.207 dB

Peak SAR (extrapolated) = 0.273 W/kg

SAR(1 g) = 0.189 mW/g; SAR(10 g) = 0.118 mW/g

Maximum value of SAR (measured) = 0.208 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4182_Veritical Back in Vertical Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 836.4 MHz;Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.956$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 ; Liquid Temperature : 21.3

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.174 mW/g


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = -0.172 dB

Peak SAR (extrapolated) = 0.247 W/kg

SAR(1 g) = 0.142 mW/g; SAR(10 g) = 0.074 mW/g

Maximum value of SAR (measured) = 0.160 mW/g



0 dB = 0.160mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4182_Verical Front in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 836.4 MHz;Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.956$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.6 ; Liquid Temperature : 21.3

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (31x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.089 mW/g


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.14 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.276 W/kg

SAR(1 g) = 0.100 mW/g; SAR(10 g) = 0.053 mW/g

Maximum value of SAR (measured) = 0.122 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4182_Veritical Back in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 836.4 MHz;Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.956$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.8 ; Liquid Temperature : 21.3

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (31x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.081 mW/g


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.97 V/m; Power Drift = -0.195 dB

Peak SAR (extrapolated) = 0.112 W/kg

SAR(1 g) = 0.076 mW/g; SAR(10 g) = 0.046 mW/g

Maximum value of SAR (measured) = 0.082 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4182_Veritical Back in Vertical Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.956$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 ; Liquid Temperature : 21.3

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4182/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.143 mW/g


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.4 V/m; Power Drift = -0.121 dB

Peak SAR (extrapolated) = 0.216 W/kg

SAR(1 g) = 0.125 mW/g; SAR(10 g) = 0.066 mW/g

Maximum value of SAR (measured) = 0.141 mW/g



0 dB = 0.141mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4233_Horizontal Down in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 847$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.7 ; Liquid Temperature : 21.3


DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4233/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.445 mW/g

Ch4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.2 V/m; Power Drift = 0.063 dB
Peak SAR (extrapolated) = 0.688 W/kg
SAR(1 g) = 0.423 mW/g; SAR(10 g) = 0.246 mW/g
Maximum value of SAR (measured) = 0.450 mW/g

Ch4233/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.2 V/m; Power Drift = 0.063 dB
Peak SAR (extrapolated) = 0.697 W/kg
SAR(1 g) = 0.378 mW/g; SAR(10 g) = 0.204 mW/g
Maximum value of SAR (measured) = 0.465 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

Body_WCDMA850 Ch4233_Verical Front in Vertical Mode_RMC12.2K

DUT: 8N2204


Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 847$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4233/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.006 mW/g

Ch4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.35 V/m; Power Drift = -0.072 dB
Peak SAR (extrapolated) = 0.009 W/kg
SAR(1 g) = 0.00514 mW/g; SAR(10 g) = 0.00301 mW/g
Maximum value of SAR (measured) = 0.006 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9262_Horizontal Down in Straight Mode_RMC12.2K

DUT: 8N2204


Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9262/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.51 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.4 V/m; Power Drift = 0.098 dB
Peak SAR (extrapolated) = 2.00 W/kg
SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.785 mW/g
Maximum value of SAR (measured) = 1.40 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9400_Veritical Back in Vertical Mode_RMC12.2k

DUT: 8N2204

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: f = 1880 MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9400/Area Scan (21x51x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.043 mW/g

Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.49 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.073 W/kg

SAR(1 g) = 0.040 mW/g; SAR(10 g) = 0.023 mW/g

Maximum value of SAR (measured) = 0.043 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.49 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.054 W/kg

SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.017 mW/g

Maximum value of SAR (measured) = 0.034 mW/g



0 dB = 0.034mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9400_Horizontal Up in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.6 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9400/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.748 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.9 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.690 mW/g; SAR(10 g) = 0.412 mW/g

Maximum value of SAR (measured) = 0.723 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9400_Veritical Back in Straight Mode_RMC12.2k

DUT: 8N2204

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: f = 1880 MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 ; Liquid Temperature : 21.6


DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9400/Area Scan (21x51x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.042 mW/g

Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.47 V/m; Power Drift = -0.172 dB
Peak SAR (extrapolated) = 0.071 W/kg
SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.023 mW/g
Maximum value of SAR (measured) = 0.042 mW/g

Ch9400/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.47 V/m; Power Drift = -0.172 dB
Peak SAR (extrapolated) = 0.052 W/kg
SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.017 mW/g
Maximum value of SAR (measured) = 0.033 mW/g



0 dB = 0.033mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9400_Vertical Front in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: f = 1880 MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9400/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.306 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = -0.068 dB

Peak SAR (extrapolated) = 0.446 W/kg

SAR(1 g) = 0.257 mW/g; SAR(10 g) = 0.148 mW/g

Maximum value of SAR (measured) = 0.279 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9400_Veritical Back in Straight Mode_RMC12.2K

DUT: 8N2204

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: f = 1880 MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9400/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.626 mW/g


Ch9400/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.7 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.902 W/kg

SAR(1 g) = 0.531 mW/g; SAR(10 g) = 0.300 mW/g

Maximum value of SAR (measured) = 0.583 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

Body_WCDMA1900 Ch9262_Vertical Front in Vertical Mode_RMC12.2K

DUT: 8N2204


Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.6 °C; Liquid Temperature : 21.5 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9262/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.047 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.18 V/m; Power Drift = 0.078 dB
Peak SAR (extrapolated) = 0.065 W/kg
SAR(1 g) = 0.043 mW/g; SAR(10 g) = 0.028 mW/g
Maximum value of SAR (measured) = 0.046 mW/g



0 dB = 0.046mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA850 Ch334_Horizontal Down in Straight Mode_RTAP-38.4K

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835.02$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.397 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.8 V/m; Power Drift = 0.050 dB
Peak SAR (extrapolated) = 0.849 W/kg
SAR(1 g) = 0.391 mW/g; SAR(10 g) = 0.227 mW/g
Maximum value of SAR (measured) = 0.431 mW/g



0 dB = 0.431mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA850 Ch334_Horizontal Down in Straight Mode_RTAP-38.4K

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835.02$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.397 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.8 V/m; Power Drift = 0.050 dB
Peak SAR (extrapolated) = 0.849 W/kg
SAR(1 g) = 0.391 mW/g; SAR(10 g) = 0.227 mW/g
Maximum value of SAR (measured) = 0.431 mW/g



0 dB = 0.431mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_CDMA850 Ch334_Horizontal Up in Straight Mode_RC1

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835.02$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.213 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.3 V/m; Power Drift = -0.155 dB
Peak SAR (extrapolated) = 0.292 W/kg
SAR(1 g) = 0.199 mW/g; SAR(10 g) = 0.126 mW/g
Maximum value of SAR (measured) = 0.209 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_CDMA850 Ch334_Vertical Back in Vertical Mode_RC1

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835.02$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (21x51x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.148 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.3 V/m; Power Drift = -0.152 dB
Peak SAR (extrapolated) = 0.261 W/kg
SAR(1 g) = 0.141 mW/g; SAR(10 g) = 0.070 mW/g
Maximum value of SAR (measured) = 0.160 mW/g



0 dB = 0.160mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_CDMA850 Ch334_Vertical Front in Straight Mode_RC1

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835.02$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.073 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.98 V/m; Power Drift = -0.130 dB
Peak SAR (extrapolated) = 0.113 W/kg
SAR(1 g) = 0.064 mW/g; SAR(10 g) = 0.041 mW/g
Maximum value of SAR (measured) = 0.072 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_CDMA850 Ch334_Verical Back in Straight Mode_RC1

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 835.02$ MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.088 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.82 V/m; Power Drift = 0.015 dB
Peak SAR (extrapolated) = 0.129 W/kg
SAR(1 g) = 0.084 mW/g; SAR(10 g) = 0.049 mW/g
Maximum value of SAR (measured) = 0.093 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

Body_CDMA850 Ch334_Vertical Front in Vertical Mode_RTAP-38.4k

DUT: 8N2204

Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: f = 835.02 MHz; $\sigma = 0.955$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch334/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.006 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.34 V/m; Power Drift = 0.095 dB
Peak SAR (extrapolated) = 0.011 W/kg
SAR(1 g) = 0.0052 mW/g; SAR(10 g) = 0.00304 mW/g
Maximum value of SAR (measured) = 0.006 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch25_Horizontal Down in Straight Mode_RETAP-128

DUT: 8N2204


Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch25/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.856 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.2 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 1.50 W/kg
SAR(1 g) = 0.716 mW/g; SAR(10 g) = 0.411 mW/g
Maximum value of SAR (measured) = 0.742 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch600_Verical Back in Vertical Mode_RC1

DUT: 8N2204

Communication System: CDMA ; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: f = 1880 MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.6 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch600/Area Scan (21x51x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.016 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.53 V/m; Power Drift = -0.192 dB

Peak SAR (extrapolated) = 0.027 W/kg

SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00848 mW/g

Maximum value of SAR (measured) = 0.016 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.53 V/m; Power Drift = -0.192 dB

Peak SAR (extrapolated) = 0.017 W/kg

SAR(1 g) = 0.0097 mW/g; SAR(10 g) = 0.00611 mW/g

Maximum value of SAR (measured) = 0.011 mW/g



0 dB = 0.011mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch600_Horizontal Up in Straight Mode_RC1

DUT: 8N2204

Communication System: CDMA ; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch600/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.220 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.97 V/m; Power Drift = 0.185 dB

Peak SAR (extrapolated) = 0.419 W/kg

SAR(1 g) = 0.229 mW/g; SAR(10 g) = 0.136 mW/g

Maximum value of SAR (measured) = 0.249 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch600_Verical Back in Vertical Mode_RC1

DUT: 8N2204

Communication System: CDMA ; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.4 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch600/Area Scan (21x51x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.015 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.53 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.024 W/kg

SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00883 mW/g

Maximum value of SAR (measured) = 0.015 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.53 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.025 W/kg

SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00662 mW/g

Maximum value of SAR (measured) = 0.012 mW/g



0 dB = 0.012mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch600_Verical Front in Straight Mode_RC1

DUT: 8N2204

Communication System: CDMA ; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch600/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.098 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.07 V/m; Power Drift = 0.105 dB

Peak SAR (extrapolated) = 0.146 W/kg

SAR(1 g) = 0.087 mW/g; SAR(10 g) = 0.050 mW/g

Maximum value of SAR (measured) = 0.093 mW/g



0 dB = 0.093mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch600_Vertical Back in Straight Mode_RC1

DUT: 8N2204

Communication System: CDMA ; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch600/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.221 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.02 V/m; Power Drift = 0.160 dB

Peak SAR (extrapolated) = 0.276 W/kg

SAR(1 g) = 0.179 mW/g; SAR(10 g) = 0.100 mW/g

Maximum value of SAR (measured) = 0.208 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/22

Body_CDMA1900 Ch25_Vertical Front in Vertical Mode_RETAP-128

DUT: 8N2204

Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.5 °C


DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch25/Area Scan (41x41x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.019 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.31 V/m; Power Drift = 0.182 dB
Peak SAR (extrapolated) = 0.038 W/kg
SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.013 mW/g
Maximum value of SAR (measured) = 0.022 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.31 V/m; Power Drift = 0.182 dB
Peak SAR (extrapolated) = 0.040 W/kg
SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.012 mW/g
Maximum value of SAR (measured) = 0.025 mW/g



0 dB = 0.025mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/13

Body_GSM850 Ch251_Horizontal Down in Straight Mode_GPRS10_2D

DUT: 8N2204


Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:4
Medium: MSL_850 Medium parameters used: f = 849 MHz; sigma = 0.967 mho/m; epsilon_r = 52.5; rho = 1000 kg/m^3
Ambient Temperature : 22.5 ; Liquid Temperature : 21.5

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch251/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.896 mW/g

Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.6 V/m; Power Drift = -0.135 dB
Peak SAR (extrapolated) = 1.49 W/kg
SAR(1 g) = 0.851 mW/g; SAR(10 g) = 0.479 mW/g
Maximum value of SAR (measured) = 0.936 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_GSM1900 Ch661_Horizontal Down in Straight Mode_GPRS10_2D

DUT: 8N2204


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4
Medium: MSL_1900 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 51$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch661/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.657 mW/g

Ch661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.6 V/m; Power Drift = -0.010 dB
Peak SAR (extrapolated) = 0.952 W/kg
SAR(1 g) = 0.603 mW/g; SAR(10 g) = 0.358 mW/g
Maximum value of SAR (measured) = 0.627 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/11

Body_WCDMA850 Ch4233_Horizontal Down in Straight Mode_RMC12.2K_2D

DUT: 8N2204

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 847$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.7 ; Liquid Temperature : 21.3

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(5.91, 5.91, 5.91); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2008/5/21
- Phantom: SAM-Left; Type: QD 000 P40 C; Serial: TP-1477
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch4233/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.445 mW/g

Ch4233/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 0.688 W/kg

SAR(1 g) = 0.423 mW/g; SAR(10 g) = 0.246 mW/g

Maximum value of SAR (measured) = 0.450 mW/g


Ch4233/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 0.697 W/kg

SAR(1 g) = 0.378 mW/g; SAR(10 g) = 0.204 mW/g

Maximum value of SAR (measured) = 0.465 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_WCDMA1900 Ch9262_Horizontal Down in Straight Mode_RMC12.2K_2D

DUT: 8N2204


Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9262/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.51 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.4 V/m; Power Drift = 0.098 dB
Peak SAR (extrapolated) = 2.00 W/kg
SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.785 mW/g
Maximum value of SAR (measured) = 1.40 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA850 Ch334_Horizontal Down in Straight Mode_RTAP-38.4K_2D

DUT: 8N2204


Communication System: CDMA ; Frequency: 835.02 MHz;Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: f = 835.02 MHz; $\sigma = 0.954$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.4 ; Liquid Temperature : 21.4

DASY5 Configuration:

- Probe: ET3DV6 - SN1788; ConvF(6.34, 6.34, 6.34); Calibrated: 2008/9/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Back; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.2 Build 87

Ch334/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.397 mW/g

Ch334/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.8 V/m; Power Drift = 0.050 dB
Peak SAR (extrapolated) = 0.849 W/kg
SAR(1 g) = 0.391 mW/g; SAR(10 g) = 0.227 mW/g
Maximum value of SAR (measured) = 0.431 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2008/12/20

Body_CDMA1900 Ch25_Horizontal Down in Straight Mode_RETAP-128_2D

DUT: 8N2204


Communication System: CDMA ; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 ; Liquid Temperature : 21.6

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2008/11/12
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch25/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.856 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.2 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 1.50 W/kg
SAR(1 g) = 0.716 mW/g; SAR(10 g) = 0.411 mW/g
Maximum value of SAR (measured) = 0.742 mW/g





Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2009/2/11

Body_WCDMA1900 Ch9262_Horizontal Down in Straight Mode_RMC12.2K_1cm Gap_Back-Off SAR

DUT: 8N2204

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: MSL_1900 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³
Ambient Temperature : 22.5 °C; Liquid Temperature : 21.4 °C

DASY4 Configuration:

- Probe: ET3DV6 - SN1787; ConvF(4.49, 4.49, 4.49); Calibrated: 2008/8/26
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2008/9/22
- Phantom: SAM-Right; Type: QD 000 P40 C; Serial: TP-1383
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Ch9262/Area Scan (41x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.720 mW/g

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.4 V/m; Power Drift = -0.101 dB
Peak SAR (extrapolated) = 1.02 W/kg
SAR(1 g) = 0.640 mW/g; SAR(10 g) = 0.378 mW/g
Maximum value of SAR (measured) = 0.681 mW/g

