



Appendix F - FCC 3G SAR Measurement Procedures

Conducted Output Power:

The EUT was tested according to the requirements of the FCC 3G procedures and the 3.1.2.3.4. A detailed analysis of the output power verification is provided as the table below:


Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Midd Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				1013	384	777
CDMA2000 BC0	FCH	1	1	1	55	Full	All Up	23.78	24.05	23.75
		3	3	3	55	Full	All Up	23.83	24.09	23.78
	FCH+SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	23.68	24.02	23.65

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Midd Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				25	600	1175
CDMA2000 BC1	FCH	1	1	1	55	Full	All Up	23.46	23.47	23.61
		3	3	3	55	Full	All Up	23.53	23.50	23.54
	FCH+SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	23.42	23.55	23.60

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Midd Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				1215	1225	1275
CDMA2000 BC14 (G Block)	FCH	1	1	1	55	Full	All Up	23.24	23.17	22.89
		3	3	3	55	Full	All Up	23.07	23.03	22.81
	FCH+SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	22.96	22.95	22.74

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Midd Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				25	425	875
CDMA2000 BC15	FCH	1	1	1	55	Full	All Up	23.38	23.56	23.46
		3	3	3	55	Full	All Up	23.29	23.48	23.41
	FCH+SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	23.28	23.39	23.27

CDMA2000 Setup Configuration:



Setup Configuration

1. The EUT was connected to System Simulator, Agilent 8960. Refer to the drawing of Setup Configuration.
2. The RF path losses were compensated into the measurements.
3. A call was established between EUT and System Simulator with following setting:
 - a. Set the Radio Configuration to test mode1 or test mode 3
 - b. Set the Service Option to SO55 or SO32
 - c. Set the Power Control to All Up for (FCH) and (FCH+SCH)
4. The transmitted maximum output power was recorded.

Call Setup Screen		
Call Control	Active Cell Operating Mode	Call Parm
Close Menu	Mobile Station Information	
	ESN (Hex):	
	ESN (Dec):	
	NCC:	
	MNC:	
	MSIN:	
	Slot Class:	
	Slot Cycle Index: ----	
	Protocol Revision:	
	FCH Service Option Setup	
	Service Option	S055 (Loopback)
	Service Option f	S09 (Loopback)
	Service Option f	S01 (Voice)
	Service Option f	S02 (Loopback)
	Service Option f	S03 (Voice)
	Service Option f	S06 (SMS)
	Service Option f	S055 (Loopback)
	Service Option f	S068 (Voice)
	Active Cell	Sys Type: IS-2000
	Idle	
	IntRef	Offset
		1 of 4

Test Mode 1 in Radio Configuration 1 with Service Option 55



Call Setup Screen																					
Call Control	Active Cell Operating Mode		Call Parm																		
Close Menu	Mobile Station Information ESN (Hex): ESN (Dec): MCC: MNC: MSIN: Slot Class: Slot Cycle Index: ---- Protocol Revision:		Cell Power -86.00 dBm/1.23 MHz Cell Band US PCS Channel 1175																		
	FCH Service Option Setup		Protocol Rev 6 (IS-2000-0)																		
	<table border="1"> <thead> <tr> <th>Service Option</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>S055 (Loopback)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S09 (Loopback)</td> <td>S09 (Loopback)</td> </tr> <tr> <td>S01 (Voice)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S02 (Loopback)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S03 (Voice)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S06 (SIS)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S055 (Loopback)</td> <td></td> </tr> <tr> <td>S032 (+ F-SCH)</td> <td></td> </tr> </tbody> </table>		Service Option	Value	S055 (Loopback)	S055 (Loopback)	S09 (Loopback)	S09 (Loopback)	S01 (Voice)	S055 (Loopback)	S02 (Loopback)	S055 (Loopback)	S03 (Voice)	S055 (Loopback)	S06 (SIS)	S055 (Loopback)	S055 (Loopback)		S032 (+ F-SCH)		Radio Config (Fud3, Rvs3) S055 (Loopback)
	Service Option	Value																			
	S055 (Loopback)	S055 (Loopback)																			
	S09 (Loopback)	S09 (Loopback)																			
	S01 (Voice)	S055 (Loopback)																			
	S02 (Loopback)	S055 (Loopback)																			
	S03 (Voice)	S055 (Loopback)																			
	S06 (SIS)	S055 (Loopback)																			
S055 (Loopback)																					
S032 (+ F-SCH)																					
Active Cell Idle		Sys Type: IS-2000																			
IntRef Offset		FCH Service Option Setup																			
		1 of 4																			

Test Mode 3 in Radio Configuration 3 with Service Option 55

Call Setup Screen																					
Call Control	Active Cell Operating Mode		Call Parm																		
Close Menu	Mobile Station Information ESN (Hex): ESN (Dec): MCC: MNC: MSIN: Slot Class: Slot Cycle Index: ---- Protocol Revision:		Cell Power -86.00 dBm/1.23 MHz Cell Band US PCS Channel 1175																		
	FCH Service Option Setup		Protocol Rev 6 (IS-2000-0)																		
	<table border="1"> <thead> <tr> <th>Service Option</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>S055 (Loopback)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S09 (Loopback)</td> <td>S09 (Loopback)</td> </tr> <tr> <td>S02 (Loopback)</td> <td>S032 (+ SCH)</td> </tr> <tr> <td>S03 (Voice)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S06 (SIS)</td> <td>S055 (Loopback)</td> </tr> <tr> <td>S055 (Loopback)</td> <td></td> </tr> <tr> <td>S032 (+ F-SCH)</td> <td></td> </tr> <tr> <td>S032 (+ SCH)</td> <td></td> </tr> </tbody> </table>		Service Option	Value	S055 (Loopback)	S055 (Loopback)	S09 (Loopback)	S09 (Loopback)	S02 (Loopback)	S032 (+ SCH)	S03 (Voice)	S055 (Loopback)	S06 (SIS)	S055 (Loopback)	S055 (Loopback)		S032 (+ F-SCH)		S032 (+ SCH)		Radio Config (Fud3, Rvs3) S032 (+ SCH)
	Service Option	Value																			
	S055 (Loopback)	S055 (Loopback)																			
	S09 (Loopback)	S09 (Loopback)																			
	S02 (Loopback)	S032 (+ SCH)																			
	S03 (Voice)	S055 (Loopback)																			
	S06 (SIS)	S055 (Loopback)																			
	S055 (Loopback)																				
S032 (+ F-SCH)																					
S032 (+ SCH)																					
Active Cell Idle		Sys Type: IS-2000																			
IntRef Offset		FCH Service Option Setup																			
		1 of 4																			

Test Mode 3 in Radio Configuration 3 with Service Option 32



Reference:

- [1] SAR Measurement Procedures for 3G Devices CDMA 2000/Ev-Do/WCDMA/HSDPA, June 2006
Laboratory Division Office of Engineering and Technology Federal Communications Commission
- [2] 3.1.2.3.4 Maximum RF Output Power 3GPP2 C.S0033-0 Version 2.0, Date: 12 December 2003
Recommended Minimum Performance Standards for cdma2000 High Rate Packet Data Access
Terminal