



Report No.: SZ12100107W01



FCC TEST REPORT

Issued to

ZTE Corporation

For

GSM Dual-Band GPRS Digital Mobile phone

Model Name: ZTE F310
 Trade Name: ZTE 中兴
 Brand Name: ZTE 中兴
 FCC ID : Q78-F310
 Standard: 47 CFR Part 22 Subpart H
 47 CFR Part 24 Subpart E
 Test date: 2012-10-23 to 2012-11-22
 Issue date: 2012-11-22

Shenzhen Morlab Communications Technology Co., Ltd.



Tested by Nie Quan

Nie Quan

Date 2012.11.22

Approved by Wu Xuewen



Date 2012.11.22

Reviewed by Peng Huarui

Peng Huarui

Date 2012.11.22



IEEE 1725

OTA




電訊管理局



Testing Laboratory 2036



Official Observer of Global Certification Forum



BQTF



Reg. No. 741109

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer, Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1	EUT Description	3
1.2	Test Standards and Results	5
1.3	Facilities and Accreditations	6
2.	47 CFR PART 2, PART 22H & 24E REQUIREMENTS	7
2.1	Conducted RF Output Power	7
2.2	99% Occupied Bandwidth	19
2.3	Frequency Stability	33
2.4	Conducted Out of Band Emissions	39
2.5	Band Edge	71
2.6	Transmitter Radiated Power (EIRP/ERP)	85
2.7	Radiated Out of Band Emissions	92

Change History		
Issue	Date	Reason for change
1.0	Nov 22, 2012	First edition

1. GENERAL INFORMATION

1.1 EUT Description

EUT Type: GSM Dual-Band GPRS Digital Mobile phone
Serial No.....: (n.a, marked #1 by test site)
Hardware Version.....: F310_V1_Z0_S_G2CL103
Software Version: F310_V1AMB_A
Applicant: ZTE Corporation
ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan
District, Shenzhen, Guangdong, P.R.China
Manufacturer: ZTE Corporation
ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan
District, Shenzhen, Guangdong, P.R.China
Frequency Range.....: GSM 850MHz:
Tx: 824.20 - 848.80MHz (at intervals of 200kHz);
Rx: 869.20 - 893.80MHz (at intervals of 200kHz)
GSM 1900MHz:
Tx: 1850.20 - 1909.80MHz (at intervals of 200kHz);
Rx: 1930.20 - 1989.80MHz (at intervals of 200kHz)
WCDMA 850MHz
Tx: 826.4 - 846.6MHz (at intervals of 200kHz);
Rx: 871.4 - 891.6MHz (at intervals of 200kHz)
WCDMA 1900MHz
Tx: 1852.4 - 1907.6MHz (at intervals of 200kHz);
Rx: 1932.4 - 1987.6MHz (at intervals of 200kHz)
Modulation Type.....: GPRS/GSM Mode with GMSK Modulation
EDGE Mode with 8PSK Modulation
WCDMA Mode with QPSK Modulation
HSDPA Mode with QPSK Modulation
HSUPA Mode with QPSK Modulation
Multislot Class.....: GPRS: Multislot Class12,EGPRS: Multislot Class12
Antenna Type.....: PIFA Antenna
Emission Designators: GSM:251KGXW,
EGPRS:247KG7W,
WCDMA:4M18F9W
GPRS:251KGXW

Note 1: The transmitter (Tx) frequency arrangement of the Cellular 850MHz band used by the EUT can be represented with the formula $F(n)=824.2+0.2*(n-128)$, $128 \leq n \leq 251$; the lowest, middle, highest channel numbers (ARFCHs) used and tested in this report are separately 128 (824.2MHz), 190 (836.6MHz) and 251 (848.8MHz).

Note 2: The transmitter (Tx) frequency arrangement of the PCS 1900MHz band used by the EUT can be represented with the formula $F(n)=1850.2+0.2*(n-512)$, $512 \leq n \leq 810$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 512 (1850.2MHz), 661 (1880.0MHz) and 810 (1909.8MHz).

Note 3: The transmitter (Tx) frequency arrangement of the WCDMA 850MHz band used by the EUT can be represented with the formula $F(n)=826.4+0.2*(n-4132)$, $4132 \leq n \leq 4233$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 4132 (826.4MHz), 4175(835MHz) and 4233 (846.6MHz).

Note 4: The transmitter (Tx) frequency arrangement of the WCDMA 1900MHz band used by the EUT can be represented with the formula $F(n)=1852.4+0.2*(n-9262)$, $9262 \leq n \leq 9538$; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 9262 (1852.4MHz), 9400 (1880MHz) and 9538 (1907.6MHz).

Note 5: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part 24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-09 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-09 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-09 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	2.1046	Conducted RF Output Power	PASS
2	2.1049 22.917 24.238	99% Occupied Bandwidth	PASS
3	2.1055 22.355 24.235	Frequency Stability	PASS
4	2.1051 2.1057 22.917 24.238	Conducted Out of Band Emissions	PASS
5	2.1051 2.1057 22.917 24.238	Band Edge	PASS
6	22.913 24.232	Transmitter Radiated Power (EIPR/ERP)	PASS
7	2.1053 2.1057 22.917 24.238	Radiated Out of Band Emissions	PASS

NOTE: Measurement method according to TIA/EIA 603.D-2010

1.3 Facilities and Accreditations

1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 2, PART 22H & 24E REQUIREMENTS


2.1 Conducted RF Output Power

2.1.1 Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

The Power Meter was just used for the Conducted RF Output Power test of WCDMA Model.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Agilent	E5515C	GB43130131	2012.05	2013.05
Spectrum Analyzer	Agilent	E7405A	US44210471	2012.05	2013.05
Power Meter	Agilent	E4418B	GB43318055	2012.05	2013.05
Power Sensor	Agilent	8482A	MY41091706	2012.05	2013.05
Power Splitter	Weinschel	1506A	NW521	2012.05	2013.05
Attenuator 1	Resnet	20dB	(n.a.)	2012.05	2013.05
Attenuator 2	Resnet	3dB	(n.a.)	2012.05	2013.05

2.1.3 Test Results

Here the lowest, middle and highest channels are selected to perform testing to verify the conducted RF output power of the EUT.

1. GSM Model Test Verdict:

Band	Channel	Frequency (MHz)	Measured Output Power		Limit	Verdict
			dBm	Refer to Plot	dBm	
GSM 850MHz	128	824.2	33.1	Plot A1 to A3	35	PASS
	190	836.6	32.74			PASS
	251	848.8	32.59			PASS
GSM 1900MHz	512	1850.2	29.58	Plot B1 to B3	32	PASS
	661	1880.0	28.65			PASS
	810	1909.8	28.11			PASS
GPRS 850MHz	128	824.2	32.29	Plot C1 to C3 ^{Note 1}	35	PASS
	190	836.6	31.92			PASS
	251	848.8	31.77			PASS
GPRS 1900MHz	512	1850.2	28.93	Plot D1 to D3 ^{Note 1}	32	PASS
	661	1880.0	27.86			PASS
	810	1909.8	27.34			PASS
EGPRS 850MHz	128	824.2	31.48	Plot E1 to E3 ^{Note 1}	35	PASS
	190	836.6	31.31			PASS
	251	848.8	32.09			PASS
EGPRS 1900MHz	512	1850.2	28.79	Plot F1 to F3 ^{Note 1}	32	PASS
	661	1880.0	27.93			PASS
	810	1909.8	27.95			PASS

Note 1: For the GPRS and EGPRS model, all the slots were tested and just the worst data was record in this report.

GPRS Mode Conducted peak output power

Band	Channel	Frequency (MHz)	Output Power(dBm)			
			Slot 1	Slot 2	Slot 3	Slot 4
GSM 850	128	824.2	32.29	31.98	30.37	29.22
	190	836.6	31.92	31.24	30.30	29.15
	251	848.8	31.77	31.90	30.23	29.08
PCS 1900	512	1850.2	28.93	28.02	27.38	27.07
	661	1880.0	27.86	27.66	27.43	26.78
	810	1909.8	27.34	27.12	27.25	26.37


EDGE Mode Conducted peak output power

Band	Channel	Frequency (MHz)	Output Power(dBm)			
			Slot 1	Slot 2	Slot 3	Slot 4
GSM 850	128	824.2	31.48	30.76	30.15	29.10
	190	836.6	31.31	30.92	30.22	29.18
	251	848.8	32.09	31.05	30.11	29.20
PCS 1900	512	1850.2	28.79	28.06	27.41	27.21
	661	1880.0	27.93	27.43	27.03	26.65
	810	1909.8	27.95	27.13	26.72	26.11


2. WCDMA Model Test Verdict:

Item	band	WCDMA 850			WCDMA 1900		
	ARFCN	4132	4175	4233	9262	9400	9538
	subtest	dBm			dBm		
5.2(WCDMA)	non	21.69	21.87	21.79	22.78	22.65	22.69
HSDPA	1	21.67	21.73	21.68	22.62	22.59	22.61
	2	21.65	21.61	21.69	22.59	22.57	22.62
	3	21.17	21.15	21.52	22.13	22.01	22.12
	4	21.16	21.11	21.58	22.09	22.03	22.11
HSUPA	1	21.65	21.55	21.65	22.59	22.55	22.56
	2	19.78	19.76	19.73	20.56	20.57	20.56
	3	20.59	20.52	20.63	21.57	21.56	21.55
	4	19.71	19.67	19.65	20.58	20.56	20.51
	5	21.61	21.51	21.57	22.57	22.53	22.59
Note:	The Conducted RF Output Power test of WCDMA /HSDPA /HSUPA was tested by power meter.						


3. GSM Model Test Plots:




(Plot A1: GSM 850MHz Channel = 128)




(Plot A2: GSM 850MHz Channel = 190)




(Plot A3: GSM 850MHz Channel = 251)




(Plot B1: GSM 1900MHz Channel = 512)




(Plot B2: GSM 1900MHz Channel = 661)




(Plot B3: GSM 1900MHz Channel = 810)




(Plot C1: GPRS 850MHz Channel = 128)




(Plot C2: GPRS 850MHz Channel = 190)




(Plot C3: GPRS 850MHz Channel = 251)




(Plot D1: GPRS 1900MHz Channel = 512)




(Plot D2: GPRS 1900MHz Channel = 661)




(Plot D3: GPRS 1900Hz Channel = 810)




(Plot E 1: EGPRS 850MHz Channel = 128)




(Plot E 2: EGPRS 850MHz Channel = 190)




(Plot E 3: EGPRS 850MHz Channel = 251)



(Plot F 1: EGPRS 1900MHz Channel = 512)



(Plot F 2: EGPRS 1900MHz Channel = 661)



(Plot F 3: EGPRS 1900MHz Channel = 810)

2.2 99% Occupied Bandwidth

2.2.1 Definition

According to FCC section 2.1049 and FCC § 22.917 & 24.238, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth,

2.2.2 Test Description

See section 2.1.2 of this report.

2.2.3 Test Verdict

Here the lowest, middle and highest channels are selected to perform testing to verify the 99% occupied bandwidth.


1. Test Verdict:

Band	Channel	Frequency (MHz)	26dB bandwidth	99% Occupied Bandwidth	Refer to Plot
GSM 850MHz	128	824.2	322.696 kHz	243.4836 kHz	Plot A
	190	836.6	316.125 kHz	246.5572 kHz	Plot B
	251	848.8	320.965 kHz	251.2678 kHz	Plot C
GSM 1900MHz	512	1850.2	320.510 kHz	246.0821 kHz	Plot D
	661	1880.0	322.504 kHz	244.8943 kHz	Plot E
	810	1909.8	321.701 kHz	249.6423 kHz	Plot F
EDGE 850MHz	128	824.2	320.641 kHz	243.0872 kHz	Plot G
	190	836.6	320.991 kHz	242.6634 kHz	Plot H
	251	848.8	329.641 kHz	243.6410 kHz	Plot I
EDGE 1900MHz	512	1850.2	309.559 kHz	238.3624 kHz	Plot J
	661	1880.0	321.638 kHz	247.1988 kHz	Plot K
	810	1909.8	317.775 kHz	243.8860 kHz	Plot L
WCDMA 850MHz	4175	835	4.712 MHz	4.1720 MHz	Plot M
WCDMA 1900MHz	9400	1880	4.704 MHz	4.1669 MHz	Plot N
HSDPA 850MHz	4175	835	4.708 MHz	4.1656 MHz	Plot O
HSDPA 1900MHz	9400	1880	4.707 MHz	4.1667 MHz	Plot P
HSUPA 850MHz	4175	835	4.698 MHz	4.1571 MHz	Plot Q
HSUPA 1900MHz	9400	1880	4.690 MHz	4.1798 MHz	Plot R
GPRS 850MHz	128	824.2	314.883kHz	244.6038 kHz	Plot S

Band	Channel	Frequency (MHz)	26dB bandwidth	99% Occupied Bandwidth	Refer to Plot
	190	836.6	316.023 kHz	244.4861 kHz	Plot T
	251	848.8	321.815 kHz	250.7953 kHz	Plot U
GPRS 1900MHz	512	1850.2	323.746 kHz	246.7347 kHz	Plot V
	661	1880.0	319.623 kHz	251.1446 kHz	Plot W
	810	1909.8	321.862 kHz	244.0260 kHz	Plot X


Note 1: For the GPRS and EGPRS model, all the slots were tested and just the worst data was record in this report.

2. Test Plots:



(Plot A: GSM 850MHz Channel = 128)

Agilent 15:00:23 Oct 27, 2012 T S



Center 836.6 MHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 246.572 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -3.875 kHz
 x dB Bandwidth 316.125 kHz

C:\TMP\IMAGE.GIF file saved

(Plot B: GSM 850MHz Channel = 190)

Agilent 14:59:26 Oct 27, 2012 T S



Center 848.8 MHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 251.2678 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -3.188 kHz
 x dB Bandwidth 320.965 kHz

C:\TMP\IMAGE.GIF file saved

(Plot C: GSM 850MHz Channel = 251)

Agilent 15:05:11 Oct 27, 2012 T S



Center 1.85 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 246.0821 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -2.277 kHz
 x dB Bandwidth 320.510 kHz

C:\TMP\IMAGE.GIF file saved

(Plot D: GSM 1900MHz Channel = 512)

Agilent 15:04:12 Oct 27, 2012 T S



Center 1.88 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 244.8943 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -1.745 kHz
 x dB Bandwidth 322.504 kHz

C:\TMP\IMAGE.GIF file saved

(Plot E: GSM 1900MHz Channel = 661)

Agilent 15:03:35 Oct 27, 2012 T S



Center 1.91 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 249.6423 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -2.213 kHz
 x dB Bandwidth 321.701 kHz

C:\TMP\IMAGE.GIF file saved

(Plot F: GSM 1900MHz Channel = 810)

Agilent 17:30:30 Oct 27, 2012 T S



Center 824.2 MHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 243.0872 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error 277.801 Hz
 x dB Bandwidth 320.641 kHz

C:\TMP\IMAGE.GIF file saved

(Plot G: EDGE 850MHz Channel = 128)

Agilent 17:32:14 Oct 27, 2012 T S



Center 836.6 MHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 242.6634 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -2.121 kHz
 x dB Bandwidth 320.991 kHz

C:\TMP\IMAGE.GIF file saved

(Plot H: EDGE 850MHz Channel = 190)

Agilent 17:32:55 Oct 27, 2012 T S



Center 848.8 MHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 243.6410 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -2.585 kHz
 x dB Bandwidth 329.641 kHz

C:\TMP\IMAGE.GIF file saved

(Plot I: EDGE 850MHz Channel = 251)

Agilent 17:27:30 Oct 27, 2012 T S



Center 1.85 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 238.3624 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -622.616 Hz
 x dB Bandwidth 309.559 kHz

C:\TMP\IMAGE.GIF file saved

(Plot J: EDGE 1900MHz Channel = 512)

Agilent 17:28:38 Oct 27, 2012 T S



Center 1.88 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 247.1988 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -321.742 Hz
 x dB Bandwidth 321.638 kHz

C:\TMP\IMAGE.GIF file saved

(Plot K: EDGE 1900MHz Channel = 661)

Agilent 17:29:20 Oct 27, 2012 T S



Center 1.91 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 100 kHz Sweep 20.07 ms (401 pts)

Occupied Bandwidth
 243.8860 kHz


Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -3.067 kHz
 x dB Bandwidth 317.775 kHz

C:\TMP\IMAGE.GIF file saved

(Plot L: EDGE 1900MHz Channel = 810)

Agilent 09:45:12 Nov 2, 2012 T



Center 835 MHz Span 8 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)


Occupied Bandwidth
 4.1720 MHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -6.036 kHz
 x dB Bandwidth 4.712 MHz

(Plot M: WCDMA 850MHz Channel = 4175)

Agilent 09:47:22 Nov 2, 2012 T



Center 1.88 GHz Span 8 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)


Occupied Bandwidth
 4.1669 MHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error 656.291 Hz
 x dB Bandwidth 4.704 MHz

(Plot N: WCDMA 1900MHz Channel = 9400)

Agilent 09:45:41 Nov 2, 2012 T



Center 835 MHz Span 8 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)


Occupied Bandwidth
 4.1656 MHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -736.936 Hz
 x dB Bandwidth 4.708 MHz

(Plot O: HSDPA 850MHz Channel = 4175)

Agilent 09:47:06 Nov 2, 2012 T




Center 1.88 GHz Span 8 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)

Occupied Bandwidth 4.1667 MHz Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -4.971 kHz
 x dB Bandwidth 4.707 MHz

(Plot P: HSDPA1900MHz Channel = 9400)

Agilent 09:46:09 Nov 2, 2012 T




Center 835 MHz Span 8 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)

Occupied Bandwidth 4.1571 MHz Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -4.834 kHz
 x dB Bandwidth 4.698 MHz

(Plot Q: HSUPA 850MHz Channel = 4175)

Agilent 09:46:42 Nov 2, 2012 T



Center 1.88 GHz Span 8 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)


Occupied Bandwidth
 4.1798 MHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error 1.553 kHz
 x dB Bandwidth 4.690 MHz

(Plot R: HSUPA1900MHz Channel = 9400)

Agilent 14:54:09 Nov 22, 2012 T



Center 824.2 MHz Span 2 MHz
 #Res BW 10 kHz #VBW 300 kHz Sweep 20.01 ms (401 pts)


Occupied Bandwidth
 244.6038 kHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error 1.475 kHz
 x dB Bandwidth 314.883 kHz

(Plot S: GPRS 850MHz Channel = 128)

Agilent 14:53:39 Nov 22, 2012 T



Center 836.6 MHz Span 2 MHz
#Res BW 10 kHz #VBW 300 kHz Sweep 20.01 ms (401 pts)


Occupied Bandwidth
244.4861 kHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -1.910 kHz
x dB Bandwidth 316.023 kHz

(Plot T: GPRS 850MHz Channel = 190)

Agilent 14:53:02 Nov 22, 2012 T



Center 848.8 MHz Span 2 MHz
#Res BW 10 kHz #VBW 300 kHz Sweep 20.01 ms (401 pts)


Occupied Bandwidth
250.7953 kHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -493.309 Hz
x dB Bandwidth 321.815 kHz

(Plot U: GPRS 850MHz Channel = 251)

Agilent 14:50:49 Nov 22, 2012 T



Center 1.85 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 300 kHz Sweep 20.01 ms (401 pts)


Occupied Bandwidth
 246.7347 kHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error 106.519 Hz
 x dB Bandwidth 323.746 kHz

(Plot V: GPRS 1900MHz Channel = 512)

Agilent 14:51:36 Nov 22, 2012 T



Center 1.88 GHz Span 2 MHz
 #Res BW 10 kHz #VBW 300 kHz Sweep 20.01 ms (401 pts)


Occupied Bandwidth
 251.1446 kHz

Occ BW % Pwr 99.00 %
 x dB -26.00 dB

Transmit Freq Error -810.383 Hz
 x dB Bandwidth 319.623 kHz

(Plot W: GPRS 1900MHz Channel = 661)

Agilent 14:52:11 Nov 22, 2012 T



Center 1.91 GHz Span 2 MHz
#Res BW 10 kHz #VBW 300 kHz Sweep 20.01 ms (401 pts)

Occupied Bandwidth
244.0260 kHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -765.317 Hz
x dB Bandwidth 321.862 kHz

(Plot X: GPRS 1900MHz Channel = 810)

2.3 Frequency Stability


2.3.1 Requirement

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to $+50^{\circ}\text{C}$ at intervals of not more than 10°C .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

2.3.2 Test Description

1. Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Agilent	E5515C	GB43130131	2012.05	2013.05
DC Power Supply	Good Will	GPS-3030DD	EF920938	2012.05	2013.05
Temperature Chamber	YinHe Experimental Equip.	HL4003T	(n.a.)	2012.05	2013.05

2.3.3 Test Verdict

The nominal, highest and lowest extreme voltages are separately 3.7VDC, 4.2VDC and 3.6VDC, which are specified by the applicant; the normal temperature here used is 25°C . The frequency

deviation limit of 850MHz band is $\pm 2.5\text{ppm}$, and 1900MHz is $\pm 1\text{ppm}$

1. GSM 850MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 128 (824.2MHz)		Channel = 190 (836.6MHz)		Channel = 251 (848.8MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	10.72	± 2060.5	-9.66	± 2091.5	5.05	± 2122	PASS
	-20	-11.17		19.70		8.41		
	-10	17.28		-11.06		1.19		
	0	-23.03		21.06		34.30		
	+10	-13.02		13.05		17.11		
	+20	-10.39		-12.76		-15.51		
	+30	27.75		-2.05		19.46		
	+40	5.31		-3.77		-6.80		
+50	-22.19	5.39	7.58					
4.2	+25	23.74	19.65	23.11				
3.6	+25	23.29	-20.70	-14.93				

2. GSM 1900MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 512 (1850.2MHz)		Channel = 661 (1880.0MHz)		Channel = 810 (1909.8MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	-10.39	± 1850.2	38.28	± 1880.0	27.27	± 1909.8	PASS
	-20	27.75		-2.15		9.49		
	-10	5.31		40.06		-12.90		
	0	-22.19		1.99		12.66		
	+10	23.74		-19.86		5.05		
	+20	-10.39		-2.32		3.02		
	+30	-18.89		23.12		-13.01		
	+40	44.49		11.33		0.51		
+50	40.72	-17.55	21.45					
4.2	+25	16.15	38.10	-16.04				
3.6	+25	32.34	-22.06	-21.86				

3. EDGE 850MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 128 (824.2MHz)		Channel = 190 (836.6MHz)		Channel = 251 (848.8MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	-3.10	±2060.5	23.12	±2091.5	8.51	±2122	PASS
	-20	38.28		11.33		-12.90		
	-10	-2.15		-17.55		12.66		
	0	40.06		38.10		5.05		
	+10	1.99		-22.06		3.02		
	+20	-19.86		-16.11		10.76		
	+30	39.56		17.76		-16.51		
	+40	46.60		15.64		-2.10		
+50	39.98	3.67	-12.99					
4.2	+25	-15.71	13.95	-7.53				
3.6	+25	-17.70	6.23	6.78				

4. EDGE 1900MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 512 (1850.2MHz)		Channel = 661 (1880.0MHz)		Channel = 810 (1909.8MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	-13.77	±1850.2	23.62	±1880.0	2.47	±1909.8	PASS
	-20	0.62		7.23		-11.76		
	-10	1.65		-24.78		-12.21		
	0	2.47		-1.26		13.33		
	+10	-10.76		-18.68		5.33		
	+20	-2.11		-21.61		35.26		
	+30	13.33		14.58		-26.78		
	+40	5.33		-0.68		19.54		
+50	-2.56	36.87	-16.67					
4.2	+25	17.60	3.88	26.79				
3.6	+25	-8.09	13.12	19.93				

5. WCDMA 850MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 4123 (826.4MHz)		Channel = 4175 (835MHz)		Channel = 4233 (846.6MHz)		
		Hz	Limit	Hz	Limit	Hz	Limit	
3.7	-30	17.29	±2066	11.87	±2087.5	-9.81	±2116.5	PASS
	-20	-7.32		-0.59		-23.82		
	-10	-3.40		21.45		26.39		
	0	16.47		13.45		30.98		
	+10	30.18		1.31		-2.65		
	+20	32.07		-12.52		18.30		
	+30	-7.98		30.62		-12.57		
	+40	26.21		13.45		28.93		
	+50	11.10		-12.52		19.66		
4.2	+25	-6.18	30.62	22.19				
3.6	+25	18.66	-18.00	-18.70				

6. WCDMA 1900MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 9262 (1852.4MHz)		Channel = 9400 (1880.0MHz)		Channel = 9538 (1907.6MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	17.29	±1852.4	18.25	±1880.0	-8.99	±1907.6	PASS
	-20	-7.32		2.49		23.60		
	-10	-3.40		-10.71		14.81		
	0	16.47		-7.77		-3.07		
	+10	30.18		21.97		17.42		
	+20	-2.62		11.87		-10.39		
	+30	22.31		-0.59		17.47		
	+40	0.32		21.45		27.84		
	+50	-13.55		-5.71		-2.53		
4.2	+25	23.21	14.58	20.95				
3.6	+25	22.00	26.37	-23.22				

7. HSDPA 850MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 4123 (826.4MHz)		Channel = 4175 (835MHz)		Channel = 4233 (846.6MHz)		
		Hz	Limit	Hz	Limit	Hz	Limit	
3.7	-30	27.46	±2066	-24.37	±2087.5	15.81	±2116.5	PASS
	-20	-8.56		-13.96		14.41		
	-10	20.65		35.23		21.57		
	0	12.88		-8.31		-24.37		
	+10	-14.75		-13.95		-13.96		
	+20	8.78		-24.37		35.23		
	+30	-1.49		12.88		-8.31		
	+40	17.14		-14.75		-13.95		
4.2	+25	32.03	7.93	7.90				
	3.6	+25	17.51	-31.21	1.78			

8. HSDPA 1900MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 9262 (1852.4MHz)		Channel = 9400 (1880.0MHz)		Channel = 9538 (1907.6MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	11.87	±1852.4	-3.01	±1880	2.61	±1907.6	PASS
	-20	-16.65		21.71		-8.38		
	-10	20.12		14.37		-13.02		
	0	-3.01		-11.21		-8.51		
	+10	21.71		10.60		5.64		
	+20	20.12		-4.81		-3.85		
	+30	-15.01		34.31		9.57		
	+40	22.71		8.36		27.54		
4.2	+25	-11.28	29.43	-2.83				
	3.6	+25	10.33	-2.27	14.42			

9. HSUPA 850MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 4123 (826.4MHz)		Channel = 4175 (835MHz)		Channel = 4233 (846.6MHz)		
		Hz	Limit	Hz	Limit	Hz	Limit	
3.7	-30	29.57	±2066	13.5	±2087.5	13.55	±2116.5	PASS
	-20	-6.20		-15.31		7.43		
	-10	-12.61		-11.79		7.00		
	0	-13.09		-0.44		-7.32		
	+10	-0.38		0.01		-4.91		
	+20	-11.85		-6.64		21.35		
	+30	29.57		24.25		-5.94		
	+40	-11.79		9.63		13.78		
	+50	-0.44		23.76		28.45		
4.2	+25	1.71	-4.57	29.11				
3.6	+25	1.54	5.25	-7.70				

10. HSUPA 1900MHz Band

Test Conditions		Frequency Deviation						Verdict
Power (VDC)	Temperature (°C)	Channel = 9262 (1852.4MHz)		Channel = 9400 (1880.0MHz)		Channel = 9538 (1907.6MHz)		
		Hz	Limits	Hz	Limits	Hz	Limits	
3.7	-30	11.57	±1852.4	-11.79	±1880	8.69	±1907.6	PASS
	-20	21.13		-0.44		2.01		
	-10	7.62		0.01		-4.75		
	0	2.31		13.82		16.38		
	+10	-4.73		-15.25		-1.76		
	+20	16.22		-11.79		23.52		
	+30	-1.55		-0.44		-0.38		
	+40	23.16		1.15		-11.85		
	+50	13.79		-7.94		-5.91		
4.2	+25	-7.08	6.81	25.48				
3.6	+25	22.58	-1.83	-15.78				

2.4 Conducted Out of Band Emissions

2.4.1 Requirement

According to FCC section 22.917(a) and FCC section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.

2.4.2 Test Description

See section 2.1.2 of this report.

2.4.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.


1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-21.89	Plot A1toA1.1	-13	PASS
	190	836.6	-22.31	Plot A2toA2.1		PASS
	251	848.8	-22.62	Plot A3toA3.1		PASS
GSM 1900MHz	512	1850.2	-21.12	Plot B1toB1.1	-13	PASS
	661	1880.0	-20.03	Plot B2toB2.1		PASS
	810	1909.8	-21.16	Plot B3toB3.1		PASS
EDGE 850MHz	128	824.2	-22.12	Plot C1toC1.1	-13	PASS
	190	836.6	-22.27	Plot C2toC2.1		PASS
	251	848.8	-22.62	Plot C3toC3.1		PASS
EDGE 1900MHz	512	1850.2	-20.65	Plot D1toD1.1	-13	PASS
	661	1880.0	-21.2	Plot D2toD2.1		PASS
	810	1909.8	-20.18	Plot D3toD3.1		PASS
WCDMA 850MHz	4132	826.4	-26.26	Plot E1toE1.1	-13	PASS
	4175	835	-25.39	Plot E2toE2.1		PASS
	4233	846.6	-25.45	Plot E3toE3.1		PASS
WCDMA 1900MHz	9262	1852.4	-20.68	Plot F1toF1.1	-13	PASS
	9400	1880	-20.87	Plot F2toF2.1		PASS
	9538	1907.6	-20.16	Plot F3toF3.1		PASS
HSDPA	4132	826.4	-26.37	Plot G1toG1.1	-13	PASS


Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
850MHz	4175	835	-26.09	Plot G2toG2.1		PASS
	4233	846.6	-26.41	Plot G3toG3.1		PASS
HSDPA 1900MHz	9262	1852.4	-21.15	Plot H1toH1.1	-13	PASS
	9400	1880	-21.55	Plot H2toH2.1		PASS
	9538	1907.6	-20.22	Plot H3toH3.1		PASS
HSUPA 850MHz	4132	826.4	-24.88	Plot I1toI1.1	-13	PASS
	4175	835	-26.14	Plot I2toI2.1		PASS
	4233	846.6	-16.18	Plot I3toI3.1		PASS
HSUPA 1900MHz	9262	1852.4	-20.91	Plot J1toJ1.1	-13	PASS
	9400	1880	-21.6	Plot J2toJ2.1		PASS
	9538	1907.6	-19.23	Plot J3toJ3.1		PASS

2. Test Plots for the Whole Measurement Frequency Range:


Note: the power of the EUT transmitting frequency should be ignored.




(Plot A1: GSM 850MHz Channel = 128, 30MHz to 1GHz)




(Plot A1.1: GSM 850MHz Channel = 128, 1GHz to 9GHz)




(Plot A2: GSM 850MHz Channel = 190, 30MHz to 1GHz)




(Plot A2.1: GSM 850MHz Channel = 190, 1GHz to 9GHz)




(Plot A3: GSM 850MHz Channel = 251, 30MHz to 1GHz)




(Plot A3.1: GSM 850MHz Channel = 251, 1GHz to 9GHz)




(Plot B1: GSM 1900MHz Channel = 512, 30MHz to 1GHz)




(Plot B1.1: GSM 1900MHz Channel = 512, 1GHz to 20GHz)




(Plot B2: GSM 1900MHz Channel = 661, 30MHz to 1GHz)




(Plot B2.1: GSM 1900MHz Channel = 661, 1GHz to 20GHz)




(Plot B3: GSM 1900MHz Channel = 810, 30MHz to 1GHz)




(Plot B3.1: GSM 1900MHz Channel = 810, 1GHz to 20GHz)




(Plot C1: EDGE 850MHz Channel = 128, 30MHz to 1GHz)




(Plot C1.1: EDGE 850MHz Channel = 128, 1GHz to 9GHz)




(Plot C2: EDGE 850MHz Channel = 190, 30MHz to 1GHz)




(Plot C2.1: EDGE 850MHz Channel = 190, 1GHz to 9GHz)




(Plot C3: EDGE 850MHz Channel = 251, 30MHz to 1GHz)




(Plot C3.1: EDGE 850MHz Channel = 251, 1GHz to 9GHz)




(Plot D1: EDGE 1900MHz Channel = 512, 30MHz to 1GHz)




(Plot D1.1: EDGE 1900MHz Channel = 512, 1GHz to 20GHz)




(Plot D2: EDGE 1900MHz Channel = 661, 30MHz to 1GHz)




(Plot D2.1: EDGE 1900MHz Channel = 661,1GHz to 20GHz)




(Plot D3: EDGE 1900MHz Channel = 810, 30MHz to 1GHz)




(Plot D3.1: EDGE 1900MHz Channel = 810, 1GHz to 20GHz)




(Plot E1: WCDMA850MHz Channel = 4132, 30MHz to 1GHz)




(Plot E1.1: WCDMA850MHz Channel = 4132, 1GHz to 9GHz)




(Plot E2: WCDMA850MHz Channel = 4175, 30MHz to 1GHz)




(Plot E2.1: WCDMA850MHz Channel = 4175, 1GHz to 9GHz)




(Plot E3: WCDMA850MHz Channel = 4233, 30MHz to 1GHz)




(Plot E3.1: WCDMA850MHz Channel = 4233, 1GHz to 9GHz)




(Plot F1: WCDMA1900MHz Channel = 9262, 30MHz to 1GHz)




(Plot F1.1: WCDMA1900MHz Channel = 9262, 1GHz to 20GHz)




(Plot F2: WCDMA1900MHz Channel = 9400, 30MHz to 1GHz)




(Plot F2.1: WCDMA1900MHz Channel = 9400, 1GHz to 20GHz)




(Plot F3: WCDMA1900MHz Channel = 9538, 30MHz to 1GHz)




(Plot F3.1: WCDMA1900MHz Channel = 9538 1GHz to 20GHz)




(Plot G1: HSDPA 850MHz Channel = 4132, 30MHz to 1GHz)




(Plot G1.1: HSDPA 850MHz Channel = 4132, 1GHz to 9GHz)




(Plot G2: HSDPA 850MHz Channel = 4175, 30MHz to 1GHz)




(Plot G2.1: HSDPA 850MHz Channel = 4175, 1GHz to 9GHz)




(Plot G3: HSDPA850MHz Channel = 4233, 30MHz to 1GHz)




(Plot G3.1: HSDPA850MHz Channel = 4233, 1GHz to 9GHz)




(Plot H1: HSDPA1900MHz Channel = 9262, 30MHz to 1GHz)




(Plot H1.1: HSDPA1900MHz Channel = 9262, 1GHz to 20GHz)




(Plot H2: HSDPA1900MHz Channel = 9400, 30MHz to 1GHz)




(Plot H2.1: HSDPA1900MHz Channel = 9400, 1GHz to 20GHz)




(Plot H3: HSDPA1900MHz Channel = 9538, 30MHz to 1GHz)




(Plot H3.1: HSDPA1900MHz Channel = 9538 1GHz to 20GHz)




(Plot I 1: HSUPA 850MHz Channel = 4132, 30MHz to 1GHz)




(Plot I1.1: HSUPA 850MHz Channel = 4132, 1GHz to 9GHz)




(Plot I 2: HSUPA 850MHz Channel = 4175, 30MHz to 1GHz)




(Plot I2.1: HSUPA 850MHz Channel = 4175, 1GHz to 9GHz)




(Plot I 3: HSUPA850MHz Channel = 4233, 30MHz to 1GHz)




(Plot I3.1: HSUPA850MHz Channel = 4233, 1GHz to 9GHz)




(Plot J 1: HSUPA1900MHz Channel = 9262, 30MHz to 1GHz)




(Plot J1.1: HSUPA1900MHz Channel = 9262, 1GHz to 20GHz)




(Plot J 2: HSUPA1900MHz Channel = 9400, 30MHz to 1GHz)



(Plot J2.1: HSUPA1900MHz Channel = 9400, 1GHz to 20GHz)



(Plot J 3: HSUPA1900MHz Channel = 9538, 30MHz to 1GHz)



(Plot J3.1: HSUPA1900MHz Channel = 9538 1GHz to 20GHz)

2.5 Band Edge

2.5.1 Requirement

According to FCC section 22.917(b) and FCC section 24.238(b), in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

2.5.2 Test Description

See section 2.1.2 of this report.

2.5.3 Test Result

The lowest and highest channels are tested to verify the band edge emissions.


1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Band Edge Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-14.17	Plat A	-13	PASS
	251	848.8	-14.23	Plot B		PASS
GSM 1900MHz	512	1850.2	-16.95	Plat C	-13	PASS
	810	1909.8	-14.23	Plot D		PASS
EDGE 850MHz	128	824.2	-14.92	Plat E	-13	PASS
	251	848.8	-14.5	Plot F		PASS
EDGE 1900MHz	512	1850.2	-15.66	Plat G	-13	PASS
	810	1909.8	-14.55	Plot H		PASS
WCDMA 850MHz	4132	826.4	-17.92	Plat I	-13	PASS
	4233	846.6	-15.26	Plot J		PASS
WCDMA 1900MHz	9262	1852.4	-18.04	Plat K	-13	PASS
	9538	1907.6	-16.63	Plot L		PASS
HSDPA 850MHz	4132	826.4	-21.57	Plat M	-13	PASS
	4233	846.6	-15.79	Plot N		PASS
HSDPA 1900MHz	9262	1852.4	-18.32	Plat O	-13	PASS
	9538	1907.6	-15.16	Plot P		PASS
HSUPA 850MHz	4132	826.4	-17.81	Plat Q	-13	PASS
	4233	846.6	-15.29	Plot R		PASS
HSUPA	9262	1852.4	-18.25	Plat S	-13	PASS




1900MHz	9538	1907.6	-16.29	Plot T		PASS
GPRS	128	824.2	-15.74	Plat U	-13	PASS
850MHz	251	848.8	-17.34	Plot V		PASS
GPRS	512	1850.2	-17.7	Plat W	-13	PASS
1900MHz	810	1909.8	-18.73	Plot X		PASS


2. Test Plots:




(Plot A: GSM 850 Channel = 128)




(Plot B: GSM 850 Channel = 251)




(Plot C: GSM 1900 Channel = 512)




(Plot D: GSM 1900 Channel = 810)




(Plot E: EDGE 850 Channel = 128)




(Plot F: EDGE 850 Channel = 251)




(Plot G: EDGE 1900 Channel = 512)




(Plot H: EDGE 1900 Channel = 810)




(Plot I: WCDMA 850 Channel = 4132)




(Plot J: WCDMA 850 Channel = 4233)




(Plot K: WCDMA 1900 Channel = 9262)




(Plot L: WCDMA 1900 Channel = 9538)




(Plot M: HSDPA 850 Channel = 4132)




(Plot N: HSDPA850 Channel = 4233)




(Plot O: HSDPA 1900 Channel = 9262)




(Plot P: HSDPA 1900 Channel = 9538)




(Plot Q: HSUPA 850 Channel = 4132)




(Plot R: HSUPA850 Channel = 4233)




(Plot S: HSUPA 1900 Channel = 9262)




(Plot T: HSUPA 1900 Channel = 9538)




(Plot U: GPRS 850 Channel = 128)



(Plot V: GPRS 850 Channel = 251)



(Plot W: GPRS 1900 Channel = 512)



(Plot X: GPRS 1900 Channel = 810)


2.6 Transmitter Radiated Power (EIRP/ERP)

2.6.1 Requirement

According to FCC section 22.913, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2 Watts e.i.r.p. peak power.

2.6.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery charged with the AC Adapter, is located in a 3m Full-Anechoic Chamber; the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading.

A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power (i.e. GSM850MHz band Power Control Level (PCL) = 5/19 and Power Class = 4, GSM1900MHz band Power Control Level (PCL) = 0/15 and Power Class = 1), and only the test result of the maximum output power was recorded.

- GSM Maximum RF output power: GSM850 33.1dBm, GSM 1900 29.58dBm, WCDMA 850 21.87, WCDMA 1900 22.78, Please refer to section 2.1.3 of this report.

- Step size (dB): 3dB

- Minimum RF power: GSM850 3.1dBm, GSM 1900 0.3dBm, WCDMA 850 2.09dBm, WCDMA 1900 0.5dBm.

The Test Antenna is a Bi-Log one (used for 30MHz to 1GHz) or a Horn one (used for above 3GHz), and it's located at the same height as the EUT. The Filters consists of Notch Filters and High Pass Filter.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Agilent	E5515C	GB43130131	2012.05	2013.05
Spectrum Analyzer	Agilent	E7405A	US44210471	2012.05	2013.05
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2012.05	2013.05
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2012.05	2013.05
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2012.05	2013.05

2.6.3 Test Result

The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST_TX}} - P_{\text{SUBST_RX}} - L_{\text{SUBST_CABLES}} + G_{\text{SUBST_TX_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

$P_{\text{SUBST_TX}}$ is signal generator level,

$P_{\text{SUBST_RX}}$ is receiver level,

$L_{\text{SUBST_CABLES}}$ is cable losses including TX cable,

$G_{\text{SUBST_TX_ANT}}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the Test Spectrum Analyze, so Spectrum Analyze reading is the final values which contain the data of A_{TOT} .

1. GSM Model Test Verdict:

Band	Channel	Frequency (MHz)	PCL	Measured ERP			Limit		Verdict
				dBm	W	Refer to Plot	dBm	W	
GSM 850MHz	128	824.20	5	33.94	2.477	Plot A	38.5	7	PASS
	190	836.60	5	33.74	2.366				PASS
	251	848.80	5	33.21	2.094				PASS
GPRS 850MHz	128	824.20	5	33.8	2.399	Plot B ^{Note 1}	38.5	7	PASS
	190	836.60	5	33.49	2.234				PASS
	251	848.80	5	32.79	1.901				PASS
EGPRS 850MHz	128	824.20	5	33.92	2.466	Plot C ^{Note 1}	38.5	7	PASS
	190	836.60	5	33.85	2.427				PASS
	251	848.80	5	32.84	1.923				PASS

Band	Channel	Frequency (MHz)	PCL	Measured EIRP			Limit		Verdict
				dBm	W	Refer to Plot	dBm	W	
GSM 1900MHz	512	1850.2	0	29.79	0.953	Plot D	33	2	PASS
	661	1880.0	0	29.9	0.977				PASS
	810	1909.8	0	28.12	0.649				PASS
GPRS 1900MHz	512	1850.2	0	28.91	0.778	Plot E ^{Note 1}	33	2	PASS
	661	1880.0	0	28.72	0.745				PASS
	810	1909.8	0	27.63	0.579				PASS
EGPRS 1900MHz	512	1850.2	0	28.34	0.682	Plot F ^{Note 1}	33	2	PASS
	661	1880.0	0	28.86	0.769				PASS
	810	1909.8	0	28.31	0.678				PASS

Note 1: For the GPRS and EGPRS model, all the slots were tested and just the worst data was record in this report


2. WCDMA Model Test Verdict:

Band	Channel	Frequency (MHz)	Measured ERP		Limit		Verdict
			dBm	W	dBm	W	
WCDMA 850MHz	4132	826.4	22.12	0.163	38.5	7	PASS
	4175	835	22.19	0.166			PASS
	4233	846.6	22.11	0.163			PASS
HSDPA 850MHz	4132	826.4	22.07	0.161	38.5	7	PASS
	4175	835	22.05	0.160			PASS
	4233	846.6	22.06	0.161			PASS
HSUPA 850MHz	4132	826.4	22.02	0.159	38.5	7	PASS
	4175	835	22.06	0.161			PASS
	4233	846.6	22.02	0.159			PASS


Band	Channel	Frequency (MHz)	Measured EIRP		Limit		Verdict
			dBm	W	dBm	W	
WCDMA 1900MHz	9262	1852.4	23.11	0.205	33	2	PASS
	9400	1880	23.13	0.206			PASS
	9538	1907.6	23.12	0.205			PASS
HSDPA 1900MHz	9262	1852.4	23.09	0.204	33	2	PASS
	9400	1880	23.02	0.200			PASS
	9538	1907.6	23.06	0.202			PASS
HSUPA 1900MHz	9262	1852.4	23.13	0.206	33	2	PASS
	9400	1880	23.15	0.207			PASS
	9538	1907.6	23.16	0.207			PASS

Note2: For the WCDMA and HSDPA test band, the measured output power was calculated by the reading of the Power Meter.


3. Test Plots:




(Plot A: GSM 850MHz Channel = 128, 190, 251)




(Plot B: GPRS 850MHz Channel = 128, 190, 251)




(Plot C: EDGE 850MHz Channel = 128, 190, 251)



(Plot D: GSM1900MHz Channel = 512, 661, 810)



(Plot E: GPRS 1900MHz Channel = 512, 661, 810)



(Plot F: EDGE 1900MHz Channel = 512, 661, 810)

2.7 Radiated Out of Band Emissions

2.7.1 Requirement

According to FCC section 22.917(a) and section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.

The spurious emission with frequency band 1900 according to FCC section 2.1057.

2.7.2 Test Description

See section 2.6.2 of this report.

Note: when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.7.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)		Refer to Plot	Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical			
GSM 850MHz	128	824.2	< -25	< -25	Plot A.1/A.2	-13	PASS
	190	836.6	< -25	< -25	Plot A.3/A.4		PASS
	251	848.8	< -25	< -25	Plot A.5/A.6		PASS
GSM 1900MHz	512	1850.2	< -25	< -25	Plot B.1/B.2	-13	PASS
	661	1880.0	< -25	< -25	Plot B.3/B.4		PASS
	810	1909.8	< -25	< -25	Plot B.5/B.6		PASS
EDGE 850MHz	128	824.2	< -25	< -25	Plot C.1/C.2	-13	PASS
	190	836.6	< -25	< -25	Plot C.3/C.4		PASS
	251	848.8	< -25	< -25	Plot C.5/C.6		PASS
EDGE 1900MHz	512	1850.2	< -25	< -25	Plot D.1/D.2	-13	PASS
	661	1880.0	< -25	< -25	Plot D.3/D.4		PASS
	810	1909.8	< -25	< -25	Plot D.5/D.6		PASS

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)		Refer to Plot	Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical			
WCDMA 850MHz	4132	826.4	< -25	< -25	Plot E.1/E.2	-13	PASS
	4175	835	< -25	< -25	Plot E.3/E.4		PASS
	4233	846.6	< -25	< -25	Plot E.5/E.6		PASS
WCDMA 1900MHz	9262	1852.4	< -25	< -25	Plot F.1/F.2	-13	PASS
	9400	1880	< -25	< -25	Plot F.3/F.4		PASS
	9538	1907.6	< -25	< -25	Plot F.5/F.6		PASS
HSDPA 850MHz	4132	826.4	< -25	< -25	Plot G.1/G.2	-13	PASS
	4175	835	< -25	< -25	Plot G.3/G.4		PASS
	4233	846.6	< -25	< -25	Plot G.5/G.6		PASS
HSDPA 1900MHz	9262	1852.4	< -25	< -25	Plot H.1/H.2	-13	PASS
	9400	1880	< -25	< -25	Plot H.3/H.4		PASS
	9538	1907.6	< -25	< -25	Plot H.5/H.6		PASS
HSUPA 850MHz	4132	826.4	< -25	< -25	Plot I.1/I.2	-13	PASS
	4175	835	< -25	< -25	Plot I.3/I.4		PASS
	4233	846.6	< -25	< -25	Plot I.5/I.6		PASS
HSUPA 1900MHz	9262	1852.4	< -25	< -25	Plot J.1/J.2	-13	PASS
	9400	1880	< -25	< -25	Plot J.3/J.4		PASS
	9538	1907.6	< -25	< -25	Plot J.5/J.6		PASS

2. Test Plots for the Whole Measurement Frequency Range:

Note1: the power of the EUT transmitting frequency should be ignored.


Note2: All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.



(Plot A.1: GSM 850MHz Channel = 128, Test Antenna Horizontal)



(Plot A.2: GSM 850MHz Channel = 128, Test Antenna Vertical)



(Plot A.3: GSM 850MHz Channel = 190, Test Antenna Horizontal)




(Plot A.4: GSM 850MHz Channel = 190, Test Antenna Vertical)



(Plot A.5: GSM 850MHz Channel = 251, Test Antenna Horizontal)




(Plot A.6: GSM 850MHz Channel = 251, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-45.93	-13.0	32.9	262.0	Horizontal	PASS
3720.698	-42.99	-13.0	30.0	351.2	Horizontal	PASS
7408.978	-36.30	-13.0	23.3	101.0	Horizontal	PASS
18812.968	-32.00	-13.0	19.0	351.2	Horizontal	PASS

(Plot B.1: GSM 1900MHz Channel = 512, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-48.87	-13.0	35.9	230.8	Vertical	PASS
2436.409	-48.40	-13.0	35.4	158.5	Vertical	PASS
3720.698	-42.73	-13.0	29.7	147.9	Vertical	PASS
19872.818	-30.39	-13.0	17.4	297.0	Vertical	PASS

(Plot B.2: GSM 1900MHz Channel = 512, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-45.83	-13.0	32.8	91.5	Horizontal	PASS
3763.092	-48.43	-13.0	35.4	9.1	Horizontal	PASS
18558.603	-31.69	-13.0	18.7	301.7	Horizontal	PASS

(Plot B.3: GSM 1900MHz Channel = 661, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-49.39	-13.0	36.4	236.2	Vertical	PASS
1957.606	-52.59	-13.0	39.6	292.9	Vertical	PASS
3763.092	-48.05	-13.0	35.1	102.7	Vertical	PASS
18770.574	-30.19	-13.0	17.2	128.0	Vertical	PASS

(Plot B.4: GSM 1900MHz Channel = 661, Test Antenna Vertical)



Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-45.97	-13.0	33.0	93.9	Horizontal	PASS
3847.880	-48.38	-13.0	35.4	335.0	Horizontal	PASS
5713.217	-47.93	-13.0	34.9	10.3	Horizontal	PASS
7620.948	-41.28	-13.0	28.3	42.7	Horizontal	PASS
19660.848	-32.75	-13.0	19.7	191.4	Horizontal	PASS

(Plot B.5: GSM 1900MHz Channel = 810, Test Antenna Horizontal)



Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-48.90	-13.0	35.9	228.1	Vertical	PASS
1987.531	-51.98	-13.0	39.0	19.2	Vertical	PASS
3847.880	-46.15	-13.0	33.2	161.5	Vertical	PASS
19533.666	-31.82	-13.0	18.8	322.5	Vertical	PASS

(PlotB.6: GSM 1900MHz Channel = 810, Test Antenna Vertical)



(Plot C.1: EGPRS 850MHz Channel = 128, Test Antenna Horizontal)



(Plot C.2: EGPRS 850MHz Channel = 128, Test Antenna Vertical)



(Plot C.3: EGPRS 850MHz Channel = 190, Test Antenna Horizontal)




(Plot C.4: EGPRS 850MHz Channel = 190, Test Antenna Vertical)



(Plot C.5: EGPRS 850MHz Channel = 251, Test Antenna Horizontal)




(Plot C.6: EGPRS 850MHz Channel = 251, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-40.74	-13.0	27.7	84.1	Horizontal	PASS
1927.681	-51.25	-13.0	38.3	148.6	Horizontal	PASS
3720.698	-42.41	-13.0	29.4	360.0	Horizontal	PASS
7408.978	-35.34	-13.0	22.3	148.5	Horizontal	PASS
19533.666	-31.84	-13.0	18.8	189.0	Horizontal	PASS

(Plot D.1: EGPRS 1900MHz Channel = 512, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-44.40	-13.0	31.4	230.4	Vertical	PASS
1927.681	-52.18	-13.0	39.2	340.7	Vertical	PASS
3720.698	-43.60	-13.0	30.6	268.1	Vertical	PASS
7408.978	-42.95	-13.0	29.9	193.0	Vertical	PASS
18940.150	-31.12	-13.0	18.1	41.6	Vertical	PASS

(Plot D.2: EGPRS 1900MHz Channel = 512, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-40.96	-13.0	28.0	196.4	Horizontal	PASS
1957.606	-51.29	-13.0	38.3	189.2	Horizontal	PASS
3763.092	-48.28	-13.0	35.3	353.0	Horizontal	PASS
18177.057	-30.43	-13.0	17.4	360.0	Horizontal	PASS

(Plot D.3: EGPRS 1900MHz Channel = 661, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-44.69	-13.0	31.7	325.4	Vertical	PASS
1957.606	-49.83	-13.0	36.8	62.7	Vertical	PASS
3763.092	-48.09	-13.0	35.1	117.6	Vertical	PASS
18092.269	-31.10	-13.0	18.1	83.4	Vertical	PASS

(Plot D.4: EGPRS 1900MHz Channel = 661, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-40.93	-13.0	27.9	282.5	Horizontal	PASS
1987.531	-50.95	-13.0	38.0	188.9	Horizontal	PASS
3847.880	-47.30	-13.0	34.3	358.7	Horizontal	PASS
7620.948	-42.45	-13.0	29.5	19.3	Horizontal	PASS
19364.090	-32.42	-13.0	19.4	0.0	Horizontal	PASS

(Plot D.5: EGPRS 1900MHz Channel = 810, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
871.796	-44.19	-13.0	31.2	236.1	Vertical	PASS
1987.531	-47.90	-13.0	34.9	360.0	Vertical	PASS
3847.880	-48.59	-13.0	35.6	251.0	Vertical	PASS
18092.269	-31.48	-13.0	18.5	217.8	Vertical	PASS


(Plot D.6: EGPRS 1900MHz Channel = 810, Test Antenna Vertical)



(Plot E.1: WCDMA 850MHz Channel = 4132, Test Antenna Horizontal)




(Plot E.2: WCDMA 850MHz Channel = 4132, Test Antenna Vertical)




(Plot E.3: WCDMA 850MHz Channel = 4175, Test Antenna Horizontal)




(Plot E.4: WCDMA 850MHz Channel = 4175, Test Antenna Vertical)



(Plot E.5: WCDMA 850MHz Channel = 4233, Test Antenna Horizontal)




(Plot E.6: WCDMA 850MHz Channel = 4233, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
102.569	-69.99	-13.0	57.0	42.8	Horizontal	PASS
1932.668	-43.27	-13.0	30.3	6.2	Horizontal	PASS
3720.698	-46.67	-13.0	33.7	360.0	Horizontal	PASS
5543.641	-50.95	-13.0	38.0	47.3	Horizontal	PASS
18431.421	-31.84	-13.0	18.8	97.5	Horizontal	PASS

(Plot F.1: WCDMA 1900MHz Channel = 9262, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
75.960	-67.52	-13.0	54.5	351.5	Vertical	PASS
1927.681	-40.97	-13.0	28.0	299.7	Vertical	PASS
3720.698	-45.83	-13.0	32.8	263.7	Vertical	PASS
16354.115	-30.79	-13.0	17.8	358.7	Vertical	PASS
19576.060	-32.85	-13.0	19.9	75.2	Vertical	PASS

(Plot F.2: WCDMA 1900MHz Channel = 9262, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
80.798	-64.48	-13.0	51.5	155.4	Horizontal	PASS
1957.606	-42.86	-13.0	29.9	194.5	Horizontal	PASS
3763.092	-50.17	-13.0	37.2	-0.0	Horizontal	PASS
5628.429	-45.45	-13.0	32.4	49.3	Horizontal	PASS
19406.484	-31.69	-13.0	18.7	2.9	Horizontal	PASS

(Plot F.3: WCDMA 1900MHz Channel = 9400, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
34.838	-57.24	-13.0	44.2	115.9	Vertical	PASS
1957.606	-37.50	-13.0	24.5	59.9	Vertical	PASS
3763.092	-46.37	-13.0	33.4	140.1	Vertical	PASS
5628.429	-47.46	-13.0	34.5	173.9	Vertical	PASS
19236.908	-32.32	-13.0	19.3	55.7	Vertical	PASS

(Plot F.4: WCDMA 1900MHz Channel = 9400, Test Antenna Vertical)



Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
121.920	-64.17	-13.0	51.2	69.9	Horizontal	PASS
1982.544	-39.48	-13.0	26.5	248.1	Horizontal	PASS
3805.486	-42.39	-13.0	29.4	139.3	Horizontal	PASS
5713.217	-46.53	-13.0	33.5	48.6	Horizontal	PASS
16099.751	-30.63	-13.0	17.6	0.6	Horizontal	PASS

(Plot F.5: WCDMA 1900MHz Channel = 9538, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
34.838	-59.41	-13.0	46.4	334.0	Vertical	PASS
1987.531	-34.85	-13.0	21.9	316.4	Vertical	PASS
3805.486	-38.40	-13.0	25.4	143.6	Vertical	PASS
5713.217	-47.99	-13.0	35.0	168.1	Vertical	PASS
19703.242	-33.61	-13.0	20.6	85.3	Vertical	PASS


(Plot F.6: WCDMA 1900MHz Channel = 9538, Test Antenna Vertical)




(Plot G.1: HSDPA 850MHz Channel = 4132, Test Antenna Horizontal)



(Plot G.2: HSDPA 850MHz Channel = 4132, Test Antenna Vertical)




(Plot G.3: HSDPA 850MHz Channel = 4175, Test Antenna Horizontal)




(Plot G.4: HSDPA 850MHz Channel = 4175, Test Antenna Vertical)



(Plot G.5: HSDPA 850MHz Channel = 4233, Test Antenna Horizontal)




(Plot G.6: HSDPA 850MHz Channel = 4233, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
102.569	-70.95	-13.0	58.0	309.7	Horizontal	PASS
1927.681	-43.70	-13.0	30.7	45.0	Horizontal	PASS
3720.698	-47.56	-13.0	34.6	351.2	Horizontal	PASS
5543.641	-50.74	-13.0	37.7	52.7	Horizontal	PASS
19024.938	-31.77	-13.0	18.8	226.0	Horizontal	PASS

(Plot H.1: HSDPA 1900 MHz Channel = 9262, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
34.838	-61.16	-13.0	48.2	205.9	Vertical	PASS
1927.681	-40.86	-13.0	27.9	51.4	Vertical	PASS
3720.698	-45.44	-13.0	32.4	265.1	Vertical	PASS
18092.269	-31.45	-13.0	18.4	3.2	Vertical	PASS

(Plot H.2: HSDPA 1900 MHz Channel = 9262, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
80.798	-65.29	-13.0	52.3	155.1	Horizontal	PASS
1957.606	-41.62	-13.0	28.6	244.2	Horizontal	PASS
3763.092	-50.45	-13.0	37.4	76.0	Horizontal	PASS
5628.429	-44.62	-13.0	31.6	58.8	Horizontal	PASS
18049.875	-31.45	-13.0	18.4	331.7	Horizontal	PASS

(Plot H.3: HSDPA 1900 MHz Channel = 9400, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
34.838	-59.94	-13.0	46.9	46.9	Vertical	PASS
1957.606	-36.85	-13.0	23.9	-0.0	Vertical	PASS
3763.092	-45.40	-13.0	32.4	125.8	Vertical	PASS
5628.429	-47.52	-13.0	34.5	159.2	Vertical	PASS
19576.060	-31.31	-13.0	18.3	335.5	Vertical	PASS

(Plot H.4: HSDPA 1900 MHz Channel = 9400, Test Antenna Vertical)



Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
78.379	-65.56	-13.0	52.6	134.3	Horizontal	PASS
1987.531	-41.21	-13.0	28.2	113.6	Horizontal	PASS
3805.486	-43.51	-13.0	30.5	9.4	Horizontal	PASS
5713.217	-44.85	-13.0	31.9	9.4	Horizontal	PASS
19321.696	-32.44	-13.0	19.4	158.1	Horizontal	PASS

(Plot H.5: HSDPA 1900 MHz Channel = 9538, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
34.838	-58.95	-13.0	45.9	334.0	Vertical	PASS
1987.531	-35.41	-13.0	22.4	316.4	Vertical	PASS
3805.486	-38.21	-13.0	25.2	143.6	Vertical	PASS
5713.217	-47.72	-13.0	34.7	168.1	Vertical	PASS
19703.242	-32.16	-13.0	19.2	85.3	Vertical	PASS


(Plot H.6: HSDPA 1900 MHz Channel = 9538, Test Antenna Vertical)




(Plot I.1: HSUPA 850MHz Channel = 4132, Test Antenna Horizontal)




(Plot I.2: HSUPA 850 MHz Channel = 4132, Test Antenna Vertical)




(Plot I.3: HSUPA 850MHz Channel = 4175, Test Antenna Horizontal)




(Plot I.4: HSUPA 850MHz Channel = 4175, Test Antenna Vertical)



(Plot I.5: HSUPA 850MHz Channel = 4233, Test Antenna Horizontal)




(Plot I.6: HSUPA 850MHz Channel = 4233, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
363.815	-69.53	-13.0	56.5	54.8	Horizontal	PASS
1932.668	-43.12	-13.0	30.1	77.7	Horizontal	PASS
3720.698	-47.96	-13.0	35.0	-0.0	Horizontal	PASS
19618.454	-32.31	-13.0	19.3	158.1	Horizontal	PASS

(Plot J.1: HSUPA 1900 MHz Channel = 9262, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
366.234	-66.82	-13.0	53.8	69.6	Vertical	PASS
1932.668	-40.26	-13.0	27.3	234.2	Vertical	PASS
3720.698	-45.46	-13.0	32.5	257.8	Vertical	PASS
18049.875	-31.25	-13.0	18.2	91.9	Vertical	PASS

(Plot J.2: HSUPA 1900 MHz Channel = 9262, Test Antenna Vertical)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
80.798	-65.54	-13.0	52.5	136.1	Horizontal	PASS
1957.606	-42.01	-13.0	29.0	240.3	Horizontal	PASS
3763.092	-51.54	-13.0	38.5	81.3	Horizontal	PASS
5628.429	-46.63	-13.0	33.6	48.2	Horizontal	PASS
18812.968	-32.20	-13.0	19.2	-0.0	Horizontal	PASS

(Plot J.3: HSUPA 1900 MHz Channel = 9400, Test Antenna Horizontal)




Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
358.978	-67.02	-13.0	54.0	253.9	Vertical	PASS
1957.606	-37.37	-13.0	24.4	286.5	Vertical	PASS
3763.092	-46.08	-13.0	33.1	142.3	Vertical	PASS
5628.429	-47.99	-13.0	35.0	191.0	Vertical	PASS
19660.848	-32.27	-13.0	19.3	200.3	Vertical	PASS

(Plot J.4: HSUPA 1900 MHz Channel = 9400, Test Antenna Vertical)



Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
361.397	-71.61	-13.0	58.6	60.5	Horizontal	PASS
1987.531	-39.28	-13.0	26.3	182.7	Horizontal	PASS
3805.486	-43.50	-13.0	30.5	226.7	Horizontal	PASS
5713.217	-46.87	-13.0	33.9	3.0	Horizontal	PASS
18092.269	-31.72	-13.0	18.7	134.1	Horizontal	PASS

(Plot J.5: HSUPA 1900 MHz Channel = 9538, Test Antenna Horizontal)



Fre. (MHz)	Peak	Limit(PK)	Margin	Degree	Antenna	Verdict
68.703	-67.11	-13.0	54.1	359.1	Vertical	PASS
1982.544	-36.06	-13.0	23.1	61.8	Vertical	PASS
3805.486	-38.52	-13.0	25.5	135.6	Vertical	PASS
5713.217	-47.57	-13.0	34.6	192.5	Vertical	PASS
18473.815	-30.15	-13.0	17.2	94.7	Vertical	PASS

(Plot J.6: HSUPA 1900 MHz Channel = 9538, Test Antenna Vertical)

** END OF REPORT **