



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : GSM(GPRS/EDGE-RX) Quad-band
Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : ZTE-G R290
FCC ID : Q78-GR290
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Aug. 29, 2012 and completely tested on Oct. 11, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test 5

 1.4 Testing Site 6

 1.5 Applied Standards 6

 1.6 Ancillary Equipment List 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1 Carrier Frequency Channel 7

 2.2 Pre-Scanned RF Power 8

 2.3 Test Mode 9

 2.4 Connection Diagram of Test System 10

 2.5 RF Utility 10

3 TEST RESULT 11

 3.1 6dB Bandwidth Measurement 11

 3.2 Output Power Measurement 20

 3.3 Power Spectral Density Measurement 23

 3.4 Conducted Band Edges and Spurious Emission Measurement 42

 3.5 Radiated Emission Measurement 59

 3.6 AC Conducted Emission Measurement 79

 3.7 Antenna Requirements 83

4 LIST OF MEASURING EQUIPMENT 84

5 UNCERTAINTY OF EVALUATION 85

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	A8.4	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	A8.5	Radiated Band Edges	15.209(a) & 15.247(d)	Pass	-
			Radiated Spurious Emission		Pass	Under limit 0.99 dB at 2483.500 MHz
3.6	15.207	Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 7.71 dB at 1.960 MHz
3.7	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	GSM(GPRS/EDGE-RX) Quad-band Digital Mobile Phone
Brand Name	ZTE
Model Name	ZTE-G R290
FCC ID	Q78-GR290
EUT supports Radios application	GSM/GPRS/WLAN 11bgn/Bluetooth 3.0
HW Version	GMAW
SW Version	ZTE-CN-QS-P155A10V0.0.1
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2412 MHz ~ 2462 MHz
Number of Channels	11
Carrier Frequency of Each Channel	2412+(n-1)*5 MHz; n=1~11
Maximum Output Power to Antenna	802.11b : 20.65 dBm (0.1161 W) 802.11g : 20.28 dBm (0.1067 W) 802.11n HT20 : 21.31 dBm (0.1352 W) 802.11n HT40 : 21.41 dBm (0.1384 W)
Antenna Type	Chip Antenna with gain -0.48 dBi
Type of Modulation	802.11b : DSSS (BPSK / QPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC/IC Registration No.
	TH01-KS	CO01-KS	03CH01-KS	149928/4086E-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v02
- ♦ ANSI C63.4-2003 and ANSI C63.10-2009
- ♦ IC RSS-210 Issue 8
- ♦ IC RSS-Gen Issue 3

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	P08S	QDS-BRCM1030	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m
4.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
5.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 KHz to 30 MHz) and radiated emission (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and antenna configurations as following table and the highest power data rates were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412 MHz	20.65	20.61	20.07	20.46
CH 06	2437 MHz	20.45	20.56	19.86	20.26
CH 11	2462 MHz	20.03	20.19	19.65	19.84

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412 MHz	20.28	18.88	19.93	19.02	20.08	20.21	20.13	20.19
CH 06	2437 MHz	19.85	19.49	19.91	19.11	20.21	19.16	19.83	20.12
CH 11	2462 MHz	19.94	18.89	20.01	19.11	19.88	19.31	20.15	20.08

Channel	Frequency	2.4GHz 802.11n HT20 RF Power (dBm)							
		OFDM Data Rate							
		MCS=0	MCS=1	MCS=2	MCS=3	MCS=4	MCS=5	MCS=6	MCS=7
CH 01	2412 MHz	20.28	20.12	20.51	20.25	20.22	20.05	21.31	20.43
CH 06	2437 MHz	20.81	20.38	20.56	20.41	20.27	20.22	21.28	20.37
CH 11	2462 MHz	20.67	20.48	20.76	20.23	20.49	20.51	20.83	20.65

Channel	Frequency	2.4GHz 802.11n HT40 RF Power (dBm)							
		OFDM Data Rate							
		MCS=0	MCS=1	MCS=2	MCS=3	MCS=4	MCS=5	MCS=6	MCS=7
CH 03	2422 MHz	20.75	20.81	20.61	21.31	21.32	21.41	21.03	21.04
CH 06	2437 MHz	21.28	20.75	20.81	21.12	21.01	21.08	20.95	20.85
CH 09	2452 MHz	20.95	20.65	20.56	20.85	20.71	20.86	20.81	20.56


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
	Test Items	Mode	Data Rate	Test Channel
Conducted TCs	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
	Conducted Band EDGE	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	6.5 Mbps	1/11
		802.11n HT40	13.5 Mbps	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
Radiated TCs	Radiated Band EDGE	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	6.5 Mbps	1/11
		802.11n HT40	13.5 Mbps	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	6.5 Mbps	1/6/11
		802.11n HT40	13.5 Mbps	3/6/9
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone			

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 RF Utility

For WLAN function, key in “* #3141133 #” on the EUT directly. Then, the EUT will get into the engineering modes to contact with WLAN AP for continuous transmitting and receiving signals.

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 KHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance and TCB Workshop 2012, April.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1-5% of the emission bandwidth (EBW). Set the Video bandwidth (VBW) $\geq 3 * RBW$. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 KHz.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Test Mode :	802.11b	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11b 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	9.20	0.5	Pass
06	2437	9.20	0.5	Pass
11	2462	9.20	0.5	Pass


6 dB Bandwidth Plot on 802.11b Channel 01



Date: 20.SEP.2012 10:28:49




6 dB Bandwidth Plot on 802.11b Channel 06



Date: 20.SEP.2012 10:41:22

6 dB Bandwidth Plot on 802.11b Channel 11




Date: 20.SEP.2012 10:44:11



Test Mode :	802.11g	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11g 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	16.88	0.5	Pass
06	2437	16.68	0.5	Pass
11	2462	16.78	0.5	Pass


6 dB Bandwidth Plot on 802.11g Channel 01



Date: 20.SEP.2012 10:48:21




6 dB Bandwidth Plot on 802.11g Channel 06



Date: 20.SEP.2012 10:57:00

6 dB Bandwidth Plot on 802.11g Channel 11




Date: 20.SEP.2012 11:00:55



Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	2.4GHz 802.11n HT20 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	17.88	0.5	Pass
06	2437	17.94	0.5	Pass
11	2462	17.92	0.5	Pass


6 dB Bandwidth Plot on 802.11n HT20 Channel 01



Date: 20.SEP.2012 11:15:32




6 dB Bandwidth Plot on 802.11n HT20 Channel 06



Date: 20.SEP.2012 11:18:48

6 dB Bandwidth Plot on 802.11n HT20 Channel 11




Date: 20.SEP.2012 11:21:47



Test Mode :	802.11n HT40	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11n HT40 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
03	2422	36.68	0.5	Pass
06	2437	36.72	0.5	Pass
09	2452	36.64	0.5	Pass


6 dB Bandwidth Plot on 802.11n HT40 Channel 03



Date: 20.SEP.2012 11:25:49




6 dB Bandwidth Plot on 802.11n HT40 Channel 06



Date: 20.SEP.2012 11:28:44

6 dB Bandwidth Plot on 802.11n HT40Channel 09



Date: 20.SEP.2012 11:32:35

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v02.
2. The RF output of EUT was connected to the power meter by a low loss cable
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test Mode :	802.11b	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11b Peak Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	20.65	30	Pass
06	2437	20.45	30	Pass
11	2462	20.03	30	Pass

Test Mode :	802.11g	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11g Peak Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	20.28	30	Pass
06	2437	19.85	30	Pass
11	2462	19.94	30	Pass

Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	2.4GHz 802.11n HT20 Peak Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	21.31	30	Pass
06	2437	21.28	30	Pass
11	2462	20.83	30	Pass

Test Mode :	2.4GHz 802.11n HT40	Temperature :	21~22
Test Engineer :	Cloud Peng	Relative Humidity :	41~42

Channel	Frequency (MHz)	2.4GHz 802.11n HT40 Peak Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
03	2422	21.41	30	Pass
06	2437	21.08	30	Pass
09	2452	20.86	30	Pass



3.2.6 Test Result of Average output Power (Reporting Only)

Test Mode :	802.11b	Temperature :	21~22
Test Engineer :	Cloud Peng	Relative Humidity :	41~42
Duty Cycle:	100%	Duty Factor:	0.00dB

Channel	Frequency (MHz)	802.11b Average Output Power (dBm)
01	2412	18.75
06	2437	18.54
11	2462	17.55

Test Mode :	802.11g	Temperature :	21~22
Test Engineer :	Cloud Peng	Relative Humidity :	41~42
Duty Cycle:	100%	Duty Factor:	0.00dB

Channel	Frequency (MHz)	802.11g Average Output Power (dBm)
01	2412	10.33
06	2437	9.82
11	2462	9.90

Test Mode :	802.11n HT20	Temperature :	21~22
Test Engineer :	Cloud Peng	Relative Humidity :	41~42
Duty Cycle:	100%	Duty Factor:	0.00dB

Channel	Frequency (MHz)	802.11n HT20 Average Output Power (dBm)
01	2412	11.34
06	2437	11.11
11	2462	11.31

Test Mode :	802.11n HT40	Temperature :	21~22
Test Engineer :	Cloud Peng	Relative Humidity :	41~42
Duty Cycle:	100%	Duty Factor:	0.00dB

Channel	Frequency (MHz)	802.11n HT40 Average Output Power (dBm)
03	2422	12.16
06	2437	11.65
09	2452	11.89

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3KHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 9.1 Option 1 of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v02
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Record the measurement data derived from spectrum analyzer.

3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Test Mode :	802.11b	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11b Power Density		Max. Limits (dBm)	Pass/Fail
		PSD/100KHz (dBm)	PSD/3KHz (dBm)		
01	2412	6.23	-10.46	8	Pass
06	2437	5.60	-10.61	8	Pass
11	2462	5.40	-10.81	8	Pass

Test Mode :	802.11g	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11g Power Density		Max. Limits (dBm)	Pass/Fail
		PSD/100KHz (dBm)	PSD/3KHz (dBm)		
01	2412	-6.83	-19.41	8	Pass
06	2437	-7.25	-19.38	8	Pass
11	2462	-7.05	-18.64	8	Pass



Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11n HT20 Power Density		Max. Limits (dBm)	Pass/Fail
		PSD/100KHz (dBm)	PSD/3KHz (dBm)		
01	2412	-5.92	-17.26	8	Pass
06	2437	-5.85	-17.60	8	Pass
11	2462	-5.86	-16.90	8	Pass

Test Mode :	802.11n HT40	Temperature :	21~22°C
Test Engineer :	Cloud Peng	Relative Humidity :	41~42%

Channel	Frequency (MHz)	802.11n HT40 Power Density		Max. Limits (dBm)	Pass/Fail
		PSD/100KHz (dBm)	PSD/3KHz (dBm)		
01	2412	-8.66	-16.96	8	Pass
06	2437	-8.90	-17.08	8	Pass
11	2462	-8.85	-17.09	8	Pass

Note:


1. Measured power density (dBm) has offset with cable loss.
2. Measured power density (dBm)/ 100KHz is for 20dBc reference only



3.3.6 Test Result of Power Spectral Density Plots (100KHz)


<802.11b>

PSD 100KHz Plot on 802.11b Channel 01



Date: 20.SEP.2012 10:29:12


PSD 100KHz Plot on 802.11b Channel 06



Date: 20.SEP.2012 10:41:43



PSD 100KHz Plot on 802.11b Channel 11




Date: 20.SEP.2012 10:44:30




<802.11g>

PSD 100KHz Plot on 802.11g Channel 01



Date: 20.SEP.2012 10:48:40


PSD 100KHz Plot on 802.11g Channel 06



Date: 20.SEP.2012 10:57:21



PSD 100KHz Plot on 802.11g Channel 11




Date: 20.SEP.2012 11:01:14




<2.4GHz 802.11n HT-20>

PSD 100KHz Plot on 2.4G 802.11n HT20 Channel 01



Date: 20.SEP.2012 11:15:51


PSD 100KHz Plot on 2.4G 802.11n HT20 Channel 06



Date: 20.SEP.2012 11:19:07



PSD 100KHz Plot on 2.4G 802.11n HT20 Channel 11




Date: 20.SEP.2012 11:22:08




<2.4GHz 802.11n HT-40>

PSD 100KHz Plot on 2.4G 802.11n HT40 Channel 03



Date: 20.SEP.2012 11:26:08


PSD 100KHz Plot on 2.4G 802.11n HT40 Channel 06



Date: 20.SEP.2012 11:29:04



PSD 100KHz Plot on 2.4G 802.11n HT40 Channel 09




Date: 20.SEP.2012 11:32:55



3.3.7 Test Result of Power Spectral Density Plots (3KHz)


<802.11b>

PSD 3KHz Plot on 802.11b Channel 01



Date: 11.OCT.2012 20:14:34


PSD 3KHz Plot on 802.11b Channel 06



Date: 11.OCT.2012 20:16:10



PSD 3KHz Plot on 802.11b Channel 11




Date: 11.OCT.2012 20:16:52




<802.11g>

PSD 3KHz Plot on 802.11g Channel 01



Date: 11.OCT.2012 20:19:26


PSD 3KHz Plot on 802.11g Channel 06



Date: 11.OCT.2012 20:20:27



PSD 3KHz Plot on 802.11g Channel 11




Date: 11.OCT.2012 20:21:22




<2.4GHz 802.11n HT-20>

PSD 3KHz Plot on 2.4G 802.11n HT20 Channel 01



Date: 11.OCT.2012 20:23:14


PSD 3KHz Plot on 2.4G 802.11n HT20 Channel 06



Date: 11.OCT.2012 20:24:02



PSD 3KHz Plot on 2.4G 802.11n HT20 Channel 11




Date: 11.OCT.2012 20:24:51




<2.4GHz 802.11n HT-40>

PSD 3KHz Plot on 2.4G 802.11n HT40 Channel 03



Date: 11.OCT.2012 22:08:49


PSD 3KHz Plot on 2.4G 802.11n HT40 Channel 06



Date: 11.OCT.2012 20:26:56



PSD 3KHz Plot on 2.4G 802.11n HT40 Channel 09



Date: 11.OCT.2012 22:09:55

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows the guidelines in the Measurement Procedure of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance and TCB Workshop 2012, April.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 KHz, VBW=300 KHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz, when maximum peak conducted output power procedure is used. The attenuation is set to 30dB, when maximum conducted output power procedure is used.
4. Measure and record the results in the test report.


3.4.4 Test Setup



3.4.5 Test Plots of Conducted Band Edges


Test Mode :	802.11b	Temperature :	21~22°C
Test Band :	Low and High	Relative Humidity :	41~42%
Test Channel :	01 and 11	Test Engineer :	Cloud Peng

Low Band Edge Plot on 802.11b Channel 01



Date: 20.SEP.2012 10:35:07

High Band Edge Plot on 802.11b Channel 11




Date: 20.SEP.2012 10:45:09




Test Mode :	802.11g	Temperature :	21~22°C
Test Band :	Low and High	Relative Humidity :	41~42%
Test Channel :	01 and 11	Test Engineer :	Cloud Peng

Low Band Edge Plot on 802.11g Channel 01



Date: 20.SEP.2012 10:54:25

High Band Edge Plot on 802.11g Channel 11




Date: 20.SEP.2012 11:02:51




Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Band :	Low and High	Relative Humidity :	41~42%
Test Channel :	01 and 11	Test Engineer :	Cloud Peng

Low Band Edge Plot on 802.11n HT20 Channel 01



Date: 20.SEP.2012 11:16:07

High Band Edge Plot on 802.11n HT20 Channel 11




Date: 20.SEP.2012 11:22:22




Test Mode :	802.11n HT40	Temperature :	21~22°C
Test Band :	Low and High	Relative Humidity :	41~42%
Test Channel :	03 and 09	Test Engineer :	Cloud Peng

Low Band Edge Plot on 802.11n HT40 Channel 03



Date: 20.SEP.2012 11:26:23

High Band Edge Plot on 802.11n HT40 Channel 09




Date: 20.SEP.2012 11:33:10

3.4.6 Test Plots of Spurious Emission

Test Mode :	802.11b	Temperature :	21~22°C
Test Band :	30MHz-3GHz and 2G-25GHz	Relative Humidity :	41~42%
Test Channel :	01, 06, 11	Test Engineer :	Cloud Peng

802.11b 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 01



Date: 20.SEP.2012 10:35:31

802.11b 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 01




Date: 20.SEP.2012 10:35:50



802.11b 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 06



Date: 20.SEP.2012 10:42:08

802.11b 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 06




Date: 20.SEP.2012 10:42:26



802.11b 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 11



Date: 20.SEP.2012 10:45:32

802.11b 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 11




Date: 20.SEP.2012 10:45:51



Test Mode :	802.11g	Temperature :	21~22°C
Test Band :	30MHz-3GHz and 2G-25GHz	Relative Humidity :	41~42%
Test Channel :	01, 06, 11	Test Engineer :	Cloud Peng

802.11g 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 01



Date: 20.SEP.2012 10:54:49

802.11g 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 01




Date: 20.SEP.2012 10:55:08



802.11g 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 06



Date: 20.SEP.2012 10:57:47

802.11g 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 06




Date: 20.SEP.2012 10:58:05



802.11g 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 11



Date: 20.SEP.2012 11:01:50

802.11g 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 11




Date: 20.SEP.2012 11:02:08



Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Band :	30MHz-3GHz and 2G-25GHz	Relative Humidity :	41~42%
Test Channel :	01, 06, 11	Test Engineer :	Cloud Peng

802.11n HT20 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 01



Date: 20.SEP.2012 11:16:28

802.11n HT20 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 01




Date: 20.SEP.2012 11:16:46



802.11n HT20 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 06



Date: 20.SEP.2012 11:19:29

802.11n HT20 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 06




Date: 20.SEP.2012 11:19:47



802.11n HT20 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 11



Date: 20.SEP.2012 11:22:42

802.11n HT20 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 11




Date: 20.SEP.2012 11:23:00



Test Mode :	802.11n HT40	Temperature :	21~22
Test Band :	30MHz-3GHz and 2G-25GHz	Relative Humidity :	41~42
Test Channel :	03, 06, 09	Test Engineer :	Cloud Peng

802.11n HT40 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 03



Date: 20.SEP.2012 11:26:46

802.11n HT40 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 03




Date: 20.SEP.2012 11:27:04



802.11n HT40 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 06



Date: 20.SEP.2012 11:29:34

802.11n HT40 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 06




Date: 20.SEP.2012 11:29:52



802.11n HT40 30 MHz~3 GHz


Conducted Spurious Emission Plot on Channel 09



Date: 20.SEP.2012 11:33:36

802.11n HT40 2 GHz~25 GHz

Conducted Spurious Emission Plot on Channel 09



Date: 20.SEP.2012 11:33:54

3.5 Radiated Emission Measurement

3.5.1 Limit of Radiated Emission

In any 100 KHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures


1. The testing follows TCB Workshop 2012, April and fulfills ANSI C63.4-2003 and the guidelines in ANSI C63.10-2009 test site requirement. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving Antenna, which was mounted on the top of a variable height Antenna tower.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 KHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for Peak measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent while maintaining all of the other instrument settings for Average measurement.

Band	Duty Cycle(%)	T(ms)	1/T(KHz)	VBW Setting
802.11b	100.00	-	-	10Hz
802.11g	100.00	-	-	10Hz
2.4G 802.11n HT20	100.00	-	-	10Hz
2.4G 802.11n HT40	100.00	-	-	10Hz


6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. If the emission level of the EUT measured by the peak detector is more than 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be reported by using the quasi-peak detector.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.5.6 Test Result of Radiated Band Edges

Test Mode :	802.11b	Temperature :	21~22°C
Test Band :	Low	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.74	56.58	-17.42	74	48.57	32.86	4.23	29.08	100	0	Peak
2390	45.93	-8.07	54	37.92	32.86	4.23	29.08	101	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.2	53.37	-20.63	74	45.36	32.86	4.23	29.08	199	40	Peak
2387.04	42.09	-11.91	54	34.08	32.86	4.23	29.08	200	40	Average

Test Mode :	802.11b	Temperature :	21~22°C
Test Band :	High	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2487.8	59.97	-14.03	74	51.63	33.05	4.29	29	100	2	Peak
2483.5	53.01	-0.99	54	44.71	33.01	4.29	29	100	2	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.88	56.24	-17.76	74	47.94	33.01	4.29	29	198	44	Peak
2483.5	47.51	-6.49	54	39.21	33.01	4.29	29	134	43	Average



Test Mode :	802.11g	Temperature :	21~22°C
Test Band :	Low	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2339.25	53.63	-20.37	74	45.82	32.78	4.2	29.17	200	0	Peak
2390	40.3	-13.7	54	32.29	32.86	4.23	29.08	183	180	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2342.04	53.85	-20.15	74	46.02	32.78	4.21	29.16	200	57	Peak
2390	39.79	-14.21	54	31.78	32.86	4.23	29.08	200	41	Average

Test Mode :	802.11g	Temperature :	21~22°C
Test Band :	High	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.16	61.37	-12.63	74	53.07	33.01	4.29	29	198	2	Peak
2483.62	44.75	-9.25	54	36.45	33.01	4.29	29	200	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.9	55.29	-18.71	74	46.99	33.01	4.29	29	200	310	Peak
2483.62	41.11	-12.89	54	32.81	33.01	4.29	29	192	305	Average



Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Band :	Low	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2385.24	53.5	-20.5	74	45.53	32.83	4.22	29.08	100	355	Peak
2389.74	41.89	-12.11	54	33.88	32.86	4.23	29.08	189	356	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2364.09	53.17	-20.83	74	45.26	32.81	4.22	29.12	133	291	Peak
2361.48	42.28	-11.72	54	34.38	32.81	4.21	29.12	133	360	Average

Test Mode :	802.11n HT20	Temperature :	21~22°C
Test Band :	High	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.9	56.55	-17.45	74	48.25	33.01	4.29	29	112	0	Peak
2483.54	44.3	-9.7	54	36	33.01	4.29	29	154	353	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2486.9	53.62	-20.38	74	45.32	33.01	4.29	29	200	0	Peak
2484.58	41.85	-12.15	54	33.55	33.01	4.29	29	140	283	Average



Test Mode :	802.11n HT40	Temperature :	21~22°C
Test Band :	Low	Relative Humidity :	45~46%
Test Channel :	03	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2383.08	54.16	-19.84	74	46.19	32.83	4.22	29.08	200	24	Peak
2390	42.65	-11.35	54	34.64	32.86	4.23	29.08	100	356	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.3	53.4	-20.6	74	45.39	32.86	4.23	29.08	200	360	Peak
2373.18	42.35	-11.65	54	34.4	32.83	4.22	29.1	124	273	Average

Test Mode :	802.11n HT40	Temperature :	21~22°C
Test Band :	High	Relative Humidity :	45~46%
Test Channel :	09	Test Engineer :	Chenmy Cheng

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2485.18	58.72	-15.28	74	50.42	33.01	4.29	29	100	110	Peak
2484.38	45.2	-8.8	54	36.9	33.01	4.29	29	100	91	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.16	54.22	-19.78	74	45.92	33.01	4.29	29	100	56	Peak
2483.62	41.92	-12.08	54	33.62	33.01	4.29	29	100	183	Average



3.5.7 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	802.11b	Temperature :	21~22°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
56.197	23.59	-16.41	40	47.45	5.98	0.3	30.14	100	26	Peak
94.428	20.36	-23.14	43.5	40.28	9.66	0.4	29.98	-	-	Peak
147.404	21.48	-22.02	43.5	40.75	10.21	0.5	29.98	-	-	Peak
233.349	20.41	-25.59	46	38.45	11.17	0.65	29.86	-	-	Peak
390.723	22.2	-23.8	46	35.42	15.79	0.84	29.85	-	-	Peak
948.761	27.05	-18.95	46	34.53	20.73	1.33	29.54	-	-	Peak
2412	99.53	-	-	91.45	32.89	4.24	29.05	102	0	Average
2412	105.41	-	-	97.33	32.89	4.24	29.05	102	0	Peak

Test Mode :	802.11b	Temperature :	21~22°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
33.562	29.78	-10.22	40	44.08	15.56	0.23	30.09	100	29	Peak
88.964	21.5	-22	43.5	42.49	8.61	0.39	29.99	-	-	Peak
132.221	21.18	-22.32	43.5	39.15	11.55	0.47	29.99	-	-	Peak
234.168	16.52	-29.48	46	34.56	11.17	0.65	29.86	-	-	Peak
793.396	22.82	-23.18	46	31.32	19.85	1.24	29.59	-	-	Peak
948.761	27.42	-18.58	46	34.9	20.73	1.33	29.54	-	-	Peak
2412	93.48	-	-	85.4	32.89	4.24	29.05	200	41	Average
2412	99.06	-	-	90.98	32.89	4.24	29.05	200	41	Peak



Test Mode :	802.11b	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.289	21.67	-18.33	40	34.21	17.29	0.25	30.08	-	-	Peak
79.8	23.97	-16.03	40	47.19	6.47	0.35	30.04	100	165	Peak
147.404	20.58	-22.92	43.5	39.85	10.21	0.5	29.98	-	-	Peak
252.063	19.87	-26.13	46	37.02	12.03	0.67	29.85	-	-	Peak
389.355	23	-23	46	36.27	15.74	0.84	29.85	-	-	Peak
945.44	27.42	-18.58	46	34.92	20.71	1.33	29.54	-	-	Peak
2437	100.72	-	-	92.55	32.95	4.25	29.03	186	0	Average
2437	105.25	-	-	97.08	32.95	4.25	29.03	186	0	Peak

Test Mode :	802.11b	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.317	24.92	-15.08	40	36.74	18	0.26	30.08	100	0	Peak
53.882	18.43	-21.57	40	41.78	6.49	0.29	30.13	-	-	Peak
88.964	23.41	-20.09	43.5	44.4	8.61	0.39	29.99	-	-	Peak
101.644	23.51	-19.99	43.5	42.32	10.74	0.41	29.96	-	-	Peak
234.168	17.3	-28.7	46	35.34	11.17	0.65	29.86	-	-	Peak
948.761	27.99	-18.01	46	35.47	20.73	1.33	29.54	-	-	Peak
2437	96.32	-	-	88.15	32.95	4.25	29.03	171	58	Average
2437	101.82	-	-	93.65	32.95	4.25	29.03	171	58	Peak



Test Mode :	802.11b	Temperature :	21~22°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2462 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.289	21.01	-18.99	40	33.55	17.29	0.25	30.08	-	-	Peak
97.456	15.47	-28.03	43.5	34.88	10.15	0.41	29.97	-	-	Peak
144.335	20.52	-22.98	43.5	39.56	10.45	0.5	29.99	-	-	Peak
226.099	20.44	-25.56	46	39.16	10.59	0.63	29.94	-	-	Peak
383.932	22.37	-23.63	46	35.81	15.59	0.83	29.86	-	-	Peak
948.761	28.14	-17.86	46	35.62	20.73	1.33	29.54	100	312	Peak
2462	100.43	-	-	92.19	32.98	4.27	29.01	101	360	Average
2462	105.74	-	-	97.5	32.98	4.27	29.01	101	360	Peak

Test Mode :	802.11b	Temperature :	21~22°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2462 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.211	25.74	-14.26	40	37.56	18	0.26	30.08	100	269	Peak
88.964	22.85	-20.65	43.5	43.84	8.61	0.39	29.99	-	-	Peak
97.115	17.87	-25.63	43.5	37.41	10.03	0.4	29.97	-	-	Peak
229.293	16.96	-29.04	46	35.4	10.83	0.64	29.91	-	-	Peak
580.703	22.6	-23.4	46	32.62	18.57	1.05	29.64	-	-	Peak
948.761	27.64	-18.36	46	35.12	20.73	1.33	29.54	-	-	Peak
2462	92.63	-	-	84.39	32.98	4.27	29.01	154	43	Average
2462	98.17	-	-	89.93	32.98	4.27	29.01	154	43	Peak



Test Mode :	802.11g	Temperature :	21~22°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.179	19.9	-20.1	40	33.2	16.55	0.24	30.09	-	-	Peak
97.115	15.5	-28	43.5	35.04	10.03	0.4	29.97	-	-	Peak
147.404	21.35	-22.15	43.5	40.62	10.21	0.5	29.98	-	-	Peak
234.991	19.45	-26.55	46	37.43	11.23	0.65	29.86	-	-	Peak
385.281	23.62	-22.38	46	37.03	15.62	0.83	29.86	-	-	Peak
942.131	27.42	-18.58	46	34.92	20.7	1.33	29.53	100	166	Peak
2412	87.57	-	-	79.49	32.89	4.24	29.05	184	179	Average
2412	98.33	-	-	90.25	32.89	4.24	29.05	184	179	Peak

Test Mode :	802.11g	Temperature :	21~22°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.962	24.28	-15.72	40	36.82	17.29	0.25	30.08	100	113	Peak
88.964	22.36	-21.14	43.5	43.35	8.61	0.39	29.99	-	-	Peak
96.775	17.64	-25.86	43.5	37.18	10.03	0.4	29.97	-	-	Peak
233.349	16.43	-29.57	46	34.47	11.17	0.65	29.86	-	-	Peak
709.182	22.51	-23.49	46	31.69	19.38	1.14	29.7	-	-	Peak
948.761	28.69	-17.31	46	36.17	20.73	1.33	29.54	-	-	Peak
2412	84.03	-	-	75.95	32.89	4.24	29.05	200	44	Average
2412	95.42	-	-	87.34	32.89	4.24	29.05	200	44	Peak



Test Mode :	802.11g	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.531	21.73	-18.27	40	34.27	17.29	0.25	30.08	-	-	Peak
37.812	16.81	-23.19	40	32.93	13.7	0.24	30.06	-	-	Peak
147.404	21.31	-22.19	43.5	40.58	10.21	0.5	29.98	-	-	Peak
234.991	19.28	-26.72	46	37.26	11.23	0.65	29.86	-	-	Peak
386.634	21.78	-24.22	46	35.11	15.68	0.84	29.85	-	-	Peak
948.761	28.5	-17.5	46	35.98	20.73	1.33	29.54	100	162	Peak
2437	88.28	-	-	80.11	32.95	4.25	29.03	100	355	Average
2437	98.93	-	-	90.76	32.95	4.25	29.03	100	355	Peak

Test Mode :	802.11g	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.955	24.88	-15.12	40	38.18	16.55	0.24	30.09	121	0	Peak
88.964	22.18	-21.32	43.5	43.17	8.61	0.39	29.99	-	-	Peak
96.099	17.64	-25.86	43.5	37.3	9.91	0.4	29.97	-	-	Peak
234.168	16.8	-29.2	46	34.84	11.17	0.65	29.86	-	-	Peak
689.565	22.12	-23.88	46	31.49	19.23	1.12	29.72	-	-	Peak
948.761	29.72	-16.28	46	37.2	20.73	1.33	29.54	-	-	Peak
2437	82.74	-	-	74.57	32.95	4.25	29.03	200	304	Average
2437	92.75	-	-	84.58	32.95	4.25	29.03	200	304	Peak



Test Mode :	802.11g	Temperature :	21~22°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2462 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.399	19.76	-20.24	40	32.3	17.29	0.25	30.08	-	-	Peak
52.391	16.89	-23.11	40	39.72	7.01	0.29	30.13	-	-	Peak
146.888	20.94	-22.56	43.5	40.21	10.21	0.5	29.98	-	-	Peak
254.728	20.36	-25.64	46	37.47	12.07	0.67	29.85	-	-	Peak
383.932	23.19	-22.81	46	36.63	15.59	0.83	29.86	-	-	Peak
945.44	28.52	-17.48	46	36.02	20.71	1.33	29.54	100	56	Peak
2462	89.8	-	-	81.56	32.98	4.27	29.01	100	353	Average
2462	100.37	-	-	92.13	32.98	4.27	29.01	100	353	Peak

Test Mode :	802.11g	Temperature :	21~22°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2462 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.071	24.6	-15.4	40	37.14	17.29	0.25	30.08	100	182	Peak
56.001	18.84	-21.16	40	42.7	5.98	0.3	30.14	-	-	Peak
88.964	22.48	-21.02	43.5	43.47	8.61	0.39	29.99	-	-	Peak
97.115	19.73	-23.77	43.5	39.27	10.03	0.4	29.97	-	-	Peak
233.349	17.36	-28.64	46	35.4	11.17	0.65	29.86	-	-	Peak
948.761	27.08	-18.92	46	34.56	20.73	1.33	29.54	-	-	Peak
2462	83.03	-	-	74.79	32.98	4.27	29.01	192	304	Average
2462	93.91	-	-	85.67	32.98	4.27	29.01	192	304	Peak



Test Mode :	802.11n-HT20	Temperature :	21~22°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.531	21.44	-18.56	40	33.98	17.29	0.25	30.08	-	-	Peak
146.374	21.01	-22.49	43.5	40.2	10.29	0.5	29.98	-	-	Peak
233.349	19.64	-26.36	46	37.68	11.17	0.65	29.86	-	-	Peak
389.355	23.25	-22.75	46	36.52	15.74	0.84	29.85	-	-	Peak
478.846	23.35	-22.65	46	35.31	16.85	0.94	29.75	-	-	Peak
948.761	27.75	-18.25	46	35.23	20.73	1.33	29.54	100	26	Peak
2412	87.71	-	-	79.63	32.89	4.24	29.05	187	350	Average
2412	98.55	-	-	90.47	32.89	4.24	29.05	187	350	Peak

Test Mode :	802.11n-HT20	Temperature :	21~22°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2412 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.105	24.86	-15.14	40	36.68	18	0.26	30.08	100	21	Peak
88.964	22.38	-21.12	43.5	43.37	8.61	0.39	29.99	-	-	Peak
97.115	17.91	-25.59	43.5	37.45	10.03	0.4	29.97	-	-	Peak
234.991	17.73	-28.27	46	35.71	11.23	0.65	29.86	-	-	Peak
570.61	21.91	-24.09	46	32	18.54	1.03	29.66	-	-	Peak
942.131	26.61	-19.39	46	34.11	20.7	1.33	29.53	-	-	Peak
2412	80.66	-	-	72.58	32.89	4.24	29.05	137	282	Average
2412	91.26	-	-	83.18	32.89	4.24	29.05	137	282	Peak



Test Mode :	802.11n-HT20	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.105	21.16	-18.84	40	32.98	18	0.26	30.08	-	-	Peak
37.285	16.55	-23.45	40	32.67	13.7	0.24	30.06	-	-	Peak
144.335	21.44	-22.06	43.5	40.48	10.45	0.5	29.99	-	-	Peak
252.948	19.13	-26.87	46	36.27	12.04	0.67	29.85	-	-	Peak
390.723	20.8	-25.2	46	34.02	15.79	0.84	29.85	-	-	Peak
945.44	27.67	-18.33	46	35.17	20.71	1.33	29.54	100	29	Peak
2437	86.2	-	-	78.03	32.95	4.25	29.03	185	352	Average
2437	96.46	-	-	88.29	32.95	4.25	29.03	185	352	Peak

Test Mode :	802.11n-HT20	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.424	25.02	-14.98	40	36.84	18	0.26	30.08	100	291	Peak
88.964	22.11	-21.39	43.5	43.1	8.61	0.39	29.99	-	-	Peak
94.098	18.36	-25.14	43.5	38.28	9.66	0.4	29.98	-	-	Peak
142.324	16.18	-27.32	43.5	35.04	10.64	0.49	29.99	-	-	Peak
661.151	22.81	-23.19	46	32.4	18.97	1.1	29.66	-	-	Peak
948.761	27.54	-18.46	46	35.02	20.73	1.33	29.54	-	-	Peak
2437	80.74	-	-	72.57	32.95	4.25	29.03	140	279	Average
2437	91.21	-	-	83.04	32.95	4.25	29.03	140	279	Peak



Test Mode :	802.11n-HT20	Temperature :	21~22°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2462 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.18	21.55	-18.45	40	34.09	17.29	0.25	30.08	-	-	Peak
38.752	16.82	-23.18	40	33.63	12.98	0.25	30.04	-	-	Peak
147.921	20.85	-22.65	43.5	40.18	10.14	0.51	29.98	-	-	Peak
234.168	19.88	-26.12	46	37.92	11.17	0.65	29.86	-	-	Peak
383.932	22.73	-23.27	46	36.17	15.59	0.83	29.86	-	-	Peak
942.131	27.57	-18.43	46	35.07	20.7	1.33	29.53	100	152	Peak
2462	87.93	-	-	79.69	32.98	4.27	29.01	100	353	Average
2462	97.93	-	-	89.69	32.98	4.27	29.01	100	353	Peak

Test Mode :	802.11n-HT20	Temperature :	21~22°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2462 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.289	24.73	-15.27	40	37.27	17.29	0.25	30.08	100	0	Peak
37.548	17.4	-22.6	40	33.52	13.7	0.24	30.06	-	-	Peak
88.964	22.04	-21.46	43.5	43.03	8.61	0.39	29.99	-	-	Peak
97.115	17.66	-25.84	43.5	37.2	10.03	0.4	29.97	-	-	Peak
779.607	22.97	-23.03	46	31.45	19.87	1.22	29.57	-	-	Peak
948.761	28.04	-17.96	46	35.52	20.73	1.33	29.54	-	-	Peak
2462	83.55	-	-	75.31	32.98	4.27	29.01	140	280	Average
2462	94.02	-	-	85.78	32.98	4.27	29.01	140	280	Peak



Test Mode :	802.11n-HT40	Temperature :	21~22°C
Test Channel :	03	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2422 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.752	16.21	-23.79	40	33.02	12.98	0.25	30.04	-	-	Peak
146.888	21	-22.5	43.5	40.27	10.21	0.5	29.98	-	-	Peak
253.837	19.37	-26.63	46	36.49	12.06	0.67	29.85	-	-	Peak
387.992	21.01	-24.99	46	34.31	15.71	0.84	29.85	-	-	Peak
478.846	22.18	-23.82	46	34.14	16.85	0.94	29.75	-	-	Peak
942.131	26.96	-19.04	46	34.46	20.7	1.33	29.53	100	112	Peak
2422	84.41	-	-	76.29	32.92	4.24	29.04	100	355	Average
2422	94.95	-	-	86.83	32.92	4.24	29.04	100	355	Peak

Test Mode :	802.11n-HT40	Temperature :	21~22°C
Test Channel :	03	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2422 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.853	24.52	-15.48	40	37.06	17.29	0.25	30.08	100	0	Peak
37.285	17.22	-22.78	40	33.34	13.7	0.24	30.06	-	-	Peak
88.964	21.9	-21.6	43.5	42.89	8.61	0.39	29.99	-	-	Peak
97.115	17.75	-25.75	43.5	37.29	10.03	0.4	29.97	-	-	Peak
234.991	17.05	-28.95	46	35.03	11.23	0.65	29.86	-	-	Peak
942.131	27.5	-18.5	46	35	20.7	1.33	29.53	-	-	Peak
2422	76.65	-	-	68.53	32.92	4.24	29.04	200	288	Average
2422	87.58	-	-	79.46	32.92	4.24	29.04	200	288	Peak



Test Mode :	802.11n-HT40	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
88.964	22.52	-20.98	43.5	43.51	8.61	0.39	29.99	-	-	Peak
144.842	21.1	-22.4	43.5	40.14	10.45	0.5	29.99	-	-	Peak
195.137	18.39	-25.11	43.5	39.04	8.75	0.58	29.98	-	-	Peak
238.31	19.44	-26.56	46	37.15	11.46	0.66	29.83	-	-	Peak
383.932	24.1	-21.9	46	37.54	15.59	0.83	29.86	-	-	Peak
948.761	28.89	-17.11	46	36.37	20.73	1.33	29.54	200	0	Peak
2437	85.03	-	-	76.86	32.95	4.25	29.03	100	0	Average
2437	93.72	-	-	85.55	32.95	4.25	29.03	100	0	Peak

Test Mode :	802.11n-HT40	Temperature :	21~22°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2437 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.289	25.25	-14.75	40	37.79	17.29	0.25	30.08	100	215	Peak
88.964	23.4	-20.1	43.5	44.39	8.61	0.39	29.99	-	-	Peak
96.775	18.92	-24.58	43.5	38.46	10.03	0.4	29.97	-	-	Peak
236.645	17.51	-28.49	46	35.35	11.35	0.65	29.84	-	-	Peak
562.662	22.92	-23.08	46	33.06	18.52	1.01	29.67	-	-	Peak
948.761	28.19	-17.81	46	35.67	20.73	1.33	29.54	-	-	Peak
2437	77.08	-	-	68.91	32.95	4.25	29.03	100	282	Average
2437	86.95	-	-	78.78	32.95	4.25	29.03	100	282	Peak



Test Mode :	802.11n-HT40	Temperature :	21~22°C
Test Channel :	09	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	2452 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.853	21.28	-18.72	40	33.82	17.29	0.25	30.08	-	-	Peak
151.067	21.11	-22.39	43.5	40.61	9.96	0.51	29.97	-	-	Peak
197.893	18.17	-25.33	43.5	38.67	8.91	0.59	30	-	-	Peak
237.476	19.47	-26.53	46	37.25	11.4	0.65	29.83	-	-	Peak
387.992	20.38	-25.62	46	33.68	15.71	0.84	29.85	-	-	Peak
948.761	28.94	-17.06	46	36.42	20.73	1.33	29.54	100	229	Peak
2452	84.7	-	-	76.51	32.95	4.26	29.02	100	0	Average
2452	93.83	-	-	85.64	32.95	4.26	29.02	100	0	Peak

Test Mode :	802.11n-HT40	Temperature :	21~22°C
Test Channel :	09	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	2452 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.853	21.28	-18.72	40	33.82	17.29	0.25	30.08	-	-	Peak
151.067	21.11	-22.39	43.5	40.61	9.96	0.51	29.97	-	-	Peak
197.893	18.17	-25.33	43.5	38.67	8.91	0.59	30	-	-	Peak
237.476	19.47	-26.53	46	37.25	11.4	0.65	29.83	-	-	Peak
387.992	20.38	-25.62	46	33.68	15.71	0.84	29.85	-	-	Peak
948.761	28.94	-17.06	46	36.42	20.73	1.33	29.54	100	0	Peak
2452	78.44	-	-	70.25	32.95	4.26	29.02	107	276	Average
2452	87.97	-	-	79.78	32.95	4.26	29.02	107	276	Peak

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in ANSI C63.4-2003 and ANSI C63.10-2009.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 KHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS
 Condition: FCC PART15C LISN-111230 LINE
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	1.83	28.19	-17.81	46.00	17.60	-0.11	10.70	Average
2	1.83	39.49	-16.51	56.00	28.90	-0.11	10.70	QP
3	1.93	30.49	-15.51	46.00	19.90	-0.11	10.70	Average
4	1.93	41.49	-14.51	56.00	30.90	-0.11	10.70	QP
5	1.98	31.09	-14.91	46.00	20.50	-0.11	10.70	Average
6	1.98	41.29	-14.71	56.00	30.70	-0.11	10.70	QP
7	2.08	31.19	-14.81	46.00	20.60	-0.11	10.70	Average
8	2.08	40.69	-15.31	56.00	30.10	-0.11	10.70	QP
9	2.16	30.50	-15.50	46.00	19.90	-0.11	10.71	Average
10	2.16	39.80	-16.20	56.00	29.20	-0.11	10.71	QP
11	2.24	30.00	-16.00	46.00	19.40	-0.11	10.71	Average
12	2.24	38.20	-17.80	56.00	27.60	-0.11	10.71	QP
13	2.32	37.01	-18.99	56.00	26.40	-0.11	10.72	QP
14	2.32	29.01	-16.99	46.00	18.40	-0.11	10.72	Average



Test Mode :	Mode 1	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
 Condition: FCC PART15C LISN-111230 NEUTRAL

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	1.18	40.06	-15.94	56.00	29.49	-0.09	10.66	QP
2	1.18	31.26	-14.74	46.00	20.69	-0.09	10.66	Average
3	1.37	40.67	-15.33	56.00	30.10	-0.10	10.67	QP
4	1.37	31.27	-14.73	46.00	20.70	-0.10	10.67	Average
5	1.43	33.48	-12.52	46.00	22.90	-0.10	10.68	Average
6	1.43	42.28	-13.72	56.00	31.70	-0.10	10.68	QP
7	1.50	42.48	-13.52	56.00	31.90	-0.10	10.68	QP
8	1.50	33.98	-12.02	46.00	23.40	-0.10	10.68	Average
9	1.56	33.28	-12.72	46.00	22.69	-0.10	10.69	Average
10	1.56	42.38	-13.62	56.00	31.79	-0.10	10.69	QP
11	1.67	45.69	-10.31	56.00	35.11	-0.11	10.69	QP
12	1.67	36.39	-9.61	46.00	25.81	-0.11	10.69	Average
13	1.73	35.69	-10.31	46.00	25.11	-0.11	10.69	Average
14	1.73	45.79	-10.21	56.00	35.21	-0.11	10.69	QP
15	1.82	37.29	-8.71	46.00	26.70	-0.11	10.70	Average
16	1.82	47.49	-8.51	56.00	36.90	-0.11	10.70	QP
17	1.88	37.99	-8.01	46.00	27.40	-0.11	10.70	Average
18	1.88	47.99	-8.01	56.00	37.40	-0.11	10.70	QP
19	1.96	38.19	-7.81	46.00	27.60	-0.11	10.70	Average
20	1.96	48.29	-7.71	56.00	37.70	-0.11	10.70	QP
21	2.11	36.19	-9.81	46.00	25.59	-0.11	10.71	Average
22	2.11	46.49	-9.51	56.00	35.89	-0.11	10.71	QP
23	2.25	33.50	-12.50	46.00	22.90	-0.11	10.71	Average
24	2.25	42.90	-13.10	56.00	32.30	-0.11	10.71	QP
25	2.38	31.31	-14.69	46.00	20.70	-0.11	10.72	Average
26	2.38	41.41	-14.59	56.00	30.80	-0.11	10.72	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Connected Construction

Non-standard connector used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Sep. 20, 2012~ Oct. 11, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY451015 55	N/A	Aug. 22, 2012	Sep. 20, 2012~ Oct. 11, 2012	Aug. 21, 2013	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY444211 98	N/A	Aug. 22, 2012	Sep. 20, 2012~ Oct. 11, 2012	Aug. 21, 2013	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 22, 2012	Sep. 20, 2012~ Oct. 11, 2012	Aug. 21, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-9605 02	N/A	Dec. 30, 2011	Sep. 20, 2012~ Oct. 11, 2012	Dec. 29, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Aug. 29, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Aug. 29, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Aug. 29, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/ 001	9 kHz~30 MHz	Jul. 03, 2012	Aug. 29, 2012	Jul. 02, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Aug. 29, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 30, 2011	Aug. 29, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A023 70	1GHz~26.5GHz	Dec. 30, 2011	Aug. 29, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 07, 2011	Aug. 29, 2012	Nov. 06, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Oct. 11, 2011	Aug. 29, 2012	Oct.10, 2012	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 01, 2012	Sep. 18, 2012	May 31, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 30, 2011	Sep. 18, 2012	Dec. 29, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Dec. 30, 2011	Sep. 18, 2012	Dec. 29, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	N/A	Nov. 16, 2011	Sep. 18, 2012	Nov. 15, 2012	Conduction (CO01-KS)
System Simulator	R&S	CMU200	837587/06 6	2G Full-Band	Dec. 30, 2011	Sep. 18, 2012	Dec. 29, 2012	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------



Appendix A. Photographs of EUT

Please refer to Sporton report number EP291301 as below.