

美标

Passive Test For							
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	Max (dB)	Min (dB)	Attenut Hor
824	31.15	-5.07	-0.71	-2.86	-0.71	-15.17	45.02
845	34.48	-4.62	0.9	-1.25	0.9	-19.93	45.53
894	37.8	-4.22	1.03	-1.12	1.03	-22.58	45.77
1850	55.54	-2.55	2.34	0.19	2.34	-17.25	44.99
1920	47.32	-3.25	2.22	0.07	2.22	-18.44	44.74
1990	38.84	-4.11	1.8	-0.35	1.8	-21.55	44.66

欧标

Passive Test For							
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	Max (dB)	Min (dB)	Attenut Hor
880	37.31	-4.28	1.39	-0.76	1.39	-20.95	45.52
914	38.95	-4.09	1.67	-0.48	1.67	-22.92	45.46
960	35.09	-4.55	0.51	-1.64	0.51	-19.98	45.93
1710	51.6	-2.87	1.77	-0.38	1.77	-14.52	45.04
1750	45.4	-3.43	1.08	-1.07	1.08	-14.45	44.81
1880	44.84	-3.48	1.8	-0.35	1.8	-16.1	44.6

Attenut Ver
44.84
45.17
45.36
44.76
44.52
44.66

Attenut Ver
45.4
45.33
45.23
44.86
44.67
44.24