



# TEST REPORT

No. 2011TAR479

for

**ZTE CORPORATION**

**Tablet PC**

**Model Name: V9C**

**FCC ID: Q78-LIGHTV9C**

with

**Hardware Version: d49a**

**Software Version: GB\_V9\_GENERICV1.0.0B07**

**Issued Date: Oct 09, 2011**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

***DAR accreditation (DIN EN ISO/IEC 17025): No. DAT-P-114/01-01***

***FCC 2.948 Listed: No.733176***

***IC O.A.T.S listed: No.6629A-1***

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

Shouxiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633-2678, Fax:+86(0)10-62304793 Email:welcome@emcite.com. [www.emcite.com](http://www.emcite.com)

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>3</b>
<b>1.1. TESTING LOCATION .....</b>	<b>3</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>3</b>
<b>1.3. PROJECT DATA .....</b>	<b>3</b>
<b>1.4. SIGNATURE.....</b>	<b>3</b>
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>4</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>4</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
<b>3.1. ABOUT EUT .....</b>	<b>5</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>5</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>5</b>
<b>3.4. GENERAL DESCRIPTION .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED.....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
<b>A.1 OUTPUT POWER (§24.232(B)).....</b>	<b>11</b>
<b>A.2 EMISSION LIMIT (§2.1051/ §24.238).....</b>	<b>15</b>
<b>A.3 CONDUCTED EMISSION (§15.107 §15.207) .....</b>	<b>19</b>
<b>A.4 FREQUENCY STABILITY (§2.1055/ §24.235) .....</b>	<b>23</b>
<b>A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I)).....</b>	<b>25</b>
<b>A.6 EMISSION BANDWIDTH (§22.917(B)/ §24.238(B)) .....</b>	<b>27</b>
<b>A.7 BAND EDGE COMPLIANCE (§22.917(B)/ §24.238(B)) .....</b>	<b>29</b>
<b>A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/ §22.917/ §24.238).....</b>	<b>30</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT  
Address: Shouxiang Science Building, No 51, Xueyuan Road, Haidian District,  
Beijing, P.R.China  
Postal Code: 100191  
Telephone: 00861062304633  
Fax: 00861062304793


### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: Sep 17, 2011  
Testing End Date: Oct 09, 2011

### 1.4. Signature



---

**Zi Xiaogang**  
**(Prepared this test report)**



---

**Sun Xiangqian**  
**(Reviewed this test report)**



---

**Lu Bingsong**  
**Deputy Director of the laboratory**  
**(Approved this test report)**

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: ZTE CORPORATION  
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, 518057, P.R.China  
City: Shenzhen  
Country: China  
Telephone: 0086 21 68897541  
Fax: 0086 21 50801070

### **2.2. Manufacturer Information**

Company Name: ZTE CORPORATION  
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, 518057, P.R.China  
City: Shenzhen  
Country: China  
Telephone: 0086 21 68897541  
Fax: 0086 21 50801070

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	Tablet PC
Model Name	V9C
FCC ID	Q78-LIGHTV9C
Frequency	GSM 850MHz; PCS 1900MHz; WCDMA Band II;
Antenna	Internal
Power supply	Battery or Charger(AC Adaptor)
Output power	25.65dBm maximum EIRP measured for WCDMA Band II
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
N11	355913040854221	d49a	GB_V9_GENERICV1.0.0B07
N17	355913040854528	d49a	GB_V9_GENERICV1.0.0B07

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>
AE1	Battery	
AE2	Charger	

##### AE1

Model	Li3734T42P3h1286049
Manufacturer	ZTE
Capacitance	3400mAh
Nominal Voltage	3.7V

##### AE2

Model	STC-A22O50I1500M5
Manufacturer	RUIDE
Length of DC line	122cm

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. General Description**

The Equipment Under Test (EUT) is a model of Tablet PC with integrated antenna. It consists of normal options: lithium battery, charger Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber** (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber** (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

**6. SUMMARY OF TEST RESULTS**

<b>Items</b>	<b>List</b>	<b>Clause in FCC rules</b>	<b>Verdict</b>
1	Output Power	24.232(b)	P
2	Emission Limit	2.1051/24.238	P
3	CONDUCTED EMISSION	15.107/15.207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	24.238(b)	P
7	Band Edge Compliance	24.238(b)	P
8	Conducted Spurious Emission	2.1057/24.238	P

## 7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2011-12-06
2	Test Receiver	ESI40	831564/002	R&S	2011-12-12
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2011-12-05
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2011-12-10
5	Signal Generator	SMB100A	102063	R&S	2011-12-05
7	LISN	ESH2-Z5	829991/012	R&S	2011-12-20
8	Spectrum Analyzer	FSU26	200030	R&S	2011-12-18
9	Spectrum Analyzer	FSU46	100054	R&S	2011-12-14
10	Universal Radio Communication Tester	CMU200	100680	R&S	2011-12-23
11	Universal Radio Communication Tester	CMU200	109914	R&S	2011-12-21
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2012-12-31
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2013-12-09
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2011-12-01
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-12-01
16	Climatic chamber	PL-2G	343074	ESPEC	2011-12-15

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER** (§24.232(b))

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### **A.1.2 Conducted**

##### **A.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak) These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II; (bottom, middle and top of operational frequency range).

##### **Limit**

According to FCC§2.1046.

##### **A.1.2.2 Test Condition**

RBW	VBW	Sweep Time	Span
10MHz	10MHz	800ms	50MHz

#### **WCDMA Band II**

##### **Measurement result**

WCDMA (Band II)	CH	Frequency(MHz)	output power(dBm)	Target (dB)
	9262	1852.4	22.68	22.5±0.5
	9400	1880.0	22.50	22.5±0.5
	9538	1907.6	22.39	22.5±0.5

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



**For 1900MHz working frequency test**

In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. For 1900MHz working frequency test:

A cable should be connected between the Signal Source and the Substitution Antenna.

The cable loss ( $P_{cl}$ ) and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

**WCDMA Band II-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

**Measurement result**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Peak EIRP(dBm)	Polarization
1852.40	-25.45	3.90	-50.00	-4.55	25.20	H
1880.00	-25.14	3.64	-50.00	-4.43	<b>25.65</b>	H
1907.60	-26.92	3.60	-50.00	-4.31	23.79	H

Frequency: 1880MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-25.14dBm)- P<sub>cl</sub>(3.64dB)- P<sub>Ag</sub> (-50)-G<sub>a</sub> (-4.43dB) =25.65dBm

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

## A.2 EMISSION LIMIT (§2.1051/§24.238)


### A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 24.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### A.2.2 Measurement Limit

Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**A.2.4 Measurement Results Table**

Frequency	Channel	Frequency Range	Result
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

**A.2.5 Sweep Table**

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3703.41	-57.10	5.80	-8.14	-54.76	-13.00	H
5560.60	-55.88	6.83	-10.02	-52.69	-13.00	H
6857.31	-60.55	9.38	-10.96	-58.97	-13.00	V
8787.51	-66.88	9.10	-12.43	-63.55	-13.00	H
10327.64	-62.99	8.22	-12.47	-58.74	-13.00	H
17796.70	-52.20	10.77	-13.48	-49.49	-13.00	H

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3757.87	-51.84	6.52	-8.21	-50.15	-13.00	H
5642.28	-53.56	6.80	-10.06	-50.30	-13.00	H
8217.82	-60.57	12.57	-12.03	-61.11	-13.00	H
9398.96	-55.17	8.22	-12.60	-50.79	-13.00	H
11277.60	-53.06	8.24	-12.40	-48.90	-13.00	H
13178.76	-60.93	8.62	-13.48	-56.07	-13.00	V

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3817.66	-53.62	6.19	-8.28	-51.53	-13.00	H
6316.23	-65.84	7.07	-10.45	-62.46	-13.00	H
9542.52	-53.25	8.63	-12.58	-49.30	-13.00	H
11447.58	-49.66	8.19	-12.40	-45.45	-13.00	V
13243.65	-61.30	8.48	-13.54	-56.24	-13.00	V
15010.62	-57.07	8.87	-13.50	-52.44	-13.00	H

### A.3 CONDUCTED EMISSION (§15.107§15.207)


The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.

#### A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

\* Decreases with logarithm of the frequency

#### A.3.2 Measurement result WCDMA Band II




#### MEASUREMENT RESULT: "11A06425\_W8C\_fin QP"

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line dB	PE
0.150000	47.10	10.1	66	18.9	L1	GND
0.226500	42.90	10.1	63	19.6	L1	GND
0.262500	36.40	10.1	61	25.0	L1	GND
0.289500	33.40	10.1	61	27.1	N	GND
0.316500	39.30	10.1	60	20.5	L1	GND
0.357000	41.40	10.1	59	17.4	L1	GND

**MEASUREMENT RESULT: "11A06425\_W8C\_fin AV"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line	PE
0.361500	34.50	10.1	49	14.1	L1	GND
0.406500	33.60	10.1	48	14.2	L1	GND
0.496500	33.40	10.1	46	12.7	L1	GND
0.541500	35.50	10.1	46	10.5	L1	GND
0.586500	34.60	10.1	46	11.4	L1	GND
0.631500	34.00	10.1	46	12.0	L1	GND

**MP3**




**MEASUREMENT RESULT: "11A06425\_MC\_fin QP"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line	PE
0.150000	52.00	10.1	66	14.0	L1	GND
0.172500	50.00	10.1	65	14.8	L1	GND
0.195000	47.70	10.1	64	16.1	L1	GND
0.208500	46.70	10.1	63	16.6	L1	GND
0.217500	46.60	10.1	63	16.3	N	GND
0.316500	40.70	10.1	60	19.1	L1	GND

**MEASUREMENT RESULT: "11A06425\_MC\_fin AV"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line	PE
0.406500	33.60	10.1	48	14.1	L1	GND
0.451500	31.80	10.1	47	15.0	L1	GND
0.496500	33.40	10.1	46	12.7	L1	GND
0.541500	35.50	10.1	46	10.5	L1	GND
0.586500	34.40	10.1	46	11.6	L1	GND
0.631500	34.10	10.1	46	11.9	L1	GND

**Camera**



**MEASUREMENT RESULT: "11A06425\_PC\_fin QP"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line	PE
0.154500	54.00	10.1	66	11.7	L1	GND
0.186000	49.50	10.1	64	14.7	N	GND
0.222000	47.30	10.1	63	15.4	N	GND
0.244500	44.30	10.1	62	17.6	L1	GND
0.267000	42.70	10.1	61	18.5	N	GND
0.289500	42.00	10.1	61	18.6	N	GND

**MEASUREMENT RESULT: "11A06425\_PC\_fin AV"**

Frequency MHz	Level dB $\mu$ V	Transd	Limit dB	Margin dB $\mu$ V	Line dB	PE
0.361500	34.20	10.1	49	14.5	L1	GND
0.411000	29.90	10.1	48	17.7	L1	GND
0.496500	33.50	10.1	46	12.6	L1	GND
0.541500	35.30	10.1	46	10.7	L1	GND
0.586500	34.50	10.1	46	11.5	L1	GND
0.631500	34.20	10.1	46	11.8	L1	GND

## **A.4 FREQUENCY STABILITY** (§2.1055/§24.235)

### **A.4.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 9400 for WCDMA Band II, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.4.2 Measurement Limit**

#### **A.4.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### **A.4.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section

2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

#### A.4.3 Measurement results

##### WCDMA Band II

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-25	0.047
3.7	-23	0.043
4.2	-28	0.052

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-28	0.052
-20	-25	0.047
-10	-25	0.047
0	-23	0.043
10	-23	0.043
20	-23	0.043
30	-25	0.047
40	-25	0.047
50	-28	0.052

## A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

### A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II . The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

#### WCDMA Band II(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1852.4	4.182
1880.0	4.166
1907.6	4.182


#### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (-20dBc BW)




Date: 1.SEP.2011 07:12:47

### Channel 9400-Occupied Bandwidth (-20dBc BW)



Date: 1.SEP.2011 07:13:22

### Channel 9538-Occupied Bandwidth (-20dBc BW)



Date: 1.SEP.2011 07:13:56

**A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))**

**A.6.1 Emission Bandwidth Results**


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

**WCDMA Band II(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1852.4	4.471
1880.0	4.487
1907.6	4.487


**WCDMA Band II**

**Channel 9262-Occupied Bandwidth (-26dBc BW)**




Date: 1.SEP.2011 07:14:33

### Channel 9400-Occupied Bandwidth (-26dBc BW)



Date: 1.SEP.2011 07:15:07

### Channel 9538-Occupied Bandwidth (-26dBc BW)




Date: 1.SEP.2011 07:15:42

## A.7 BAND EDGE COMPLIANCE (§22.917(b)/§24.238(b))


### WCDMA Band II

#### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262



Date: 1.SEP.2011 07:15:53

#### HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538



Date: 1.SEP.2011 07:16:04

**A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)**

**A.8.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

**WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

**A. 8.2 Measurement Limit**

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.8.3 Measurement result

#### WCDMA Band II

##### A. 8.3.1 Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:16:35

##### A.8.3.2 Channel 9262: 1GHz –2.5GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 1.SEP.2011 07:17:04

### A.8.3.3 Channel 9262: 2.5GHz –7.5GHz


Spurious emission limit –13dBm.



Date: 1.SEP.2011 07:17:32


### A.8.3.4 Channel 9262: 7.5GHz –10GHz

Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:18:01

**A.8.3.5 Channel 9262: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:18:29

**A.8.3.6 Channel 9262: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 1.SEP.2011 07:18:58


**A. 8.3.7 Channel 9400: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 1.SEP.2011 07:19:29


**A.8.3.8 Channel 9400: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 1.SEP.2011 07:19:58

**A.8.3.9 Channel 9400: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:20:26

**A.8.3.10 Channel 9400: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:20:54

**A.8.3.11 Channel 9400: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:21:23

**A.8.3.12 Channel 9400: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 1.SEP.2011 07:21:51

**A. 8.3.13 Channel 9538: 30MHz –1GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:22:23

**A.8.3.14 Channel 9538: 1GHz –2.5GHz**


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 1.SEP.2011 07:22:51

**A.8.3.15 Channel 9538: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:23:19

**A.8.3.16 Channel 9538: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:23:47

**A.8.3.17 Channel 9538: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:24:16

**A.8.3.18 Channel 9538: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:24:44

**A. 8.3.19 Idle mode: 30MHz –1GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:25:13

**A.8.3.20 Idle mode: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:25:41

**A.8.3.21 Idle mode: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:26:10

**A.8.3.22 Idle mode: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 1.SEP.2011 07:26:38

**A.8.3.23 Idle mode: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 1.SEP.2011 07:27:06

**A.8.3.24 Idle mode: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 1.SEP.2011 07:27:34

\*\*\*END OF REPORT\*\*\*