



FCC SAR

# TEST REPORT

of

## CDMA 1X Wireless Data Terminal

Model Name: MG880+  
Trade Name: ZTE 中兴  
Report No.: SZ08120080S01  
FCC ID: Q78-MG880PLUS

prepared for

### ZTE Corporation

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District,  
Shenzhen, Guangdong, P.R. China

*prepared by*

### Shenzhen Electronic Product Quality Testing Center

#### Morlab Laboratory

3/F, Electronic Testing Building, Shahe Road, Xili,  
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



**NOTE:** This test report can be duplicated completely for the legal use with the approval of the applicant, it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

## Contents

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1. Notes .....	3
1.2. Organization item.....	3
1.3. Conclusion.....	3
<b>2. TESTING LABORATORY.....</b>	<b>4</b>
2.1. Identification of the Responsible Testing Laboratory.....	4
2.2. Identification of the Responsible Testing Location .....	4
2.3. Accreditation Certificate .....	4
2.4. List of Test Equipments .....	4
<b>3. TECHNICAL INFORMATION .....</b>	<b>5</b>
3.1. Identification of Applicant.....	5
3.2. Identification of Manufacturer .....	5
3.3. Equipment Under Test (EUT) .....	5
3.3.1. Photographs of the EUT .....	6
3.3.2. Identification of all used EUTs.....	6
<b>4. TEST RESULTS.....</b>	<b>6</b>
4.1. Applied Reference Documents .....	6
4.2. Test Environment/Conditions .....	7
4.3. Operational Conditions During Test .....	7
4.3.1. Informations On The Testing .....	8
4.3.2. The Measurement System .....	10
4.3.3. Uncertainty Assessment.....	12
4.4. MEASUREMENT PROCEDURES .....	15
4.4.1. Procedures Used To Establish Test Signal.....	15
4.5. Items used in the Test Results List.....	17
4.6. Test Results List.....	18
<b>ANNEX A                      ACCREDITATION CERTIFICATE.....</b>	<b>20</b>
<b>ANNEX B                      PHOTOGRAPHS OF THE EUT .....</b>	<b>21</b>
<b>ANNEX C                      GRAPH TEST RESULTS .....</b>	<b>24</b>

## General Information

### 1.1. Notes



The test results of this test report relate exclusively to the information specified in section 3.3. Shenzhen Electronic Product Quality Testing Center Morlab Laboratory does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the identification. The test report may only be reproduced or published in full. Reproduction or publications of extracts from the test report requires the prior written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test report shall be invalid without all the signatures of testing the Project Manager, the Deputy Project Manager and the Test Lab Manager. Any objections must be raised to Morlab within 30 days since the date when the report is received. It will not be taken into consideration beyond this limit.

### 1.2. Organization item

Report No.:	SZ08120080S01
Date of Issue:	Jan 20, 2008
Date of Tests:	Dec 20, 2008 – Jan 19, 2008
Responsible for Accreditation:	Mr. Shu Luan
Project Manager:	Li Lei
Deputy Project Manager:	Xuwen Wu

### 1.3. Conclusion

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory has verified that all tests as listed in the section 4.6 of this report haven been performed successfully with the tested equipment.

 Li Lei <b>Tested by</b> (Responsible for the Test Report)		 Xuwen Wu <b>Reviewed by</b> (Verification of the Test Report)
 Shu Luan <b>Approved by</b> (Responsible Test Lab Manager)		

## 2. Testing Laboratory

### 2.1. Identification of the Responsible Testing Laboratory

Company Name: Shenzhen Electronic Product Quality Testing Center  
Department: Morlab Laboratory  
Address: 3/F, Electronic Testing Building, Shahe Road, Nanshan District, Shenzhen, 518055 P. R. China  
Responsible Test Lab Manager: Mr. Shu Luan  
Telephone: +86 755 86130268  
Facsimile: +86 755 86130218

### 2.2. Identification of the Responsible Testing Location

Name: Shenzhen Electronic Product Quality Testing Center Morlab Laboratory  
Address: 3/F, Electronic Testing Building, Shahe Road, Nanshan District, Shenzhen, 518055 P. R. China

### 2.3. Accreditation Certificate

Accredited Testing Laboratory: No. CNAS L1659 (see Annex A)

### 2.4. List of Test Equipments

No.	Instrument	Type
1	PC	Dell (Pentium IV 2.4GHz, SN:X10-23533)
2	Network Emulator	Rohde&Schwarz (CMU200, SN:105894)
3	Voltmeter	Keithley (2000, SN:1000572)
4	Synthetizer	Rohde&Schwarz (SML_03, SN:101868)
5	Amplifier	Nucl udes (ALB216, SN:10800)
6	Power Meter	Rohde&Schwarz (NRVD, SN:101066)
7	Probe	Antennessa (SN:SN_3708_EP80)
8	Phantom	Antennessa (SN:SN_36_08_SAM62)
9	Liquid	Antennessa (Last Calibration:21 08 04)

### 3. Technical Information

Note: the following data is based on the information by the applicant.

#### 3.1. Identification of Applicant

Company Name: ZTE Corporation.  
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Contact Person: gong.bolin  
Telephone: (86) 755-86360379  
Facsimile: (86) 755-86360298  
E-mail: gong.bolin1@zte.com.cn

#### 3.2. Identification of Manufacturer

Company Name: ZTE Corporation.  
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Contact Person: gong.bolin  
Telephone: (86) 755-86360379  
Facsimile: (86) 755-86360298  
E-mail: gong.bolin1@zte.com.cn

#### 3.3. Equipment Under Test (EUT)

Brand Name: ZTE 中兴  
Type Name: MG880+  
Marking Name: MG880+  
Hardware Version: EVDO V3.4.0  
Software Version: MG880+MB\_D3  
Frequency Bands: Tx: 825.25 MHz—847.75MHz Rx: 870.25 MHz—892.75MHz  
Modulation Mode: CDMA  
Antenna type: Build inside

### 3.3.1. Photographs of the EUT

Please see for photographs of the EUT.

### 3.3.2. Identification of all used EUTs

The EUT Identity consists of numerical and letter characters (see the table below), the first five numerical characters indicates the Type of the EUT defined by Morlab, the next letter character indicates the test sample, and the following two numerical characters indicates the software version of the test sample.

EUT Identity	ESN	Hardware Version	Software Version
1#	00000000	EVDO V3.4.0	MG880+MB_D3
2#	00000000	EVDO V3.4.0	MG880+MB_D3

## 4. Test Results

### 4.1. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR § 2. 1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
2	FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01)	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
3	ANSI C95.1-1999	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 GHz
4	IEEE 1528-2003	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

## 4.2. Test Environment/Conditions

Normal Temperature (NT):	20 ... 25 °C
Relative Humidity:	30 ... 75 %
Air Pressure:	980 ... 1020 hPa
Details of Power Supply:	220V/50Hz AC
Extreme Temperature:	Low Temperature (LT) = -10°C
	High Temperature (HT) = 55°C
Extreme Voltage of the EUT:	Normal Voltage (NV) = 3.80V
	Low Voltage (LV) = 3.60V
	High Voltage (HV) = 4.20V
Test frequency:	CDMA 800MHz
Operation mode:	Call established
Power Level:	Maximum output power

During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established.

The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 1013, 384 and 777 respectively in the case of CDMA 800MHz, The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset.

The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 35 dB.

### 4.3. Operational Conditions During Test

#### 4.3.1. Informations On The Testing

##### I. INFORMATIONS ON THE TESTING


###### I.1. Normative reference

IEEE 1528: Recommended Practice for determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques. Institute of Electrical and Electronics Engineers, INC., 2003.

###### I.3. Positions and test conditions of the mobile phone under test

The mobile phone antenna and battery are those specified by the manufacturer. The battery is fully charged before each measurement. The output power and frequency are controlled using a base station simulator. The mobile phone is set to transmit at its highest output peak power level.

The mobile phone is test in the “cheek” and “tilted” positions on the left and right sides of the phantom. The mobile phone is placed with the vertical centre line of the body of the mobile phone and the horizontal line crossing the centre of the earpiece in a plane parallel to the sagittal plane of the phantom.



Description of the « cheek » position:

The mobile phone is well placed in the reference plane and the earpiece is in contact with the ear. Then the mobile phone is moved until any point on the front side get in contact with the cheek of the phantom or until contact with the ear is lost.

Description of the « tilted » position:

The mobile phone is well place in the "cheek" position as described above. Then the mobile phone is moved outward away from the mouth by an angle of 15 degrees or until contact with the ear lost.

### 4.3.2. The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



COMOSAR bench

The mobile phone under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10 g mass.

#### II.1. Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2 mm +/- 0,2 mm. It enables the dosimetric evaluation of left and right hand phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

#### II.2. Probe

For the measurements the Specific Dosimetric E-Field Probe SSE5 with following specifications is used.

- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 5 mm

- Distance between probe tip and sensor center : 2.5 mm
- Distance between sensor center and the inner phantom surface: 4 mm (repeatability better than +/- 1mm).
- Probe linearity : <0.25 dB
- Axial Isotropy : <0.25 dB
- Spherical Isotropy : <0.50 dB
- Calibration range : 835 to 2500 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line : less than 30°

### II.3. Measurement procedure

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16 mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors can not directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8 \* 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

### II.4 Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

### 4.3.3. Uncertainty Assessment

The following table includes the uncertainty table of the IEEE 1528.

The values are determined by Antennessa.

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+-% %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	$\infty$
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1-C_p)^{1/2}$	$(1-C_p)^{1/2}$	1.02	1.02	$\infty$
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$\sqrt{C_n}$	$\sqrt{C_n}$	1.63	1.63	$\infty$
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	$\infty$
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	$\infty$
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	$\infty$
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	$\infty$
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	$\infty$
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	$\infty$
Test sample Related									
Test sample positioning	E.4.2.1	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR drift measurement	6.6.2	4.76	R	$\sqrt{3}$	1	1	2.75	2.75	$\infty$
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	$\infty$
Liquid conductivity - deviation from target value	E.3.2	0.57	R	$\sqrt{3}$	0.64	0.43	0.21	0.14	$\infty$

Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	M
Liquid permittivity - deviation from target value	E.3.2	3.66	R	$\sqrt{3}$	0.6	0.49	1.27	1.04	$\infty$
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty			RSS				11.28	10.78	
Expanded Uncertainty (95% Confidence interval)			k				21.99	21.03	

#### 4.3.4. Equipments and results of validation testing

Equipments :

name	Type and specification
Signal generator	E4433B
Directional coupler	450MHz-3GHz
Amplifier	3W 502(10-2500MHz)
Reference dipole	SN 36/08 DIPF 101

Results:

Frequency	Target value (1g)	Test value (1g)
835MHz	9.5W/Kg	10.06 (body)

Results (2009/1/17) :

Frequency	Target value (1g)	Test value (1g)
835MHz	9.5W/Kg	9.548 (body)

**Note:**Please refer to check the system performance data, the first 72-77 page.

#### 4.3.5. Dielectric Performance

The measured 1-gram averaged SAR values of the device against the head and the body are provided in Tables 1 and 2 respectively. The humidity and ambient temperature of test facility were 54% ~60% and 23.0 °C ~23.8°C respectively. The SAM head phantom (SN 0381 SH) were full of the head tissue

simulating liquid. The depth of the body tissue was 15.1cm. The distance between the back of the device and the bottom of the flat phantom is 1.5cm (taking into account of the IEEE 1528 and the place of the antenna). A base station simulator was used to control the device during the SAR measurement. The phone was supplied with full-charged battery for each measurement. For head measurement, the device was tested at the lowest, middle and highest frequencies in the transmit band.

For body-worn measurements, the device was tested against flat phantom representing the user body. Under measurement phone was put on in the belt holder.

**Table 1: Dielectric Performance of Body Tissue Simulating Liquid**

<b>Temperature: 23.0~23.8°C, humidity: 54~60%.</b>			
<b>/</b>	<b>Frequency</b>	<b>Permittivity <math>\epsilon</math></b>	<b>Conductivity <math>\sigma</math> (S/m)</b>
<b>Target value</b>	835 MHz	55.0	1.05
<b>Validation value</b> (Dec 20 )	835 MHz	51.540001	0.975187

**Table 2: Dielectric Performance of Body Tissue Simulating Liquid**

<b>Temperature: 23.0~23.8°C, humidity: 54~60%.</b>			
<b>/</b>	<b>Frequency</b>	<b>Permittivity <math>\epsilon</math></b>	<b>Conductivity <math>\sigma</math> (S/m)</b>
<b>Target value</b>	835 MHz	55.0	1.05
<b>Validation value</b> (Jan 17 )	835 MHz	53.745551	1.116643

#### 4.3.6. Simulant liquids

Simulant liquids that are used for testing at frequencies of GSM 1900MHz, which are made mainly of sugar, salt and water solutions may be left in the phantoms. Approximately 20litres are needed for an upright head compared to about 20litres for a horizontal bath phantom.

Ingredients (% by weight )	Frequency Band	
	835	
Tissue Type	Head	Body
Water	41.45	52.4
Salt(NaCl)	1.45	1.4
Sugar	56.0	45.0
HEC	1.0	1.0
Bactericide	0.1	0.1
Triton	0.0	0.0
DGBE	0.0	0.0
Acticide SPX	0.0	0.0
Dielectric Constant	42.45	56.1
Conductivity (S/m)	0.91	0.95

### 4.4. MEASUREMENT PROCEDURES

#### 4.4.1. Procedures Used To Establish Test Signal

The device was placed into a simulated call using a base station in a screen room. Such test signals offer a consistent means for testing SAR and recommended for evaluating SAR. The SAR measurement software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more than 5% occurred, the tests were repeated.

#### 4.4.2 SAR Measurement Conditions for CDMA2000 1x

These procedures were followed according to FCC "SAR Measurement Procedures for 3G Devices", October 2007 (Revised).

##### 4.4.2.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by "SAR Measurement Procedures for 3G Devices", October 2007 (Revised).

Maximum output power is verified on the High, Middle and Low channels according to procedures in section 3.1.2.3.4 of 3GPP2 C.S0033-0/TIA-866 for Rev. 0 and section 4.3.4 of

3GPP2 C.S0033-A for Rev. A. For Rev. A, maximum output power for both Subtype 0/1 and Subtype 2 Physical Layer configurations should be measured. The device operating configurations under TAP/ETAP should be documented in the test report; including power control, code channel and RF channel output power levels. The measurement results should be tabulated in the SAR report with any measurement difficulties and equipment limitations clearly identified.

#### **4.4.2.2 SAR Measurement**

SAR is measured using FTAP/RTAP and FETAP/RETAP respectively for Rev. 0 and Rev. A devices. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations. Both FTAP and FETAP are configured with a Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots. AT power control should be in “All Bits Up” conditions for TAP/ETAP.

Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. SAR for Subtype 2 Physical layer configurations is not required for Rev. A when the maximum average output of each RF channels is less than that measured in Subtype 0/1 Physical layer configurations. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for that RF channels in Rev. 0.17 Head SAR is required for Ev-Do devices that support operations next to the ear; for example, with VOIP, using Subtype 2 Physical Layer configurations according to the required handset configurations.

#### **4.4.2.3 1x RTT Support**

For Ev-Do devices that also support 1x RTT voice and/or data operations, SAR is not required for 1x RTT when the maximum average output of each channel is less than  $\frac{1}{4}$  dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0. Otherwise, the ‘Body SAR Measurements’ procedures in the ‘CDMA 2000 1x Handsets’ section should be applied.

#### **4.4.2.4 Output Power Verification 1x RTT**

Maximum output power is verified on the High, Middle, and Low channels according to procedures in Section 4.4.5.2 of 3 GPP2 C.S0011/TIA-98-E. Results for at least steps 3,4 and 10 of the power measurement procedures should be tabulated in the SAR report. Steps 3 and 4 should be measured using SO55 with power control bits in “All Up” condition. TDSO/SO32 may be used instead of SO55 for step 4. Step 10 should be measured using TDSO/SO32 with power control bits in the “Bits Hold”

### 1xRTT Power Measurements

Channel	Radio Configuration and conducted Power (dBm)				
	RC1	RC2	RC3	RC4	RC5
Low	27.63	27.44	27.8	27.8	27.43
Mid	26.13	26.52	26.13	26.78	26.14
High	27.73	28.15	27.41	28.17	27.73
SO	SO2	SO9	SO55	SO55	SO55

Power Control was set in ‘All Bits Up’ for all measurements.

#### 4.5. Items used in the Test Results List

Terms in the column “Verdict” for the test results list of the section 4.6:

Verdict	Description
PASS	EUT passed this test case
FAIL	EUT failed this test case
INC.	EUT did not pass and did not fail this test case, therefore the verdict is inconclusive
Decl.	“Declaration”: Morlab has received documents from the applicant and/or manufacturer which show conformity to the applied standards for this test case.
N/A	Test case not applicable for the EUT, see the column “Note” for detailed

#### 4.6. Test Results List

Summary of Measurement Results (CDMA 800MHz Band)

SAR Values (CDMA 800MHz Band), Measured against the body0.

Temperature: 23.0~23.8°C, humidity: 54~60%.		
Limit of SAR (W/kg)	1 g Average	
	1.6	
Test Case	Measurement Result (W/kg)	
	1 g Average (W/kg)	Power level (dBm)
Validation Plane with Body device position on Low Channel in CDMA mode (Horizontal-Up)	0.377	27.8
Validation Plane with Body device position on Middle Channel in CDMA mode (Horizontal-Up)	0.721	26.78
Validation Plane with Body device position on High Channel in CDMA mode (Horizontal-Up)	0.702	28.17
Validation Plane with Body device position on Low Channel in CDMA mode (Horizontal-Down)	0.735	27.8
Validation Plane with Body device position on Middle Channel in CDMA mode (Horizontal-Down)	0.988	26.78
Validation Plane with Body device position on High Channel in CDMA mode (Horizontal-Down)	0.865	28.17
Validation Plane with Body device position on Low Channel in CDMA mode (Vertical-Front)	0.325	27.8
Validation Plane with Body device position on Middle Channel in CDMA mode (Vertical-Front)	0.518	26.78
Validation Plane with Body device position on High Channel in CDMA mode (Vertical-Front)	0.658	28.17
Validation Plane with Body device position on Low Channel in CDMA mode (Vertical-Back)	0.031	27.8
Validation Plane with Body device position on Middle Channel in CDMA mode (Vertical-Back)	0.095	26.78
Validation Plane with Body device position on High Channel in CDMA mode (Vertical-Back)	0.102	28.17

Summary of Measurement Results (CDMA 800MHz Band)

## SAR Values (CDMA 800MHz Band), Measured against the body0.

Temperature: 23.0~23.8°C, humidity: 54~60%.		
Limit of SAR (W/kg)	1 g Average	
	1.6	
Test Case	Measurement Result (W/kg)	
	1 g Average (W/kg)	Power level (dBm)
Validation Plane with Body device position on Low Channel in CDMA mode (EUT Antenna swivel)	0.757	27.8
Validation Plane with Body device position on Middle Channel in CDMA mode (EUT Antenna swivel)	1.188	26.78
Validation Plane with Body device position on High Channel in CDMA mode (EUT Antenna swivel)	1.048	28.17

**Note:** 1. Antenna swivel is the most stringent state.

2. The depth of the body tissue was 15.1cm. The distance between the back of the device and the bottom of the flat phantom is 5mm (taking into account of the IEEE 1528 and the place of the antenna)

**Annex A Accreditation Certificate**

 
<b>China National Accreditation Service for Conformity Assessment</b>
<b>LABORATORY ACCREDITATION CERTIFICATE</b>
<b>(No. CNAS L1659 )</b>
<i>China National Accreditation Service for Conformity Assessment has accredited</i>
<b>Shenzhen Electronic Product Quality Testing Center</b>
<b>(CQCS Testing Co. Ltd.)</b>
<u>Electronic Testing Building Wenguang Road, Shahe West, Xili Town, Nanshan</u>
<u>District, Shenzhen, Guangdong, China</u>
<i>to ISO/IEC 17025:1999 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing and calibration.</i>
<i>The scope of accreditation is detailed in the attached schedule bearing the same accreditation number as above. The schedule forms an integral part of this certificate.</i>
Date of Issue: 2007-01-17
Date of Expiry: 2009-10-08
Date of Initial Accreditation: 1999-08-03

Signed on behalf of China National Accreditation Service for Conformity Assessment
<small>China National Accreditation Service for Conformity Assessment(CNAS) is authorized by Certification and Accreditation Administration of the People's Republic of China (CNCA) to operate the national accreditation systems for conformity assessment. CNAS is the signatory to International Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (ILAC-MRA), and the signatory to Asia Pacific Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (APLAC-MRA).</small>

## Annex B Photographs of the EUT


### 1 EUT Horizontal-Up(PC:IBM T42)




### 2 EUT Horizontal-Down



3 EUT Vertical-Front(PC:IBM T20)



4 EUT Vertical-Back



## 5 EUT Antenna swivel



## 6. Data line



### Annex C Graph Test Results

	<b>BAND</b>	<b><u>PARAMETERS</u></b>
<b><u>TYPE</u></b>	CDMA850	Measurement 1: Validation Plane with Body device position on Low Channel in CDMA mode <b>(Horizontal-Up)</b> Measurement 2: Validation Plane with Body device position on Middle Channel in CDMA mode <b>(Horizontal-Up)</b> Measurement 3: Validation Plane with Body device position on High Channel in CDMA mode <b>(Horizontal-Up)</b> Measurement 4: Validation Plane with Body device position on Low Channel in CDMA mode <b>(Horizontal-Down)</b> Measurement 5: Validation Plane with Body device position on Middle Channel in CDMA mode <b>(Horizontal-Down)</b> Measurement 6: Validation Plane with Body device position on High Channel in CDMA mode <b>(Horizontal-Down)</b> Measurement 7: Validation Plane with Body device position on Low Channel in CDMA mode <b>(Vertical-Front)</b> Measurement 8: Validation Plane with Body device

		<p>position on Middle Channel in CDMA mode <b>(Vertical-Front)</b></p> <p>Measurement 9: Validation Plane with Body device position on High Channel in CDMA mode <b>(Vertical-Front)</b></p> <p>Measurement 10: Validation Plane with Body device position on Low Channel in CDMA mode <b>(Vertical-Back)</b></p> <p>Measurement 11: Validation Plane with Body device position on Middle Channel in CDMA mode <b>(Vertical-Back)</b></p> <p>Measurement 12: Validation Plane with Body device position on High Channel in CDMA mode <b>(Vertical-Back)</b></p> <p>Measurement 13: Validation Plane with Body device position on Low Channel in CDMA mode <b>(Antenna swivel)</b></p> <p>Measurement 14: Validation Plane with Body device position on Middle Channel in CDMA mode <b>(Antenna swivel)</b></p> <p>Measurement 15: Validation Plane with Body device position on High Channel in CDMA mode <b>(Antenna swivel)</b></p>
--	--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## MEASUREMENT 1 (Horizontal-Up)

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 27 seconds

Mobile Phone IMEI number: --

### **A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850
<b>Channels</b>	Low

<b>Signal</b>	<b>CDMA</b>
---------------	-------------

**B. SAR Measurement Results**

Lower Band SAR (Channel 1013):

<b>Frequency (MHz)</b>	824.700012
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	0.490000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=10.00, Y=6.00**

<b>SAR 10g (W/Kg)</b>	0.222963
<b>SAR 1g (W/Kg)</b>	0.377188


### Z Axis Scan

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.3992</b>	<b>0.2368</b>	<b>0.1461</b>	<b>0.0979</b>

**SAR, Z Axis Scan (X = 10, Y = 6)**



<b>3D scene shot</b>	<b>Hot spot position</b>
----------------------	--------------------------



**MEASUREMENT 2 (Horizontal-Up)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 27 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	Middle
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 384):

<b>Frequency (MHz)</b>	836.520020
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	0.490000




**Maximum location: X=10.00, Y=6.00**

<b>SAR 10g (W/Kg)</b>	0.422982
<b>SAR 1g (W/Kg)</b>	0.721465


**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.3992</b>	<b>0.2368</b>	<b>0.1461</b>	<b>0.0979</b>

**SAR, Z Axis Scan (X = 10, Y = 6)**



<b>3D scen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**MEASUREMENT 3 (Horizontal-Up)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 27 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	High
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 777):

<b>Frequency (MHz)</b>	848.309998
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	0.490000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=10.00, Y=6.00**


<b>SAR 10g (W/Kg)</b>	0.425435
<b>SAR 1g (W/Kg)</b>	0.702719

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.3992</b>	<b>0.2368</b>	<b>0.1461</b>	<b>0.0979</b>

**SAR, Z Axis Scan (X = 10, Y = 6)**





**MEASUREMENT 4 (Horizontal-Down)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 28 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	Low
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 1013):

<b>Frequency (MHz)</b>	824.700012
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.740000




**Maximum location: X=18.00, Y=-5.00**

<b>SAR 10g (W/Kg)</b>	0.399934
<b>SAR 1g (W/Kg)</b>	0.735564


### Z Axis Scan

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.7913</b>	<b>0.4359</b>	<b>0.2499</b>	<b>0.1591</b>

**SAR, Z Axis Scan (X = 18, Y = -5)**



<b>3D scen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**MEASUREMENT 5 (Horizontal-Down)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 28 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	Middle
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 384):

<b>Frequency (MHz)</b>	836.520020
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.740000




**Maximum location: X=18.00, Y=-5.00**

<b>SAR 10g (W/Kg)</b>	0.463932
<b>SAR 1g (W/Kg)</b>	0.988657


**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.7913</b>	<b>0.4359</b>	<b>0.2499</b>	<b>0.1591</b>

**SAR, Z Axis Scan (X = 18, Y = -5)**



<b>3D scen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**MEASUREMENT 6 (Horizontal-Down)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 28 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	High
<b>Signal</b>	CDMA

### **B. SAR Measurement Results**

Lower Band SAR (Channel 777):

<b>Frequency (MHz)</b>	848.309998
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.740000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=18.00, Y=-5.00**


<b>SAR 10g (W/Kg)</b>	0.458512
<b>SAR 1g (W/Kg)</b>	0.865448

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.7913</b>	<b>0.4359</b>	<b>0.2499</b>	<b>0.1591</b>

**SAR, Z Axis Scan (X = 18, Y = -5)**





**MEASUREMENT 7 (Vertical-Front)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 6 minutes 2 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	Low
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 1013):

<b>Frequency (MHz)</b>	824.700012
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.710000




**Maximum location: X=-2.00, Y=-8.00**

<b>SAR 10g (W/Kg)</b>	0.176249
<b>SAR 1g (W/Kg)</b>	0.325677


### Z Axis Scan

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.3504</b>	<b>0.1879</b>	<b>0.1058</b>	<b>0.0677</b>

**SAR, Z Axis Scan (X = -2, Y = -8)**



<b>3D scen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



## MEASUREMENT 8 (Vertical-Front)

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 6 minutes 2 seconds

Mobile Phone IMEI number: --

### **A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	Middle
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 384):

<b>Frequency (MHz)</b>	836.520020
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.710000




**Maximum location: X=-2.00, Y=-8.00**

<b>SAR 10g (W/Kg)</b>	0.277692
<b>SAR 1g (W/Kg)</b>	0.517599


**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.3504</b>	<b>0.1879</b>	<b>0.1058</b>	<b>0.0677</b>

**SAR, Z Axis Scan (X = -2, Y = -8)**



<b>3D scen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**MEASUREMENT 9 (Vertical-Front)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 6 minutes 2 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	High
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 777):

<b>Frequency (MHz)</b>	848.309998
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.710000




**Maximum location: X=-2.00, Y=-8.00**

<b>SAR 10g (W/Kg)</b>	0.359885
<b>SAR 1g (W/Kg)</b>	0.658422


**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.3504</b>	<b>0.1879</b>	<b>0.1058</b>	<b>0.0677</b>

**SAR, Z Axis Scan (X = -2, Y = -8)**



<b>3D scen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**MEASUREMENT 10 (Vertical-Back)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 23 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body
<b>Band</b>	CDMA850

<b>Channels</b>	Low
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 1013):

<b>Frequency (MHz)</b>	824.700012
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	3.900000




**Maximum location: X=3.00, Y=16.00**

<b>SAR 10g (W/Kg)</b>	0.017879
<b>SAR 1g (W/Kg)</b>	0.031054


**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.0325</b>	<b>0.0170</b>	<b>0.0093</b>	<b>0.0059</b>

**SAR, Z Axis Scan (X = 3, Y = 16)**



<b>3D seen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**MEASUREMENT 11 (Vertical-Back)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 23 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	Middle
<b>Signal</b>	CDMA

## **B. SAR Measurement Results**

Lower Band SAR (Channel 384):

<b>Frequency (MHz)</b>	836.520020
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	3.900000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=3.00, Y=16.00**


<b>SAR 10g (W/Kg)</b>	0.035488
<b>SAR 1g (W/Kg)</b>	0.095445

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.0325</b>	<b>0.0170</b>	<b>0.0093</b>	<b>0.0059</b>

**SAR, Z Axis Scan (X = 3, Y = 16)**





**MEASUREMENT 12 (Vertical-Back)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 23 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	High
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 777):

<b>Frequency (MHz)</b>	848.309998
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	3.900000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=3.00, Y=16.00**


<b>SAR 10g (W/Kg)</b>	0.054112
<b>SAR 1g (W/Kg)</b>	0.102255

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.0325</b>	<b>0.0170</b>	<b>0.0093</b>	<b>0.0059</b>

**SAR, Z Axis Scan (X = 3, Y = 16)**





**MEASUREMENT 13 (Antenna swivel)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 20/12/2008

Measurement duration: 5 minutes 28 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	Low
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Lower Band SAR (Channel 1013):

<b>Frequency (MHz)</b>	824.700012
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.740000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=18.00, Y=-5.00**


<b>SAR 10g (W/Kg)</b>	0.383957
<b>SAR 1g (W/Kg)</b>	0.757483

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.7913</b>	<b>0.4359</b>	<b>0.2499</b>	<b>0.1591</b>

**SAR, Z Axis Scan (X = 18, Y = -5)**





**MEASUREMENT 14 (Antenna swivel)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 17/1/2009

Measurement duration: 5 minutes 28 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	Middle
<b>Signal</b>	CDMA

### B. SAR Measurement Results

Lower Band SAR (Channel 384):

<b>Frequency (MHz)</b>	836.520020
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.740000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=18.00, Y=-5.00**


<b>SAR 10g (W/Kg)</b>	0.624345
<b>SAR 1g (W/Kg)</b>	1.188474

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.7913</b>	<b>0.4359</b>	<b>0.2499</b>	<b>0.1591</b>

**SAR, Z Axis Scan (X = 18, Y = -5)**





**MEASUREMENT 15 (Antenna swivel)**

Type: Phone measurement (Very fast, 27 points in the volume)

Date of measurement: 17/1/2009

Measurement duration: 5 minutes 28 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA850
<b>Channels</b>	High
<b>Signal</b>	CDMA

### **B. SAR Measurement Results**

Lower Band SAR (Channel 777):

<b>Frequency (MHz)</b>	848.309998
<b>Relative permittivity (real part)</b>	54.116001
<b>Relative permittivity (imaginary part)</b>	21.284550
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.740000

<b>SURFACE SAR</b>	<b>VOLUME SAR</b>
	


**Maximum location: X=18.00, Y=-5.00**


<b>SAR 10g (W/Kg)</b>	0.543323
<b>SAR 1g (W/Kg)</b>	1.0483733

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>0.7913</b>	<b>0.4359</b>	<b>0.2499</b>	<b>0.1591</b>

**SAR, Z Axis Scan (X = 18, Y = -5)**





**System Performance Check Data(Body)**

Type: Validation measurement (Very fast, 27 points in the volume)

Date of measurement:20/12/2008

Measurement duration: 5 minutes 27 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA 835MHz
<b>Channels</b>	Middle
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Middle Band SAR (Channel 384):

<b>Frequency (MHz)</b>	836.520020
<b>Relative permittivity (real part)</b>	51.540001
<b>Relative permittivity (imaginary part)</b>	15.070000
<b>Conductivity (S/m)</b>	0.975187
<b>Variation (%)</b>	-0.140000




**Maximum location: X=5.00, Y=1.00**

<b>SAR 10g (W/Kg)</b>	1.236559
<b>SAR 1g (W/Kg)</b>	2.515698



**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>2.8536</b>	<b>1.3061</b>	<b>0.6041</b>	<b>0.3211</b>

**SAR, Z Axis Scan (X = 5, Y = 1)**



<b>3D seen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------



**System Performance Check Data(Body)**

Type: Validation measurement (Very fast, 27 points in the volume)

Date of measurement: 17/1/2009

Measurement duration: 5 minutes 27 seconds

Mobile Phone IMEI number: --

**A. Experimental conditions.**


<b>Phantom File</b>	surf_sam_plan.txt
<b>Phantom</b>	Validation plane
<b>Device Position</b>	Body

<b>Band</b>	CDMA 835MHz
<b>Channels</b>	
<b>Signal</b>	CDMA

**B. SAR Measurement Results**

Band SAR:

<b>Frequency (MHz)</b>	835.000000
<b>Relative permittivity (real part)</b>	53.745551
<b>Relative permittivity (imaginary part)</b>	15.070000
<b>Conductivity (S/m)</b>	1.116643
<b>Variation (%)</b>	-0.140000




**Maximum location: X=5.00, Y=1.00**

<b>SAR 10g (W/Kg)</b>	1.115934
<b>SAR 1g (W/Kg)</b>	2.387533

**Z Axis Scan**

<b>Z (mm)</b>	<b>0.00</b>	<b>4.00</b>	<b>9.00</b>	<b>14.00</b>	<b>19.00</b>
<b>SAR (W/Kg)</b>	<b>0.0000</b>	<b>2.8536</b>	<b>1.3061</b>	<b>0.6041</b>	<b>0.3211</b>

**SAR, Z Axis Scan (X = 5, Y = 1)**



<b>3D seen shot</b>	<b>Hot spot position</b>
---------------------	--------------------------

