


# FCC RF Test Report

APPLICANT : ZTE CORPORATION  
EQUIPMENT : 3G Smart Mobile phone  
BRAND NAME : ZTE  
MODEL NAME : ZTE-U N720  
FCC ID : Q78-N720  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Feb. 28, 2011 and completely tested on Mar. 16, 2011. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**



# TABLE OF CONTENTS

REVISION HISTORY ..... 3

SUMMARY OF TEST RESULT ..... 4

1 GENERAL DESCRIPTION ..... 5

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Feature of Equipment Under Test ..... 5

    1.4 Testing Site ..... 6

    1.5 Applied Standards ..... 6

    1.6 Ancillary Equipment List ..... 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 7

    2.1 RF Output Power ..... 7

    2.2 Test Mode ..... 8

    2.3 Connection Diagram of Test System ..... 9

    2.4 RF Utility ..... 9

3 TEST RESULT ..... 10

    3.1 Number of Channel Measurement ..... 10

    3.2 20dB Bandwidth Measurement ..... 12

    3.3 Hopping Channel Separation Measurement ..... 19

    3.4 Dwell Time Measurement ..... 22

    3.5 Peak Output Power Measurement ..... 24

    3.6 Band Edges Measurement ..... 27

    3.7 Spurious Emission Measurement ..... 38

    3.8 AC Conducted Emission Measurement ..... 42

    3.9 Radiated Emission Measurement ..... 46

    3.10 Antenna Requirements ..... 55

4 LIST OF MEASURING EQUIPMENT ..... 56

5 UNCERTAINTY OF EVALUATION ..... 57

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	A8.5	Spurious Emission	< 20 dBc	Pass	-
3.8	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 17.17 dB at 0.16 MHz
3.9	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.97 dB at 2483.5 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

### ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

## 1.2 Manufacturer

### ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

## 1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	3G Smart Mobile phone
Brand Name	ZTE
Model Name	ZTE-U N720
FCC ID	Q78-N720
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 7.23 dBm (0.005 W) Bluetooth EDR (2Mbps) : 6.51 dBm (0.005 W) Bluetooth EDR (3Mbps) : 6.13 dBm (0.004 W)
Antenna Type	PIFA Antenna with gain -1 dBi
HW Version	QB7202AV1AMB_B
SW Version	N720_H1_Z0_C_TSDCD210
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi$ /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Identical Prototype

### Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.	
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-KS	03CH01-KS

## 1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

## 1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	Router	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
4.	Notebook	Dell	P08S	QDS-BRCM1030	N/A	AC I/P: Unshielded, 1.84m DC O/P: Shielded, 0.9m
5.	Bluetooth Earphone	Cellink	BTHS-6025-F	PQY-4710874200357	N/A	N/A
6.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi$ /4-DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	7.23 dBm	5.97 dBm	5.51 dBm
Ch39	2441MHz	6.45 dBm	6.51 dBm	6.13 dBm
Ch78	2480MHz	5.86 dBm	5.33 dBm	4.92 dBm

**Remark:**

1. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

## 2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi$ /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	N/A	N/A
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + GPS Rx		
<b>Remark:</b> For radiated TCs, the data rate was set in 1Mbps due to the highest RF output power; only the data of these modes was reported.			

## 2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



## 2.4 RF Utility

For Bluetooth function, the RF utility, "ADB" was installed in EUT which was programmed in order to make the EUT transmitting and receiving signals continuously.

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Span = the frequency band of operation; RBW  $\geq$  1% of the span; VBW  $\geq$  RBW; Sweep = auto;  
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


<b>Test Mode :</b>	Mode 1~3	<b>Temperature :</b>	20~21°C
<b>Test Engineer :</b>	Fly Chen	<b>Relative Humidity :</b>	40~41%
<b>Number of Hopping Channels (Channel)</b>		<b>Limits (Channel)</b>	<b>Pass/Fail</b>
79		> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



TH-01  
Date: 4.MAR.2011 13:46:01



TH-01  
Date: 4.MAR.2011 13:51:19

## 3.2 20dB Bandwidth Measurement

### 3.2.1 Limit of 20dB Bandwidth

N/A


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

### 3.2.4 Test Setup




3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.936
39	2441	0.932
78	2480	0.940


20 dB Bandwidth Plot on Channel 00



TH-01  
 Date: 4.MAR.2011 13:52:42




20 dB Bandwidth Plot on Channel 39



TH-01  
Date: 4.MAR.2011 13:53:15

20 dB Bandwidth Plot on Channel 78




TH-01  
Date: 4.MAR.2011 13:53:40



Test Mode :	Mode 4, 5, 6	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.278


20 dB Bandwidth Plot on Channel 00



TH-01  
Date: 4.MAR.2011 14:05:12




20 dB Bandwidth Plot on Channel 39



TH-01  
Date: 4.MAR.2011 14:03:58

20 dB Bandwidth Plot on Channel 78




TH-01  
Date: 4.MAR.2011 14:02:44



Test Mode :	Mode 7, 8, 9	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.236
39	2441	1.236
78	2480	1.236


20 dB Bandwidth Plot on Channel 00



TH-01  
Date: 4.MAR.2011 14:06:33




### 20 dB Bandwidth Plot on Channel 39



TH-01  
Date: 4.MAR.2011 14:07:38

### 20 dB Bandwidth Plot on Channel 78



TH-01  
Date: 4.MAR.2011 14:08:05

### 3.3 Hopping Channel Separation Measurement

#### 3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  $RBW \geq 1\%$  of the span;  
VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

#### 3.3.4 Test Setup




### 3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 1, 2, 3	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.624	Pass
39	2441	1.002	0.621	Pass
78	2480	1.002	0.627	Pass

Channel Separation Plot on Channel 00 - 01




TH-01

Date: 4.MAR.2011 13:58:56




### Channel Separation Plot on Channel 39 - 40



TH-01  
Date: 4.MAR.2011 13:59:39

### Channel Separation Plot on Channel 77 - 78



TH-01  
Date: 4.MAR.2011 14:00:58

### 3.4 Dwell Time Measurement

#### 3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

#### 3.4.4 Test Setup



#### 3.4.5 Test Result of Dwell Time


<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	20~21°C		
<b>Test Engineer :</b>	Fly Chen	<b>Relative Humidity :</b>	40~41%		
Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	2.90	2960.00	0.27	0.4	Pass

**Remark:**

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)




### DH5 Dwell Time (One Pulse) Plot on Channel 39



TH-01  
Date: 4.MAR.2011 13:32:42

### DH5 Dwell Time (Count Pulses) Plot on Channel 39



TH-01  
Date: 4.MAR.2011 13:33:01

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (20.97dBm).


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

#### 3.5.4 Test Setup




#### 3.5.5 Test Result of Peak Output Power

<b>Test Mode :</b>	Mode 1, 2, 3	<b>Temperature :</b>	20~21°C	
<b>Test Engineer :</b>	Fly Chen	<b>Relative Humidity :</b>	40~41%	
Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	7.23	20.97	Pass
39	2441	6.45	20.97	Pass
78	2480	5.86	20.97	Pass




Peak Output Power Plot on Channel 00



TH-01  
Date: 4.MAR.2011 14:50:50


Peak Output Power Plot on Channel 39



TH-01  
Date: 4.MAR.2011 14:47:54



Peak Output Power Plot on Channel 78



TH-01

Date: 4.MAR.2011 14:48:11

## 3.6 Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW)  $\geq$  RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

### 3.6.4 Test Setup

#### <Radiated Band Edges>



#### <Conducted Band Edges>





3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	21~23°C
Test Channel :	00	Relative Humidity :	41~43%
		Test Engineer :	Allen Chang

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2332.8	49.68	-24.32	74	47.55	32.76	3.27	33.9	100	320	Peak
2332.8	38.78	-15.22	54	36.65	32.76	3.27	33.9	100	320	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2366.81	50.08	-23.92	74	47.87	32.81	3.38	33.98	100	190	Peak
2366.81	37.67	-16.33	54	35.46	32.81	3.38	33.98	100	190	Average



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
		Test Engineer :	Allen Chang

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.5	68.03	-5.97	74	65.54	33.01	3.68	34.2	108	313	Peak
2483.5	29.31	-24.69	54	26.82	33.01	3.68	34.2	108	313	Average

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Average Result (dBµV/m)	Average Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	89.07	59.76	29.31	54	-24.69	Pass
Hopping Mode	89.07	60.24	28.83	54	-25.17	Pass

Note : Average result = Maximum field strength – Delta result

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.5	67.93	-6.07	74	65.44	33.01	3.68	34.2	100	270	Peak
2483.5	30.52	-23.48	54	28.03	33.01	3.68	34.2	100	270	Average


Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Average Result (dBµV/m)	Average Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	90.14	59.62	30.52	54	-23.48	Pass
Hopping Mode	90.14	60.28	29.86	54	-24.14	Pass

Note : Average result = Maximum field strength – Delta result



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal



Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL


Mode : mode 3  
 : E1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	105.38	31.38	74.00	102.89	33.01	3.68	34.20	200	300	Peak
2 X	2480.00	89.07	35.07	54.00	86.58	33.01	3.68	34.20	200	300	Average

\* Maximum field strength of the fundamental emission



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal



Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANI-100803 HORIZONTAL


Mode : mode 3  
 : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	Remark
1 X	2480.01	105.22	31.22	74.00	102.73	3.68	34.20	200	360	Peak
2	2499.54	45.46	-28.54	74.00	42.92	3.72	34.23	200	360	Peak

\* Marker-Delta Method (RBW/BW=100KHz): 59.76 dB , single carrier Mode



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal




Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANI-100803 HORIZONTAL  
 Mode : mode 3  
 : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2477.85	104.98	30.98	74.00	102.49	33.01	3.68	34.20	100	360 Peak
2	2483.90	44.74	-29.26	74.00	42.25	33.01	3.68	34.20	100	360 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 60.24 dB , Hopping Mode



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical



Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANI-100803 VERTICAL


Mode : mode 3  
 : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	dBuV	Loss	Factor	Pos	Pos	Remark
						dB	dB	cm	deg	
1 X	2480.00	105.92	31.92	74.00	103.43	3.68	34.20	187	283	Peak
2 X	2480.00	90.14	36.14	54.00	87.65	3.68	34.20	187	283	Average

\* Maximum field strength of the fundamental emission



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical



Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANI-100803 VERTICAL


Mode : mode 3  
 : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	dBuV	Loss	Factor	Pos	Pos	Remark
						dB	dB	cm	deg	
1 X	2479.84	105.48	31.48	74.00	102.99	3.68	34.20	200	360	Peak
2	2483.51	45.86	-28.14	74.00	43.37	3.68	34.20	200	360	Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 59.62 dB , single carrier Mode



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical



Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANI-100803 VERTICAL

Mode : mode 3  
 : E1


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	dBuV	Loss	Factor	Pos	Pos	Remark
						dB	dB	cm	deg	
1 X	2479.89	105.48	31.48	74.00	102.99	3.68	34.20	100	360	Peak
2	2483.61	45.20	-28.80	74.00	42.71	3.68	34.20	100	360	Peak

\* Marker-Delta Method (RBW/BW=100KHz): 60.28 dB , Hopping Mode

### 3.6.6 Test Result of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	20~21°C
Test Channel :	00 and 78	Relative Humidity :	40~41%
		Test Engineer :	Fly Chen

Low Band Edge Plot on Channel 00



TH-01  
 Date: 4.MAR.2011 13:54:32

High Band Edge Plot on Channel 78



TH-01  
 Date: 4.MAR.2011 13:55:51

## 3.7 Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW)  $\geq$  RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


### 3.7.4 Test Setup



### 3.7.5 Test Result


Test Mode :	Mode 1	Temperature :	20~21°C
Test Channel :	00	Relative Humidity :	40~41%
		Test Engineer :	Fly Chen

#### Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01  
 Date: 9.MAR.2011 20:44:56

#### Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01  
 Date: 9.MAR.2011 20:45:18




Test Mode :	Mode 2	Temperature :	20~21°C
Test Channel :	39	Relative Humidity :	40~41%
		Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01  
Date: 9.MAR.2011 20:47:19

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01  
Date: 9.MAR.2011 20:47:41




Test Mode :	Mode 3	Temperature :	20~21°C
Test Channel :	78	Relative Humidity :	40~41%
		Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01  
Date: 9.MAR.2011 20:49:35

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz



TH-01  
Date: 9.MAR.2011 20:49:57

### 3.8 AC Conducted Emission Measurement

#### 3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.8.3 Test Procedures

1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.8.4 Test Setup





3.8.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Jason Chia	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS  
 Condition: FCC PART15C LISN-100807 LINE

Mode : mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
		dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	48.13	-17.17	65.30	37.80	-0.07	10.40	QP
2	0.16	36.03	-19.27	55.30	25.70	-0.07	10.40	Average
3	0.21	41.14	-22.22	63.36	30.80	-0.07	10.41	QP
4	0.21	31.14	-22.22	53.36	20.80	-0.07	10.41	Average
5	0.25	37.94	-23.66	61.60	27.60	-0.07	10.41	QP
6	0.25	25.84	-25.76	51.60	15.50	-0.07	10.41	Average
7	0.28	38.83	-22.11	60.94	28.50	-0.07	10.40	QP
8	0.28	33.33	-17.61	50.94	23.00	-0.07	10.40	Average
9	0.36	29.43	-19.22	48.65	19.10	-0.08	10.41	Average
10	0.36	37.13	-21.52	58.65	26.80	-0.08	10.41	QP
11	2.00	26.33	-19.67	46.00	15.90	-0.11	10.54	Average
12	2.00	35.03	-20.97	56.00	24.60	-0.11	10.54	QP



Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Jason Chia	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS  
 Condition: FCC PART15C LISN-100807 NEUTRAL

Mode : mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16	29.12	-26.26	55.38	18.81	-0.09	10.40	Average
2	0.16	42.32	-23.06	65.38	32.01	-0.09	10.40	QP
3	0.20	26.24	-27.25	53.49	15.90	-0.07	10.41	Average
4	0.20	38.04	-25.45	63.49	27.70	-0.07	10.41	QP
5	0.28	29.83	-21.11	50.94	19.50	-0.07	10.40	Average
6	0.28	37.03	-23.91	60.94	26.70	-0.07	10.40	QP
7	0.36	38.13	-20.61	58.74	27.80	-0.08	10.41	QP
8	0.36	30.63	-18.11	48.74	20.30	-0.08	10.41	Average
9	0.62	28.96	-27.04	56.00	18.60	-0.08	10.44	QP
10	0.62	23.06	-22.94	46.00	12.70	-0.08	10.44	Average
11	1.87	26.33	-19.67	46.00	15.90	-0.11	10.54	Average
12	1.87	33.03	-22.97	56.00	22.60	-0.11	10.54	QP

### 3.9 Radiated Emission Measurement

#### 3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.9.3 Test Procedures


1. The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
2. Use the following spectrum analyzer settings:
  - (1) Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
  - (2) Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.  
 Distance extrapolation factor =  $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$  (dB)
3. Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.
4. Measured average value for the peak value is greater than 54 dBuV/m

### 3.9.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz





3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Allen Chang	Temperature :	21~23°C	
		Relative Humidity :	41~43%	
Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



3.9.6 Test Result of Radiated Emission (30 MHz ~ 10<sup>th</sup> Harmonic)

Test Mode :	Mode 1	Temperature :	21~23°C
Test Channel :	00	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
68.88	25.1	-14.9	40	49.57	5.28	0.34	30.09	100	360	Peak
102.63	24	-19.5	43.5	42.67	10.87	0.42	29.96	-	-	Peak
211.17	16.08	-27.42	43.5	35.93	9.54	0.6	29.99	-	-	Peak
364.4	20.18	-25.82	46	34.41	14.86	0.82	29.91	-	-	Peak
583.5	21.44	-24.56	46	31.46	18.57	1.05	29.64	-	-	Peak
871.9	29.95	-16.05	46	37.76	20.49	1.29	29.59	-	-	Peak
2332.8	49.68	-24.32	74	47.55	32.76	3.27	33.9	100	320	Peak
2332.8	38.78	-15.22	54	36.65	32.76	3.27	33.9	100	320	Average
2402	103.64	-	-	101.36	32.86	3.47	34.05	106	316	Peak
2402	88.95	-	-	86.67	32.86	3.47	34.05	106	316	Average
2490.88	38.21	-15.79	54	35.67	33.05	3.72	34.23	110	300	Average
2490.88	49.5	-24.5	74	46.96	33.05	3.72	34.23	110	300	Peak
4806	53.84	-20.16	74	45.97	35.17	4.97	32.27	100	0	Peak
4806	46.16	-7.84	54	38.29	35.17	4.97	32.27	100	0	Average



<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	21~23°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	41~43%
<b>Test Engineer :</b>	Allen Chang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2402 MHz is Fundamental Signals which can be ignored.		

Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
47.82	25.73	-14.27	40	47.09	8.5	0.27	30.13	200	55	Peak
88.86	22.94	-20.56	43.5	43.93	8.61	0.39	29.99	-	-	Peak
120.45	23.11	-20.39	43.5	40.83	11.8	0.45	29.97	-	-	Peak
501.6	18.8	-27.2	46	30.35	17.22	0.96	29.73	-	-	Peak
727	22.06	-23.94	46	30.87	19.65	1.16	29.62	-	-	Peak
958.7	27.04	-26.96	54	34.46	20.78	1.34	29.54	-	-	Peak
2366.81	50.08	-23.92	74	47.87	32.81	3.38	33.98	100	190	Peak
2366.81	37.67	-16.33	54	35.46	32.81	3.38	33.98	100	190	Average
2402	99.66	-	-	97.38	32.86	3.47	34.05	107	192	Peak
2402	86.88	-	-	84.6	32.86	3.47	34.05	107	192	Average
2492.02	37.93	-16.07	54	35.39	33.05	3.72	34.23	105	179	Average
2492.02	49.45	-24.55	74	46.91	33.05	3.72	34.23	105	179	Peak



<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	21~23°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	41~43%
<b>Test Engineer :</b>	Allen Chang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2441 MHz is Fundamental Signals which can be ignored.		

Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level (dBuV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
88.86	24.44	-19.06	43.5	45.43	8.61	0.39	29.99	100	0	Peak
102.36	22.34	-21.16	43.5	41.01	10.87	0.42	29.96	-	-	Peak
211.17	16.77	-26.73	43.5	36.62	9.54	0.6	29.99	-	-	Peak
364.4	20.28	-25.72	46	34.51	14.86	0.82	29.91	-	-	Peak
871.9	30.71	-15.29	46	38.52	20.49	1.29	29.59	-	-	Peak
958.7	26.29	-27.71	54	33.71	20.78	1.34	29.54	-	-	Peak
2312.85	40.53	-13.47	54	38.44	32.73	3.22	33.86	200	0	Average
2312.85	50.64	-23.36	74	48.55	32.73	3.22	33.86	200	0	Peak
2441	89.13	-	-	86.73	32.95	3.6	34.15	130	322	Average
2441	104	-	-	101.6	32.95	3.6	34.15	130	322	Peak
2494.68	50.36	-23.64	74	47.82	33.05	3.72	34.23	200	0	Peak
2494.68	39	-15	54	36.46	33.05	3.72	34.23	200	0	Average



<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	21~23°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	41~43%
<b>Test Engineer :</b>	Allen Chang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2441 MHz is Fundamental Signals which can be ignored.		

Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
47.82	26.47	-13.53	40	47.83	8.5	0.27	30.13	100	0	Peak
88.86	21.67	-21.83	43.5	42.66	8.61	0.39	29.99	-	-	Peak
122.34	22.09	-21.41	43.5	39.83	11.78	0.45	29.97	-	-	Peak
601.7	21.28	-24.72	46	31.23	18.6	1.07	29.62	-	-	Peak
871.9	28.99	-17.01	46	36.8	20.49	1.29	29.59	-	-	Peak
956.6	28.66	-25.34	54	36.09	20.77	1.34	29.54	-	-	Peak
2355.41	50.15	-23.85	74	47.94	32.81	3.38	33.98	100	360	Peak
2355.41	39.09	-14.91	54	36.88	32.81	3.38	33.98	100	360	Average
2441	90.83	-	-	88.43	32.95	3.6	34.15	100	298	Average
2441	106.12	-	-	103.72	32.95	3.6	34.15	100	298	Peak
2498.86	49.92	-24.08	74	47.38	33.05	3.72	34.23	100	360	Peak
2498.86	39.28	-14.72	54	36.74	33.05	3.72	34.23	100	360	Average



<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	21~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~43%
<b>Test Engineer :</b>	Allen Chang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2480 MHz is Fundamental Signals which can be ignored.		

Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
88.86	21.22	-22.28	43.5	42.21	8.61	0.39	29.99	-	-	Peak
102.36	23.6	-19.9	43.5	42.27	10.87	0.42	29.96	100	158	Peak
211.17	15.55	-27.95	43.5	35.4	9.54	0.6	29.99	-	-	Peak
364.4	20.18	-25.82	46	34.41	14.86	0.82	29.91	-	-	Peak
871.9	25.94	-20.06	46	33.75	20.49	1.29	29.59	-	-	Peak
958.7	27.59	-26.41	54	35.01	20.78	1.34	29.54	-	-	Peak
2351.99	51.29	-22.71	74	49.08	32.81	3.38	33.98	148	0	Peak
2351.99	38.86	-15.14	54	36.65	32.81	3.38	33.98	148	0	Average
2480	105.38	-	-	102.89	33.01	3.68	34.2	200	300	Peak
2480	89.07	-	-	86.58	33.01	3.68	34.2	200	300	Average
2483.5	68.03	-5.97	74	65.54	33.01	3.68	34.2	108	313	Peak
2483.5	29.31	-24.69	54	26.82	33.01	3.68	34.2	108	313	Average



<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	21~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~43%
<b>Test Engineer :</b>	Allen Chang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2480 MHz is Fundamental Signals which can be ignored.		

Frequency ( MHz )	Level ( dBuV/m )	Over Limit ( dB )	Limit Line ( dBuV/m )	Read Level ( dBuV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
47.82	26.47	-13.53	40	47.83	8.5	0.27	30.13	100	0	Peak
88.86	21.22	-22.28	43.5	42.21	8.61	0.39	29.99	-	-	Peak
122.07	23.31	-20.19	43.5	41.05	11.78	0.45	29.97	-	-	Peak
561.1	21.25	-24.75	46	31.39	18.52	1.01	29.67	-	-	Peak
871.9	30.37	-15.63	46	38.18	20.49	1.29	29.59	-	-	Peak
941.2	28.37	-25.63	54	35.88	20.69	1.33	29.53	-	-	Peak
2352.18	50.87	-23.13	74	48.66	32.81	3.38	33.98	138	297	Peak
2352.18	40.97	-13.03	54	38.76	32.81	3.38	33.98	138	297	Average
2480	105.92	-	-	103.43	33.01	3.68	34.2	187	283	Peak
2480	90.14	-	-	87.65	33.01	3.68	34.2	187	283	Average
2483.5	30.52	-23.48	54	28.03	33.01	3.68	34.2	100	270	Average
2483.5	67.93	-6.07	74	65.44	33.01	3.68	34.2	100	270	Peak



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.10.2 Antenna Connected Construction**

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY451015 55	N/A	Aug. 24, 2010	Aug. 23, 2011	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY444211 98	N/A	Aug. 24, 2010	Aug. 23, 2011	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-9605 02	N/A	Dec. 28, 2010	Dec. 27, 2011	Conducted (TH01-KS)
DC Power Supply	TOPWARD	3306D	N/A	N/A	N/A	N/A	Conducted (TH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 22, 2010	Jun. 21, 2011	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	N/A	Nov. 10, 2010	Nov. 09, 2011	Conduction (CO01-KS)
System Simulator	R&S	CMU200	837587/06 6	Full-Band	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
GPS Station	T&E	GS-50	N/A	N/A	N/A	N/A	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 16, 2010	Nov. 15, 2011	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2010	Dec. 06, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 09, 2010	Dec. 08, 2011	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A023 70	1GHz~26.5GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Active horn antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 09, 2010	Nov. 08, 2011	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 06, 2011	Jan. 05, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15-40GHz	Oct. 15, 2010	Oct. 14, 2011	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00 1	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH01-KS)
Bluetooth Base Station	R&S	CBT	100519	N/A	May 12, 2009	May 11, 2011	Radiation (03CH01-KS)

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.13</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.26</b>		

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.27</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.54</b>		

**Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)**

Contribution	Uncertainty of $X_i$		$u(X_i)$	$C_i$	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>2.36</b>				
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>4.72</b>				



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP122812 as below.