


FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : 3G Smart Mobile phone
BRAND NAME : ZTE
MODEL NAME : ZTE-U N720
FCC ID : Q78-N720
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Transmission System (DTS)

The product was received on Feb. 28, 2011 and completely tested on Mar. 16, 2011. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test 5

 1.4 Testing Site 6

 1.5 Applied Standards 6

 1.6 Ancillary Equipment List 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1 RF Power 7

 2.2 Test Mode 8

 2.3 Connection Diagram of Test System 8

 2.4 RF Utility 9

3 TEST RESULT 10

 3.1 6dB Bandwidth Measurement 10

 3.2 Output Power Measurement 15

 3.3 Band Edges Measurement 17

 3.4 Spurious Emission Measurement 23

 3.5 Power Spectral Density Measurement 30

 3.6 AC Conducted Emission Measurement 35

 3.7 Radiated Emission Measurement 39

 3.8 Antenna Requirements 54

4 LIST OF MEASURING EQUIPMENT 55

5 UNCERTAINTY OF EVALUATION 56

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	A8.4	Power Output	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.4	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.5	15.247(e)	A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}$	Pass	-
3.6	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 17.17 dB at 0.16 MHz
3.7	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.26 dB at 2487.65 MHz
3.8	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	3G Smart Mobile phone
Brand Name	ZTE
Model Name	ZTE-U N720
FCC ID	Q78-N720
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	11
Carrier Frequency of Each Channel	2412+(n-1)*5 MHz; n=1~11
Channel Spacing	5 MHz
Maximum Output Power to Antenna	802.11b : 16.45 dBm (0.04 W) 802.11g : 14.55 dBm (0.03 W)
Antenna Type	PIFA Antenna with gain -1 dBi
HW Version	QB7202AV1AMB_B
SW Version	N720_H1_Z0_C_TSDCD210
Type of Modulation	802.11b : DSSS (BPSK / QPSK / CCK) 802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM)
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Transmission System (DTS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	
	TH01-KS	03CH01-KS

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 (Measurement Guidelines of DTS)
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	Router	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
4.	Notebook	Dell	P08S	QDS-BRCM1030	N/A	AC I/P: Unshielded, 1.84m DC O/P: Shielded, 0.9m
5.	Bluetooth Earphone	Cellink	BTHS-6025-F	PQY-4710874200357	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Power

Preliminary tests were performed in different data rate and recorded the RF power output in the following table:

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412 MHz	16.45	16.23	16.38	16.23
CH 06	2437 MHz	15.65	15.89	15.64	15.75
CH 11	2462 MHz	15.71	15.92	15.81	15.99

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412 MHz	13.98	13.57	13.86	13.72	14.22	13.9	13.95	14.55
CH 06	2437 MHz	13.86	13.01	14.42	13.34	13.89	13.35	13.31	13.98
CH 11	2462 MHz	14.18	13.61	14.31	13.57	14.23	13.42	13.52	14.32

Remark:

1. The data rates of WLAN 802.11b/g were set in 1Mbps for 802.11b and 54Mbps for 802.11g, for all the test cases due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz), radiated emission (30 MHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases		
Test Item	802.11b	802.11g
Conducted TCs	Mode 1 : 802.11b CH01_2412 MHz Mode 2 : 802.11b CH06_2437 MHz Mode 3 : 802.11b CH11_2462 MHz	Mode 4 : 802.11g CH01_2412 MHz Mode 5 : 802.11g CH06_2437 MHz Mode 6 : 802.11g CH11_2462 MHz
Radiated TCs	Mode 1 : 802.11b CH01_2412 MHz Mode 2 : 802.11b CH06_2437 MHz Mode 3 : 802.11b CH11_2462 MHz	Mode 4 : 802.11g CH01_2412 MHz Mode 5 : 802.11g CH06_2437 MHz Mode 6 : 802.11g CH11_2462 MHz
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + GPS Rx	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

The programmed RF utility, “ADB” is installed in EUT to provide channel selection, power level, data rate and the application type. RF utility can send transmitting signal for all testing. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	802.11b 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	12.12	0.5	Pass
06	2437	12.04	0.5	Pass
11	2462	12.12	0.5	Pass


Mode 1 : 6 dB Bandwidth Plot on 802.11b Channel 01



TH-01
Date: 5.MAR.2011 11:01:57




Mode 2 : 6 dB Bandwidth Plot on 802.11b Channel 06



TH-01
Date: 5.MAR.2011 10:59:33

Mode 3 : 6 dB Bandwidth Plot on 802.11b Channel 11




TH-01
Date: 5.MAR.2011 11:06:19



Test Mode :	Mode 4, 5, 6	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	802.11g 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	16.44	0.5	Pass
06	2437	16.44	0.5	Pass
11	2462	16.48	0.5	Pass

Mode 4 : 6 dB Bandwidth Plot on 802.11g Channel 01




TH-01

Date: 5.MAR.2011 13:07:14




Mode 5 : 6 dB Bandwidth Plot on 802.11g Channel 06



TH-01
Date: 5.MAR.2011 13:51:35

Mode 6 : 6 dB Bandwidth Plot on 802.11g Channel 11



TH-01
Date: 5.MAR.2011 13:38:01

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the power meter by a low loss cable.
3. Measure the power by power meter.

3.2.4 Test Setup



3.2.5 Test Result of Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	802.11b Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	16.45	30	Pass
06	2437	15.65	30	Pass
11	2462	15.71	30	Pass

Test Mode :	Mode 4, 5, 6	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	802.11g Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	14.55	30	Pass
06	2437	13.98	30	Pass
11	2462	14.32	30	Pass



3.3 Band Edges Measurement

3.3.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. Conducted emission test: Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Apply to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep=Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation as in FCC Section 15.35(b) and (c).

3.3.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>





3.3.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	21~23°C
Test Band :	802.11b	Relative Humidity :	41~43%
Test Channel :	01	Test Engineer :	Allen Chang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2390	54.5	-19.5	74	52.22	32.86	3.47	34.05	200	103	Peak
2390	48.37	-5.63	54	46.09	32.86	3.47	34.05	200	103	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.9	51.41	-22.59	74	49.13	32.86	3.47	34.05	100	138	Peak
2387.9	39.07	-14.93	54	36.79	32.86	3.47	34.05	100	138	Average

Test Mode :	Mode 3	Temperature :	21~23°C
Test Band :	802.11b	Relative Humidity :	41~43%
Test Channel :	11	Test Engineer :	Allen Chang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2487.65	57.09	-16.91	74	54.55	33.05	3.72	34.23	200	107	Peak
2487.65	48.74	-5.26	54	46.2	33.05	3.72	34.23	200	107	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.61	54.57	-19.43	74	52.08	33.01	3.68	34.2	100	59	Peak
2484.61	46.62	-7.38	54	44.13	33.01	3.68	34.2	100	59	Average



Test Mode :	Mode 4	Temperature :	21~23°C
Test Band :	802.11g	Relative Humidity :	41~43%
Test Channel :	01	Test Engineer :	Allen Chang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2390	55.56	-18.44	74	53.28	32.86	3.47	34.05	200	308	Peak
2390	42.3	-11.7	54	40.02	32.86	3.47	34.05	200	308	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2390	50.42	-23.58	74	48.14	32.86	3.47	34.05	100	0	Peak
2390	41.12	-12.88	54	38.84	32.86	3.47	34.05	100	0	Average

Test Mode :	Mode 6	Temperature :	21~23°C
Test Band :	802.11g	Relative Humidity :	41~43%
Test Channel :	11	Test Engineer :	Allen Chang


ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	50.44	-23.56	74	550.44	-500	-500	-500	100	335	Peak
2483.5	37.95	-16.05	54	35.46	33.01	3.68	34.2	100	335	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.42	51.24	-22.76	74	551.24	-500	-500	-500	100	108	Peak
2484.42	39.69	-14.31	54	37.2	33.01	3.68	34.2	100	108	Average

3.3.6 Test Plots of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	20~21°C
Test Band :	802.11b	Relative Humidity :	40~41%
Test Channel :	01 and 11	Test Engineer :	Fly Chen

Low Band Edge Plot on 802.11b Channel 01



TH-01
Date: 5.MAR.2011 11:03:06

High Band Edge Plot on 802.11b Channel 11




TH-01
Date: 5.MAR.2011 11:07:21




Test Mode :	Mode 4 and 6	Temperature :	20~21°C
Test Band :	802.11g	Relative Humidity :	40~41%
Test Channel :	01 and 11	Test Engineer :	Fly Chen

Low Band Edge Plot on 802.11g Channel 01



TH-01
Date: 5.MAR.2011 13:08:28

High Band Edge Plot on 802.11g Channel 11



TH-01
Date: 5.MAR.2011 13:38:49

3.4 Spurious Emission Measurement

3.4.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW, scan up through 10th harmonic. All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.4.4 Test Setup



3.4.5 Test Plots of Spurious Emission


Test Mode :	Mode 1	Temperature :	20~21°C
Test Band :	802.11b	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01
Date: 5.MAR.2011 12:22:26

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01
Date: 5.MAR.2011 12:20:53




Test Mode :	Mode 2	Temperature :	20~21°C
Test Band :	802.11b	Relative Humidity :	40~41%
Test Channel :	06	Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01
Date: 5.MAR.2011 12:43:46

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01
Date: 5.MAR.2011 12:44:03




Test Mode :	Mode 3	Temperature :	20~21°C
Test Band :	802.11b	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01
Date: 5.MAR.2011 11:32:05

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01
Date: 5.MAR.2011 11:32:23




Test Mode :	Mode 4	Temperature :	20~21°C
Test Band :	802.11g	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01
Date: 5.MAR.2011 13:09:59

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01
Date: 5.MAR.2011 13:10:16




Test Mode :	Mode 5	Temperature :	20~21°C
Test Band :	802.11g	Relative Humidity :	40~41%
Test Channel :	06	Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01
Date: 5.MAR.2011 13:25:56

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




TH-01
Date: 5.MAR.2011 13:26:13




Test Mode :	Mode 6	Temperature :	20~21°C
Test Band :	802.11g	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Fly Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



TH-01
Date: 5.MAR.2011 13:39:54

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz



TH-01
Date: 5.MAR.2011 13:40:10

3.5 Power Spectral Density Measurement

3.5.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The test follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Take the measured data from spectrum analyzer.

3.5.4 Test Setup






3.5.5 Test Result of Power Spectral Density

Test Mode :	Mode 1, 2, 3	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	802.11b Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-12.75	8	Pass
06	2437	-13.44	8	Pass
11	2462	-13.11	8	Pass


Mode 1 : PSD Plot on 802.11b Channel 01



TH-01
Date: 5.MAR.2011 12:42:22




Mode 2 : PSD Plot on 802.11b Channel 06



TH-01

Date: 5.MAR.2011 12:53:12

Mode 3 : PSD Plot on 802.11b Channel 11



TH-01


Date: 5.MAR.2011 13:03:06



Test Mode :	Mode 4, 5, 6	Temperature :	20~21°C
Test Engineer :	Fly Chen	Relative Humidity :	40~41%

Channel	Frequency (MHz)	802.11g Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-21.62	8	Pass
06	2437	-21.76	8	Pass
11	2462	-21.64	8	Pass


Mode 4 : PSD Plot on 802.11g Channel 01



TH-01
Date: 5.MAR.2011 13:22:00




Mode 5 : PSD Plot on 802.11g Channel 06



TH-01
Date: 5.MAR.2011 13:35:35

Mode 6 : PSD Plot on 802.11g Channel 11



TH-01
Date: 5.MAR.2011 13:49:59

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Jason Chia	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS
 Condition: FCC PART15C LISN-100807 LINE

Mode : mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16	48.13	-17.17	65.30	37.80	-0.07	10.40	QP
2	0.16	36.03	-19.27	55.30	25.70	-0.07	10.40	Average
3	0.21	41.14	-22.22	63.36	30.80	-0.07	10.41	QP
4	0.21	31.14	-22.22	53.36	20.80	-0.07	10.41	Average
5	0.25	37.94	-23.66	61.60	27.60	-0.07	10.41	QP
6	0.25	25.84	-25.76	51.60	15.50	-0.07	10.41	Average
7	0.28	38.83	-22.11	60.94	28.50	-0.07	10.40	QP
8	0.28	33.33	-17.61	50.94	23.00	-0.07	10.40	Average
9	0.36	29.43	-19.22	48.65	19.10	-0.08	10.41	Average
10	0.36	37.13	-21.52	58.65	26.80	-0.08	10.41	QP
11	2.00	26.33	-19.67	46.00	15.90	-0.11	10.54	Average
12	2.00	35.03	-20.97	56.00	24.60	-0.11	10.54	QP



Test Mode :	Mode 1	Temperature :	20~21°C
Test Engineer :	Jason Chia	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Adapter + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS
 Condition: FCC PART15C LISN-100807 NEUTRAL

Mode : mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	29.12	-26.26	55.38	18.81	-0.09	10.40	Average
2	0.16	42.32	-23.06	65.38	32.01	-0.09	10.40	QP
3	0.20	26.24	-27.25	53.49	15.90	-0.07	10.41	Average
4	0.20	38.04	-25.45	63.49	27.70	-0.07	10.41	QP
5	0.28	29.83	-21.11	50.94	19.50	-0.07	10.40	Average
6	0.28	37.03	-23.91	60.94	26.70	-0.07	10.40	QP
7	0.36	38.13	-20.61	58.74	27.80	-0.08	10.41	QP
8	0.36	30.63	-18.11	48.74	20.30	-0.08	10.41	Average
9	0.62	28.96	-27.04	56.00	18.60	-0.08	10.44	QP
10	0.62	23.06	-22.94	46.00	12.70	-0.08	10.44	Average
11	1.87	26.33	-19.67	46.00	15.90	-0.11	10.54	Average
12	1.87	33.03	-22.97	56.00	22.60	-0.11	10.54	QP

3.7 Radiated Emission Measurement

3.7.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


- The testing follows the guidelines in FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
 Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.7.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz





3.7.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Allen Chang	Temperature :	21~23°C	
		Relative Humidity :	41~43%	
Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



3.7.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	21~23°C
Test Channel :	01	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.27	20.38	-19.62	40	32.2	18	0.26	30.08	-	-	Peak
119.91	23.06	-20.44	43.5	40.78	11.8	0.45	29.97	-	-	Peak
135.03	23.6	-19.9	43.5	41.81	11.3	0.48	29.99	-	-	Peak
872.6	28.1	-17.9	46	35.91	20.48	1.29	29.58	-	-	Peak
892.2	38.22	-7.78	46	45.96	20.46	1.3	29.5	100	0	Peak
944	36.19	-17.81	54	43.68	20.71	1.33	29.53	-	-	Peak
2390	54.5	-19.5	74	52.22	32.86	3.47	34.05	200	103	Peak
2390	48.37	-5.63	54	46.09	32.86	3.47	34.05	200	103	Average
2412	103.03	-	-	100.7	32.89	3.52	34.08	200	97	Average
2412	107.27	-	-	104.94	32.89	3.52	34.08	200	97	Peak
2497.15	54	-20	74	51.46	33.05	3.72	34.23	200	188	Peak
2497.15	44.13	-9.87	54	41.59	33.05	3.72	34.23	200	188	Average



Test Mode :	Mode 1	Temperature :	21~23°C
Test Channel :	01	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.34	23.05	-16.95	40	41.92	10.95	0.26	30.08	-	-	Peak
73.2	24.04	-15.96	40	48.08	5.68	0.34	30.06	-	-	Peak
113.16	23.03	-20.47	43.5	40.76	11.8	0.44	29.97	-	-	Peak
872.6	26.71	-19.29	46	34.52	20.48	1.29	29.58	-	-	Peak
899.9	32.68	-13.32	46	40.41	20.45	1.3	29.48	100	360	Peak
944	35.61	-18.39	54	43.1	20.71	1.33	29.53	-	-	Peak
2387.9	51.41	-22.59	74	49.13	32.86	3.47	34.05	100	138	Peak
2387.9	39.07	-14.93	54	36.79	32.86	3.47	34.05	100	138	Average
2412	97.63	-	-	95.3	32.89	3.52	34.08	100	77	Average
2412	101.04	-	-	98.71	32.89	3.52	34.08	100	77	Peak
2496.77	52.4	-21.6	74	49.86	33.05	3.72	34.23	100	64	Peak
2496.77	42.58	-11.42	54	40.04	33.05	3.72	34.23	100	64	Average



Test Mode :	Mode 2	Temperature :	21~23°C
Test Channel :	06	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.43	20.42	-19.58	40	34.23	16.04	0.24	30.09	-	-	Peak
133.41	23.88	-19.62	43.5	42	11.39	0.48	29.99	-	-	Peak
217.92	22.67	-23.33	46	42.07	9.96	0.62	29.98	-	-	Peak
872.6	27.15	-18.85	46	34.96	20.48	1.29	29.58	-	-	Peak
915.3	28.65	-17.35	46	36.31	20.53	1.31	29.5	-	-	Peak
950.3	37.25	-16.75	54	44.73	20.73	1.33	29.54	200	0	Peak
2331.47	52.74	-21.26	74	50.61	32.76	3.27	33.9	200	188	Peak
2331.47	46.33	-7.67	54	44.2	32.76	3.27	33.9	200	188	Average
2437	103.56	-	-	101.16	32.95	3.6	34.15	200	105	Average
2437	107.74	-	-	105.34	32.95	3.6	34.15	200	105	Peak
2487.08	51.34	-22.66	74	48.85	33.01	3.68	34.2	200	317	Peak
2487.08	43.59	-10.41	54	41.1	33.01	3.68	34.2	200	317	Average



Test Mode :	Mode 2	Temperature :	21~23°C
Test Channel :	06	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.07	23.69	-16.31	40	41.85	11.64	0.25	30.05	-	-	Peak
74.55	23.83	-16.17	40	47.75	5.8	0.34	30.06	100	360	Peak
113.7	23.5	-20	43.5	41.23	11.8	0.44	29.97	-	-	Peak
871.9	26.8	-19.2	46	34.61	20.49	1.29	29.59	-	-	Peak
915.3	28.91	-17.09	46	36.57	20.53	1.31	29.5	-	-	Peak
950.3	35.73	-18.27	54	43.21	20.73	1.33	29.54	-	-	Peak
2330.9	50.45	-23.55	74	48.32	32.76	3.27	33.9	100	199	Peak
2330.9	47.03	-6.97	54	44.9	32.76	3.27	33.9	100	199	Average
2437	96.6	-	-	94.2	32.95	3.6	34.15	100	220	Average
2437	101.63	-	-	99.23	32.95	3.6	34.15	100	220	Peak
2485.37	50.08	-23.92	74	47.59	33.01	3.68	34.2	100	91	Peak
2485.37	45.69	-8.31	54	43.2	33.01	3.68	34.2	100	91	Average



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	11	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.16	22.73	-17.27	40	36.03	16.55	0.24	30.09	200	0	Peak
120.99	22.15	-21.35	43.5	39.88	11.79	0.45	29.97	-	-	Peak
135.03	24.36	-19.14	43.5	42.57	11.3	0.48	29.99	-	-	Peak
871.2	26.55	-19.45	46	34.36	20.49	1.29	29.59	-	-	Peak
915.3	24.25	-21.75	46	31.91	20.53	1.31	29.5	-	-	Peak
944	36.02	-17.98	54	43.51	20.71	1.33	29.53	-	-	Peak
2385.24	52.79	-21.21	74	50.55	32.83	3.42	34.01	200	112	Peak
2385.24	46.34	-7.66	54	44.1	32.83	3.42	34.01	200	112	Average
2462	106.69	-	-	104.24	32.98	3.64	34.17	200	112	Peak
2462	103.23	-	-	100.78	32.98	3.64	34.17	200	111	Average
2487.65	57.09	-16.91	74	54.55	33.05	3.72	34.23	200	107	Peak
2487.65	48.74	-5.26	54	46.2	33.05	3.72	34.23	200	107	Average



Test Mode :	Mode 3	Temperature :	21~23°C
Test Channel :	11	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.07	23.35	-16.65	40	41.51	11.64	0.25	30.05	-	-	Peak
74.55	23.69	-16.31	40	47.61	5.8	0.34	30.06	100	0	Peak
113.43	23.2	-20.3	43.5	40.93	11.8	0.44	29.97	-	-	Peak
769.7	22.7	-23.3	46	31.17	19.88	1.21	29.56	-	-	Peak
872.6	25.78	-20.22	46	33.59	20.48	1.29	29.58	-	-	Peak
946.1	35.49	-18.51	54	42.99	20.71	1.33	29.54	-	-	Peak
2356.93	49.79	-24.21	74	47.58	32.81	3.38	33.98	100	317	Peak
2356.93	43.41	-10.59	54	41.2	32.81	3.38	33.98	100	317	Average
2462	101.43	-	-	98.98	32.98	3.64	34.17	100	60	Peak
2462	98.36	-	-	95.91	32.98	3.64	34.17	100	60	Average
2484.61	54.57	-19.43	74	52.08	33.01	3.68	34.2	100	59	Peak
2484.61	46.62	-7.38	54	44.13	33.01	3.68	34.2	100	59	Average



Test Mode :	Mode 4	Temperature :	21~23°C
Test Channel :	01	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	21.37	-18.63	40	33.19	18	0.26	30.08	-	-	Peak
121.8	22.38	-21.12	43.5	40.12	11.78	0.45	29.97	-	-	Peak
132.87	22.91	-20.59	43.5	40.95	11.47	0.48	29.99	-	-	Peak
871.2	28.84	-17.16	46	36.65	20.49	1.29	29.59	-	-	Peak
894.3	30.11	-15.89	46	37.85	20.46	1.3	29.5	200	0	Peak
950.3	36.78	-17.22	54	44.26	20.73	1.33	29.54	-	-	Peak
2390	55.56	-18.44	74	53.28	32.86	3.47	34.05	200	308	Peak
2390	42.3	-11.7	54	40.02	32.86	3.47	34.05	200	308	Average
2412	101.99	-	-	99.66	32.89	3.52	34.08	200	307	Peak
2412	89.4	-	-	87.07	32.89	3.52	34.08	200	307	Average
2493.54	52.6	-21.4	74	50.06	33.05	3.72	34.23	200	0	Peak
2493.54	41.97	-12.03	54	39.43	33.05	3.72	34.23	200	0	Average



Test Mode :	Mode 4	Temperature :	21~23°C
Test Channel :	01	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.34	23.63	-16.37	40	42.5	10.95	0.26	30.08	-	-	Peak
72.93	23.18	-16.82	40	47.36	5.55	0.34	30.07	-	-	Peak
112.62	24.44	-19.06	43.5	42.17	11.8	0.44	29.97	-	-	Peak
871.2	28.85	-17.15	46	36.66	20.49	1.29	29.59	-	-	Peak
895	37.38	-8.62	46	45.12	20.45	1.3	29.49	100	0	Peak
950.3	36.76	-17.24	54	44.24	20.73	1.33	29.54	-	-	Peak
2390	50.42	-23.58	74	48.14	32.86	3.47	34.05	100	0	Peak
2390	41.12	-12.88	54	38.84	32.86	3.47	34.05	100	0	Average
2412	96.18	-	-	93.85	32.89	3.52	34.08	100	0	Peak
2412	83.97	-	-	81.64	32.89	3.52	34.08	100	0	Average
2496.77	49.3	-24.7	74	46.76	33.05	3.72	34.23	100	360	Peak
2496.77	37.48	-16.52	54	34.94	33.05	3.72	34.23	100	360	Average



Test Mode :	Mode 5	Temperature :	21~23°C
Test Channel :	06	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.16	23.46	-16.54	40	36.76	16.55	0.24	30.09	-	-	Peak
120.45	22.86	-20.64	43.5	40.58	11.8	0.45	29.97	-	-	Peak
133.14	23.64	-19.86	43.5	41.68	11.47	0.48	29.99	-	-	Peak
872.6	28.05	-17.95	46	35.86	20.48	1.29	29.58	-	-	Peak
915.3	28.05	-17.95	46	35.71	20.53	1.31	29.5	-	-	Peak
943.3	38.72	-15.28	54	46.21	20.71	1.33	29.53	100	0	Peak
2355.41	49.8	-24.2	74	549.8	-500	-500	-500	100	86	Peak
2355.41	38.41	-15.59	54	36.2	32.81	3.38	33.98	100	86	Average
2437	85.95	-	-	83.55	32.95	3.6	34.15	100	206	Average
2437	96.53	-	-	596.53	-500	-500	-500	100	206	Peak
2486.32	49.35	-24.65	74	549.35	-500	-500	-500	100	108	Peak
2486.32	37.79	-16.21	54	35.3	33.01	3.68	34.2	100	108	Average



Test Mode :	Mode 5	Temperature :	21~23°C
Test Channel :	06	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.8	23.74	-16.26	40	41.9	11.64	0.25	30.05	-	-	Peak
73.2	23.5	-16.5	40	47.54	5.68	0.34	30.06	-	-	Peak
112.35	24.4	-19.1	43.5	42.13	11.8	0.44	29.97	-	-	Peak
876.1	28.34	-17.66	46	36.13	20.48	1.29	29.56	-	-	Peak
890.8	32.08	-13.92	46	39.83	20.46	1.3	29.51	100	360	Peak
944	38.44	-15.56	54	45.93	20.71	1.33	29.53	-	-	Peak
2350.47	49.52	-24.48	74	549.52	-500	-500	-500	100	310	Peak
2350.47	37.97	-16.03	54	35.8	32.78	3.33	33.94	100	310	Average
2437	83.55	-	-	81.15	32.95	3.6	34.15	100	360	Average
2437	93.87	-	-	91.47	32.95	3.6	34.15	100	360	Peak
2489.36	38.74	-15.26	54	36.2	33.05	3.72	34.23	100	108	Average
2489.36	48.89	-25.11	74	548.89	-500	-500	-500	100	108	Peak



Test Mode :	Mode 6	Temperature :	21~23°C
Test Channel :	11	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	21.64	-18.36	40	34.18	17.29	0.25	30.08	-	-	Peak
120.45	23.43	-20.07	43.5	41.15	11.8	0.45	29.97	-	-	Peak
133.41	19.4	-24.1	43.5	37.52	11.39	0.48	29.99	-	-	Peak
734.7	25.15	-20.85	46	33.82	19.75	1.17	29.59	-	-	Peak
872.6	29.22	-16.78	46	37.03	20.48	1.29	29.58	-	-	Peak
943.3	38.59	-15.41	54	46.08	20.71	1.33	29.53	100	0	Peak
2352.37	49.22	-24.78	74	549.22	-500	-500	-500	100	35	Peak
2352.37	37.31	-16.69	54	35.1	32.81	3.38	33.98	100	35	Average
2462	93.72	-	-	593.72	-500	-500	-500	100	10	Peak
2462	85.54	-	-	83.09	32.98	3.64	34.17	100	10	Average
2483.5	50.44	-23.56	74	550.44	-500	-500	-500	100	335	Peak
2483.5	37.95	-16.05	54	35.46	33.01	3.68	34.2	100	335	Average



Test Mode :	Mode 6	Temperature :	21~23°C
Test Channel :	11	Relative Humidity :	41~43%
Test Engineer :	Allen Chang	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
41.34	23.77	-16.23	40	42.64	10.95	0.26	30.08	-	-	Peak
73.2	23.62	-16.38	40	47.66	5.68	0.34	30.06	-	-	Peak
109.92	23.33	-20.17	43.5	41.07	11.8	0.43	29.97	-	-	Peak
872.6	29.18	-16.82	46	36.99	20.48	1.29	29.58	-	-	Peak
897.1	27.88	-18.12	46	35.62	20.45	1.3	29.49	-	-	Peak
943.3	38.04	-15.96	54	45.53	20.71	1.33	29.53	100	360	Peak
2388.66	49.62	-24.38	74	549.62	-500	-500	-500	100	156	Peak
2388.66	39.08	-14.92	54	36.8	32.86	3.47	34.05	100	156	Average
2462	83.05	-	-	80.6	32.98	3.64	34.17	100	65	Average
2462	92.74	-	-	592.74	-500	-500	-500	100	65	Peak
2484.42	51.24	-22.76	74	551.24	-500	-500	-500	100	108	Peak
2484.42	39.69	-14.31	54	37.2	33.01	3.68	34.2	100	108	Average



3.8 Antenna Requirements

3.8.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.8.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.8.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY45101555	N/A	Aug. 24, 2010	Aug. 23, 2011	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY44421198	N/A	Aug. 24, 2010	Aug. 23, 2011	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 28, 2010	Dec. 27, 2011	Conducted (TH01-KS)
DC Power Supply	TOPWARD	3306D	N/A	N/A	N/A	N/A	Conducted (TH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 22, 2010	Jun. 21, 2011	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	N/A	Nov. 10, 2010	Nov. 09, 2011	Conduction (CO01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 07, 2011	Jan. 06, 2012	Conduction (CO01-KS)
GPS Station	T&E	GS-50	N/A	N/A	N/A	N/A	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 16, 2010	Nov. 15, 2011	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2010	Dec. 06, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 09, 2010	Dec. 08, 2011	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Active horn antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 09, 2010	Nov. 08, 2011	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 06, 2011	Jan. 05, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 15, 2010	Oct. 14, 2011	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP122812 as below.