


# FCC Test Report

APPLICANT : ZTE CORPORATION  
EQUIPMENT : cdma2000 Digital Mobile Handset  
BRAND NAME : ZTE  
MODEL NAME : N8000  
FCC ID : Q78-N8000  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification

The product was received on Aug. 03, 2013 and completely tested on Aug. 30, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Louis Wu / Manager



Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL (SHENZHEN) INC.**

**No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.**



## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Feature of Equipment Under Test.....	5
1.4. Product Specification of Equipment Under Test .....	6
1.5. Modification of EUT.....	6
1.6. Test Site .....	7
1.7. Applied Standards .....	7
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
2.1. Test Mode .....	8
2.2. Connection Diagram of Test System .....	10
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup.....	11
<b>3. TEST RESULT.....</b>	<b>12</b>
3.1. Test of AC Conducted Emission Measurement .....	12
3.2. Test of Radiated Emission Measurement .....	20
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>24</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>25</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 3.87 dB at 0.930 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 10.69 dB at 719.670 MHz

## 1. General Description

### 1.1. Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

### 1.2. Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

### 1.3. Feature of Equipment Under Test

Product Feature	
Equipment	cdma2000 Digital Mobile Handset
Brand Name	ZTE
Model Name	N8000
FCC ID	Q78-N8000
EUT supports Radios application	CDMA/EV-DO/WLAN 2.4GHz 11bgn (HT20)/ Bluetooth v2.1 + EDR
HW Version	QB8655-03A_V1CMB_B
SW Version	N8000_CKT_D201
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx Frequency</b>	CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1815.25 MHz ~ 1908.75 MHz CDMA2000 BC15 : 1711.25 ~ 1753.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency Range</b>	CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz CDMA2000 BC15 : 2111.25 ~ 2153.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz
<b>Antenna Type</b>	WWAN : Fixed Internal Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna
<b>Type of Modulation</b>	CDMA2000 : QPSK CDMA2000 1xEV-DO : QPSK / 8PSK 802.11b : DSSS (BPSK / QPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK GPS : BPSK

### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6. Test Site

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.		
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-3320-2398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Registration No.</b>
	CO01-SZ	03CH01-SZ	831040

### 1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	Note 1
2.	Data application transferred mode (EUT with notebook)	☒	☒	☒

**Abbreviations:**


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

**Note 1:** Testing for this mode is not required or not the worst case.


**Remark:** For signal above 1GHz, the worst case is test item 2.

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Camera <Fig. 1> Mode 2: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + MPEG4 <Fig. 1> Mode 3: CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx <Fig. 2>
Radiated Emissions < 1GHz	1/2	Mode 1: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Camera <Fig. 1> Mode 2: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + MPEG4 <Fig. 1> Mode 3: CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx <Fig. 2>
Radiated Emissions ≥ 1GHz	2	Mode 1: CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx <Fig. 2>
<b>Remark:</b> <ol style="list-style-type: none"> <li>The worst case of AC is mode 1; the test data of this mode is reported.</li> <li>The USB link mode of AC is mode 3; the test data of this mode is reported.</li> <li>The worst case of RE &lt; 1G is mode 3; only the test data of this mode is reported.</li> <li>Link with Notebook means data application transferred mode between EUT and Notebook.</li> </ol>		

## 2.2. Connection Diagram of Test System



<Fig. 1>



<Fig. 2>

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-link	DIR-612	FCC DoC	N/A	Unshielded, 1.8 m
4.	WLAN AP	D-link	DIR-615	FCC DoC	N/A	Unshielded, 1.8 m
5.	Notebook	Dell	P08S	QDS-BRCM1030	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m
6.	Monitor	DELL	IN1940MWB	FCC DoC	Shielded, 1.2 m	Unshielded, 1.8 m
7.	Monitor	Dell	1707FPt	FCC DoC	Shielded, 1.2 m	Unshielded, 1.8 m
8.	Bluetooth Earphone	Nokia	BH-108	FCC DoC	N/A	N/A
9.	iPod	Apple	MC525 ZP/A	FCC DoC	Unshielded, 1.0 m	N/A

### 2.4. EUT Operation Test Setup

The EUT was in CDMA2000 idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Execute the program, "Winthrax" under WIN7 installed in Notebook for files transfer with EUT via USB cable.
2. Turn on GPS function to make the EUT receive continuous signals from GPS station.
3. Execute "Video Player" to play MPEG4 files.
4. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Henry Chen	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Camera		




Site : CO01-SZ  
 Condition: FCC 15B\_QP LISN\_L\_2000601 LINE  
 Project : (FC) 280303-01  
 Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.38	39.10	-9.20	48.30	29.01	0.02	10.07	Average
2	0.38	43.70	-14.60	58.30	33.61	0.02	10.07	QP
3	0.46	35.10	-11.57	46.67	25.00	0.02	10.08	Average
4	0.46	39.90	-16.77	56.67	29.80	0.02	10.08	QP
5	0.50	36.81	-9.19	46.00	26.70	0.02	10.09	Average
6	0.50	42.11	-13.89	56.00	32.00	0.02	10.09	QP
7	0.55	37.71	-8.29	46.00	27.60	0.02	10.09	Average
8	0.55	43.11	-12.89	56.00	33.00	0.02	10.09	QP
9	0.58	36.61	-9.39	46.00	26.50	0.02	10.09	Average
10	0.58	42.91	-13.09	56.00	32.80	0.02	10.09	QP
11	0.63	36.52	-9.48	46.00	26.40	0.02	10.10	Average
12	0.63	42.12	-13.88	56.00	32.00	0.02	10.10	QP
13	0.67	37.42	-8.58	46.00	27.30	0.02	10.10	Average
14	0.67	42.42	-13.58	56.00	32.30	0.02	10.10	QP
15	0.71	39.23	-6.77	46.00	29.11	0.02	10.10	Average
16	0.71	45.13	-10.87	56.00	35.01	0.02	10.10	QP
17	0.76	37.83	-8.17	46.00	27.71	0.02	10.10	Average
18	0.76	44.13	-11.87	56.00	34.01	0.02	10.10	QP
19	0.80	37.63	-8.37	46.00	27.50	0.02	10.11	Average
20	0.80	43.53	-12.47	56.00	33.40	0.02	10.11	QP
21	0.85	37.43	-8.57	46.00	27.30	0.02	10.11	Average
22	0.85	42.73	-13.27	56.00	32.60	0.02	10.11	QP
23	0.88	39.23	-6.77	46.00	29.10	0.02	10.11	Average
24	0.88	44.23	-11.77	56.00	34.10	0.02	10.11	QP
25	0.93	39.04	-6.96	46.00	28.90	0.03	10.11	Average
26	0.93	45.14	-10.86	56.00	35.00	0.03	10.11	QP
27	0.96	38.64	-7.36	46.00	28.50	0.03	10.11	Average
28	0.96	44.84	-11.16	56.00	34.70	0.03	10.11	QP
29	1.01	37.84	-8.16	46.00	27.70	0.03	10.11	Average



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Henry Chen	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Camera		




Site : CO01-SZ  
 Condition: FCC 15B\_QP LISN\_L\_2000601 LINE  
 Project : (FC) 280303-01  
 Mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
30	1.01	43.24	-12.76	56.00	33.10	0.03	10.11	QP
31	1.05	38.64	-7.36	46.00	28.49	0.03	10.12	Average
32	1.05	43.34	-12.66	56.00	33.19	0.03	10.12	QP
33 *	1.10	39.24	-6.76	46.00	29.09	0.03	10.12	Average
34	1.10	44.64	-11.36	56.00	34.49	0.03	10.12	QP
35	1.14	39.15	-6.85	46.00	29.00	0.03	10.12	Average
36	1.14	45.55	-10.45	56.00	35.40	0.03	10.12	QP
37	1.18	38.45	-7.55	46.00	28.30	0.03	10.12	Average
38	1.18	44.45	-11.55	56.00	34.30	0.03	10.12	QP
39	1.22	37.95	-8.05	46.00	27.80	0.03	10.12	Average
40	1.22	43.15	-12.85	56.00	33.00	0.03	10.12	QP
41	1.31	38.45	-7.55	46.00	28.30	0.03	10.12	Average
42	1.31	44.55	-11.45	56.00	34.40	0.03	10.12	QP
43	1.35	38.15	-7.85	46.00	28.00	0.03	10.12	Average
44	1.35	44.85	-11.15	56.00	34.70	0.03	10.12	QP
45	1.48	36.46	-9.54	46.00	26.30	0.03	10.13	Average
46	1.48	42.36	-13.64	56.00	32.20	0.03	10.13	QP
47	1.56	35.36	-10.64	46.00	25.20	0.03	10.13	Average
48	1.56	42.86	-13.14	56.00	32.70	0.03	10.13	QP
49	1.73	35.17	-10.83	46.00	25.00	0.03	10.14	Average
50	1.73	42.17	-13.83	56.00	32.00	0.03	10.14	QP
51	2.24	33.50	-12.50	46.00	23.30	0.04	10.16	Average
52	2.24	40.20	-15.80	56.00	30.00	0.04	10.16	QP
53	2.36	34.21	-11.79	46.00	24.00	0.04	10.17	Average
54	2.36	42.61	-13.39	56.00	32.40	0.04	10.17	QP



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Henry Chen	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Camera		




Site : CO01-SZ  
 Condition: FCC 15B\_QP LISN\_N\_2000601 NEUTRAL  
 Project : (FC) 280303-01  
 Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.30	44.88	-5.44	50.32	34.80	0.02	10.06	Average
2	0.30	48.38	-11.94	60.32	38.30	0.02	10.06	QP
3	0.38	43.09	-5.21	48.30	33.00	0.02	10.07	Average
4	0.38	47.09	-11.21	58.30	37.00	0.02	10.07	QP
5	0.42	40.09	-7.28	47.37	29.99	0.02	10.08	Average
6	0.42	45.69	-11.68	57.37	35.59	0.02	10.08	QP
7	0.47	40.10	-6.48	46.58	30.00	0.02	10.08	Average
8	0.47	44.40	-12.18	56.58	34.30	0.02	10.08	QP
9	0.51	39.20	-6.80	46.00	29.09	0.02	10.09	Average
10	0.51	45.50	-10.50	56.00	35.39	0.02	10.09	QP
11	0.55	41.10	-4.90	46.00	30.99	0.02	10.09	Average
12	0.55	46.10	-9.90	56.00	35.99	0.02	10.09	QP
13	0.59	40.41	-5.59	46.00	30.30	0.02	10.09	Average
14	0.59	46.11	-9.89	56.00	36.00	0.02	10.09	QP
15	0.63	40.91	-5.09	46.00	30.79	0.02	10.10	Average
16	0.63	45.51	-10.49	56.00	35.39	0.02	10.10	QP
17	0.68	39.92	-6.08	46.00	29.80	0.02	10.10	Average
18	0.68	45.12	-10.88	56.00	35.00	0.02	10.10	QP
19	0.72	41.52	-4.48	46.00	31.40	0.02	10.10	Average
20	0.72	46.52	-9.48	56.00	36.40	0.02	10.10	QP
21	0.76	41.22	-4.78	46.00	31.10	0.02	10.10	Average
22	0.76	46.12	-9.88	56.00	36.00	0.02	10.10	QP
23	0.80	40.93	-5.07	46.00	30.80	0.02	10.11	Average
24	0.80	46.13	-9.87	56.00	36.00	0.02	10.11	QP
25	0.85	40.13	-5.87	46.00	30.00	0.02	10.11	Average
26	0.85	44.63	-11.37	56.00	34.50	0.02	10.11	QP
27	0.89	41.23	-4.77	46.00	31.10	0.02	10.11	Average
28	0.89	46.33	-9.67	56.00	36.20	0.02	10.11	QP
29 *	0.93	42.13	-3.87	46.00	32.00	0.02	10.11	Average



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Henry Chen	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Camera		




Site : CO01-SZ  
 Condition: FCC 15B\_QP LISN\_N\_2000601 NEUTRAL  
 Project : (FC) 280303-01  
 Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
30	0.93	46.93	-9.07	56.00	36.80	0.02	10.11	QP
31	0.97	40.83	-5.17	46.00	30.70	0.02	10.11	Average
32	0.97	45.93	-10.07	56.00	35.80	0.02	10.11	QP
33	1.02	40.34	-5.66	46.00	30.21	0.02	10.11	Average
34	1.02	45.14	-10.86	56.00	35.01	0.02	10.11	QP
35	1.05	41.54	-4.46	46.00	31.40	0.02	10.12	Average
36	1.05	46.34	-9.66	56.00	36.20	0.02	10.12	QP
37	1.10	41.94	-4.06	46.00	31.80	0.02	10.12	Average
38	1.10	47.14	-8.86	56.00	37.00	0.02	10.12	QP
39	1.14	41.14	-4.86	46.00	31.00	0.02	10.12	Average
40	1.14	45.64	-10.36	56.00	35.50	0.02	10.12	QP
41	1.19	40.14	-5.86	46.00	30.00	0.02	10.12	Average
42	1.19	45.14	-10.86	56.00	35.00	0.02	10.12	QP
43	1.22	40.54	-5.46	46.00	30.40	0.02	10.12	Average
44	1.22	46.44	-9.56	56.00	36.30	0.02	10.12	QP
45	1.27	41.15	-4.85	46.00	31.01	0.02	10.12	Average
46	1.27	46.35	-9.65	56.00	36.21	0.02	10.12	QP
47	1.31	38.75	-7.25	46.00	28.61	0.02	10.12	Average
48	1.31	44.65	-11.35	56.00	34.51	0.02	10.12	QP
49	1.41	38.55	-7.45	46.00	28.40	0.03	10.12	Average
50	1.41	45.15	-10.85	56.00	35.00	0.03	10.12	QP
51	1.53	37.56	-8.44	46.00	27.40	0.03	10.13	Average
52	1.53	43.46	-12.54	56.00	33.30	0.03	10.13	QP
53	1.74	36.17	-9.83	46.00	26.00	0.03	10.14	Average
54	1.74	43.17	-12.83	56.00	33.00	0.03	10.14	QP



Test Mode :	Mode 3	Temperature :	23~24°C
Test Engineer :	Henry Chen	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx		




Site : CO01-SZ  
 Condition: FCC 15B\_QP LISN\_L\_2000601 LINE  
 Project : (FC) 280303-01  
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.20	35.78	-18.02	53.80	25.69	0.03	10.06	Average
2	0.20	52.78	-11.02	63.80	42.69	0.03	10.06	QP
3	0.21	32.58	-20.69	53.27	22.50	0.02	10.06	Average
4	0.21	51.08	-12.19	63.27	41.00	0.02	10.06	QP
5	0.45	15.10	-31.83	46.93	5.00	0.02	10.08	Average
6	0.45	30.50	-26.43	56.93	20.40	0.02	10.08	QP
7	14.52	37.36	-12.64	50.00	26.69	0.25	10.42	Average
8	14.52	43.36	-16.64	60.00	32.69	0.25	10.42	QP
9	15.15	38.89	-11.11	50.00	28.20	0.25	10.44	Average
10	15.15	44.89	-15.11	60.00	34.20	0.25	10.44	QP
11 *	15.72	39.21	-10.79	50.00	28.50	0.26	10.45	Average
12	15.72	45.01	-14.99	60.00	34.30	0.26	10.45	QP



Test Mode :	Mode 3	Temperature :	23~24°C
Test Engineer :	Henry Chen	Relative Humidity :	49~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx		



Site : CO01-SZ  
 Condition: FCC 15B\_QP LISN\_N\_2000601 NEUTRAL  
 Project : (FC) 280303-01  
 Mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.16	23.07	-32.58	55.65	13.00	0.02	10.05	Average
2	0.16	43.07	-22.58	65.65	33.00	0.02	10.05	QP
3	0.19	32.67	-21.31	53.98	22.60	0.02	10.05	Average
4	0.19	51.77	-12.21	63.98	41.70	0.02	10.05	QP
5	0.20	33.17	-20.37	53.54	23.09	0.02	10.06	Average
6	0.20	50.47	-13.07	63.54	40.39	0.02	10.06	QP
7	0.21	30.77	-22.50	53.27	20.69	0.02	10.06	Average
8	0.21	49.57	-13.70	63.27	39.49	0.02	10.06	QP
9	14.52	36.76	-13.24	50.00	26.00	0.34	10.42	Average
10	14.52	42.36	-17.64	60.00	31.60	0.34	10.42	QP
11 *	15.80	39.22	-10.78	50.00	28.39	0.37	10.46	Average
12	15.80	44.22	-15.78	60.00	33.39	0.37	10.46	QP

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments


See list of measuring instruments of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	23~25°C
Test Engineer :	Gavin Zhang	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx		




Site : 03CH01-SZ  
 Condition : FCC CLASS-B 3m LF\_ANT\_121103 HORIZONTAL  
 Project : (FC) 280303-01  
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss Factor	Preamp Loss Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	76.56	16.69	-23.31	40.00	39.53	6.65	1.11	30.60	---	---	Peak
2	152.22	23.24	-20.26	43.50	41.89	10.35	1.49	30.49	---	---	Peak
3	263.77	29.84	-16.16	46.00	44.96	13.10	1.90	30.12	---	---	Peak
4 P	382.11	31.40	-14.60	46.00	42.85	16.04	2.24	29.73	145	136	Peak
5	687.66	29.93	-16.07	46.00	36.82	19.24	2.95	29.08	---	---	Peak
6	840.92	31.15	-14.85	46.00	35.81	21.00	3.22	28.88	---	---	Peak



Test Mode :	Mode 3	Temperature :	23~25°C
Test Engineer :	Gavin Zhang	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Vertical
Function Type :	CDMA2000 BC15 + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + GPS Rx		



Site : 03CH01-SZ  
 Condition : FCC CLASS-B 3m LF\_ANT\_121103 VERTICAL  
 Project : (FC) 280303-01  
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	100.81	18.03	-25.47	43.50	36.22	11.20	1.27	30.66	---	---	Peak
2	166.77	20.25	-23.25	43.50	39.23	9.90	1.56	30.44	---	---	Peak
3	243.40	27.09	-18.91	46.00	43.45	12.00	1.83	30.19	---	---	Peak
4	381.14	29.08	-16.92	46.00	40.57	16.00	2.24	29.73	---	---	Peak
5 P	719.67	35.31	-10.69	46.00	41.36	20.00	2.99	29.04	145	287	Peak
6	837.04	27.97	-18.03	46.00	32.61	21.00	3.24	28.88	---	---	Peak



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC LISN (for auxiliary equipment)	ETS-LINDGREN	3816/2SH	00103912	9kHz~30MHz	Mar. 28, 2013	Aug. 27, 2013	Mar. 27, 2014	Conduction (CO01-SZ)
AC LISN	ETS-LINDGREN	3816/2SH	00103892	9kHz~30MHz	Mar. 28, 2013	Aug. 27, 2013	Mar. 27, 2014	Conduction (CO01-SZ)
ESCIO TEST Receiver	R&S	1142.8007.03	100724	9kHz-3GHz	Mar. 28, 2013	Aug. 27, 2013	Mar. 27, 2014	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	N/A	Nov. 20, 2012	Aug. 27, 2013	Nov. 19, 2013	Conduction (CO01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	Apr. 04, 2013	Aug. 30, 2013	Apr. 03, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 12, 2012	Aug. 30, 2013	Oct. 11, 2013	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Nov. 03, 2012	Aug. 30, 2013	Nov. 02, 2013	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz-3000MHz GAIN 30db	Mar. 28, 2013	Aug. 30, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	Aug. 30, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
SHF-EHF-Horn	Schwarzbeck	BBHA9170	BBHA9170249	14GHz~40GHz	Nov. 23, 2012	Aug. 30, 2013	Nov. 22, 2013	Radiation (03CH01-SZ)
Turn Table	EM Electronics	EM 1000	N/A	0 ~ 360 degree	N/A	Aug. 30, 2013	N/A	Radiation (03CH01-SZ)
Antenna Mast	EM Electronics	EM 1000	N/A	1 m - 4 m	N/A	Aug. 30, 2013	N/A	Radiation (03CH01-SZ)

## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.54
---	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.72
---	------