Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

| RF | 50 Ω | AC | | SENSE:EXT | | ALIGN AUTO | 05:56:19 PM Apr 14, 2016 | TRACE **1** 2 3 4 5 6 |

Marker 1 5.150000000000 GHz

Gate: LO   PNO: Fast ◄►   Trig: External1   Avg Type: RMS   Avg|Hold: 1/1   TYPE A wwwww
                            IFGain:Low   #Atten: 16 dB   Ext Gain: -15.40 dB   DET A N N N N N

Mkr2 5.350 0 GHz
-52.994 dBm

10 dB/div   **Ref 8.00 dBm**
Log
-2.00
-12.0
-22.0
-32.0
-42.0
                                    1   2
-52.0
-62.0
-72.0
-82.0

Start 5.0000 GHz   **Stop 5.5000 GHz**
#Res BW 100 kHz   **#VBW 300 kHz***   **#Sweep 100.0 ms (1001 pts)**

R	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	5.150 0 GHz	-56.605 dBm			
2	N	1	f	5.350 0 GHz	-52.994 dBm			
3								
4								
5								
6								
7								
8								
9								
0								
1								

MSG   STATUS

Recall State

Register 5
Last: 4/14/2016
2:30:28 PM

Register 6
Last: 4/14/2016
2:05:44 PM

Register 7
TDS6S

Register 8
Last: 4/14/2016
2:01:36 PM

Register 9
Last: 1/27/2016
9:13:02 AM

Register 10
Last: 1/27/2016
9:22:49 AM

More
2 of 3

Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

RF	50 Ω	AC	SENSE:EXT	ALIGN AUTO	05:52:22 PM Apr 22, 2016

Marker 1 858.380000000 MHz

Gate: LO   PNO: Fast ➡   Trig: External1   Avg Type: RMS

IFGain:Low   #Atten: 16 dB   Ext Gain: -10.50 dB

TRACE 1 2 3 4 5 6   TYPE WWWWWW   DET A N N N N N

Peak Search

Mkr1 858.38 MHz
-63.68 dBm

10 dB/div   **Ref 16.50 dBm**
Log

6.50
-3.50
-13.5
-23.5
-33.5
-43.5
-53.5
-63.5
-73.5

Start 30.0 MHz   **Stop 1.0000 GHz**
#Res BW 1.0 MHz   **#VBW 3.0 MHz***   **Sweep 9.733 ms (1001 pts)**

MSG   STATUS

Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

RF	50 Ω	AC	SENSE:EXT	ALIGN AUTO	05:53:29 PM Apr 22, 2016

Marker 1 3.664000000000 GHz

Gate: LO   PNO: Fast ➡   Trig: External1   Avg Type: RMS

IFGain:Low   #Atten: 16 dB   Ext Gain: -16.00 dB

TRACE 1 2 3 4 5 6   TYPE WWWWWW   DET A N N N N N

Peak Search

Mkr1 3.664 GHz
-54.17 dBm

10 dB/div   **Ref 22.00 dBm**
Log

12.0
2.00
-8.00
-18.0
-28.0
-38.0
-48.0
-58.0
-68.0

Start 1.000 GHz   **Stop 10.000 GHz**
#Res BW 1.0 MHz   **#VBW 3.0 MHz***   **Sweep 90.00 ms (1001 pts)**

MSG   STATUS

Agilent Spectrum Analyzer - Swept SA (Prototype - Limited Sale Allowed)

Marker 1 10.396000000000 GHz

Gate: LO | PNO: Fast | Trig: External1 | Avg Type: RMS | TRACE 1 2 3 4 5 6 | Peak Search
IFGain:High | #Atten: 0 dB | Ext Gain: -20.10 dB | 05:54:33 PM Apr 22, 2016

Mkr1 10.396 0 GHz
-56.69 dBm

10 dB/div   Ref -4.00 dBm
Log

-14.0
-24.0
-34.0
-44.0
-54.0
-64.0
-74.0
-84.0
-94.0

Start 10.000 GHz   Stop 26.500 GHz
#Res BW 1.0 MHz   #VBW 3.0 MHz*   Sweep 330.0 ms (1001 pts)

Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

Agilent Spectrum Analyzer - Swept SA (Prototype - Limited Sale Allowed)

Marker 1 868.080000000 MHz

Gate: LO | PNO: Fast | Trig: External1 | Avg Type: RMS | TRACE 1 2 3 4 5 6 | Peak Search
IFGain:Low | #Atten: 16 dB | Ext Gain: -10.50 dB | 05:39:49 PM Apr 22, 2016

Mkr1 868.08 MHz
-63.57 dBm

10 dB/div   Ref 16.50 dBm
Log

6.50
-3.50
-13.5
-23.5
-33.5
-43.5
-53.5
-63.5
-73.5

Start 30.0 MHz   Stop 1.0000 GHz
#Res BW 1.0 MHz   #VBW 3.0 MHz*   Sweep 9.733 ms (1001 pts)

Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2

Top Spectrum Analyzer Display:

Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

LXI   RF   50 Ω   AC   SENSE:EXT   ALIGN AUTO   06:20:08 PM Apr 22, 2016

Marker 1 10.396000000000 GHz

Gate: LO   PNO: Fast →•   Trig: External1   Avg Type: RMS   TRACE 1 2 3 4 5 6
IFGain:High   #Atten: 0 dB   Ext Gain: -20.10 dB   TYPE W W W W W W
                                                                    DET A N N N N N

Peak Search

Mkr1 10.396 0 GHz
-57.21 dBm

10 dB/div   Ref -4.00 dBm
Log

-14.0
-24.0
-34.0
-44.0
-54.0
-64.0
-74.0
-84.0
-94.0

Start 10.000 GHz   Stop 26.500 GHz
#Res BW 1.0 MHz   #VBW 3.0 MHz*   Sweep 330.0 ms (1001 pts)

Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lv
More 1 of 2

MSG   STATUS

Bottom Spectrum Analyzer Display:

Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

LXI   RF   50 Ω   AC   SENSE:EXT   ALIGN AUTO   06:05:05 PM Apr 22, 2016

Marker 1 855.470000000 MHz

Gate: LO   PNO: Fast →•   Trig: External1   Avg Type: RMS   TRACE 1 2 3 4 5 6
IFGain:Low   #Atten: 16 dB   Ext Gain: -10.50 dB   TYPE W W W W W W
                                                                    DET A N N N N N

Peak Search

Mkr1 855.47 MHz
-63.97 dBm

10 dB/div   Ref 16.50 dBm
Log

6.50
-3.50
-13.5
-23.5
-33.5
-43.5
-53.5
-63.5
-73.5

Start 30.0 MHz   Stop 1.0000 GHz
#Res BW 1.0 MHz   #VBW 3.0 MHz*   Sweep 9.733 ms (1001 pts)

Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lv
More 1 of 2

MSG   STATUS

Screen 1 (Top)

Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

RF   50 Ω   AC   SENSE:EXT   ALIGN AUTO   06:06:24 PM Apr 22, 2016

Marker 1 3.637000000000 GHz   Avg Type: RMS   TRACE 1 2 3 4 5 6
                                                             TYPE W W W W W W
Gate: LO   PNO: Fast →   Trig: External1   DET A N N N N N
                  IFGain:Low   #Atten: 16 dB   Ext Gain: -16.00 dB

Mkr1 3.637 GHz
-54.87 dBm

10 dB/div   Ref 22.00 dBm
Log

12.0
2.00
-8.00
-18.0
-28.0
-38.0
-48.0
-58.0
-68.0

Start 1.000 GHz   Stop 10.000 GHz
#Res BW 1.0 MHz   #VBW 3.0 MHz*   Sweep 90.00 ms (1001 pts)

Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lv
More
1 of 2

MSG   STATUS

Screen 2 (Bottom)

Agilent Spectrum Analyzer - Swept SA   (Prototype - Limited Sale Allowed)

RF   50 Ω   AC   SENSE:EXT   ALIGN AUTO   06:07:54 PM Apr 22, 2016

Marker 1 10.396000000000 GHz   Avg Type: RMS   TRACE 1 2 3 4 5 6
                                                             TYPE W W W W W W
Gate: LO   PNO: Fast →   Trig: External1   DET A N N N N N
                  IFGain:High   #Atten: 0 dB   Ext Gain: -20.10 dB

Mkr1 10.396 0 GHz
-57.63 dBm

10 dB/div   Ref -4.00 dBm
Log

-14.0
-24.0
-34.0
-44.0
-54.0
-64.0
-74.0
-84.0
-94.0

Start 10.000 GHz   Stop 26.500 GHz
#Res BW 1.0 MHz   #VBW 3.0 MHz*   Sweep 330.0 ms (1001 pts)

Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lv
More
1 of 2

MSG   STATUS

Radiated spurious emission test data:

Comment: HOR-30MHz~6.7GHz

Radiated spurious emission test data:

Note: Only worst case test data was shown in the report

Comment: **HOR-30MHz~6.7GHz**

Frequency (MHz)	MaxPeak-MaxHold (dBm)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Limit (dBm)	Margin (dB)
34.4135	-75.1	150	H	338	-108.6	-33	42.1
88.297	-71.8	150	H	338	-109.3	-33	38.8
90.8675	-71.7	150	H	356	-107.4	-33	38.7
165.9455	-66	150	H	320	-111.6	-33	33
368.627	-72.4	150	H	0	-105.5	-33	39.4
737.2755	-73.3	150	H	302	-101.7	-33	40.3
871.184	-60.7	150	H	153	-100.3	-33	27.7
872.0085	-60.9	150	H	70	-100.2	-33	27.9
873.997	-63	150	H	5	-99.9	-33	30
874.5305	-65.6	150	H	5	-99.9	-33	32.6
877.974	-66	150	H	228	-99.5	-33	33
2227.2	-62.9	150	H	0	-109	-33	29.9
3774.04	-55.7	150	H	295	-103.1	-33	22.7
4276.87	-54	150	H	83	-101.3	-33	21
4993.93	-52.4	150	H	0	-101.5	-33	19.4
5246.64	-32.3	150	H	313	-101.4	-33	-0.7
6614.16	-52.7	150	H	221	-98.7	-33	19.7

TEST

Comment: VER-30MHz~6.7GHz

Frequency (MHz)	MaxPeak-MaxHold (dBm)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Limit (dBm)	Margin (dB)
34.5105	-76.4	150	V	142	-110.2	-33	43.4
80.4885	-64.1	150	V	348	-111.3	-33	31.1
89.1215	-68.2	150	V	26	-109.9	-33	35.2
163.0355	-68.6	150	V	26	-108.6	-33	35.6
368.627	-62.3	150	V	215	-106.8	-33	29.3
737.324	-72.8	150	V	336	-100.9	-33	39.8
870.7475	-60.5	150	V	336	-99.4	-33	27.5
871.2325	-61.5	150	V	336	-99.5	-33	28.5
873.9	-57.9	150	V	227	-99.8	-33	24.9
2261.2	-62.5	150	V	147	-108.5	-33	29.5
3461.76	-56.3	150	V	0	-104.7	-33	23.3
3859.51	-55.7	150	V	20	-102.7	-33	22.7
4361.23	-54	150	V	20	-102.1	-33	21
4674.99	-53.7	150	V	60	-101	-33	20.7
4993.93	-43.6	150	V	138	-101.6	-33	10.6
5243.31	-33.3	150	V	308	-101.9	-33	0.3
6552.37	-52.9	150	V	297	-99	-33	19.9

Comment: HOR-6.7GHz~18GHz

Data Reduction Result 1 [4]

Frequency (MHz)	MaxPeak-MaxHold (dBm)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Limit (dBm)	Margin (dB)
7087.966667	-50.6	150	H	241	-96.1	-33	17.6
7879.343333	-50.1	150	H	0	-95.9	-33	17.1
8748.69	-49.8	150	H	102	-95	-33	16.8
9880.196667	-50	150	H	351	-94.8	-33	17
10265.15	-49.5	150	H	241	-94.1	-33	16.5
11158.98	-49.8	150	H	0	-93.6	-33	16.8
13377.92333	-48.5	150	H	344	-91.2	-33	15.5
13985.11	-46.5	150	H	92	-89	-33	13.5
14733.54667	-45.1	150	H	205	-88.5	-33	12.1
15153.90667	-44.1	150	H	344	-86.8	-33	11.1
16378.82667	-42.5	150	H	142	-83.7	-33	9.5
16872.63667	-43.8	150	H	228	-85.7	-33	10.8
17289.98333	-42.1	150	H	81	-83	-33	9.1
17564.95	-39.3	150	H	18	-78.3	-33	6.3
17953.29333	-40.7	150	H	146	-80.8	-33	7.7

Comment: VER-6.7GHz~18GHz

Data Reduction Result 1 [4]

Frequency (MHz)	MaxPeak-MaxHold (dBm)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Limit (dBm)	Margin (dB)
7002.086667	-49.4	150	H	351	-96.4	-33	16.4
8108.356667	-50.4	150	H	167	-95.3	-33	17.4
8767.146667	-49.1	150	H	309	-95	-33	16.1
9321.223333	-50.1	150	H	255	-95.1	-33	17.1
10244.05667	-50	150	H	297	-94.2	-33	17
10632.02333	-49.6	150	H	114	-93.7	-33	16.6
11604.2	-49.5	150	H	242	-92.5	-33	16.5
12372.22333	-49.1	150	H	91	-93	-33	16.1
13967.40667	-46.4	150	H	154	-88.9	-33	13.4
15159.93333	-45.4	150	H	193	-86.9	-33	12.4
16251.51333	-44.6	150	H	170	-86.5	-33	11.6
16346.43333	-43.2	150	H	170	-84.4	-33	10.2
17212.39	-42.2	150	H	0	-82.3	-33	9.2
17547.62333	-39.1	150	H	319	-78.6	-33	6.1
17901.31333	-40.3	150	H	177	-80.5	-33	7.3

8 FREQUENCY STABILITY

Applicable Standard: FCC§15.407(g)

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
GZ-ESPEC	Temperature Chamber	EW0470	06113028	2014.06.25	2015.06.25
Agilent	MXA Series Spectrum Analyzer	N9020A	MY51240300	2015.12.10	2016.12.10
Agilent	MXA Series Spectrum Analyzer	N9030A	MY53310566	2015.06.28	2016.06.28
Grentech	10dB Attenuator	SGR-SJQ-10	09112005	2015.06.13	2016.06.13

*__statement of traceability:__ ZTE Corporation Reliability Testing Center attest that all calibration have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Spectrum Analyzer via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.
After the temperature stabilized for approximately 150 minutes, the frequency output was recorded from the counter.
Frequency Stability vs. Voltage: An external variable DC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

Environmental Conditions

Normal condition:	25° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Test Result: Pass

Test Mode: Transmitting OFDM MIMO Access Point

Test Data

Frequency Stability versus Temperature

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5160MHz）					
Temperature (℃)	**Power Supplied (V$_{DC}$)**	**Port**	**Modulation**	**Frequency Measure Error (Hz)**	**Result**
-40	-48	0	QPSK	2.84	Pass
			16QAM	0.96	Pass
			64QAM	4.54	Pass
		1	QPSK	1.43	Pass
			16QAM	3.32	Pass
			64QAM	-1.41	Pass
		2	QPSK	2.39	Pass
			16QAM	-1.52	Pass
			64QAM	0.73	Pass
		3	QPSK	-3.52	Pass
			16QAM	-3.91	Pass
			64QAM	-0.11	Pass
-30	-48	0	QPSK	1.03	Pass
			16QAM	2.15	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5160MHz）					
Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-0.47	Pass
		1	QPSK	2.16	Pass
		1	16QAM	4.68	Pass
			64QAM	-0.95	Pass
		2	QPSK	-2.74	Pass
		2	16QAM	-4.68	Pass
			64QAM	1.43	Pass
		3	QPSK	-0.8	Pass
		3	16QAM	4.39	Pass
			64QAM	4.24	Pass
-20	-48	0	QPSK	-0.28	Pass
		0	16QAM	-2.77	Pass
			64QAM	-4.66	Pass
		1	QPSK	1.44	Pass
		1	16QAM	-0.8	Pass
			64QAM	-2.57	Pass
		2	QPSK	-1.13	Pass
		2	16QAM	1.3	Pass
			64QAM	-4.68	Pass
		3	QPSK	0.08	Pass
		3	16QAM	0.88	Pass
			64QAM	2.4	Pass
-10	-48	0	QPSK	1.75	Pass
		0	16QAM	-2.09	Pass
			64QAM	2.77	Pass
		1	QPSK	3.27	Pass
		1	16QAM	-1.57	Pass
			64QAM	0.31	Pass
		2	QPSK	3.62	Pass
		2	16QAM	-4.87	Pass
			64QAM	4.64	Pass
		3	QPSK	0.1	Pass
		3	16QAM	3.53	Pass
			64QAM	-0.6	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5160MHz）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
0	-48	0	QPSK	3.79	Pass
			16QAM	1.72	Pass
			64QAM	-3.49	Pass
		1	QPSK	-2.97	Pass
			16QAM	-2.78	Pass
			64QAM	-2.36	Pass
		2	QPSK	0.05	Pass
			16QAM	1.15	Pass
			64QAM	3.94	Pass
		3	QPSK	2.86	Pass
			16QAM	1.47	Pass
			64QAM	2.09	Pass
10	-48	0	QPSK	1.55	Pass
			16QAM	1.36	Pass
			64QAM	0.2	Pass
		1	QPSK	0.59	Pass
			16QAM	-3.48	Pass
			64QAM	-1.04	Pass
		2	QPSK	0.16	Pass
			16QAM	4.99	Pass
			64QAM	-0.16	Pass
		3	QPSK	-1.23	Pass
			16QAM	-4.5	Pass
			64QAM	-1.68	Pass
20	-48	0	QPSK	3.37	Pass
			16QAM	-2.05	Pass
			64QAM	-4.35	Pass
		1	QPSK	-1.47	Pass
			16QAM	2.23	Pass
			64QAM	4.46	Pass
		2	QPSK	1.67	Pass
			16QAM	-3.71	Pass
			64QAM	3.88	Pass
		3	QPSK	-1.78	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5160MHz）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	-2.62	Pass
			64QAM	4.93	Pass
30	-48	0	QPSK	1.97	Pass
			16QAM	4.48	Pass
			64QAM	2.71	Pass
		1	QPSK	2	Pass
			16QAM	0.17	Pass
			64QAM	3.64	Pass
		2	QPSK	3.21	Pass
			16QAM	3.55	Pass
			64QAM	1.71	Pass
		3	QPSK	-3.24	Pass
			16QAM	-4.41	Pass
			64QAM	3.35	Pass
40	-48	0	QPSK	-4.99	Pass
			16QAM	-1.35	Pass
			64QAM	-2.24	Pass
		1	QPSK	1.31	Pass
			16QAM	-0.74	Pass
			64QAM	0.46	Pass
		2	QPSK	3.82	Pass
			16QAM	-4.08	Pass
			64QAM	0.61	Pass
		3	QPSK	-4.18	Pass
			16QAM	-3.04	Pass
			64QAM	0.17	Pass
50	-48	0	QPSK	-4.67	Pass
			16QAM	1.35	Pass
			64QAM	4.95	Pass
		1	QPSK	4.74	Pass
			16QAM	2.44	Pass
			64QAM	-1.72	Pass
		2	QPSK	-2.61	Pass
			16QAM	3.58	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5160MHz）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-1.13	Pass
		3	QPSK	-0.46	Pass
			16QAM	-3.73	Pass
			64QAM	-1.51	Pass
55	-48	0	QPSK	-3.18	Pass
			16QAM	-1.87	Pass
			64QAM	-1.28	Pass
		1	QPSK	-2.34	Pass
			16QAM	-3.04	Pass
			64QAM	-3.03	Pass
		2	QPSK	1.81	Pass
			16QAM	-3.74	Pass
			64QAM	3.91	Pass
		3	QPSK	-1.63	Pass
			16QAM	2.71	Pass
			64QAM	2.1	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
-40	-48	0	QPSK	4.46	Pass
			16QAM	4.38	Pass
			64QAM	-1.77	Pass
		1	QPSK	0.98	Pass
			16QAM	-1.91	Pass
			64QAM	-0.87	Pass
		2	QPSK	0.13	Pass
			16QAM	0.13	Pass
			64QAM	-1.95	Pass
		3	QPSK	0.26	Pass
			16QAM	-3.48	Pass
			64QAM	3.21	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）					
Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
-30	-48	0	QPSK	0.34	Pass
			16QAM	0.59	Pass
			64QAM	0.11	Pass
		1	QPSK	2.8	Pass
			16QAM	2.08	Pass
			64QAM	-3.74	Pass
		2	QPSK	-4.7	Pass
			16QAM	2.03	Pass
			64QAM	2.9	Pass
		3	QPSK	3.95	Pass
			16QAM	-1.67	Pass
			64QAM	-4.07	Pass
-20	-48	0	QPSK	-2.56	Pass
			16QAM	2.08	Pass
			64QAM	-3.85	Pass
		1	QPSK	3.71	Pass
			16QAM	-4.95	Pass
			64QAM	0.67	Pass
		2	QPSK	2.73	Pass
			16QAM	-2.15	Pass
			64QAM	0.09	Pass
		3	QPSK	-3.42	Pass
			16QAM	0.44	Pass
			64QAM	2.31	Pass
-10	-48	0	QPSK	3.84	Pass
			16QAM	-2.77	Pass
			64QAM	4.41	Pass
		1	QPSK	1.66	Pass
			16QAM	1.1	Pass
			64QAM	-3.39	Pass
		2	QPSK	3.67	Pass
			16QAM	0.97	Pass
			64QAM	-0.11	Pass
		3	QPSK	3.1	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）					
Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	-2.72	Pass
			64QAM	4.25	Pass
0	-48	0	QPSK	0.03	Pass
			16QAM	-4.37	Pass
			64QAM	2.94	Pass
		1	QPSK	-3.54	Pass
			16QAM	2.88	Pass
			64QAM	-4.4	Pass
		2	QPSK	3.02	Pass
			16QAM	-4.84	Pass
			64QAM	-1.38	Pass
		3	QPSK	-2.11	Pass
			16QAM	1.35	Pass
			64QAM	3.98	Pass
10	-48	0	QPSK	0.63	Pass
			16QAM	1.73	Pass
			64QAM	-3.77	Pass
		1	QPSK	4.53	Pass
			16QAM	2.64	Pass
			64QAM	0.09	Pass
		2	QPSK	2.92	Pass
			16QAM	-0.51	Pass
			64QAM	4	Pass
		3	QPSK	-0.33	Pass
			16QAM	-4.29	Pass
			64QAM	-0.28	Pass
20	-48	0	QPSK	3.1	Pass
			16QAM	4.64	Pass
			64QAM	1.63	Pass
		1	QPSK	2.31	Pass
			16QAM	2.08	Pass
			64QAM	-3.84	Pass
		2	QPSK	-1.08	Pass
			16QAM	-0.35	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）					
Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-2.86	Pass
		3	QPSK	-2.48	Pass
			16QAM	-4.26	Pass
			64QAM	4.66	Pass
30	-48	0	QPSK	-4.83	Pass
			16QAM	-4.4	Pass
			64QAM	2.98	Pass
		1	QPSK	-0.43	Pass
			16QAM	-0.53	Pass
			64QAM	4.6	Pass
		2	QPSK	-0.96	Pass
			16QAM	0.63	Pass
			64QAM	-0.95	Pass
		3	QPSK	-3.81	Pass
			16QAM	-4.38	Pass
			64QAM	3.39	Pass
40	-48	0	QPSK	-3.41	Pass
			16QAM	3.06	Pass
			64QAM	-1.2	Pass
		1	QPSK	-3.64	Pass
			16QAM	-3.18	Pass
			64QAM	4.63	Pass
		2	QPSK	2.67	Pass
			16QAM	3.67	Pass
			64QAM	-4.38	Pass
		3	QPSK	-1.57	Pass
			16QAM	2.99	Pass
			64QAM	4.65	Pass
50	-48	0	QPSK	-4.47	Pass
			16QAM	-3.53	Pass
			64QAM	1.5	Pass
		1	QPSK	-0.78	Pass
			16QAM	1.81	Pass
			64QAM	3.35	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）

Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
		2	QPSK	0.63	Pass
			16QAM	-3.19	Pass
			64QAM	0.75	Pass
		3	QPSK	4.71	Pass
			16QAM	4	Pass
			64QAM	2.02	Pass
55	-48	0	QPSK	3.36	Pass
			16QAM	-3.76	Pass
			64QAM	2.77	Pass
		1	QPSK	-4.5	Pass
			16QAM	-0.91	Pass
			64QAM	-2.03	Pass
		2	QPSK	-2.63	Pass
			16QAM	0.91	Pass
			64QAM	-0.64	Pass
		3	QPSK	4.76	Pass
			16QAM	0.42	Pass
			64QAM	4.93	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）

Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
-40	-48	0	QPSK	-2.1	Pass
			16QAM	0.88	Pass
			64QAM	-2.07	Pass
		1	QPSK	-1.04	Pass
			16QAM	3.89	Pass
			64QAM	4.89	Pass
		2	QPSK	1.73	Pass
			16QAM	3.72	Pass
			64QAM	4.56	Pass
		3	QPSK	0.6	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）					
Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	1.38	Pass
			64QAM	4.04	Pass
-30	-48	0	QPSK	-2.78	Pass
			16QAM	-5	Pass
			64QAM	-0.16	Pass
		1	QPSK	4.43	Pass
			16QAM	0.52	Pass
			64QAM	1.92	Pass
		2	QPSK	1.25	Pass
			16QAM	-1.74	Pass
			64QAM	1.03	Pass
		3	QPSK	-0.89	Pass
			16QAM	3.28	Pass
			64QAM	3.03	Pass
-20	-48	0	QPSK	-2.21	Pass
			16QAM	1.33	Pass
			64QAM	4.26	Pass
		1	QPSK	-1.1	Pass
			16QAM	2.62	Pass
			64QAM	-0.89	Pass
		2	QPSK	-1.45	Pass
			16QAM	4.05	Pass
			64QAM	-3	Pass
		3	QPSK	2.39	Pass
			16QAM	3.31	Pass
			64QAM	2.74	Pass
-10	-48	0	QPSK	-3.55	Pass
			16QAM	0.8	Pass
			64QAM	-0.83	Pass
		1	QPSK	3.47	Pass
			16QAM	4.61	Pass
			64QAM	2.62	Pass
		2	QPSK	-1.59	Pass
			16QAM	2.4	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-4.07	Pass
		3	QPSK	-1.47	Pass
			16QAM	2.47	Pass
			64QAM	-4.23	Pass
0	-48	0	QPSK	-4.83	Pass
			16QAM	-0.41	Pass
			64QAM	4.06	Pass
		1	QPSK	2.21	Pass
			16QAM	-0.54	Pass
			64QAM	-4.5	Pass
		2	QPSK	1.67	Pass
			16QAM	3.59	Pass
			64QAM	3.04	Pass
		3	QPSK	-2.74	Pass
			16QAM	1.63	Pass
			64QAM	-2.63	Pass
10	-48	0	QPSK	4.93	Pass
			16QAM	-2.88	Pass
			64QAM	4.35	Pass
		1	QPSK	-4.93	Pass
			16QAM	3.59	Pass
			64QAM	1.59	Pass
		2	QPSK	-4.88	Pass
			16QAM	-5	Pass
			64QAM	-4.5	Pass
		3	QPSK	-0.5	Pass
			16QAM	0.67	Pass
			64QAM	3.59	Pass
20	-48	0	QPSK	2.15	Pass
			16QAM	3	Pass
			64QAM	-0.75	Pass
		1	QPSK	3.4	Pass
			16QAM	-4.69	Pass
			64QAM	-3.71	Pass

ZTE Corporation

FCC ID: Q78-R8984ES5100

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）					
Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
		2	QPSK	-3.61	Pass
			16QAM	0.04	Pass
			64QAM	-1.35	Pass
		3	QPSK	-0.05	Pass
			16QAM	-3.55	Pass
			64QAM	2.73	Pass
30	-48	0	QPSK	4.61	Pass
			16QAM	1.1	Pass
			64QAM	-2.97	Pass
		1	QPSK	4.39	Pass
			16QAM	4.9	Pass
			64QAM	-4.07	Pass
		2	QPSK	2.77	Pass
			16QAM	-4.12	Pass
			64QAM	4.85	Pass
		3	QPSK	-3.36	Pass
			16QAM	-0.72	Pass
			64QAM	1.76	Pass
40	-48	0	QPSK	-3.72	Pass
			16QAM	2.36	Pass
			64QAM	-4.1	Pass
		1	QPSK	4.73	Pass
			16QAM	1.57	Pass
			64QAM	0.75	Pass
		2	QPSK	1.26	Pass
			16QAM	4.04	Pass
			64QAM	4.51	Pass
		3	QPSK	2.29	Pass
			16QAM	1.33	Pass
			64QAM	-3.93	Pass
50	-48	0	QPSK	1.72	Pass
			16QAM	-4.94	Pass
			64QAM	-2.99	Pass
		1	QPSK	0.11	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）					
Temperature (℃)	Power Supplied (V$_{DC)}$	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	-0.91	Pass
			64QAM	-4.72	Pass
		2	QPSK	-2.17	Pass
			16QAM	3.09	Pass
			64QAM	2.48	Pass
		3	QPSK	-4.35	Pass
			16QAM	2.23	Pass
			64QAM	-1.34	Pass
55	-48	0	QPSK	3.86	Pass
			16QAM	-3.63	Pass
			64QAM	-4.18	Pass
		1	QPSK	-3.05	Pass
			16QAM	-3.57	Pass
			64QAM	4.16	Pass
		2	QPSK	-4.11	Pass
			16QAM	-4.8	Pass
			64QAM	-4.89	Pass
		3	QPSK	-3.26	Pass
			16QAM	3.89	Pass
			64QAM	-2.59	Pass

Frequency Stability vs. Temperature （Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz）					
Temperature (℃)	Power Supplied (V$_{DC)}$	Port	Modulation	Frequency Measure Error (Hz)	Result
-40	-48	0	QPSK	-2.72	Pass
			16QAM	1.37	Pass
			64QAM	1.71	Pass
		1	QPSK	-0.97	Pass
			16QAM	-4.59	Pass
			64QAM	0.49	Pass
		2	QPSK	1.75	Pass
			16QAM	0.64	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz**）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-0.24	Pass
		3	QPSK	-3.51	Pass
			16QAM	0.55	Pass
			64QAM	-1.54	Pass
-30	-48	0	QPSK	-3.17	Pass
			16QAM	-0.03	Pass
			64QAM	0.17	Pass
		1	QPSK	3.93	Pass
			16QAM	0.58	Pass
			64QAM	-4.22	Pass
		2	QPSK	-3.4	Pass
			16QAM	2.87	Pass
			64QAM	4.27	Pass
		3	QPSK	2.41	Pass
			16QAM	-3.4	Pass
			64QAM	-4.95	Pass
-20	-48	0	QPSK	0.13	Pass
			16QAM	3.69	Pass
			64QAM	-2.89	Pass
		1	QPSK	1.23	Pass
			16QAM	3.9	Pass
			64QAM	3.43	Pass
		2	QPSK	-1	Pass
			16QAM	2.12	Pass
			64QAM	4.31	Pass
		3	QPSK	-3.61	Pass
			16QAM	-0.74	Pass
			64QAM	-0.45	Pass
-10	-48	0	QPSK	-3.73	Pass
			16QAM	1.07	Pass
			64QAM	-1.65	Pass
		1	QPSK	-4.83	Pass
			16QAM	-2.49	Pass
			64QAM	0.62	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz**）

Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
		2	QPSK	-1	Pass
			16QAM	2.21	Pass
			64QAM	2.29	Pass
		3	QPSK	2.21	Pass
			16QAM	4.23	Pass
			64QAM	-1.08	Pass
0	-48	0	QPSK	-2.87	Pass
			16QAM	4.57	Pass
			64QAM	2.14	Pass
		1	QPSK	3.83	Pass
			16QAM	3.34	Pass
			64QAM	3.43	Pass
		2	QPSK	2.7	Pass
			16QAM	4.59	Pass
			64QAM	-0.44	Pass
		3	QPSK	3.57	Pass
			16QAM	-0.87	Pass
			64QAM	3.24	Pass
10	-48	0	QPSK	3.09	Pass
			16QAM	0.4	Pass
			64QAM	-1.95	Pass
		1	QPSK	-4.15	Pass
			16QAM	-2.72	Pass
			64QAM	4.46	Pass
		2	QPSK	-3.65	Pass
			16QAM	-4.54	Pass
			64QAM	-3.53	Pass
		3	QPSK	3.28	Pass
			16QAM	-2.89	Pass
			64QAM	-0.62	Pass
20	-48	0	QPSK	-2.21	Pass
			16QAM	4.7	Pass
			64QAM	2.34	Pass
		1	QPSK	-2	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	4.98	Pass
			64QAM	3.41	Pass
		2	QPSK	-0.81	Pass
			16QAM	-4.88	Pass
			64QAM	-2.99	Pass
		3	QPSK	-2.27	Pass
			16QAM	-4.36	Pass
			64QAM	-3.95	Pass
30	-48	0	QPSK	1.57	Pass
			16QAM	-0.25	Pass
			64QAM	2.95	Pass
		1	QPSK	-3.71	Pass
			16QAM	-2.03	Pass
			64QAM	1.61	Pass
		2	QPSK	1.64	Pass
			16QAM	1.47	Pass
			64QAM	3.8	Pass
		3	QPSK	-1.38	Pass
			16QAM	2.71	Pass
			64QAM	1.25	Pass
40	-48	0	QPSK	-2.78	Pass
			16QAM	-1.49	Pass
			64QAM	2.89	Pass
		1	QPSK	-0.31	Pass
			16QAM	-3.86	Pass
			64QAM	1.32	Pass
		2	QPSK	4.82	Pass
			16QAM	4.59	Pass
			64QAM	4.47	Pass
		3	QPSK	4.38	Pass
			16QAM	3.83	Pass
			64QAM	-2.35	Pass
50	-48	0	QPSK	-0.49	Pass
			16QAM	-0.26	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	3.56	Pass
		1	QPSK	-1.18	Pass
			16QAM	-4.88	Pass
			64QAM	0.34	Pass
		2	QPSK	0	Pass
			16QAM	-0.71	Pass
			64QAM	-2.17	Pass
		3	QPSK	-1.42	Pass
			16QAM	1.62	Pass
			64QAM	4.33	Pass
		0	QPSK	-1.28	Pass
			16QAM	3.31	Pass
			64QAM	1.39	Pass
		1	QPSK	-4.55	Pass
			16QAM	2.24	Pass
			64QAM	-0.68	Pass
55	-48	2	QPSK	2.62	Pass
			16QAM	-2.57	Pass
			64QAM	-4.85	Pass
		3	QPSK	-2.17	Pass
			16QAM	-0.67	Pass
			64QAM	-2	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
		0	QPSK	1.98	Pass
			16QAM	-1.31	Pass
			64QAM	3.97	Pass
-40	-48	1	QPSK	-2.38	Pass
			16QAM	-2.03	Pass
			64QAM	4.7	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
		2	QPSK	4.31	Pass
			16QAM	4.67	Pass
			64QAM	-3.96	Pass
		3	QPSK	2.38	Pass
			16QAM	0.3	Pass
			64QAM	2.83	Pass
-30	-48	0	QPSK	4.79	Pass
			16QAM	3.25	Pass
			64QAM	-2.23	Pass
		1	QPSK	-0.95	Pass
			16QAM	-2.98	Pass
			64QAM	4.53	Pass
		2	QPSK	-1.52	Pass
			16QAM	3.49	Pass
			64QAM	-4.28	Pass
		3	QPSK	1.25	Pass
			16QAM	-3.33	Pass
			64QAM	1.05	Pass
-20	-48	0	QPSK	-4.01	Pass
			16QAM	2.26	Pass
			64QAM	-2.01	Pass
		1	QPSK	3.67	Pass
			16QAM	1.3	Pass
			64QAM	1.46	Pass
		2	QPSK	-0.85	Pass
			16QAM	-2.26	Pass
			64QAM	-1.9	Pass
		3	QPSK	4.22	Pass
			16QAM	-1.51	Pass
			64QAM	-2.55	Pass
-10	-48	0	QPSK	-4.78	Pass
			16QAM	-0.2	Pass
			64QAM	3.45	Pass
		1	QPSK	-2.83	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz**）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	-0.98	Pass
			64QAM	4.08	Pass
		2	QPSK	0.25	Pass
		2	16QAM	-0.29	Pass
		2	64QAM	-0.14	Pass
		3	QPSK	2.57	Pass
		3	16QAM	1.02	Pass
		3	64QAM	4.56	Pass
0	-48	0	QPSK	-4.49	Pass
		0	16QAM	-4.36	Pass
		0	64QAM	1.6	Pass
		1	QPSK	2.14	Pass
		1	16QAM	0.55	Pass
		1	64QAM	4.88	Pass
		2	QPSK	0.82	Pass
		2	16QAM	3.51	Pass
		2	64QAM	-3.74	Pass
		3	QPSK	-1.7	Pass
		3	16QAM	4.32	Pass
		3	64QAM	4.14	Pass
10	-48	0	QPSK	-3.53	Pass
		0	16QAM	-0.73	Pass
		0	64QAM	4.57	Pass
		1	QPSK	-2.23	Pass
		1	16QAM	-0.87	Pass
		1	64QAM	-3.91	Pass
		2	QPSK	4.36	Pass
		2	16QAM	-4.32	Pass
		2	64QAM	-2.11	Pass
		3	QPSK	-3.23	Pass
		3	16QAM	1.66	Pass
		3	64QAM	0.41	Pass
20	-48	0	QPSK	2.04	Pass
		0	16QAM	-1.14	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz**）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-1.53	Pass
		1	QPSK	2.28	Pass
		1	16QAM	0.13	Pass
		1	64QAM	-1.92	Pass
		2	QPSK	-0.08	Pass
		2	16QAM	-1.26	Pass
		2	64QAM	0.58	Pass
		3	QPSK	-2.14	Pass
		3	16QAM	-4.78	Pass
		3	64QAM	-1.91	Pass
30	-48	0	QPSK	-1.26	Pass
		0	16QAM	0.05	Pass
		0	64QAM	1.15	Pass
		1	QPSK	-3.52	Pass
		1	16QAM	3.89	Pass
		1	64QAM	-4.93	Pass
		2	QPSK	1.86	Pass
		2	16QAM	-4.03	Pass
		2	64QAM	-2.51	Pass
		3	QPSK	-4.01	Pass
		3	16QAM	-1.37	Pass
		3	64QAM	-4.23	Pass
40	-48	0	QPSK	-0.5	Pass
		0	16QAM	3.61	Pass
		0	64QAM	-2.4	Pass
		1	QPSK	-2.24	Pass
		1	16QAM	-4.96	Pass
		1	64QAM	-0.41	Pass
		2	QPSK	4.66	Pass
		2	16QAM	4.99	Pass
		2	64QAM	-0.76	Pass
		3	QPSK	0.75	Pass
		3	16QAM	-3.82	Pass
		3	64QAM	-4.41	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
50	-48	0	QPSK	-1.19	Pass
			16QAM	-2.41	Pass
			64QAM	4.79	Pass
		1	QPSK	-3.36	Pass
			16QAM	-5	Pass
			64QAM	-0.03	Pass
		2	QPSK	-0.75	Pass
			16QAM	4.72	Pass
			64QAM	4.71	Pass
		3	QPSK	0.15	Pass
			16QAM	-4.42	Pass
			64QAM	-1.52	Pass
55	-48	0	QPSK	2.98	Pass
			16QAM	1.74	Pass
			64QAM	2.41	Pass
		1	QPSK	3.4	Pass
			16QAM	-0.77	Pass
			64QAM	3.73	Pass
		2	QPSK	-2.8	Pass
			16QAM	1.11	Pass
			64QAM	-0.93	Pass
		3	QPSK	-1.88	Pass
			16QAM	2.82	Pass
			64QAM	2.85	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
-40	-48	0	QPSK	-4.68	Pass
			16QAM	-4.45	Pass
			64QAM	-2.95	Pass
		1	QPSK	-0.97	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	4.8	Pass
			64QAM	4.11	Pass
		2	QPSK	-1.74	Pass
		2	16QAM	3.57	Pass
		2	64QAM	4.98	Pass
		3	QPSK	1.51	Pass
		3	16QAM	3.6	Pass
		3	64QAM	-4.59	Pass
-30	-48	0	QPSK	-2.6	Pass
		0	16QAM	-2.53	Pass
		0	64QAM	3.34	Pass
		1	QPSK	-2.38	Pass
		1	16QAM	-4.97	Pass
		1	64QAM	-1.49	Pass
		2	QPSK	3.1	Pass
		2	16QAM	-3.28	Pass
		2	64QAM	0.08	Pass
		3	QPSK	-1.21	Pass
		3	16QAM	3.53	Pass
		3	64QAM	3.09	Pass
-20	-48	0	QPSK	-4.49	Pass
		0	16QAM	3.93	Pass
		0	64QAM	3.6	Pass
		1	QPSK	-3.94	Pass
		1	16QAM	4.84	Pass
		1	64QAM	-1.74	Pass
		2	QPSK	-4.88	Pass
		2	16QAM	4.48	Pass
		2	64QAM	-3.33	Pass
		3	QPSK	-1.08	Pass
		3	16QAM	-1.96	Pass
		3	64QAM	1.94	Pass
-10	-48	0	QPSK	-0.21	Pass
		0	16QAM	-0.02	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-1.07	Pass
		1	QPSK	0.1	Pass
		1	16QAM	2.18	Pass
		1	64QAM	3.32	Pass
		2	QPSK	4.23	Pass
		2	16QAM	1.04	Pass
		2	64QAM	1.54	Pass
		3	QPSK	-1.36	Pass
		3	16QAM	3.91	Pass
		3	64QAM	4.02	Pass
0	-48	0	QPSK	0.76	Pass
		0	16QAM	-1.51	Pass
		0	64QAM	3.14	Pass
		1	QPSK	2.6	Pass
		1	16QAM	-3.5	Pass
		1	64QAM	2.25	Pass
		2	QPSK	-2.67	Pass
		2	16QAM	1.71	Pass
		2	64QAM	1.81	Pass
		3	QPSK	1.85	Pass
		3	16QAM	-0.49	Pass
		3	64QAM	-2.77	Pass
10	-48	0	QPSK	3.98	Pass
		0	16QAM	-0.76	Pass
		0	64QAM	4.54	Pass
		1	QPSK	4.91	Pass
		1	16QAM	2.36	Pass
		1	64QAM	-4.22	Pass
		2	QPSK	-0.76	Pass
		2	16QAM	-1.03	Pass
		2	64QAM	3.24	Pass
		3	QPSK	1.59	Pass
		3	16QAM	-0.26	Pass
		3	64QAM	-4.39	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz**）

Temperature (℃)	Power Supplied (V$_{DC}$)	Port	Modulation	Frequency Measure Error (Hz)	Result
20	-48	0	QPSK	1.34	Pass
			16QAM	-4.77	Pass
			64QAM	-4.18	Pass
		1	QPSK	4.58	Pass
			16QAM	4.29	Pass
			64QAM	-4.7	Pass
		2	QPSK	4.68	Pass
			16QAM	-1.04	Pass
			64QAM	-2.28	Pass
		3	QPSK	0.88	Pass
			16QAM	2.84	Pass
			64QAM	0.4	Pass
30	-48	0	QPSK	-1.45	Pass
			16QAM	-4.22	Pass
			64QAM	-1.84	Pass
		1	QPSK	-2.42	Pass
			16QAM	-4.93	Pass
			64QAM	3.49	Pass
		2	QPSK	-0.42	Pass
			16QAM	4.65	Pass
			64QAM	0.33	Pass
		3	QPSK	-3.51	Pass
			16QAM	3.78	Pass
			64QAM	1.25	Pass
40	-48	0	QPSK	-1.12	Pass
			16QAM	-2.7	Pass
			64QAM	-1.65	Pass
		1	QPSK	-4.53	Pass
			16QAM	2.22	Pass
			64QAM	0.86	Pass
		2	QPSK	3.13	Pass
			16QAM	0.27	Pass
			64QAM	-3.77	Pass
		3	QPSK	-1.86	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	3.82	Pass
			64QAM	1.18	Pass
50	-48	0	QPSK	-3.36	Pass
			16QAM	-4.77	Pass
			64QAM	1.05	Pass
		1	QPSK	2.7	Pass
			16QAM	0.93	Pass
			64QAM	3.64	Pass
		2	QPSK	-3.33	Pass
			16QAM	1.02	Pass
			64QAM	-1.05	Pass
		3	QPSK	-0.52	Pass
			16QAM	1.86	Pass
			64QAM	-0.14	Pass
55	-48	0	QPSK	3.7	Pass
			16QAM	-0.03	Pass
			64QAM	3.5	Pass
		1	QPSK	3.36	Pass
			16QAM	4.78	Pass
			64QAM	-0.96	Pass
		2	QPSK	-1.44	Pass
			16QAM	-1.05	Pass
			64QAM	4.8	Pass
		3	QPSK	1.78	Pass
			16QAM	4.56	Pass
			64QAM	0.31	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
-40	-48	0	QPSK	0.97	Pass
			16QAM	3.18	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-0.45	Pass
		1	QPSK	2.56	Pass
		1	16QAM	1.09	Pass
		1	64QAM	2.14	Pass
		2	QPSK	-0.22	Pass
		2	16QAM	-4.36	Pass
		2	64QAM	2.05	Pass
		3	QPSK	3.17	Pass
		3	16QAM	4.33	Pass
		3	64QAM	-3.75	Pass
-30	-48	0	QPSK	-3.97	Pass
		0	16QAM	-4.38	Pass
		0	64QAM	4.31	Pass
		1	QPSK	4.91	Pass
		1	16QAM	-2.72	Pass
		1	64QAM	0.17	Pass
		2	QPSK	-0.97	Pass
		2	16QAM	-2.26	Pass
		2	64QAM	-3.46	Pass
		3	QPSK	-0.28	Pass
		3	16QAM	-0.1	Pass
		3	64QAM	0.07	Pass
-20	-48	0	QPSK	2.01	Pass
		0	16QAM	1.17	Pass
		0	64QAM	-0.53	Pass
		1	QPSK	-4.56	Pass
		1	16QAM	-3.07	Pass
		1	64QAM	-1.74	Pass
		2	QPSK	3.23	Pass
		2	16QAM	-2.17	Pass
		2	64QAM	-2.44	Pass
		3	QPSK	0.36	Pass
		3	16QAM	2.4	Pass
		3	64QAM	4.7	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz）

Temperature (℃)	Power Supplied (V_{DC)}	Port	Modulation	Frequency Measure Error (Hz)	Result
-10	-48	0	QPSK	-0.42	Pass
			16QAM	0.7	Pass
			64QAM	4.18	Pass
		1	QPSK	1.04	Pass
			16QAM	2.17	Pass
			64QAM	-0.2	Pass
		2	QPSK	1.96	Pass
			16QAM	-1.86	Pass
			64QAM	3.42	Pass
		3	QPSK	1.34	Pass
			16QAM	-4.43	Pass
			64QAM	-0.63	Pass
0	-48	0	QPSK	1.18	Pass
			16QAM	0.84	Pass
			64QAM	4.17	Pass
		1	QPSK	1.65	Pass
			16QAM	-0.88	Pass
			64QAM	0.32	Pass
		2	QPSK	1.04	Pass
			16QAM	2.28	Pass
			64QAM	-2.5	Pass
		3	QPSK	-2.71	Pass
			16QAM	-4.29	Pass
			64QAM	3.7	Pass
10	-48	0	QPSK	0.72	Pass
			16QAM	1.92	Pass
			64QAM	1.36	Pass
		1	QPSK	0.47	Pass
			16QAM	3.43	Pass
			64QAM	3.51	Pass
		2	QPSK	-0.16	Pass
			16QAM	-2.61	Pass
			64QAM	-2.89	Pass
		3	QPSK	3.92	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz**）

Temperature (℃)	Power Supplied (V_DC)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	1.85	Pass
			64QAM	-0.48	Pass
20	-48	0	QPSK	3.34	Pass
			16QAM	0.36	Pass
			64QAM	1.97	Pass
		1	QPSK	2.45	Pass
			16QAM	3.31	Pass
			64QAM	-2.83	Pass
		2	QPSK	1.57	Pass
			16QAM	0.38	Pass
			64QAM	-1.94	Pass
		3	QPSK	1.24	Pass
			16QAM	-3.06	Pass
			64QAM	-4.37	Pass
30	-48	0	QPSK	4.01	Pass
			16QAM	3.07	Pass
			64QAM	-4.68	Pass
		1	QPSK	1.73	Pass
			16QAM	-1.59	Pass
			64QAM	-1.62	Pass
		2	QPSK	-4.92	Pass
			16QAM	-1.43	Pass
			64QAM	-0.76	Pass
		3	QPSK	-4.08	Pass
			16QAM	-3.32	Pass
			64QAM	0.78	Pass
40	-48	0	QPSK	-0.83	Pass
			16QAM	0.75	Pass
			64QAM	-0.72	Pass
		1	QPSK	4.9	Pass
			16QAM	-2.94	Pass
			64QAM	-2.73	Pass
		2	QPSK	3.78	Pass
			16QAM	-1.49	Pass

Frequency Stability vs. Temperature （Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz）					
Temperature (℃)	**Power Supplied (V$_{DC)}$**	**Port**	**Modulation**	**Frequency Measure Error (Hz)**	**Result**
			64QAM	2.97	Pass
		3	QPSK	-4.89	Pass
			16QAM	-2.4	Pass
			64QAM	-0.14	Pass
50	-48	0	QPSK	-4.79	Pass
			16QAM	-0.55	Pass
			64QAM	1.33	Pass
		1	QPSK	4.46	Pass
			16QAM	-3.9	Pass
			64QAM	-1.35	Pass
		2	QPSK	-4.35	Pass
			16QAM	4.23	Pass
			64QAM	3.16	Pass
		3	QPSK	3.05	Pass
			16QAM	0.4	Pass
			64QAM	3.6	Pass
55	-48	0	QPSK	1.46	Pass
			16QAM	-3.76	Pass
			64QAM	-0.63	Pass
		1	QPSK	1.9	Pass
			16QAM	4.71	Pass
			64QAM	2.55	Pass
		2	QPSK	3.18	Pass
			16QAM	-2.02	Pass
			64QAM	2.8	Pass
		3	QPSK	2.19	Pass
			16QAM	2.74	Pass
			64QAM	-2.9	Pass

Frequency Stability versus Voltage

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5160MHz）

Voltage: Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result
85%	25℃	0	QPSK	-2.63	Pass
			16QAM	0.52	Pass
			64QAM	-0.68	Pass
		1	QPSK	4.28	Pass
			16QAM	4.76	Pass
			64QAM	-1.19	Pass
		2	QPSK	-0.33	Pass
			16QAM	3.27	Pass
			64QAM	-4.16	Pass
		3	QPSK	4.56	Pass
			16QAM	-0.68	Pass
			64QAM	-0.54	Pass
100%	25℃	0	QPSK	-2.87	Pass
			16QAM	-3.71	Pass
			64QAM	3.46	Pass
		1	QPSK	-0.57	Pass
			16QAM	1.76	Pass
			64QAM	4.09	Pass
		2	QPSK	-3.42	Pass
			16QAM	-3.6	Pass
			64QAM	3.51	Pass
		3	QPSK	2.25	Pass
			16QAM	-2.23	Pass
			64QAM	2.53	Pass
115%	25℃	0	QPSK	0.43	Pass
			16QAM	-2.16	Pass
			64QAM	-4.03	Pass
		1	QPSK	3.47	Pass
			16QAM	-3.12	Pass
			64QAM	0.18	Pass
		2	QPSK	-0.28	Pass
			16QAM	-2.43	Pass
			64QAM	-1.13	Pass
		3	QPSK	-2.9	Pass
			16QAM	-4.7	Pass
			64QAM	-0.18	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）					
Voltage: Ref=-48V （%）	**Temperature （℃）**	**Port**	**Modulation**	**Frequency Measure Error (Hz)**	**Result**
85%	25℃	0	QPSK	-1.58	Pass
			16QAM	1.53	Pass
			64QAM	-3.22	Pass
		1	QPSK	1.79	Pass
			16QAM	3.7	Pass
			64QAM	-4.85	Pass
		2	QPSK	-0.66	Pass
			16QAM	3.14	Pass
			64QAM	4.43	Pass
		3	QPSK	1.99	Pass
			16QAM	1.63	Pass
			64QAM	1.1	Pass
100%	25℃	0	QPSK	-4.1	Pass
			16QAM	-3.72	Pass
			64QAM	-0.41	Pass
		1	QPSK	0.1	Pass
			16QAM	4.34	Pass
			64QAM	1.87	Pass
		2	QPSK	-4.62	Pass
			16QAM	-4.69	Pass
			64QAM	1.6	Pass
		3	QPSK	-0.76	Pass
			16QAM	-2.56	Pass
			64QAM	-1.45	Pass
115%	25℃	0	QPSK	3.28	Pass
			16QAM	-3.04	Pass
			64QAM	2.66	Pass
		1	QPSK	0.09	Pass
			16QAM	-0.72	Pass
			64QAM	-1.64	Pass
		2	QPSK	2.77	Pass
			16QAM	-4.25	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5200MHz）

Voltage： Ref=-48V （%）	Temperature （℃）	Port	Modulation	Frequency Measure Error （Hz）	Result
			64QAM	-2.69	Pass
		3	QPSK	-1.86	Pass
			16QAM	-4.11	Pass
			64QAM	-0.16	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）

Voltage： Ref=-48V （%）	Temperature （℃）	Port	Modulation	Frequency Measure Error （Hz）	Result
85%	25℃	0	QPSK	2.24	Pass
			16QAM	-4.37	Pass
			64QAM	-3.43	Pass
		1	QPSK	-1.28	Pass
			16QAM	-2.01	Pass
			64QAM	-4.77	Pass
		2	QPSK	2.23	Pass
			16QAM	3.67	Pass
			64QAM	1.4	Pass
		3	QPSK	0.65	Pass
			16QAM	-1.49	Pass
			64QAM	4.71	Pass
100%	25℃	0	QPSK	-2.14	Pass
			16QAM	-3.64	Pass
			64QAM	4.23	Pass
		1	QPSK	2.87	Pass
			16QAM	-3.59	Pass
			64QAM	1.22	Pass
		2	QPSK	1.81	Pass
			16QAM	-1.18	Pass
			64QAM	-3.93	Pass
		3	QPSK	-2.04	Pass
			16QAM	-3.18	Pass
			64QAM	-2.38	Pass

Frequency Stability vs. Temperature（Channel Bandwidth:20M Frequency :5240MHz）

Voltage： Ref=-48V （%）	Temperature （℃）	Port	Modulation	Frequency Measure Error (Hz)	Result
115%	25℃	0	QPSK	-2.05	Pass
			16QAM	1.89	Pass
			64QAM	-0.6	Pass
		1	QPSK	0.58	Pass
			16QAM	1.98	Pass
			64QAM	-4.97	Pass
		2	QPSK	1.27	Pass
			16QAM	-3.01	Pass
			64QAM	2.4	Pass
		3	QPSK	-4.3	Pass
			16QAM	-2.02	Pass
			64QAM	1.58	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz）

Voltage： Ref=-48V （%）	Temperature （℃）	Port	Modulation	Frequency Measure Error (Hz)	Result
85%	25℃	0	QPSK	-2.74	Pass
			16QAM	3.81	Pass
			64QAM	3.85	Pass
		1	QPSK	4.33	Pass
			16QAM	2.32	Pass
			64QAM	-0.32	Pass
		2	QPSK	-2.37	Pass
			16QAM	4.95	Pass
			64QAM	2.48	Pass
		3	QPSK	1.91	Pass
			16QAM	-1.82	Pass
			64QAM	-0.35	Pass
100%	25℃	0	QPSK	-2.48	Pass
			16QAM	-0.55	Pass
			64QAM	-4.97	Pass
		1	QPSK	2.81	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5160+5180+5200+5220MHz）

Voltage： Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	-1.71	Pass
			64QAM	1.63	Pass
		2	QPSK	-1.75	Pass
			16QAM	-4.77	Pass
			64QAM	2.82	Pass
		3	QPSK	2.47	Pass
			16QAM	1.9	Pass
			64QAM	1.28	Pass
115%	25℃	0	QPSK	-1.08	Pass
			16QAM	2.44	Pass
			64QAM	-0.02	Pass
		1	QPSK	2.77	Pass
			16QAM	0.56	Pass
			64QAM	-2.01	Pass
		2	QPSK	3.27	Pass
			16QAM	-3.23	Pass
			64QAM	-4.47	Pass
		3	QPSK	-4.18	Pass
			16QAM	-4.15	Pass
			64QAM	2.01	Pass

Frequency Stability vs. Temperature
（Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz）

Voltage： Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result
85%	25℃	0	QPSK	-1.28	Pass
			16QAM	-5	Pass
			64QAM	-2.43	Pass
		1	QPSK	-0.98	Pass
			16QAM	3.14	Pass
			64QAM	-0.12	Pass
		2	QPSK	0.36	Pass
			16QAM	-0.62	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5170+5190+5210+5230MHz**）

Voltage： Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result
			64QAM	-4.94	Pass
		3	QPSK	-0.13	Pass
			16QAM	-2.44	Pass
			64QAM	-4.1	Pass
100%	25℃	0	QPSK	4.51	Pass
			16QAM	2.29	Pass
			64QAM	-4.62	Pass
		1	QPSK	-4.19	Pass
			16QAM	-2.48	Pass
			64QAM	2.98	Pass
		2	QPSK	-0.43	Pass
			16QAM	3.06	Pass
			64QAM	-2.25	Pass
		3	QPSK	4.46	Pass
			16QAM	1.7	Pass
			64QAM	0.78	Pass
115%	25℃	0	QPSK	1.95	Pass
			16QAM	-3.29	Pass
			64QAM	4.97	Pass
		1	QPSK	-4.38	Pass
			16QAM	-2.42	Pass
			64QAM	4.62	Pass
		2	QPSK	4.49	Pass
			16QAM	1.82	Pass
			64QAM	3.87	Pass
		3	QPSK	-0.06	Pass
			16QAM	-0.08	Pass
			64QAM	1.9	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz**）

Voltage： Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz**）

Voltage： Ref=-48V （%）	Temperature （℃）	Port	Modulation	Frequency Measure Error （ Hz)	Result
85%	25℃	0	QPSK	-0.17	Pass
			16QAM	3.58	Pass
			64QAM	2.74	Pass
		1	QPSK	2.99	Pass
			16QAM	3.92	Pass
			64QAM	0.94	Pass
		2	QPSK	-3.88	Pass
			16QAM	2.96	Pass
			64QAM	0.61	Pass
		3	QPSK	-4.24	Pass
			16QAM	3.55	Pass
			64QAM	1.12	Pass
100%	25℃	0	QPSK	-3.94	Pass
			16QAM	-4.87	Pass
			64QAM	-0.27	Pass
		1	QPSK	-0.1	Pass
			16QAM	-4.89	Pass
			64QAM	3.1	Pass
		2	QPSK	3.8	Pass
			16QAM	-3.27	Pass
			64QAM	3.69	Pass
		3	QPSK	2.26	Pass
			16QAM	-0.46	Pass
			64QAM	3.09	Pass
115%	25℃	0	QPSK	-1.18	Pass
			16QAM	-2.48	Pass
			64QAM	0.71	Pass
		1	QPSK	-3.01	Pass
			16QAM	-0.04	Pass
			64QAM	-0.24	Pass
		2	QPSK	4.06	Pass
			16QAM	-4.3	Pass
			64QAM	2.7	Pass
		3	QPSK	2.96	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5180+5200+5220+5240MHz**）

Voltage： Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result
			16QAM	-2.88	Pass
			64QAM	-4.06	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz**）

Voltage： Ref=-48V （%）	Temperature (℃)	Port	Modulation	Frequency Measure Error (Hz)	Result
85%	25℃	0	QPSK	-4.18	Pass
			16QAM	-1.55	Pass
			64QAM	-3.45	Pass
		1	QPSK	-0.39	Pass
			16QAM	0.78	Pass
			64QAM	4.11	Pass
		2	QPSK	-1.37	Pass
			16QAM	-0.62	Pass
			64QAM	0.31	Pass
		3	QPSK	4.84	Pass
			16QAM	-1.62	Pass
			64QAM	1.7	Pass
100%	25℃	0	QPSK	0.93	Pass
			16QAM	2.01	Pass
			64QAM	-4.18	Pass
		1	QPSK	4.12	Pass
			16QAM	-2.39	Pass
			64QAM	-1.91	Pass
		2	QPSK	0.99	Pass
			16QAM	0.89	Pass
			64QAM	-2.08	Pass
		3	QPSK	2.42	Pass
			16QAM	3.37	Pass
			64QAM	1.45	Pass
115%	25℃	0	QPSK	-0.8	Pass
			16QAM	0.15	Pass

Frequency Stability vs. Temperature
（**Channel Bandwidth:4*20M Frequency :5160+5180+5220+5240MHz**）

Voltage： Ref=-48V （%）	Temperature （℃）	Port	Modulation	Frequency Measure Error （ Hz)	Result
			64QAM	3.59	Pass
		1	QPSK	1.27	Pass
			16QAM	3.35	Pass
			64QAM	2.16	Pass
		2	QPSK	-2.48	Pass
			16QAM	2.07	Pass
			64QAM	3.41	Pass
		3	QPSK	0.7	Pass
			16QAM	-4.39	Pass
			64QAM	-2.25	Pass