


FCC Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : GSM Dual-band GPRS digital mobile phone(850/1900)
BRAND NAME : ZTE
MODEL NAME : ZTE-G S610
FCC ID : Q78-S610
STANDARD : 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~1909.8 MHz /
1930.2 ~ 1989.8 MHz
MAX. ERP/EIRP POWER : GSM850 (GPRS 12) : 1.05 W
GSM1900 (GSM) : 1.07 W
EMISSION DESIGNATOR : GSM : 244KGXW

The product sample received on Apr. 28, 2009 and completely tested on Apr. 30, 2009. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Testing Site 6

 1.5 Applied Standards 7

 1.6 Ancillary Equipment List..... 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 8

3 TEST RESULT 9

 3.1 Conducted Output Power Measurement..... 9

 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 11

 3.3 Occupied Bandwidth Measurement 14

 3.4 Band Edge Measurement..... 17

 3.5 Conducted Emission Measurement 20

 3.6 Field Strength of Spurious Radiation Measurement 26

 3.7 Frequency Stability Measurement..... 32

4 LIST OF MEASURING EQUIPMENT 35

5 UNCERTAINTY OF EVALUATION 36

6 CERTIFICATION OF TAF ACCREDITATION 37

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | IC Rule | Description | Limit | Result |
|----------------|-------------------------------------|------------------------------------|---|--|--------|
| 3.1 | §2.1046 | N/A | Conducted Output Power | N/A | PASS |
| 3.2 | §22.913(a)(2) | RSS-132(4.4) SRSP-503(5.1.3) | Effective Radiated Power | < 7 Watts for FCC (<6.3 Watts for IC) | PASS |
| 3.2 | §24.232(c) | RSS-133 (6.4) SRSP-510(5.1.2) | Equivalent Isotropic Radiated Power | < 2 Watts | PASS |
| 3.3 | §2.1049 §22.917(a) §24.238(a) | N/A | Occupied Bandwidth | N/A | PASS |
| 3.4 | §2.1051 §22.917(a) §24.238(a) | RSS-132 (4.5.1) RSS-133 (6.5.1) | Band Edge Measurement | < 43+10log ₁₀ (P[Watts]) | PASS |
| 3.5 | §2.1051 §22.917(a) §24.238(a) | RSS-132 (4.5.1) RSS-133 (6.5.1) | Conducted Emission | < 43+10log ₁₀ (P[Watts]) | PASS |
| 3.6 | §2.1053 §22.917(a) §24.238(a) | RSS-132 (4.5.1) RSS-133 (6.5.1) | Field Strength of Spurious Radiation | < 43+10log ₁₀ (P[Watts]) | PASS |
| 3.7 | §2.1055 §22.355 §24.235 | RSS-132(4.3) RSS-133(6.3) | Frequency Stability for Temperature & Voltage | < 2.5 ppm | PASS |

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, P.R.China

1.3 Feature of Equipment Under Test

| Product Feature & Specification | |
|---------------------------------|---|
| Equipment | GSM Dual-band GPRS digital mobile phone(850/1900) |
| Brand Name | ZTE |
| Model Name | ZTE-G S610 |
| FCC ID | Q78-S610 |
| Tx Frequency | GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz |
| Rx Frequency | GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz |
| Maximum Output Power to Antenna | GSM850 : 32.17 dBm GSM1900 : 28.52 dBm |
| Maximum ERP/EIRP | GSM850 (GPRS 12) : 1.05 W (30.20 dBm) GSM1900 (GSM) : 1.07 W (30.29 dBm) |
| Antenna Type | Fixed Internal Antenna |
| HW Version | MB2512AMB_B |
| SW Version | S610_Z1_C1_DFFC106 |
| Type of Modulation | GMSK |
| Type of Emission | 244KGXW |
| EUT Stage | Identical Prototype |

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter Held to Ear (PCE).

List of Accessory:

| Specification of Accessory | | |
|----------------------------|--------------------|---|
| AC Adapter | Brand Name | ZTE |
| | Model Name | STC-A22O50U5-C |
| | Power Rating | I/P:100-240Vac, 50-60Hz, 200mA; O/P: 5Vdc, 700mA |
| | AC Power Cord Type | 1.3 meter non-shielded cable without ferrite core |
| Battery | Brand Name | ZTE |
| | Model Name | Li3706T42P3h383857 |
| | Power Rating | 3.7Vdc, 670mAh |
| | Type | Li-ion |
| Earphone | Brand Name | ZTE |
| | Model Name | HEC-2313102-9R |
| | Signal Line Type | 1.56 meter non-shielded cable without ferrite core |
| LCD Panel | Brand Name | BYD |
| | Model Name | 2.0" TFT LCD |
| Camera | Brand Name | SUNY |
| | Model Name | 8133J |

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For accessories equipped with this EUT, please refer to the appendix of the external photo.

1.4 Testing Site

| | | |
|--------------------|--|-----------|
| Test Site | Sporton International (Kunshan) Inc. | |
| Test Site Location | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958 | |
| Test Site No. | Sporton Site No. | |
| | TH01-KS | 03CH01-KS |



1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E)
- ANSI C63.4-2003
- ANSI / TIA / EIA-603-C-2004
- IC RSS-132 Issue 2
- IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1. | System Simulator | R&S | CMU200 | N/A | N/A | Unshielded, 1.8 m |

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:


1. 30 MHz to 9000 MHz for GSM850.
2. 30MHz to 19000 MHz for GSM1900.

| Test Modes | | |
|------------|----------------|----------------|
| Band | Radiated TCs | Conducted TCs |
| GSM 850 | ■ GPRS 12 Link | ■ GPRS 12 Link |
| GSM 1900 | ■ GSM Link | ■ GSM Link |

Note: The maximum power levels are GPRS12 mode for GSM850 and GSM mode for GSM1900, only these modes were used for all tests. The power tables are listed as follows:

| Conducted Power (dBm) | | | | | | | |
|-----------------------|--------------|---------|--------------|-------|----------|--------------|-------|
| Mode | Band Channel | GSM 850 | | | GSM 1900 | | |
| | | 128 | 189 | 251 | 512 | 661 | 810 |
| GSM | | 31.80 | 32.14 | 31.86 | 28.36 | 28.52 | 28.49 |
| GPRS 8 | | 31.82 | 31.83 | 31.90 | 28.35 | 28.51 | 28.48 |
| GPRS 10 | | 31.77 | 32.14 | 31.87 | 28.30 | 28.48 | 28.45 |
| GPRS 12 | | 31.82 | 32.17 | 31.90 | 28.25 | 28.40 | 28.33 |

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup





3.1.5 Test Result of Conducted Output Power

| Cellular Band | | | | |
|---------------|------------|-----------------|-----------------|---------|
| Modes | Channel | Frequency (MHz) | Conducted Power | |
| | | | (dBm) | (Watts) |
| GSM | 128 (Low) | 824.2 | 31.80 | 1.51 |
| | 189 (Mid) | 836.4 | 32.14 | 1.64 |
| | 251 (High) | 848.8 | 31.86 | 1.53 |
| GPRS 8 | 128 (Low) | 824.2 | 31.82 | 1.52 |
| | 189 (Mid) | 836.4 | 31.83 | 1.52 |
| | 251 (High) | 848.8 | 31.90 | 1.55 |
| GPRS 10 | 128 (Low) | 824.2 | 31.77 | 1.50 |
| | 189 (Mid) | 836.4 | 32.14 | 1.64 |
| | 251 (High) | 848.8 | 31.87 | 1.54 |
| GPRS 12 | 128 (Low) | 824.2 | 31.82 | 1.52 |
| | 189 (Mid) | 836.4 | 32.17 | 1.65 |
| | 251 (High) | 848.8 | 31.90 | 1.55 |

| PCS Band | | | | |
|----------|------------|-----------------|-----------------|---------|
| Modes | Channel | Frequency (MHz) | Conducted Power | |
| | | | (dBm) | (Watts) |
| GSM | 512 (Low) | 1850.2 | 28.36 | 0.69 |
| | 661 (Mid) | 1880.0 | 28.52 | 0.71 |
| | 810 (High) | 1909.8 | 28.49 | 0.71 |
| GPRS 8 | 512 (Low) | 1850.2 | 28.35 | 0.68 |
| | 661 (Mid) | 1880.0 | 28.51 | 0.71 |
| | 810 (High) | 1909.8 | 28.48 | 0.70 |
| GPRS 10 | 512 (Low) | 1850.2 | 28.30 | 0.68 |
| | 661 (Mid) | 1880.0 | 28.48 | 0.70 |
| | 810 (High) | 1909.8 | 28.45 | 0.70 |
| GPRS 12 | 512 (Low) | 1850.2 | 28.25 | 0.67 |
| | 661 (Mid) | 1880.0 | 28.40 | 0.69 |
| | 810 (High) | 1909.8 | 28.33 | 0.68 |

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
Ps (dBm) : Input power to substitution antenna.
Gs (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
AF (dB/m) : Receive antenna factor
Rt : The highest received signal in spectrum analyzer for EUT.
Rs : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup



3.2.5 Test Result of ERP

| GSM850 (GPRS 12) Radiated Power ERP | | | | | | |
|-------------------------------------|----------|----------|----------|----------|-----------|---------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.2 | -16.93 | -48.12 | 0.00 | -1.08 | 30.11 | 1.03 |
| 836.4 | -17.15 | -48.28 | 0.00 | -0.93 | 30.20 | 1.05 |
| 848.8 | -18.33 | -48.35 | 0.00 | -0.76 | 29.26 | 0.84 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | ERP (W) |
| 824.2 | -32.85 | -47.97 | 0.00 | -1.08 | 14.04 | 0.03 |
| 836.4 | -32.76 | -48.01 | 0.00 | -0.93 | 14.32 | 0.03 |
| 848.8 | -33.50 | -48.05 | 0.00 | -0.76 | 13.79 | 0.02 |



3.2.6 Test Result of EIRP

| GSM1900 (GSM) Radiated Power EIRP | | | | | | |
|-----------------------------------|----------|----------|----------|----------|------------|----------|
| Horizontal Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -25.64 | -51.88 | 0.00 | 1.96 | 28.20 | 0.66 |
| 1880.0 | -25.66 | -52.99 | 0.00 | 2.00 | 29.33 | 0.86 |
| 1909.8 | -25.97 | -54.28 | 0.00 | 1.98 | 30.29 | 1.07 |
| Vertical Polarization | | | | | | |
| Frequency (MHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBi) | EIRP (dBm) | EIRP (W) |
| 1850.2 | -28.36 | -52.13 | 0.00 | 1.96 | 25.73 | 0.37 |
| 1880.0 | -27.91 | -53.17 | 0.00 | 2.00 | 27.26 | 0.53 |
| 1909.8 | -27.62 | -54.13 | 0.00 | 1.98 | 28.49 | 0.71 |

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.
3. The RBW was replaced by 10 kHz, due to the spectrum analyzer IF-Filter including an excess of the limit. A worst case correction factor of $10 \log (1\% \text{ BW}/\text{measurement RBW})$ was implemented.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


| | | | |
|-------------|--------------|---------------|------|
| Band : | GSM 850 | Power Stage : | High |
| Test Mode : | GPRS 12 Link | | |

99% Occupied Bandwidth Plot on Channel 189



Date: 30.APR.2009 03:07:46

26dB Bandwidth Plot on Channel 189




Date: 30.APR.2009 02:50:22




| | | | |
|--------------------|----------|----------------------|------|
| Band : | GSM 1900 | Power Stage : | High |
| Test Mode : | GSM Link | | |

99% Occupied Bandwidth Plot on Channel 661



Date: 30.APR.2009 04:02:40

26dB Bandwidth Plot on Channel 661



Date: 30.APR.2009 03:42:35

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.

3.4.4 Test Setup






3.4.5 Test Result (Plots) of Conducted Band Edge


| | | | |
|-------------|--------------|---------------|------|
| Band : | GSM850 | Power Stage : | High |
| Test Mode : | GPRS 12 Link | | |

Lower Band Edge Plot on Channel 128



Date: 30.APR.2009 02:55:20

Higher Band Edge Plot on Channel 251




Date: 30.APR.2009 02:57:01




| | | | |
|-------------|----------|---------------|------|
| Band : | GSM1900 | Power Stage : | High |
| Test Mode : | GSM Link | | |

Lower Band Edge Plot on Channel 512



Date: 30.APR.2009 03:49:58

Higher Band Edge Plot on Channel 810



Date: 30.APR.2009 03:52:09

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Emission


| | | | |
|-------------|--------------|-----------|-------|
| Band : | GSM850 | Channel : | CH189 |
| Test Mode : | GPRS 12 Link | | |

Conducted Emission Plot between 30M ~ 1GHz



Date: 30.APR.2009 03:26:32


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 30.APR.2009 03:29:33




Conducted Emission Plot between 3GHz ~ 7GHz



Date : 30.APR.2009 03:32:44

Conducted Emission Plot between 7GHz ~ 9GHz




Date : 30.APR.2009 03:34:17




| | | | |
|--------------------|----------|------------------|-------|
| Band : | GSM1900 | Channel : | CH661 |
| Test Mode : | GSM Link | | |

Conducted Emission Plot between 30M ~ 1GHz



Date: 30.APR.2009 04:13:56


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 30.APR.2009 04:16:15




Conducted Emission Plot between 3G ~ 7GHz



Date : 30.APR.2009 04:19:21


Conducted Emission Plot between 7G ~ 13.6G



Date : 30.APR.2009 04:23:29



Conducted Emission Plot between 13.6GH ~ 19.1GHz



Date: 30.APR.2009 04:24:46

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. Emission level (dBm) = output power + substitution Gain.


3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated

| | | | |
|-----------------|--|---------------------|------------|
| Band : | GSM850 | Temperature : | 22~23°C |
| Test Mode : | GPRS 12 | Relative Humidity : | 42~43% |
| Test Engineer : | Peter Qiu | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1672 | -33.88 | -13 | -20.88 | -41.68 | -37.09 | 0.69 | 6.05 | H | Pass |
| 2510 | -43.15 | -13 | -30.15 | -51.56 | -45.95 | 0.82 | 5.77 | H | Pass |
| 3344 | -44.14 | -13 | -31.14 | -55.08 | -48.80 | 0.99 | 7.80 | H | Pass |
| 7528 | -40.84 | -13 | -27.84 | -58.94 | -49.49 | 1.31 | 12.11 | H | Pass |



| | | | |
|-----------------|--|---------------------|----------|
| Band : | GSM850 | Temperature : | 22~23°C |
| Test Mode : | GPRS 12 | Relative Humidity : | 42~43% |
| Test Engineer : | Peter Qiu | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-K5
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

| Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|-------------------|-------------|---------------|-------------------|---------------------|--------------------|----------------------|-------------------------|----------------------|--------|
| 1674 | -32.03 | -13 | -19.03 | -39.83 | -35.24 | 0.69 | 6.05 | V | Pass |
| 2510 | -42.88 | -13 | -29.88 | -51.29 | -45.68 | 0.82 | 5.77 | V | Pass |
| 3344 | -50.80 | -13 | -37.80 | -61.74 | -55.46 | 0.99 | 7.80 | V | Pass |
| 4182 | -46.61 | -13 | -33.61 | -59.70 | -52.14 | 1.08 | 8.76 | V | Pass |
| 7528 | -41.24 | -13 | -28.24 | -59.34 | -49.89 | 1.31 | 12.11 | V | Pass |



| | | | |
|-----------------|--|---------------------|------------|
| Band : | GSM1900 | Temperature : | 22~23°C |
| Test Mode : | GSM | Relative Humidity : | 42~43% |
| Test Engineer : | Peter Qiu | Polarization : | Horizontal |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |




Site : 03CH01-K5
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 3760 | -41.78 | -13 | -28.78 | -55.49 | -49.71 | 0.11 | 8.04 | H | Pass |



| | | | |
|------------------------|--|----------------------------|----------|
| Band : | GSM1900 | Temperature : | 22~23°C |
| Test Mode : | GSM | Relative Humidity : | 42~43% |
| Test Engineer : | Peter Qiu | Polarization : | Vertical |
| Remark : | Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | |



Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

| Frequency (MHz) | EIRP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) | Result |
|----------------------|-----------------|------------------|-------------------------|---------------------------|--------------------------|----------------------------|-------------------------------|-------------------------|--------|
| 3760 | -33.47 | -13 | -20.47 | -47.18 | -41.40 | 0.11 | 8.04 | V | Pass |

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup





3.7.6 Test Result of Temperature Variation

| | | | |
|---------------|---------|-----------|-----|
| Band : | GSM 850 | Channel : | 189 |
| Limit (ppm) : | 2.5 | | |

| Temperature (°C) | GPRS 12 | | Result |
|------------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | 26 | 0.03 | PASS |
| -20 | 30 | 0.04 | |
| -10 | 27 | 0.03 | |
| 0 | -21 | -0.02 | |
| 10 | 25 | 0.03 | |
| 20 | 26 | 0.03 | |
| 30 | 23 | 0.03 | |
| 40 | -23 | -0.03 | |
| 50 | 27 | 0.03 | |

| | | | |
|---------------|----------|-----------|-----|
| Band : | GSM 1900 | Channel : | 661 |
| Limit (ppm) : | 2.5 | | |

| Temperature (°C) | GSM | | Result |
|------------------|-----------------|-----------------|--------|
| | Freq. Dev. (Hz) | Deviation (ppm) | |
| -30 | -58 | -0.03 | PASS |
| -20 | -62 | -0.03 | |
| -10 | -59 | -0.03 | |
| 0 | -93 | -0.05 | |
| 10 | -92 | -0.05 | |
| 20 | -27 | -0.01 | |
| 30 | -34 | -0.02 | |
| 40 | -33 | -0.02 | |
| 50 | -32 | -0.02 | |

3.7.7 Test Result of Voltage Variation

| Band & Channel | Mode | Voltage (Volt) | Freq. Dev. (Hz) | Deviation (ppm) | Limit (ppm) | Result |
|-------------------|---------|----------------|-----------------|-----------------|-------------|--------|
| GSM 850 CH189 | GPRS 12 | 3.7 | 20.0 | 0.02 | 2.5 | PASS |
| | | BEP | 26.0 | 0.03 | | |
| | | 4.2 | 19.0 | 0.02 | | |
| GSM 1900 CH661 | GSM | 3.7 | -32.0 | -0.02 | | |
| | | BEP | -36.0 | -0.02 | | |
| | | 4.2 | -37.0 | -0.02 | | |

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.



4 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Due Date | Remark |
|---------------------------|--------------|-----------|------------|-----------------|------------------|---------------|-----------------------|
| Spectrum Analyzer | R&S | FSP40 | 100319 | 9kHz~40GHz | Dec. 08, 2008 | Dec. 07, 2009 | Conducted (TH01-KS) |
| Power Meter | Agilent | E4416A | MY45101555 | N/A | Jun. 18, 2007 | Jun. 17, 2009 | Conducted (TH01-KS) |
| Power Sensor | Agilent | E9327A | MY44421198 | N/A | Jun. 12, 2007 | Jun. 11, 2009 | Conducted (TH01-KS) |
| Thermal Chamber | Ten Billion | TTC-B3S | TBN-930701 | N/A | Dec. 15, 2008 | Dec. 14, 2009 | Conducted (TH01-KS) |
| DC Power Supply | TOPWARD | 3306D | N/A | N/A | N/A | N/A | Conducted (TH01-KS) |
| Spectrum Analyzer | R&S | ESCI | 100534 | 9kHz – 2.75GHz | Dec. 08, 2008 | Dec. 07, 2009 | Radiation (03CH01-KS) |
| Spectrum Analyzer | R&S | FSP40 | 100319 | 9kHz~40GHz | Dec. 08, 2008 | Dec. 07, 2009 | Radiation (03CH01-KS) |
| Bilog Antenna | SCHAFFNER | CBL6112D | 23182 | 25MHz~2GHz | Dec. 17, 2008 | Dec. 16, 2009 | Radiation (03CH01-KS) |
| Double Ridge Horn Antenna | EMCO | 3117 | 75959 | 1GHz~18GHz | Dec. 17, 2008 | Dec. 16, 2009 | Radiation (03CH01-KS) |
| Amplifier | Wireless | FPA6592G | 600006 | 30MHz~2GHz | Dec. 17, 2008 | Dec. 16, 2009 | Radiation (03CH01-KS) |
| Amplifier | Agilent | 8449B | 3008A02370 | 1GHz~26.5GHz | Dec. 17, 2008 | Dec. 16, 2009 | Radiation (03CH01-KS) |
| Signal Generator | R&S | SMR40 | 100455 | 10MHz~40GHz | Aug. 29, 2007 | Aug. 28, 2009 | Radiation (03CH01-KS) |
| System Simulator | R&S | CMU200 | 837587/066 | Full-Band/BT | Jan. 08, 2009 | Jan. 07, 2011 | Radiation (03CH01-KS) |

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| Contribution | Uncertainty of x_i | | $u(x_i)$ |
|--|----------------------|--------------------------|----------|
| | dB | Probability Distribution | |
| Receiver reading | 0.41 | Normal(k=2) | 0.21 |
| Antenna factor calibration | 0.83 | Normal(k=2) | 0.42 |
| Cable loss calibration | 0.25 | Normal(k=2) | 0.13 |
| Pre Amplifier Gain calibration | 0.27 | Normal(k=2) | 0.14 |
| RCV/SPA specification | 2.50 | Rectangular | 0.72 |
| Antenna Factor Interpolation for Frequency | 1.00 | Rectangular | 0.29 |
| Site imperfection | 1.43 | Rectangular | 0.83 |
| Mismatch | +0.39/-0.41 | U-shaped | 0.28 |
| Combined standard uncertainty Uc(y) | 1.27 | | |
| Measuring uncertainty for a level of confidence of 95% U=2Uc(y) | 2.54 | | |

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

| Contribution | Uncertainty of x_i | | $u(x_i)$ | C_i | $C_i * u(x_i)$ |
|---|----------------------|--------------------------|----------|-------|----------------|
| | dB | Probability Distribution | | | |
| Receiver reading | ±0.10 | Normal(k=1) | 0.10 | 1 | 0.10 |
| Antenna factor calibration | ±1.70 | Normal(k=2) | 0.85 | 1 | 0.85 |
| Cable loss calibration | ±0.50 | Normal(k=2) | 0.25 | 1 | 0.25 |
| Receiver Correction | ±2.00 | Rectangular | 1.15 | 1 | 1.15 |
| Antenna Factor Directional | ±1.50 | Rectangular | 0.87 | 1 | 0.87 |
| Site imperfection | ±2.80 | Triangular | 1.14 | 1 | 1.14 |
| Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2)$ | +0.34/-0.35 | U-shaped | 0.244 | 1 | 0.244 |
| Combined standard uncertainty Uc(y) | 2.36 | | | | |
| Measuring uncertainty for a level of confidence of 95% U=2Uc(y) | 4.72 | | | | |

6 Certification of TAF Accreditation



Certificate No. : L1190-090417

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

| | |
|---------------------------------------|--|
| Accreditation Criteria | : ISO/IEC 17025:2005 |
| Accreditation Number | : 1190 |
| Originally Accredited | : December 15, 2003 |
| Effective Period | : January 10, 2007 to January 09, 2010 |
| Accredited Scope | : Testing Field, see described in the Appendix |
| Specific Accreditation Program | : Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities |

Jay-san Chen

Jay-San Chen
President, Taiwan Accreditation Foundation
Date : April 17, 2009

P1, total 20 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



Appendix A. Photographs of EUT

Please refer to Sporton report number EP942809 as below.