



TEST REPORT

No. 2011TAR116

for

ZTE Corporation

Tablet Computer

Model Name: ZTE-V9

FCC ID: Q78-V9

with

Hardware Version: d23B

Software Version: VIVO_V9V1.0.0B01

Issued Date: 2011-03-25

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DAT-P-114/01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

Shouxiang Science Building, No 51, Xueyuan Road, Haidian District, Beijing, P.R.China 100191

Tel:+86(0)10-62304633-2678, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT.....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS.....	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS	11
A.1 OUTPUT POWER (§22.913(A)/§24.232(B)).....	11
A.2 EMISSION LIMIT (§2.1051/§22.917§24.238).....	15
A.3 CONDUCTED EMISSION (§15.107§15.207)	20
A.4 FREQUENCY STABILITY (§2.1055/§24.235)	25
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I)).....	27
A.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B)).....	31
A.7 BAND EDGE COMPLIANCE (§22.917(B)/§24.238(B))	35
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)	37

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: Shouxiang Science Building, No 51, Xueyuan Road, Haidian District,
Beijing, P.R.China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2011-03-03
Testing End Date: 2011-03-25

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, 518057, P.R.China
City: Shenzhen
Country: China
Telephone: 0086 21 68897541
Fax: 0086 21 50801070

2.2. Manufacturer Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, 518057, P.R.China
City: Shenzhen
Country: China
Telephone: 0086 21 68897541
Fax: 0086 21 50801070

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Tablet Computer
Model Name	ZTE-V9
FCC ID	Q78-V9
Frequency	GSM 850MHz; PCS 1900MHz; WCDMA Band II; WCDMA Band V
Antenna	Internal
Power supply	Battery or Charger(AC Adaptor)
Output power	22.03dBm maximum EIRP measured for WCDMA Band V
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N01	355913040136769	d23B	VIVO_V9V1.0.0B01
N02	355913040135779	d23B	VIVO_V9V1.0.0B01

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Charger	/

AE1

Model	Li3734T42P3hC86049
Manufacturer	ZTE
Capacitance	3400mAh
Nominal Voltage	3.7V

AE2

Model	STC-A22O50I1500M5
Manufacturer	RUIDE
Length of DC line	120cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of Tablet Computer with integrated antenna. It consists of normal options: lithium battery, charger Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	CONDUCTED EMISSION	15.107/15.207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2011-12-06
2	Test Receiver	ESI40	831564/002	R&S	2011-07-12
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2011-07-05
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2011-07-10
5	Signal Generator	SMB100A	102063	R&S	2011-07-05
7	LISN	ESH2-Z5	829991/012	R&S	2011-07-20
8	Spectrum Analyzer	FSU26	200030	R&S	2011-12-18
9	Spectrum Analyzer	FSU46	100054	R&S	2011-10-14
10	Universal Radio Communication Tester	CMU200	100680	R&S	2011-12-23
11	Universal Radio Communication Tester	CMU200	109914	R&S	2011-07-21
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2012-08-31
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2013-07-09
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2011-07-01
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-07-01
16	Climatic chamber	PL-2G	343074	ESPEC	2011-12-15

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER (§22.913(a)/§24.232(b))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak) These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II;826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V. (bottom, middle and top of operational frequency range).

Limit

According to FCC§2.1046.

A.1.2.2 Test Condition

RBW	VBW	Sweep Time	Span
10MHz	10MHz	800ms	50MHz

WCDMA Band II

Measurement result

WCDMA (Band II)	CH	Frequency(MHz)	output power(dBm)	Target (dB)
	9262	1852.4	22.59	22±1
	9400	1880.0	22.55	22±1
	9538	1907.6	22.42	22±1

WCDMA Band V

Measurement result

WCDMA (Band V)	CH	Frequency(MHz)	output power(dBm)	Target (dB)
	4132	826.4	22.61	22±1
	4183	836.6	22.55	22±1
	4233	846.6	22.63	22±1

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.


1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



For 1900MHz working frequency test



For 850MHz working frequency test

In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. For 850MHz working frequency test:

A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitute Antenna.

The cable loss (P_{cl}), the Substitute Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)}=P_{Mea}+ P_{Ag} + P_{cl} + G_a$$

For 1900MHz working frequency test:

A cable should be connected between the Signal Source and the Substitute Antenna.

The cable loss (P_{cl}) and the Substitute Antenna Gain (G_a) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)}=P_{Mea}+ P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

WCDMA Band II-EIRP

Limits

	Burst Peak EIRP (dBm)
WCDMA Band II	≤33dBm (2W)

Measurement result

WCDMA Band II

Frequency(MHz)	Peak ERP(dBm)	P _{cl} Cable Loss(dB)	G _a Antenna Gain(dB)	P _{Mea} (dBm)	Polarization
1852.4	18.99	-10.9	27.5	2.39	H
1880.0	20.59	-10.8	27.5	3.89	H
1907.6	20.76	-11.3	27.5	4.56	H

Frequency: 1909.8MHz

Peak EIRP(dBm)= P_{Mea}(4.56dBm)+ P_{cl}(-11.3dB)+G_a (27.5dB) =20.76dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

WCDMA Band V-ERP

Limits

	Burst Peak EIRP (dBm)
WCDMA Band V	≤38.45dBm

Measurement result

Frequency(MHz)	Peak ERP(dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dBm)	P _{Mea} (dBm)	Polarization
826.4	22.03	-9.6	30.1	5.3	2.15	-1.62	H
836.6	21.49	-9.6	30.1	5.3	2.15	-2.16	H
846.6	20.48	-9.6	30.1	5.3	2.15	-3.17	H

Frequency: 826.4MHz

Peak ERP(dBm)= P_{Mea}(-1.62dBm)+ P_{cl}(-9.6dB)+ P_{Ag}(30.1dB)+G_a (5.3dB)-2.15dBm=22.03dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT (§2.1051/§22.917§24.238)


A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 24.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II and WCDMA Band V.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz) and WCDMA Band V (826.4MHz, 836.6MHz and 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II and WCDMA Band V into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

WCDMA BAND II Mode Channel 9262/1852.4MHz

Frequency(MHz)	Peak ERP(dBm)	Path Loss	Antenna Gain	P _{Mea} (dBm)	Limit (dBm)	Polarization
3817.77	-65.59	11.87	-8.28	-62.00	-13	V
4587.52	-59.92	12.90	-8.96	-55.98	-13	V
6057.18	-63.05	14.99	-10.25	-58.31	-13	H
9740.35	-62.28	19.56	-12.50	-55.23	-13	H
11249.29	-60.24	21.37	-12.40	-51.27	-13	V
17258.49	-58.63	27.46	-12.87	-44.03	-13	H

WCDMA BAND II Mode Channel 9400/1880MHz

Frequency(MHz)	Peak ERP(dBm)	Path Loss	Antenna Gain	P _{Mea} (dBm)	Limit (dBm)	Polarization
3761.34	-56.58	11.67	-8.21	-53.13	-13	V
5815.63	-60.47	14.72	-10.13	-55.88	-13	V
7140.93	-63.44	16.44	-11.18	-58.18	-13	H
9914.73	-60.22	19.86	-12.44	-52.80	-13	V
12009.31	-58.01	22.21	-12.50	-48.30	-13	V
15539.83	-55.35	25.87	-13.37	-42.84	-13	V

WCDMA BAND II Mode Channel 9538/1907.6MHz

Frequency(MHz)	Peak ERP(dBm)	Path Loss	Antenna Gain	P _{Mea} (dBm)	Limit (dBm)	Polarization
3813.01	-51.46	11.85	-8.27	-47.88	-13	V
8599.09	-58.68	18.39	-12.28	-52.57	-13	H
10062.24	-58.46	20.04	-12.41	-50.83	-13	V
11435.10	-57.84	21.56	-12.40	-48.68	-13	H
15476.16	-57.37	25.68	-13.40	-45.09	-13	V
17568.44	-54.01	27.80	-13.34	-39.55	-13	V

WCDMA BAND V Mode Channel 4132/826.4MHz

Frequency(MHz)	Peak ERP(dBm)	Path Loss	Antenna Gain	Correction	P _{Mea} (dBm)	Limit (dBm)	Polarization
				(dBm)			
1571.92	-64.49	7.69	-5.79	2.15	-60.44	-13	V
3476.70	-67.73	11.26	-7.85	2.15	-62.17	-13	H
4170.01	-63.92	12.32	-8.60	2.15	-58.06	-13	H
5722.58	-62.89	14.56	-10.09	2.15	-56.26	-13	V
6865.04	-62.78	16.08	-10.97	2.15	-55.52	-13	V
7997.52	-63.12	17.69	-11.90	2.15	-55.18	-13	H

WCDMA BAND V Mode Channel 4183/836.6MHz

Frequency(MHz)	Peak ERP(dBm)	Path Loss	Antenna Gain	Correction	P _{Mea} (dBm)	Limit (dBm)	Polarization
				(dBm)			
2258.21	-61.36	9.16	-4.68	2.15	-54.73	-13	V
3106.67	54.39	10.61	-6.96	2.15	60.19	-13	V
4063.13	-64.14	12.21	-8.54	2.15	-58.32	-13	H
5465.84	-67.03	14.19	-9.98	2.15	-60.68	-13	H
8386.65	-60.23	18.10	-12.13	2.15	-52.12	-13	H
8934.96	-61.32	18.85	-12.54	2.15	-52.86	-13	V

WCDMA BAND V Mode Channel 4233/846.6MHz

Frequency(MHz)	Peak ERP(dBm)	Path Loss	Antenna Gain	Correction	P _{Mea} (dBm)	Limit (dBm)	Polarization
				(dBm)			
3610.96	-67.87	11.48	-8.03	2.15	-62.28	-13	V
4409.48	-64.78	12.77	-8.75	2.15	-58.61	-13	V
7153.86	-62.28	16.43	-11.19	2.15	-54.90	-13	H
6286.71	-66.36	15.38	-10.43	2.15	-59.26	-13	H
8935.91	-65.14	18.85	-12.55	2.15	-56.69	-13	H
9773.48	-61.45	19.67	-12.49	2.15	-52.13	-13	V

A.3 CONDUCTED EMISSION (§15.107§15.207)


The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.

A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result
WCDMA Band II




MEASUREMENT RESULT: "11A01073_7C_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.316369	36.30	10.1	60	23.5	L1	GND
0.342583	37.20	10.1	59	21.9	N	GND
0.370968	38.80	10.1	59	19.7	N	GND
0.667263	32.50	10.1	56	23.5	N	GND
1.141962	31.00	10.1	56	25.0	N	GND
1.585831	32.10	10.1	56	23.9	N	GND

MEASUREMENT RESULT: "11A01073_7C_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.319533	28.80	10.1	50	20.9	L1	GND
0.346008	27.60	10.1	49	21.5	L1	GND
0.370968	32.40	10.1	49	16.1	L1	GND
0.530769	23.50	10.1	46	22.5	L1	GND
0.557844	23.40	10.1	46	22.6	L1	GND
0.634878	25.90	10.1	46	20.1	L1	GND

WCDMA Band V




MEASUREMENT RESULT: "11A01073_6C_fin QP"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.322728	36.00	10.1	60	23.7	L1	GND
0.378424	41.20	10.1	58	17.2	N	GND
0.569056	32.60	10.1	56	23.4	N	GND
0.673936	35.60	10.1	56	20.4	N	GND
1.130655	33.30	10.1	56	22.7	N	GND
1.539192	31.00	10.1	56	25.0	N	GND

MEASUREMENT RESULT: "11A01073_6C_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.378424	33.60	10.1	48	14.7	L1	GND
0.515159	20.10	10.1	46	25.9	L1	GND
0.541438	22.80	10.1	46	23.2	L1	GND
0.569056	21.90	10.1	46	24.1	L1	GND
0.622369	22.90	10.1	46	23.1	L1	GND
0.647639	25.10	10.1	46	20.9	L1	GND

MP3




MEASUREMENT RESULT: "11A01073_8C_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.382209	40.30	10.1	58	18.0	L1	GND
0.563422	32.40	10.1	56	23.6	N	GND
0.610106	34.60	10.1	56	21.4	N	GND
0.715397	33.40	10.1	56	22.6	N	GND
1.176564	31.50	10.1	56	24.5	N	GND
1.700225	29.80	10.1	56	26.2	N	GND

MEASUREMENT RESULT: "11A01073_8C_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.307065	28.00	10.1	50	22.0	L1	GND
0.332507	28.80	10.1	49	20.6	L1	GND
0.382209	34.30	10.1	48	14.0	L1	GND
0.409779	24.10	10.1	48	23.5	L1	GND
0.586299	25.00	10.1	46	21.0	L1	GND
0.667263	21.50	10.1	46	24.5	L1	GND

CAMERA



MEASUREMENT RESULT: "11A01073_9C_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.307065	30.80	10.1	60	29.2	L1	GND
0.322728	37.70	10.1	60	21.9	N	GND
0.378424	38.90	10.1	58	19.4	N	GND
0.673936	35.50	10.1	56	20.5	N	GND
1.176564	32.10	10.1	56	23.9	N	GND
1.570129	31.00	10.1	56	25.0	N	GND

MEASUREMENT RESULT: "11A01073_9C_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dBµV	dB	dBµV	dB		
0.325956	30.10	10.1	50	19.4	L1	GND
0.352963	28.30	10.1	49	20.6	L1	GND
0.378424	30.90	10.1	48	17.4	L1	GND
0.401705	26.50	10.1	48	21.4	L1	GND
0.580494	20.50	10.1	46	25.5	L1	GND
0.654116	23.10	10.1	46	22.9	L1	GND

A.4 FREQUENCY STABILITY (§2.1055/§24.235)

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 9400 for WCDMA Band II, channel 4183 for WCDMA Band V measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

WCDMA Band II

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-16	0.035
3.7	-15	0.033
4.2	-19	0.042

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-19	0.042
-20	-18	0.040
-10	-16	0.035
0	-16	0.035
10	-15	0.033
20	-15	0.033
30	-15	0.033
40	-16	0.035
50	-19	0.042

WCDMA Band V

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	13	0.028
3.7	12	0.026
4.2	15	0.032

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	16	0.033
-20	15	0.032
-10	15	0.032
0	13	0.028
10	12	0.026
20	12	0.026
30	12	0.026
40	13	0.028
50	13	0.028

A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

WCDMA Band II(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
1852.4	4.57
1880.0	4.58
1907.6	4.58


WCDMA Band II

Channel 9262-Occupied Bandwidth (-20dBc BW)




Date: 8.MAR.2011 08:05:54

Channel 9400-Occupied Bandwidth (-20dBc BW)



Channel 9538-Occupied Bandwidth (-20dBc BW)




WCDMA Band V(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)(MHz)
826.4	4.56
836.6	4.58
846.6	4.57


WCDMA Band V

Channel 4132-Occupied Bandwidth (-20dBc BW)




Date: 8.MAR.2011 08:27:34

Channel 4183-Occupied Bandwidth (-20dBc BW)



Date: 8.MAR.2011 08:28:04

Channel 4233-Occupied Bandwidth (-20dBc BW)



Date: 8.MAR.2011 08:28:33

A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))

A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II and WCDMA Band V. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

WCDMA Band II(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
1852.4	4.66
1880.0	4.66
1907.6	4.68


WCDMA Band II

Channel 9262-Occupied Bandwidth (-26dBc BW)




Date: 8.MAR.2011 08:07:25

Channel 9400-Occupied Bandwidth (-26dBc BW)



Channel 9538-Occupied Bandwidth (-26dBc BW)




WCDMA Band V (-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(MHz)
826.40	4.66
836.60	4.66
846.60	4.66


WCDMA Band V

Channel 4132-Occupied Bandwidth (-26dBc BW)




Date: 8.MAR.2011 08:29:04

Channel 4183-Occupied Bandwidth (-26dBc BW)



Date: 8.MAR.2011 08:29:34

Channel 4233-Occupied Bandwidth (-26dBc BW)




Date: 8.MAR.2011 08:30:04

A.7 BAND EDGE COMPLIANCE (§22.917(b)/§24.238(b))


WCDMA Band II

LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262




Date: 8.MAR.2011 08:08:55

HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538




Date: 8.MAR.2011 08:09:26

WCDMA Band V
LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132



Date: 8.MAR.2011 08:30:35

HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233



Date: 8.MAR.2011 08:31:06

A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

WCDMA Band II Transmitter

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

WCDMA Band V Transmitter

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


A.8.3 Measurement result

WCDMA Band II

A. 8.3.1 Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:09:57


A.8.3.2 Channel 9262: 1GHz –2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:10:26

A.8.3.3 Channel 9262: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:10:54

A.8.3.4 Channel 9262: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:11:22

A.8.3.5 Channel 9262: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 8.MAR.2011 08:11:50

A.8.3.6 Channel 9262: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:17:19

A. 8.3.7 Channel 9400: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:12:50


A.8.3.8 Channel 9400: 1GHz –2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:13:18

A.8.3.9 Channel 9400: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:13:46

A.8.3.10 Channel 9400: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:14:15

A.8.3.11 Channel 9400: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 8.MAR.2011 08:14:43

A.8.3.12 Channel 9400: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:15:12

A. 8.3.13 Channel 9538: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:15:43


A.8.3.14 Channel 9538: 1GHz –2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:16:11

A.8.3.15 Channel 9538: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:16:39

A.8.3.16 Channel 9538: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:17:08

A.8.3.17 Channel 9538: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 8.MAR.2011 08:17:36

A.8.3.18 Channel 9538: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:18:04

A. 8.3.19 Idle mode: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:18:33


A.8.3.20 Idle mode: 1GHz –2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:19:02

A.8.3.21 Idle mode: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:19:30

A.8.3.22 Idle mode: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:19:58

A.8.3.23 Idle mode: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 8.MAR.2011 08:20:27

A.8.3.24 Idle mode: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:20:55

WCDMA Band V

A. 8.3.25 Channel 4132: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:31:37

A. 8.3.26 Channel 4132: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:32:05

A. 8.3.27 Channel 4132: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:32:34

A. 8.3.28 Channel 4132: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:33:02

A. 8.3.29 Channel 4183: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:33:33

A.8.3.30 Channel 4183: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:34:01

A. 8.3.31 Channel 4183: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:34:30

A. 8.3.32 Channel 4183: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:34:58

A. 8.3.33 Channel 4233: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:35:29

A. 8.3.34 Channel 4233: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:35:58

A. 8.3.35 Channel 4233: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 8.MAR.2011 08:36:26


A. 8.3.36 Channel 4233: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 8.MAR.2011 08:36:54

A. 8.3.37 Idle mode: 30MHz – 1GHz
Spurious emission limit -13dBm.




Date: 8.MAR.2011 08:37:24

A.8.3.38 Idle mode: 1GHz – 2.5GHz
Spurious emission limit -13dBm.




Date: 8.MAR.2011 08:37:52

A.8.3.39 Idle mode: 2.5GHz – 7.5GHz
Spurious emission limit -13dBm.



Date: 8.MAR.2011 08:38:20

A.8.3.40 Idle mode: 7.5GHz – 10GHz
Spurious emission limit -13dBm.



Date: 8.MAR.2011 08:38:49

END OF REPORT