



# TEST REPORT

No. 2012TAR504

for

**ZTE CORPORATION**

**WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone**

**Model Name: ZTE V970T**

**FCC ID: Q78-V970T**

with

**Hardware Version: weyA**

**Software Version: TMO\_US\_P943EV1.0.0B02**

**Issued Date: Oct 29, 2012**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

***DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02***

***FCC 2.948 Listed: No.733176***

***IC O.A.T.S listed: No.6629B***

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.

Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304793, Email:welcome@emcite.com, web: [www.emcite.com](http://www.emcite.com)

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>3</b>
<b>1.1. TESTING LOCATION .....</b>	<b>3</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>3</b>
<b>1.3. PROJECT DATA .....</b>	<b>3</b>
<b>1.4. SIGNATURE .....</b>	<b>3</b>
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>4</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>4</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
<b>3.1. ABOUT EUT .....</b>	<b>5</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>5</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>5</b>
<b>3.4. GENERAL DESCRIPTION .....</b>	<b>6</b>
<b>4. REFERENCE DOCUMENTS.....</b>	<b>7</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>7</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>8</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>11</b>
<b>A.1 OUTPUT POWER.....</b>	<b>11</b>
<b>A.2 EMISSION LIMIT .....</b>	<b>16</b>
<b>A.3 CONDUCTED EMISSION .....</b>	<b>23</b>
<b>A.4 FREQUENCY STABILITY .....</b>	<b>29</b>
<b>A.5 OCCUPIED BANDWIDTH .....</b>	<b>32</b>
<b>A.6 EMISSION BANDWIDTH .....</b>	<b>38</b>
<b>A.7 BAND EDGE COMPLIANCE.....</b>	<b>44</b>
<b>A.8 CONDUCTED SPURIOUS EMISSION .....</b>	<b>47</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT  
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai  
Dian District, Beijing, P. R. China  
Postal Code: 100191  
Telephone: 00861062304633  
Fax: 00861062304793

### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: Sep 25, 2012  
Testing End Date: Oct 26, 2012

### 1.4. Signature



---

**Zi Xiaogang**  
**(Prepared this test report)**



---

**Sun Xiangqian**  
**(Reviewed this test report)**



---

**Lu Bingsong**  
**Deputy Director of the laboratory**  
**(Approved this test report)**

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: ZTE Corporation  
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, 518057, P.R.China  
City: Shenzhen  
Country: China  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

### **2.2. Manufacturer Information**

Company Name: ZTE Corporation  
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, 518057, P.R.China  
City: Shenzhen  
Country: China  
Telephone: 0086-21-61460890  
Fax: 0086-21-61460602

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone
Model Name	ZTE V970T
FCC ID	Q78-V970T
Frequency	GSM 850MHz; PCS 1900MHz; WCDMA Band II; WCDMA Band V WCDMA Band IV
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Output power	24.91dBm maximum EIRP measured for WCDMA BAND IV
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7 VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
N32	867820010010778	weyA	TMO_US_P943EV1.0.0B02
N31	867820010010786	weyA	TMO_US_P943EV1.0.0B02

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>
AE1	Battery
AE2	Travel charger

AE1

Model	Li3716T42P3h594650
Manufacturer	ZTE Corporation
Capacitance	1650mAh
Nominal Voltage	3.7V

AE2

Model	STC-A51-Z
Manufacturer	RUIDE
Length of DC line	123cm

\*AE ID: is used to identify the test sample in the lab internally..

### **3.4. General Description**

The Equipment Under Test (EUT) is a model of WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	V 10.1.09
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003
KDB971168 D01	Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems	2011

## 5. LABORATORY ENVIRONMENT

**Control room / conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2 / Fully-anechoic chamber 3** (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

## 6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(c)/27.50(d)(2)	P
2	Emission Limit	2.1051/22.917/24.238/27.53(h)	P
3	CONDUCTED EMISSION	15.107/15.207	P
4	Frequency Stability	2.1055/24.235/ 27.54	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)/ 27.53(g)	P
7	Band Edge Compliance	22.917(b)/24.238(b)/ 27.53(g)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238/ 27.53(g)	P

## 7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2013-03-28
2	Test Receiver	ESI40	831564/002	R&S	2012-11-08
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2014-11-10
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2014-07-31
5	Signal Generator	SMB100A	102063	R&S	2013-04-05
7	LISN	ESH2-Z5	829991/012	R&S	2013-04-16
8	Spectrum Analyzer	FSU26	200030	R&S	2013-07-06
9	Spectrum Analyzer	FSU46	100054	R&S	2013-03-16
10	Universal Radio Communication Tester	CMU200	100680	R&S	2013-03-04
11	Universal Radio Communication Tester	CMU200	109914	R&S	2013-06-28
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2014-02-17
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2014-02-02
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2014-02-02
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2013-03-19
16	Climatic chamber	PL-2G	343074	ESPEC	2013-05-12

## ANNEX A: MEASUREMENT RESULTS

### A.1 OUTPUT POWER

#### A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

##### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (RMS)

These measurements were done at 3 frequencies, 1852.4 MHz, 1880.0MHz and 1907.6MHz for WCDMA Band II;826.4MHz, 836.6MHz and 846.6MHz for WCDMA Band V and 1712.4MHz, 1740MHz, and 1752.6MHz for WCDMA Band IV(bottom, middle and top of operational frequency range).

#### Limit

##### A.1.2.2 Test Condition

RBW	VBW	Sweep Time	Span
10MHz	10MHz	800ms	50MHz

#### WCDMA Band II

##### Measurement result

WCDMA	CH	Frequency(MHz)	output power(dBm)
(Band II)	9262	1852.4	23.01
	9400	1880.0	<b>23.08</b>
	9538	1907.6	22.87

#### WCDMA Band V

##### Measurement result

WCDMA	CH	Frequency(MHz)	output power(dBm)
(Band V)	4132	826.4	23.07
	4183	836.6	<b>23.26</b>
	4233	846.6	23.02

#### WCDMA Band IV

##### Measurement result

WCDMA	CH	Frequency(MHz)	output power(dBm)
(Band IV)	1312	1712.4	22.55
	1450	1740.0	<b>22.71</b>
	1513	1752.6	22.66

### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts." Rule Part 27.50(d)(2) specifies, "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to a peak EIRP of 1 watt."


#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the

reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

**WCDMA Band II-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band II	33dBm (2W)

**Measurement result**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1852.40	-27.30	6.02	-50.00	-4.55	21.23	H
1880.00	-24.06	7.05	-50.00	-4.43	23.32	H
1907.60	-21.96	8.90	-50.00	-4.31	<b>23.45</b>	H

Frequency: 1907.60MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-21.96dBm)- P<sub>cl</sub>(8.90dB)- P<sub>Ag</sub>(-50.00dB) - G<sub>a</sub> (-4.31dB) =23.45dBm

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

**WCDMA Band V-ERP**

**Limits**

	Burst Peak ERP (dBm)
WCDMA Band V	38.45dBm (7W)

**Measurement result**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	Correction (dBm)	ERP(dBm)	Polarization
826.40	-25.13	2.25	-53.00	0.85	2.15	<b>22.62</b>	H
836.60	-25.65	2.26	-53.00	0.90	2.15	22.04	H
846.60	-25.82	2.26	-53.00	0.94	2.15	21.83	V

Frequency: 826.40MHz

Peak ERP(dBm)= P<sub>Mea</sub>(-25.13dBm)- P<sub>cl</sub>(2.25dB)- P<sub>Ag</sub>(-53.00dB)-G<sub>a</sub> (0.85dB)-2.15dBm=22.62dBm

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

**WCDMA Band IV-EIRP**

**Limits**

	Burst Peak EIRP (dBm)
WCDMA Band IV	30dBm (2W)

**Measurement result**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> Antenna Gain(dB)	EIRP(dBm)	Polarization
1712.40	-29.77	3.66	-50.00	-5.17	21.74	H
1740.00	-25.77	4.36	-50.00	-5.04	<b>24.91</b>	H
1752.60	-26.96	3.85	-50.00	-4.99	24.18	H

Frequency: 1740.00MHz

Peak EIRP(dBm)= P<sub>Mea</sub>(-25.77dBm)- P<sub>cl</sub>(4.36dB)- P<sub>Ag</sub>(-50.00dB) - G<sub>a</sub> (-5.04dB) =24.91dBm

**ANALYZER SETTINGS: RBW = VBW = 3MHz**

## A.2 EMISSION LIMIT


### **A.2.1 Measurement Method**

The measurements procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917 and Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II, WCDMA Band V and WCDMA Band IV.

#### **The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{pl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### **A.2.2 Measurement Limit**

Part 24.238 , Part 22.917 and Part 27.53 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of WCDMA Band II (1852.4 MHz, 1880.0MHz and 1907.6MHz) , WCDMA Band V(826.4MHz, 836.6MHz and 846.6MHz) and WCDMA Band IV(1712.4MHz, 1740MHz and 1752.6MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the WCDMA Band II, WCDMA Band V and WCDMA Band IV into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

#### A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
WCDMA Band V	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
WCDMA Band II	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass
WCDMA Band IV	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

#### A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
WCDMA Band V	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
WCDMA Band II	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
18~20	1 MHz	3 MHz	2	
WCDMA Band IV	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

**WCDMA BAND II Mode Channel 9262/1852.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3702.31	-52.11	5.32	-8.14	-49.29	-13.00	H
5559.53	-48.23	8.74	-10.02	-46.95	-13.00	H
7162.73	-66.29	8.79	-11.20	-63.88	-13.00	H
10199.97	-63.66	8.59	-12.44	-59.81	-13.00	H
13254.61	-63.03	10.40	-13.55	-59.88	-13.00	V
14828.14	-46.68	11.59	-13.53	-44.74	-13.00	H

**WCDMA BAND II Mode Channel 9400/1880MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3757.15	-58.79	6.04	-8.21	-56.62	-13.00	H
5643.32	-50.33	9.72	-10.06	-49.99	-13.00	H
8306.34	-66.02	7.80	-12.08	-61.74	-13.00	H
11286.65	-57.98	9.18	-12.40	-54.76	-13.00	H
13151.85	-64.68	10.26	-13.45	-61.49	-13.00	V
15039.00	-45.48	11.31	-13.49	-43.30	-13.00	H

**WCDMA BAND II Mode Channel 9538/1907.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3812.64	-50.06	5.68	-8.28	-47.46	-13.00	H
5726.58	-53.28	10.06	-10.09	-53.25	-13.00	H
8524.10	-65.50	7.72	-12.22	-61.00	-13.00	V
10180.69	-63.17	8.56	-12.44	-59.29	-13.00	V
13357.11	-60.95	10.51	-13.66	-57.80	-13.00	H
15267.85	-46.30	11.26	-13.45	-44.11	-13.00	V

**WCDMA BAND V Mode Channel 4132/826.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dBm)	Peak ERP(dBm)	Limit (dBm)	Polarization
1669.15	-64.56	3.38	-5.36	2.15	-64.73	-13.00	V
3055.79	-65.71	5.15	-6.83	2.15	-66.18	-13.00	H
4268.33	-69.08	6.07	-8.66	2.15	-68.64	-13.00	H
5076.74	-68.30	7.43	-9.75	2.15	-68.13	-13.00	V
6168.56	-68.76	10.81	-10.33	2.15	-71.39	-13.00	H
8644.12	-67.62	7.76	-12.32	2.15	-65.21	-13.00	H

**WCDMA BAND V Mode Channel 4183/836.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dBm)	Peak ERP(dBm)	Limit (dBm)	Polarization
1687.31	-66.29	3.61	-5.28	2.15	-66.77	-13.00	H
3239.44	-70.76	5.03	-7.27	2.15	-70.67	-13.00	V
4803.46	-69.50	6.64	-9.35	2.15	-68.94	-13.00	H
5986.40	-65.25	13.51	-10.19	2.15	-70.72	-13.00	H
7399.65	-65.39	9.08	-11.34	2.15	-65.28	-13.00	H
8493.31	-67.55	7.87	-12.20	2.15	-65.37	-13.00	V

**WCDMA BAND V Mode Channel 4233/846.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Correction (dBm)	Peak ERP(dBm)	Limit (dBm)	Polarization
1690.12	-63.03	3.60	-5.26	2.15	-63.52	-13.00	V
2408.05	-55.54	4.26	-5.12	2.15	-56.83	-13.00	H
3355.12	-70.06	5.49	-7.55	2.15	-70.15	-13.00	H
4226.06	-67.38	6.09	-8.64	2.15	-66.98	-13.00	H
5968.93	-64.50	13.61	-10.19	2.15	-70.07	-13.00	V
7047.81	-68.14	8.21	-11.13	2.15	-67.37	-13.00	H

**WCDMA BAND IV Mode Channel 1312/1712.4MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
5139.85	-54.28	7.07	-9.78	-51.57	-13.00	H
8566.88	-56.55	7.72	-12.25	-52.02	-13.00	V
10280.19	-53.02	8.61	-12.46	-49.17	-13.00	H
11980.70	-53.59	9.62	-12.50	-50.71	-13.00	V
13460.27	-62.81	10.71	-13.76	-59.76	-13.00	V
15772.89	-60.51	10.88	-13.18	-58.21	-13.00	V

**WCDMA BAND IV Mode Channel 1450/1740MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
3383.34	-66.55	5.04	-7.62	-63.97	-13.00	V
5218.00	-48.77	7.55	-9.83	-46.49	-13.00	H
6956.18	-59.95	7.77	-11.06	-56.66	-13.00	V
8696.22	-57.48	7.95	-12.36	-53.07	-13.00	V
10445.51	-53.77	8.77	-12.49	-50.05	-13.00	H
12186.71	-52.52	9.62	-12.57	-49.57	-13.00	H

**WCDMA BAND IV Mode Channel 1513/1752.6MHz**

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Polarization
5261.63	-46.34	7.57	-9.86	-44.05	-13.00	H
7010.33	-60.56	8.27	-11.11	-57.72	-13.00	H
8768.53	-56.27	8.17	-12.41	-52.03	-13.00	H
10521.77	-51.24	8.86	-12.50	-47.60	-13.00	H
12274.60	-47.03	9.56	-12.61	-43.98	-13.00	H
15530.49	-58.63	11.00	-13.38	-56.25	-13.00	H

### **A.3 CONDUCTED EMISSION**


The measurement procedure in ANSI C63.4-2003 is used. Conducted Emission is measured with travel charger.

#### **A.3.1 Limit**

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

\* Decreases with logarithm of the frequency

**A.3.2 Measurement result**  
**WCDMA Band II**




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.334500	40.4	GND	N	10.0	18.9	59.3
0.703500	41.5	GND	L1	10.0	14.5	56.0
1.657500	37.5	GND	L1	10.0	18.5	56.0
1.788000	40.2	GND	L1	10.0	15.8	56.0
2.179500	36.7	GND	L1	10.0	19.3	56.0
2.251500	39.3	GND	L1	10.0	16.7	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.316500	34.2	GND	L1	10.0	15.6	49.8
0.334500	29.1	GND	N	10.0	20.2	49.3
0.690000	32.7	GND	L1	10.0	13.3	46.0
1.657500	29.0	GND	L1	10.0	17.0	46.0
1.788000	31.9	GND	L1	10.0	14.1	46.0
2.251500	31.3	GND	L1	10.0	14.7	46.0

WCDMA Band V




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.312000	48.3	GND	L1	10.0	11.6	59.9
0.685500	43.7	GND	L1	10.0	12.3	56.0
0.748500	43.6	GND	L1	10.0	12.4	56.0
0.825000	40.9	GND	N	10.0	15.1	56.0
1.239000	39.0	GND	L1	10.0	17.0	56.0
1.734000	38.5	GND	L1	10.0	17.5	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.312000	42.1	GND	L1	10.0	7.8	49.9
0.438000	35.8	GND	L1	10.0	11.3	47.1
0.694500	35.5	GND	L1	10.0	10.5	46.0
0.757500	35.1	GND	L1	10.0	10.9	46.0
0.807000	34.3	GND	L1	10.0	11.7	46.0
1.239000	32.5	GND	L1	10.0	13.5	46.0

WCDMA Band IV




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.415500	46.1	GND	L1	10.0	11.4	57.5
0.433500	43.7	GND	L1	10.0	13.5	57.2
0.807000	42.2	GND	L1	10.0	13.8	56.0
1.293000	38.2	GND	L1	10.0	17.8	56.0
1.797000	41.7	GND	L1	10.0	14.3	56.0
2.278500	39.1	GND	L1	10.0	16.9	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.348000	34.3	GND	L1	10.0	14.7	49.0
0.415500	38.4	GND	L1	10.0	9.1	47.5
0.438000	37.7	GND	L1	10.0	9.4	47.1
0.820500	35.7	GND	L1	10.0	10.3	46.0
1.239000	33.9	GND	L1	10.0	12.1	46.0
1.279500	27.5	GND	L1	10.0	18.5	46.0

MP3




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.411000	46.4	GND	L1	10.0	11.2	57.6
0.433500	44.0	GND	L1	10.0	13.2	57.2
0.699000	37.4	GND	L1	10.0	18.6	56.0
1.230000	37.9	GND	L1	10.0	18.1	56.0
1.770000	37.7	GND	L1	10.0	18.3	56.0
1.810500	37.5	GND	L1	10.0	18.5	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.303000	31.8	GND	L1	10.0	18.4	50.2
0.339000	32.9	GND	L1	10.0	16.3	49.2
0.406500	36.0	GND	L1	10.0	11.7	47.7
0.438000	34.1	GND	L1	10.0	13.0	47.1
0.708000	31.2	GND	L1	10.0	14.8	46.0
0.807000	29.7	GND	L1	10.0	16.3	46.0

Camera



**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.415500	46.1	GND	L1	10.0	11.5	57.5
0.433500	43.7	GND	L1	10.0	13.5	57.2
0.708000	36.3	GND	L1	10.0	19.7	56.0
0.820500	37.7	GND	L1	10.0	18.3	56.0
1.221000	35.2	GND	L1	10.0	20.8	56.0
1.734000	33.8	GND	L1	10.0	22.2	56.0

**Final Result 2**

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.420000	39.0	GND	L1	10.0	8.5	47.4
0.433500	36.5	GND	L1	10.0	10.7	47.2
0.807000	29.5	GND	L1	10.0	16.5	46.0
1.221000	27.0	GND	L1	10.0	19.0	46.0
1.279500	28.8	GND	L1	10.0	17.2	46.0
2.283000	26.1	GND	L1	10.0	19.9	46.0

## **A.4 FREQUENCY STABILITY**

### **A.4.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of WCDMA Band II, WCDMA Band V, and WCDMA BAND IV, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **A.4.2 Measurement Limit**

#### **A.4.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### **A.4.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

#### A.4.3 Measurement results

##### WCDMA Band II

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	13	0.007
3.7	10	0.005
4.2	14	0.007

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	18	0.010
-20	17	0.009
-10	15	0.008
0	15	0.008
10	13	0.007
20	11	0.006
30	10	0.005
40	12	0.006
50	13	0.007

##### WCDMA Band V

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-7	0.008
3.7	-4	0.005
4.2	-6	0.007

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-11	0.013
-20	-11	0.013
-10	-8	0.010
0	-7	0.008
10	-6	0.007
20	-4	0.005
30	-6	0.007
40	-7	0.008
50	-9	0.011

**WCDMA Band IV****Frequency Error vs Voltage**

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	-12	0.007
3.7	-9	0.005
4.2	-11	0.006

**Frequency Error vs Temperature**

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	-16	0.009
-20	-16	0.009
-10	-14	0.008
0	-13	0.007
10	-11	0.006
20	-9	0.005
30	-10	0.006
40	-12	0.007
50	-13	0.007

## A.5 OCCUPIED BANDWIDTH

### A.5.1 Occupied Bandwidth Results


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II, WCDMA Band IV and WCDMA Band V. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.

#### WCDMA Band II(-20dBc)

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1852.4	4.151
1880.0	4.135
1907.6	4.151


#### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2012 10:55:06

### Channel 9400-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2012 10:55:41

### Channel 9538-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2012 10:56:16

**WCDMA Band IV(-20dBc)**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
1712.4	4.151
1740.0	4.135
1752.6	4.135


**WCDMA Band IV**

**Channel 1312-Occupied Bandwidth (-20dBc BW)**




Date: 26.OCT.2012 07:56:51

**Channel 1450-Occupied Bandwidth (-20dBc BW)**



Date: 26.OCT.2012 07:57:25

### Channel 1513-Occupied Bandwidth (-20dBc BW)




Date: 26.OCT.2012 07:58:00

**WCDMA Band V(-20dBc)**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( MHz)
826.4	4.167
836.6	4.135
846.6	4.151


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-20dBc BW)**




Date: 19.OCT.2012 11:38:31

**Channel 4183-Occupied Bandwidth (-20dBc BW)**



Date: 19.OCT.2012 11:39:06

### Channel 4233-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2012 11:39:40

## A.6 EMISSION BANDWIDTH

### A.6.1 Emission Bandwidth Results


Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the WCDMA Band II, WCDMA Band IV and WCDMA Band V. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

#### WCDMA Band II(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1852.4	4.503
1880.0	4.503
1907.6	4.503


#### WCDMA Band II

#### Channel 9262-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2012 10:56:52

### Channel 9400-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2012 10:57:27

### Channel 9538-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2012 10:58:01

**WCDMA Band IV(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
1712.4	4.503
1740.0	4.503
1752.6	4.519


**WCDMA Band IV**

**Channel 1312-Occupied Bandwidth (-26dBc BW)**




Date: 26.OCT.2012 08:29:15

### Channel 1450-Occupied Bandwidth (-26dBc BW)



Date: 26.OCT.2012 08:29:50

### Channel 1513-Occupied Bandwidth (-26dBc BW)




Date: 26.OCT.2012 08:30:24

**WCDMA Band V(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( MHz)
826.40	4.535
836.60	4.535
846.60	4.519


**WCDMA Band V**

**Channel 4132-Occupied Bandwidth (-26dBc BW)**




Date: 19.OCT.2012 11:40:17

### Channel 4183-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2012 11:40:51

### Channel 4233-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2012 11:41:26

## A.7 BAND EDGE COMPLIANCE


### WCDMA Band II

#### LOW BAND EDGE BLOCK-A (WCDMA Band II)-Channel 9262




Date: 19.OCT.2012 10:58:13

#### HIGH BAND EDGE BLOCK-C (WCDMA Band II) -Channel 9538




Date: 19.OCT.2012 10:58:24

**WCDMA Band IV  
LOW BAND EDGE BLOCK-A (WCDMA Band IV)-Channel 1312**



Date: 26.OCT.2012 08:30:36


**HIGH BAND EDGE BLOCK-C (WCDMA Band IV) -Channel 1513**



Date: 26.OCT.2012 08:30:47


WCDMA Band V

LOW BAND EDGE BLOCK-A (WCDMA Band V)-Channel 4132



Date: 19.OCT.2012 11:41:37

HIGH BAND EDGE BLOCK-C (WCDMA Band V) -Channel 4233



Date: 19.OCT.2012 11:41:49

## **A.8 CONDUCTED SPURIOUS EMISSION**

### **A.8.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA Band II, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band IV, data taken from 30 MHz to 20GHz. For WCDMA Band V, data taken from 30 MHz to 10GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; If the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give a optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:  
The trace mode is set to MaxHold to get the highest signal at each frequency;  
Wait 25 seconds;  
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

#### **WCDMA Band II Transmitter**

Channel	Frequency (MHz)
9262	1852.40
9400	1880.00
9538	1907.60

#### **WCDMA Band IV Transmitter**

Channel	Frequency (MHz)
1312	1712.40
1450	1740.00
1513	1752.60

#### **WCDMA Band V Transmitter**

Channel	Frequency (MHz)
4132	826.40
4183	836.60
4233	846.60

### **A. 8.2 Measurement Limit**

Part 24.238, Part 22.917 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43


+ 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### A.8.3 Measurement result

#### WCDMA Band II

##### A.8.3.1 Channel 9262: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2012 10:58:55

##### A.8.3.2 Channel 9262: 1GHz –2.5GHz


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 19.OCT.2012 10:59:24

**A.8.3.3 Channel 9262: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 10:59:52

**A.8.3.4 Channel 9262: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:00:20

**A.8.3.5 Channel 9262: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:00:48

**A.8.3.6 Channel 9262: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 19.OCT.2012 11:01:17


**A.8.3.7 Channel 9400: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 19.OCT.2012 11:01:48


**A.8.3.8 Channel 9400: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 19.OCT.2012 11:02:16

**A.8.3.9 Channel 9400: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:02:44

**A.8.3.10 Channel 9400: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:03:12

**A.8.3.11 Channel 9400: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:03:41

**A.8.3.12 Channel 9400: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 19.OCT.2012 11:04:09


**A.8.3.13 Channel 9538: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 19.OCT.2012 11:04:40


**A.8.3.14 Channel 9538: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 19.OCT.2012 11:05:08

**A.8.3.15 Channel 9538: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:05:37

**A.8.3.16 Channel 9538: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:06:05

**A.8.3.17 Channel 9538: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:06:33

**A.8.3.18 Channel 9538: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:07:01

**A.8.3.19 Idle mode: 30MHz –1GHz**  
Spurious emission limit –13dBm.




Date: 22.OCT.2012 01:01:01

**A.8.3.20 Idle mode: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.




Date: 22.OCT.2012 01:01:30

**A.8.3.21 Idle mode: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 22.OCT.2012 01:01:58

**A.8.3.22 Idle mode: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 22.OCT.2012 01:02:27

**A.8.3.23 Idle mode: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 22.OCT.2012 01:02:55

**A.8.3.24 Idle mode: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 22.OCT.2012 01:03:24

**WCDMA Band IV**

**A.8.3.25 Channel 1312: 30MHz –1GHz**

Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:31:18

**A.8.3.26 Channel 1312: 1GHz –2.5GHz**


Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 26.OCT.2012 08:31:46

**A.8.3.27 Channel 1312: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:32:15

**A.8.3.28 Channel 1312: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:32:43

**A.8.3.29 Channel 1312: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:33:11

**A.8.3.30 Channel 1312: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 26.OCT.2012 08:33:39


**A.8.3.31 Channel 1450: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 26.OCT.2012 08:34:11


**A.8.3.32 Channel 1450: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 26.OCT.2012 08:34:39

**A.8.3.33 Channel 1450: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:35:07

**A.8.3.34 Channel 1450: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:35:35

**A.8.3.35 Channel 1450: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:36:04

**A.8.3.36 Channel 1450: 15GHz –20GHz**  
Spurious emission limit –13dBm.



Date: 26.OCT.2012 08:36:32


**A.8.3.37 Channel 1513: 30MHz –1GHz**  
Spurious emission limit –13dBm.



Date: 26.OCT.2012 08:37:03


**A.8.3.38 Channel 1513: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.

**NOTE: peak above the limit line is the carrier frequency.**




Date: 26.OCT.2012 08:37:31

**A.8.3.39 Channel 1513: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:38:00

**A.8.3.40 Channel 1513: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:38:28

**A.8.3.41 Channel 1513: 10GHz –15GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:38:56

**A.8.3.42 Channel 1513: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:39:25

**A.8.3.43 Idle mode: 30MHz –1GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:51:22

**A.8.3.44 Idle mode: 1GHz –2.5GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:51:50

**A.8.3.45 Idle mode: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:52:18

**A.8.3.46 Idle mode: 7.5GHz –10GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:52:47

**A.8.3.47 Idle mode: 10GHz –15GHz**  
Spurious emission limit –13dBm.



Date: 26.OCT.2012 08:53:15

**A.8.3.48 Idle mode: 15GHz –20GHz**  
Spurious emission limit –13dBm.




Date: 26.OCT.2012 08:53:43

**WCDMA Band V**

**A.8.3.49 Channel 4132: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 19.OCT.2012 11:42:20

**A.8.3.50 Channel 4132: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:42:48



### A.8.3.53 Channel 4183: 30MHz –1GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 19.OCT.2012 11:44:16


### A.8.3.54 Channel 4183: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:44:44

**A.8.3.55 Channel 4183: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.



Date: 19.OCT.2012 11:45:12

**A.8.3.56 Channel 4183: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:45:40

**A.8.3.57 Channel 4233: 30MHz –1GHz**

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 19.OCT.2012 11:46:12


**A.8.3.58 Channel 4233: 1GHz – 2.5GHz**

Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:46:40

**A.8.3.59 Channel 4233: 2.5GHz –7.5GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:47:08

**A.8.3.60 Channel 4233: 7.5GHz – 10GHz**  
Spurious emission limit –13dBm.




Date: 19.OCT.2012 11:47:36

**A.8.3.61 Idle mode: 30MHz – 1GHz**  
Spurious emission limit -13dBm.




Date: 22.OCT.2012 01:10:39

**A.8.3.62 Idle mode: 1GHz – 2.5GHz**  
Spurious emission limit -13dBm.




Date: 22.OCT.2012 01:11:07

**A.8.3.63 Idle mode: 2.5GHz – 7.5GHz**  
Spurious emission limit -13dBm.



Date: 22.OCT.2012 01:11:35

**A.8.3.64 Idle mode: 7.5GHz – 10GHz**  
Spurious emission limit -13dBm.



Date: 22.OCT.2012 01:12:03

\*\*\*END OF REPORT\*\*\*