

TEST REPORT

REPORT NUMBER: I08GE7032-FCC-EMC

ON

Type of Equipment: Windows Mobile Smart Phone
Type of Designation: Vodafone 1231
Manufacturer: ZTE CORPORATION


ACCORDING TO

**FCC CFR Part 2, FREQUENCY ALLOCATIONS AND RADIO
TREATY MATTERS; GENERAL RULES AND REGULATIONS;
e-CFR, March 23, 2006
PART 24, PERSONAL COMMUNICATIONS SERVICES (Oct 1, 97
Edition)**

China Telecommunication Technology Labs.

Month date, year
Dec, 8, 2008

Signature



He Guili
Director

FCC ID: Q78-VDF1231

Report Date: 2008-12-08

Test Firm Name: China Telecommunication Technology Labs

Registration Number: 840587

Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, and 24. The sample tested was found to comply with the requirements defined in the applied rules.

CONTENTS

1 GENERAL INFORMATION	4
1.1 NOTES	4
1.2 TESTERS	5
1.3 TESTING LABORATORY INFORMATION	6
1.4 DETAILS OF APPLICANT OR MANUFACTURER	7
2 TEST ITEM	8
2.1 GENERAL INFORMATION	8
2.2 OUTLINE OF EUT	8
2.3 MODIFICATIONS INCORPORATED IN EUT	8
2.4 EQUIPMENT CONFIGURATION	8
2.5 OTHER INFORMATION	9
3 SUMMARY OF TEST RESULTS	10
4 TEST RESULTS OF MODE	11
4.1 RADIATED SPURIOUS EMISSION	11
4.2 RADIATED RF POWER OUTPUT AND ERP	19
4.3 OCCUPIED BANDWIDTH	22
4.4 FREQUENCY STABILITY OVER TEMPERATURE VARIATION	29
4.5 FREQUENCY STABILITY OVER VOLTAGE VARIATION	32
4.6 CONDUCTED RF POWER OUTPUT	34
4.7 CONDUCTED SPURIOUS EMISSION	36
4.8 BAND EDGE	41
ANNEX A EXTERNAL PHOTOS	46
ANNEX B INTERNAL PHOTOS.....	49
ANNEX C DEVIATIONS FROM PRESCRIBED TEST METHODS.....	51

1 General Information

1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2 and 24.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.

The following deviation from, additions to, or exclusions from the test specifications have been made. See Annex C.

China Telecommunication Technology Labs.(CTTL) authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTTL Mr. He Guili.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CTTL accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

FCC Parts 2, 24
Equipment: Vodafone 1231


REPORT NO.: I08GE7032-FCC-EMC

1.2 Testers


Name: Yuan Yuan
Position: Engineer
Department: Department of EMC test
Signature: 

Name: Li Dongjin
Position: Engineer
Department: Department of EMC test
Signature: 

Editor of this test report:

Name: Yuan Yuan
Position: Engineer
Department: Department of EMC test
Date: 2008-12-08
Signature: 

Technical responsibility for area of testing:

Name: Zou Dongyi
Position: Manager
Department: Department of EMC test
Date: 2008-12-08
Signature: 

1.3 Testing Laboratory information

1.3.1 Location

Name: China Telecommunication Technology Labs.
Address: No. 11, Yue Tan Nan Jie, Xi Cheng District
BEIJING
P. R. CHINA, 100083
Tel: +86 10 68094053
Fax: +86 10 68011404
Email: emc@chinattl.com

1.3.2 Details of accreditation status

Accredited by: China National Accreditation Service for Conformity
Assessment (CNAS)
Registration number: CNAS Registration No. CNAS L0570
Standard: ISO/IEC 17025:2005

1.3.3 Test location, where different from section 1.3.1

Name: -----
Street: -----
City: -----
Country: -----
Telephone: -----
Fax: -----
Postcode: -----

1.4 Details of applicant or manufacturer

1.4.1 Applicant

Name: ZTE CORPORATION
Address: ZTE Plaza, Keji Road South, Hi-Tech Industrial
Park, Nanshan District, Shenzhen, Guangdong,
518057, P.R.China
Country: China
Telephone: +86-021-68897541
Fax: +86-21-50701080
Contact: Zhangmin
Telephone: 021-68897541
Email: Zhang.min13@zte.com.cn

1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name: --
Address: --

1.4.3 Manufactory (if different from applicant in section 1.4.1)

Name: --
Address: --

2 Test Item

2.1 General Information

Manufacturer: ZTE CORPORATION
 Name: Windows Mobile Smart Phone
 Model Number: Vodafone 1231
 Serial Number: --
 Production Status: Production
 Receipt date of test item: 2008-11-14

2.2 Outline of EUT

E.U.T. is a Windows Mobile Smart Phone.

2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	handset	ZTE CORPORATION	Vodafone 1231	--	None
B	adapter	ZTE CORPORATION, RD, Dokocom	STC-A22O50U5- A	--	None
C	battery	ZTE CORPORATION, RD, SCUD	Li3711T42P3h51 3857	--	None
D	Earphone	Merry Electronics Ltd Full-Sound Electrical Products.Ltd	HMZ3-C4-OMTP	--	None

Cables:

Item	Cable Type	Manufacturer	Length	Shield	Quantity	Remarks
1	DC cable on Adapter	Unknown	1.0 m	No	1	None

2.5 Other Information

(a) Modulation is GFSK.

(b) Emission Designators are 276KGXW and 246KG7W.

(c) Version of hardware and software

HW Version: g5hC

SW Version: P180A1V1.0.3

(d) Adaptor information:

Input: 100-240VAC 50/60Hz 200mA

Output: 5.0VDC 700mA

(e) Battery information:

3.7VDC 1100mAh

CITL Test Report

3 Summary of Test Results

A brief summary of the tests carried out is shown as following.

GSM mode:		
Specification Clause	Name of Test	Result
2.1051, 24.238	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
2.1049, 24.238(b)	Occupied Bandwidth	*Note 1
2.1055, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,24.232(c)	Conducted RF Power Output	Pass
2.1051,24.238	Conducted spurious emissions	Pass
Note 1: No applicable performance criteria.		

GPRS mode:		
2.1051, 24.238	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
2.1049, 24.238(b)	Occupied Bandwidth	*Note 2
2.1055, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,24.232(c)	Conducted RF Power Output	Pass
2.1051,24.238	Conducted spurious emissions	Pass
Note 2: No applicable performance criteria.		

EGPRS mode:		
2.1051, 24.238	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
2.1049, 24.238(b)	Occupied Bandwidth	*Note 3
2.1055, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,24.232(c)	Conducted RF Power Output	Pass
2.1051,24.238	Conducted spurious emissions	Pass
Note 3: No applicable performance criteria.		

4 Test Results of mode

4.1 Radiated Spurious Emission

Specifications:	2.1051, 24.238					
Date of Tests	2008-11-14, 2008-11-18					
Test conditions:	Ambient Temperature: 15°C -35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Ultra Broadband Antenna	SCHWARZBECK	VULB 9160	--	2010-10-26	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:

According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

The EUT was placed in an anechoic chamber, see figure SP. The Wireless Communications Test Set was used to set the TX channel and power level and modulate the TX signal with different bit patterns. The test was done using an automated test system, where all test equipments were controlled by a computer.




Figure SP

Test Method:


The measurement was performed accordance with section 2.2.12 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

- 1 The maximum spurious emissions were searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.
- 2 Levels of EUT's transmitter harmonics and suspicious signals were recorded.
- 3 The recorded levels were corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration was made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.
- 4 The corrected values of radiated spurious emissions indicated as EIRP are reported.


Note:

- 1 The investigated ARFCNs is 661 (1880.0 MHz).
- 2 The investigated frequency range is 30 MHz ~ 18 GHz.

Test Results for GSM mode:




S661VF for GSM mode




S661HF for GSM mode

FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC




S661VT for GSM mode




S661HT for GSM mode


Test Results for GPRS mode:




S661VF for GPRS mode



S661HF for GPRS mode




S661VT for GPRS mode




S661HT for GPRS mode


Test Results for EGPRS mode:




S661VF for EGPRS mode



S661HF for EGPRS mode



S661VT for EGPRS mode



S661HT for EGPRS mode

4.2 Radiated RF Power Output and ERP

Specifications:	2.1046,24.232					
Date of Tests	2008-11-14,2008-11-18					
Test conditions:	Ambient Temperature: 15°C -35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 512, 661 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
7330	Ultra Broadband Antenna	SCHWARZBECK	VULB 9160	--	2010-10-26	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:

Radiated RF Power Output
According to Part 24.232(b), i.e., Mobile/portable stations are limited to 2 watts EIRP peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications, so the limit level is 2 W or 33 dBm.

Limits for Radiated RF Power Output

Frequency range	Limit Level (EIRP)/Resolution Bandwidth
TX channel	33dBm/1MHz

Test Setup:

The EUT was set in an anechoic chamber, which is connected to the Wireless Communications Test Set located outside the chamber over the air. The test was done using an automated test system, where all test equipments were controlled by a computer.

Test Method

The measurement was performed accordance with section 2.2.17 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

1 The maximum power was searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.

2 The measured levels are EIRP values corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration is made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.

3 The corrected maximum levels were reported for EIRP values, and ERP values can be calculated from EIRP values.

Note:

ERP dBm = EIRP dBm – 2.15dB.

EIRP Value for GSM 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.260521	24.30
661	1880.080160	23.43
810	1909.739479	23.68

EIRP Value for GPRS 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.100200	24.67
661	1880.080160	24.59
810	1909.739479	25.15

EIRP Value for EGPRS 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.100200	24.43
661	1880.080160	25.03
810	1909.899800	25.10

China Test Report

4.3 Occupied bandwidth

Specifications:	2.1049,24.238(b)					
Date of Test	2008-11-17,2008-11-18,2008-11-19					
Test conditions:	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 512, 661 and 810					
Test Results:	--					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Ultra Broadband Antenna	SCHWARZBECK	VULB 9160	--	2010-10-26	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Test Setup

The situation under which maximum EIRP values were found in the measurement of the radiated RF power output was used to determine the 99% occupied bandwidth. The Wireless Communications Test Set was used to set the TX channel, power level and modulation.

Test Method


The 99% occupied bandwidth was calculated from the spectrum analyzer. Markers in the spectrum analyzer were then placed between the calculated frequencies to show the calculated 99% power band.

Note: --

Results data of GSM mode:

EUT channel	99% occupied bandwidth [kHz]
512	276
661	276
810	276

Graphical results for GSM mode:




Date: 17.NOV.2008 11:24:40

Channel 512


FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC



Date: 17.NOV.2008 11:28:25

Channel 661




Date: 17.NOV.2008 11:29:55

Channel 810

Results data of GPRS mode:

EUT channel	99% occupied bandwidth [kHz]
512	248
661	244
810	248


Graphical results for GPRS mode:



Channel 512


FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC



Date: 19.NOV.2008 15:29:07

Channel 661




Date: 19.NOV.2008 15:30:41

Channel 810

Results data of EGPRS mode:

EUT channel	99% occupied bandwidth [kHz]
512	244
661	246
810	244


Graphical results for EGPRS mode:




Channel 512

FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC



Channel 661



Channel 810

4.4 Frequency Stability over Temperature Variation

Specifications:	2.1055,24.235					
Date of Test	2008-11-19					
Test conditions:	Ambient Temperature: -30°C-50°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
561	Temperature Chamber	Terchy Environmental Technology LTD.	MHU-800SR	84121202	2009-05-06	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal
Limit						
Frequency deviation [ppm]	±2.5					

Test Setup

The EUT was placed in a temperature chamber, demonstrated as figure T. The wireless communications test set (test simulator) was used to set the TX channel and power levels, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure T: setup for measurement of frequency stability over temperature variation

Test Method

1. The EUT was turned off and placed in the temperature chamber.
2. The temperature of the chamber was set to -30°C and allowed to stabilize.
3. The EUT temperature was allowed to stabilize for 45 minutes.
4. The EUT was turned on and set to transmit with 8960.
5. The maximum transmit frequency deviation during one minute period was measured by Wireless Communications Test Set.
6. The steps 3-5 were repeated for -20°C, -10°C, 0°C, 10°C, 20°C, 30°C, 40°C and 50°C.

Test results data for GSM mode:

Channel 661:

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	23	0.012	Pass
-20	21	0.011	Pass
-10	20	0.011	Pass
0	20	0.011	Pass
10	23	0.012	Pass
20	24	0.013	Pass
30	18	0.010	Pass
40	5	0.003	Pass
50	-7	-0.004	Pass

Test results data for GPRS mode:

Channel 661:

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	29	0.015	Pass
-20	21	0.011	Pass
-10	15	0.008	Pass
0	7	0.004	Pass
10	-3	-0.002	Pass
20	-15	-0.008	Pass
30	-24	-0.013	Pass
40	-27	-0.014	Pass
50	-30	-0.016	Pass

Test results data for EGPRS mode:

Channel 661:

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	30	0.016	Pass
-20	28	0.015	Pass
-10	27	0.014	Pass
0	32	0.017	Pass
10	23	0.012	Pass
20	16	0.009	Pass
30	5	0.003	Pass
40	-11	-0.006	Pass
50	-20	-0.011	Pass

TTL Test Report

4.5 Frequency Stability over Voltage Variation

Specifications:	2.1055, 24.235					
Date of Test	2008-11-18, 2008-11-19					
Test conditions:	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal
7982	DC Power Source	4NIC	DH1715A-3	004224	--	Normal
Limit						
Frequency deviation [ppm]	±2.5					

Test Setup

The EUT was placed in a shielding chamber and powered by the dummy battery which is connected to a DC power source, demonstrated as figure V. The wireless communications test set was used to set the TX channel and power level, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure V: test setup for measurement of frequency stability over voltage variation

Test Results data for GSM mode:

Channel 661:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	40	0.021	Pass
Cut-off point	3.3	-30	-0.016	Pass

Test Results data for GPRS mode:

Channel 661:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	37	0.020	Pass
Cut-off point	3.4	-32	-0.017	Pass

Test Results data for EGPRS mode:

Channel 661:

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	37	0.020	Pass
Cut-off point	3.3	-32	-0.017	Pass


4.6 Conducted RF Power Output

Specifications:	2.1046, 24.232(c)					
Date of Tests	2008-11-17,2008-11-19					
Test conditions:	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 512, 661 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limits for Radiated RF Power Output	
Frequency range	Limit Level (EIRP)/Resolution Bandwidth
TX channel	33dBm/1MHz

Test Setup:

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26).



Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base

station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.

2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.

3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --

Test Results for GSM mode:

EIRP Value for GSM 1900 band:

ARFCN	Peak output power [dBm]
512	28.66
661	28.87
810	29.35

Test Results for GPRS mode:

EIRP Value for GPRS 1900 band:

ARFCN	Peak output power [dBm]
512	26.31
661	27.35
810	27.38

Test Results for EGPRS mode:

EIRP Value for EGPRS 1900 band:

ARFCN	Peak output power [dBm]
512	29.58
661	29.32
810	29.57

4.7 Conducted Spurious Emission

Specifications:	2.1051, 24.238					
Date of Tests	2008-11-17,2008-11-18,2008-11-19					
Test conditions:	Ambient Temperature: 15°C -35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ES126	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

During the process of testing, the EUT was controlled via Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ES126)



Test Method

The measurement was performed accordance with section 2.2.13 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

The following steps outline the procedure used to measure the conducted emissions from the EUT.


1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment under test, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Note: --


Test Results for GSM mode:

Out of band emission	
Frequency [MHz]	Level (dBm)
--	--

Graphical results for GSM mode:




Channel 661



Test Results for GPRS mode:

Out of band emission	
Frequency [MHz]	Level (dBm)
--	--

Graphical results for GPRS mode:




Date: 19.NOV.2008 08:59:25

Channel 661

Test Results for EGPRS mode:


Out of band emission	
Frequency [MHz]	Level (dBm)
--	--

Graphical results for EGPRS mode:



Date: 18.NOV.2008 10:13:40

Channel 661



4.8 Band Edge

Specifications:	2.1051, 24.238					
Date of Tests	2008-11-17,2008-11-19					
Test conditions:	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 512 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2009-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ESI26).



Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --

Test Results:

GSM mode:

Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
512 Left band edge	1850.001600	-13.66
810 Right band edge	1909.810020	-15.47

GPRS mode:


Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
512 Left band edge	1849.989580	-13.36
810 Right band edge	1910.002400	-16.11

EGPRS mode:

Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
512 Left band edge	1850.001603	-13.77
810 Right band edge	1910.010420	-14.61


FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC



Date: 17.NOV.2008 11:49:20

GSM channel 512 Left band edge




Date: 17.NOV.2008 11:52:56

GSM channel 810 Right band edge


FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC



Date: 19.NOV.2008 09:08:49

GPRS channel 512 Left band edge




Date: 19.NOV.2008 09:03:04

GPRS channel 810 Right band edge


FCC Parts 2, 24
Equipment: Vodafone 1231

REPORT NO.: I08GE7032-FCC-EMC



Date: 19.NOV.2008 08:31:17

EGPRS channel 512 Left band edge



Date: 19.NOV.2008 08:33:41

EGPRS channel 810 Right band edge

Annex A External Photos



Front view



Back view



Adaptor




Earphone




battery

China Test

Annex B Internal Photos




Main board (face)



Main board (back)



Adaptor face



Adaptor back

ANNEX C Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

————— The End of this Report —————

TTL Test Report