



47 CFR PART 22 SUBPART H & 24 SUBPART E

# TEST REPORT

of

**GSM Dual-mode Digital Wireless Data Terminal(CARD)(EDGE)**

Model Name: Vodafone K2525  
Brand Name: ZTE  
Report No.: SH08060021E02  
FCC ID: Q78-VDFK2525

*prepared for*

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan  
District, Shenzhen, Guangdong, 518057, P.R. China



**Shenzhen Electronic Product Quality Testing Center  
Morlab Laboratory**

3/F, Electronic Testing Building, Shahe Road, Xili,  
Nanshan District, Shenzhen, 518055 P. R. China

Tel: +86 755 86130398

Fax: +86 755 86130218



*NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.*



## TABLE OF CONTENTS

<b>1. TEST CERTIFICATION</b> .....	<b>4</b>
<b>2. GENERAL INFORMATION</b> .....	<b>5</b>
<b>2.1 EUT Description</b> .....	<b>5</b>
<b>2.2 Test Standards and Results</b> .....	<b>7</b>
<b>2.3 Facilities and Accreditations</b> .....	<b>8</b>
2.3.1 Facilities .....	8
2.3.2 Test Environment Conditions.....	8
<b>3. 47 CFR PART 2, PART 22H REQUIREMENTS</b> .....	<b>9</b>
<b>3.1 Frequencies</b> .....	<b>9</b>
3.1.1 Requirement .....	9
3.1.2 Test Description.....	9
3.1.3 Test Result .....	10
<b>3.2 Conducted RF Output Power</b> .....	<b>15</b>
3.2.1 Requirement .....	15
3.2.2 Test Description .....	15
3.2.3 Test Result.....	15
<b>3.3 20dB Occupied Bandwidth</b> .....	<b>23</b>
3.3.1 Definition .....	23
3.3.2 Test Description.....	23
3.3.3 Test Verdict.....	23
<b>3.4 Frequency Stability</b> .....	<b>30</b>
3.4.1 Requirement .....	30
3.4.2 Test Description.....	30
3.4.3 Test Verdict.....	30
<b>3.5 Conducted Spurious Emissions Test</b> .....	<b>33</b>
3.5.1 Requirement .....	33
3.5.2 Test Description.....	33
3.5.3 Test Result .....	33
<b>3.6 Transmitter Radiated Power (EIRP/ERP)</b> .....	<b>39</b>
3.6.1 Requirement .....	39



3.6.2 Test Description.....	39
3.6.3 Test Result.....	40
<b>3.7 Radiated Spurious Emissions Test .....</b>	<b>49</b>
3.7.1 Requirement.....	49
3.7.2 Test Description.....	49
3.7.3 Test Result.....	49
Appendix I: Photographs of the EUT	
Appendix II: Photographs of the Test Configuration	



**1. TEST CERTIFICATION**

Equipment under Test: GSM Dual-mode Digital Wireless Data Terminal(CARD)(EDGE)

Brand Name: ZTE  
 Model Name: Vodafone K2525  
 FCC ID: Q78-VDFK2525  
 Applicant: ZTE CORPORATION  
 ZTE Plaza Keji Road South, Hi-Tech Industrial Park,Nanshan District,Shenzhen,Guangdong,518057,P.R.China  
 Manufacturer: ZTE CORPORATION  
 ZTE Plaza Keji Road South, Hi-Tech Industrial Park,Nanshan District,Shenzhen,Guangdong,518057,P.R.China

Test Standards: 47 CFR Part 2  
 47 CFR Part 22 Subpart H  
 47 CFR Part 24 Subpart E

Test Date(s): June 23, 2008 – June 29, 2008

Test Result: PASS

**\* We Hereby Certify That:**

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: Lou Qinchao Dated: 2008.07.01  
 Lou Qinchao  
 Reviewed by: Zhang Jun Dated: 2008.07.01  
 Zhang Jun  
 Approved by: Su Feng Dated: 2008.07.01  
 Su Feng





be represented with the formula  $F(n)=1850.2+0.2*(n-512)$ ,  $512 \leq n \leq 810$ ; the lowest, middle and highest channel numbers (ARFCHs) used and tested in this report are separately 512 (1850.2MHz), 661 (1880.0MHz) and 810 (1909.8MHz).

*Note 3:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part 24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-05 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-05 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-05 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	2.106 22.905 24.229	Frequencies	PASS
2	2.1046	Conducted RF Output Power	PASS
3	2.1049	20dB Occupied Bandwidth	PASS
4	2.1055 22.355 24.235	Frequency Stability	PASS
5	2.1051 2.1057 22.917 24.238	Conducted Spurious Emissions at Antenna Terminal	PASS
6	22.913 24.232	Transmitter Radiated Power (EIRP/ERP)	PASS
7	2.1053 2.1057 22.917 24.238	Radiated Spurious Emissions	PASS



## 2.3 Facilities and Accreditations

### 2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Board for Laboratories (CNAL) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### 2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	960

### 3. 47 CFR PART 2, PART 22H REQUIREMENTS

#### 3.1 Frequencies

##### 3.1.1 Requirement

According to FCC section 22.905, the frequency blocks assignment for the cellular radiotelephone service is listed as below:


- (a) Channel Block A:  
 Mobile 824 - 835MHz, Base 869 - 880MHz;  
 Mobile 845 - 846.5MHz, Base 890 - 891.5MHz
- (b) Channel Block B:  
 Mobile 835 - 845 MHz, Base 880 - 890MHz;  
 Mobile 846.5 - 849 MHz, Base 891.5 - 894MHz

According to FCC section 24.229, the frequencies available in the Broadband PCS services are listed as below, in accordance with the frequency allocations table of FCC section 2.106.

- (a) The following frequency blocks are available for assignment on an MTA basis:  
 Block A: 1850 - 1865MHz paired with 1930 - 1945MHz;  
 Block B: 1870 - 1885MHz paired with 1950 - 1965MHz.
- (b) The following frequency blocks are available for assignment on a BTA basis:  
 Block C: 1895 - 1910 MHz paired with 1975 - 1990MHz;  
 Block D: 1865 - 1870 MHz paired with 1945 - 1950MHz;  
 Block E: 1885 - 1890 MHz paired with 1965 - 1970MHz;  
 Block F: 1890 - 1895 MHz paired with 1970 - 1975MHz.

##### 3.1.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna

terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

## 2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Rohde&Schwarz	CMU200	105571	2007.11	1year
Spectrum Analyzer	Rohde&Schwarz	FSP30	101020	2007.11	1year
Power Splitter	Weinschel	1506A	NW521	(n.a.)	(n.a.)
Attenuator 1	Resnet	20dB	(n.a.)	(n.a.)	(n.a.)
Attenuator 2	Resnet	3dB	(n.a.)	(n.a.)	(n.a.)

### 3.1.3 Test Result

The Tx frequency arrangement of the Cellular 850MHz band employed by the EUT should be from 824.2MHz to 848.8MHz (the corresponding frequency block is from 824MHz to 849MHz), and Tx frequency arrangement of the PCS 1900MHz band employed by the EUT should be from 1850.2MHz to 1909.8MHz (the corresponding frequency block is from 1850MHz to 1910MHz). Here the lowest and highest channels are tested to verify the EUT's using the frequency block required.

#### 1. Test Verdict:


The required frequency block is employed legally, the verdict is PASS.

#### 2. Test Plot:


##### I. GSM 850MHz Band for GMSK Modulation

The mobile transmitter frequency arrangement of the GSM 850 MHz band is

$$f(n) = 824.2 + 0.2*(n-128), 128 \leq n \leq 251$$



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 251)


## II. GSM 850MHz Band for 8PSK Modulation

The mobile transmitter frequency arrangement of the GSM 850 MHz band is

$$F(n) = 824.2 + 0.2*(n-128), 128 \leq n \leq 251$$



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 251)


### III. PCS 1900MHz Band for GMSK Modulation

The mobile transmitter frequency arrangement of the PCS1900 band is

$$f(n) = 1850.2 + 0.2*(n-512), 512 \leq n \leq 810$$



(Plot C: GSM 1900MHz Channel = 512)




(Plot D: GSM 1900MHz Channel = 810)


IV. PCS 1900MHz Band for 8PSK Modulation

The mobile transmitter frequency arrangement of the PCS1900 band is

$$F_i(n) = 1850.2 + 0.2*(n-512), 512 \leq n \leq 810$$



(Plot C: GSM 1900MHz Channel = 512)



(Plot D: GSM 1900MHz Channel = 810)

## 3.2 Conducted RF Output Power

### 3.2.1 Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

### 3.2.2 Test Description

See section 0 of this report.


### 3.2.3 Test Result

Here the lowest, middle and highest channels are selected to perform testing to verify the conducted RF output power of the EUT. For the GSM 850MHz operates at PCL=5 (where Power Class is 4), the rated conducted RF output power is 33dBm within the tolerance of  $\pm 3$ dB, and For the GSM 1900MHz operates at PCL=0 (where Power Class is 1), the rated conducted RF output power is 30dBm within the tolerance of  $\pm 3$ dB.


Test Plot:

#### I. GSM 850MHz Band for GMSK Modulation


Band	Channel	Frequency (MHz)	Measured Output Power		Rated Output Power		Verdict
			dBm	Refer to Plot	dBm	Tolerance (dB)	
GSM 850MHz	128	824.2	28.19	Plot A	33	$\pm 3$	PASS
	190	836.6	28.10	Plot B			PASS
	251	848.9	27.92	Plot C			PASS



(Plot A: GSM 850MHz Channel = 128)



(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)

II. GSM 850MHz Band for 8PSK Modulation

Band	Channel	Frequency (MHz)	Measured Output Power		Rated Output Power		Verdict
			dBm	Refer to Plot	dBm	Tolerance (dB)	
GSM 850MHz	128	824.2	29.01	Plot A	33	±3	PASS
	190	836.6	28.67	Plot B			PASS
	251	848.9	28.57	Plot C			PASS







(Plot C: GSM 850MHz Channel = 251)

### III. PCS 1900MHz Band for GMSK Modulation


Band	Channel	Frequency (MHz)	Measured Output Power		Rated Output Power		Verdict
			dBm	Refer to Plot	dBm	Tolerance (dB)	
GSM 1900MHz	512	1850.2	24.31	Plot D	30	±3	PASS
	661	1869.9	23.96	Plot E			PASS
	810	1909.9	23.69	Plot F			PASS



(Plot D: GSM 1900MHz Channel = 512)




(Plot E: GSM 1900MHz Channel = 661)




(Plot F: GSM 1900MHz Channel = 810)

IV. PCS 1900MHz Band for 8PSK Modulation

Band	Channel	Frequency (MHz)	Measured Output Power		Rated Output Power		Verdict
			dBm	Refer to Plot	dBm	Tolerance (dB)	
GSM 1900MHz	512	1850.0	25.08	Plot D	30	±3	PASS
	661	1880.0	24.13	Plot E			PASS
	810	1910.0	24.75	Plot F			PASS



(Plot D: GSM 1900MHz Channel = 512)




(Plot E: GSM 1900MHz Channel = 661)




1 Test Plot:


I. GSM 850MHz Band for GMSK Modulation



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)


II. GSM 850MHz Band for 8PSK Modulation



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)


### III. PCS 1900MHz Band for GMSK Modulation



(Plot D: GSM 1900MHz Channel = 512)




(Plot E: GSM 1900MHz Channel = 661)




(Plot F: GSM 1900MHz Channel = 810)


#### IV. PCS 1900MHz Band for 8PSK Modulation



(Plot D: GSM 1900MHz Channel = 512)



(Plot E: GSM 1900MHz Channel = 661)



(Plot F: GSM 1900MHz Channel = 810)

### 3.4 Frequency Stability


#### 3.4.1 Requirement

According to FCC section 22.355 and FCC section 24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  at intervals of not more than  $10^{\circ}\text{C}$ .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

#### 3.4.2 Test Description

1. Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Rohde&Schwarz	FSP30	101020	2007.11	1year
DC Power Supply	Good Will	GPS-3030DD	EF920938	2007.06	2year
Temperature Chamber	YinHe Experimental Equip.	HL4003T	(n.a.)	2007.03	1year

#### 3.4.3 Test Verdict

The nominal, highest and lowest extreme voltages are separately 3.7VDC, which are specified by the applicant; the normal temperature here used is  $25^{\circ}\text{C}$ . The frequency deviation limit is  $\pm 2.5\text{ppm}$ .

I. GSM 850 MHz Band for GMSK Modulation									
Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 128		Channel = 190		Channel = 251		
			Hz	Limit	Hz	Limit	Hz	Limit	
GSM 850MHz	3.7	-30	1.0	±2060.5	-4.0	±2091.5	-17.5	±2122.0	PASS
		-20	15.1		15.0		-10.2		
		-10	13.0		3.4		-3.7		
		0	10.2		12.0		1.3		
		+10	-10.6		-12.8		4.0		
		+20	7.0		-3.0		-18.9		
		+30	6.8		12.5		11.0		
		+40	8.2		-13.59		-3.2		
		+50	-20		7.0		-8.5		
II. GSM 850MHz Band for 8PSK Modulation									
Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 128		Channel = 190		Channel = 251		
			Hz	Limit	Hz	Limit	Hz	Limit	
GSM 850MHz	3.7	-30	-19.2	±2060.5	-1.6	±2091.5	-17.5	±2122.0	PASS
		-20	-4.0		-15.5		6.3		
		-10	-18.5		-4.0		10.5		
		0	-17.0		-15.6		6.0		
		+10	-15.3		12.8		-2.1		
		+20	8.8		6.0		-2.0		
		+30	20.0		17.2		3.8		
		+40	-5		-14.7		15.5		
		+50	-17.6		-18.0		10.1		
III. PCS 1900MHz Band for GMSK Modulation									
Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 512		Channel = 661		Channel = 810		
			Hz	Limit	Hz	Limit	Hz	Limit	
GSM 1900MHz	3.7	-30	-16.5	±1850.2	-3.5	±1880.0	1.0	±1909.8	PASS
		-20	-16.38		-18.0		-12.8		
		-10	-0.6		-15.6		-17.7		



Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 512		Channel = 661		Channel = 810		
			Hz	Limit	Hz	Limit	Hz	Limit	
		0	9.9		-10.0		9.0		
		+10	14.8		4.6		17.6		
		+20	14.7		19.9		-10.2		
		+30	-20.0		-17.0		-9.6		
		+40	-11.8		10.5		-9.0		
		+50	-10.2		-2.9		-8.8		

IV. PCS 1900MHz Band for 8PSK Modulation

Band	Test Conditions		Frequency Deviation						Verdict
	Power (VDC)	Temperature (°C)	Channel = 512		Channel = 661		Channel = 810		
			Hz	Limit	Hz	Limit	Hz	Limit	
GSM 1900MHz	3.7	-30	-13.5	±1850.2	-19.5	±1880.0	2.0	±1909.8	PASS
		-20	2.6		-19.0		0.0		
		-10	-2.0		-18.8		-1.5		
		0	-7.8		-11.8		7.9		
		+10	4.6		20.0		-18.8		
		+20	4.0		-12.8		-13		
		+30	11.8		16.0		1.7		
		+40	-15.2		13.5		-11		
		+50	13.6		17.8		5.5		

### 3.5 Conducted Spurious Emissions Test

#### 3.5.1 Requirement

According to FCC section 22.917(a) and FCC section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

#### 3.5.2 Test Description

See section 0 of this report.

#### 3.5.3 Test Result

The measurement frequency range is from 30MHz to the 10<sup>th</sup> harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.

##### 1. Test Verdict:


Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	8140.0	-26.81	Plot A.1/A.2	-13	PASS
	190	9260.0	-26.43	Plot B.1/B.2		PASS
	251	9320.0	-27.25	Plot C.1/C.2		PASS
GSM 1900MHz	512	8520.0	-25.87	Plot D.1/D.2	-13	PASS
	661	3000.0	-26.85	Plot E.1/E.2		PASS
	810	3480.0	-27.31	Plot F.1/F.2		PASS

##### 2. Test Plot for the Whole Measurement Frequency Range:


Note: the power of the EUT transmitting frequency should be ignored.

##### I. GSM 850MHz Band

Plot of Band Edge




(Plot A: GSM 850MHz Channel = 128)




(Plot C: GSM 850MHz Channel = 251)


### Plot of Spurious Emission



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)

## II. PCS 1900MHz Band

### Plot of Out-of-Band Emission




(Plot D: GSM 1900MHz Channel = 512)




(Plot F: GSM 1900MHz Channel = 810)


Plot of Spurious Emission



(Plot D: GSM 1900MHz Channel = 512)



(Plot E: GSM 1900MHz Channel = 661)



(Plot F: GSM 1900MHz Channel = 810)


### 3.6 Transmitter Radiated Power (EIRP/ERP)

#### 3.6.1 Requirement

According to FCC section 22.913, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2Watts e.i.r.p. peak power.

#### 3.6.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery charged with the AC Adapter, is located in a 3m Full-Anechoic Chamber; the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. GSM850MHz band Power Control Level (PCL) = 5 and Power Class = 4 and GSM1900MHz band Power Control Level (PCL) = 0 and Power Class = 1. A call is established between the EUT and the SS via a Common Antenna.

The Test Antenna is a Bi-Log one (used for 30MHz to 1GHz) or a Horn one (used for above 3GHz), and it's located at the same height as the EUT. The Filters consists of Notch Filters and High Pass Filter.

2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	Rohde&Schw	CMU200	105571	2007.11	1year



Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
	arz				
Spectrum Analyzer	Rohde&Schwarz	FSP30	101020	2007.11	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2006.08	2year
Test Antenna - Bi-Log	Rohde&Schwarz	HL562	100385	2007.11	1year
Test Antenna - Horn	Rohde&Schwarz	HF906	100565	2007.11	1year


### 3.6.3 Test Result

The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.


#### 1. Test Verdict:

#### I. GSM 850MHz Band for GMSK Modulation


Band	Channel	Frequency (MHz)	Measured ERP			Limit		Verdict
			dBm	W	Refer to Plot	dBm	W	
GSM 850MHz	128	824.27	23.13	0.20	Plot A	38.45	7	PASS
	190	836.59	24.16	0.26	Plot B			PASS
	251	848.84	24.05	0.25	Plot C			PASS



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)

## II. GSM 850MHz Band for 8PSK Modulation


Band	Chann el	Frequency (MHz)	Measured ERP			Limit		Verdict
			dBm	W	Refer to Plot	dBm	W	
GSM 850MHz	128	824.12	27.80	0.60	Plot A	38.45	7	PASS
	190	836.68	26.42	0.43	Plot B			PASS
	251	848.91	28.27	0.67	Plot C			PASS



(Plot A: GSM 850MHz Channel = 128)




(Plot B: GSM 850MHz Channel = 190)




(Plot C: GSM 850MHz Channel = 251)

### III. PCS 1900MHz Band for GMSK Modulation


Band	Channel	Frequency (MHz)	Measured ERP			Limit		Verdict
			dBm	W	Refer to Plot	dBm	W	
GSM 1900MHz	512	1850.2	26.77	0.47	Plot D	33	2	PASS
	661	1869.9	28.17	0.65	Plot E			PASS
	810	1909.9	27.41	0.55	Plot F			PASS



(Plot D: GSM 1900MHz Channel = 512)




(Plot E: GSM 1900MHz Channel = 661)




(Plot F: GSM 1900MHz Channel = 810)

IV. PCS 1900MHz Band for 8PSK Modulation


Band	Channel	Frequency (MHz)	Measured ERP			Limit		Verdict
			dBm	W	Refer to Plot	dBm	W	
GSM 1900MHz	512	1850.2	27.83	0.60	Plot D	33	2	PASS
	661	1880.0	26.43	0.43	Plot E			PASS
	810	1909.9	26.49	0.44	Plot F			PASS



(Plot D: GSM 1900MHz Channel = 512)



(Plot E: GSM 1900MHz Channel = 661)



(Plot F: GSM 1900MHz Channel = 810)

### 3.7 Radiated Spurious Emissions Test

#### 3.7.1 Requirement

According to FCC section 22.917(a) and section 24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43+10*\log(P)$ dB. This calculated to be -13dBm.

#### 3.7.2 Test Description

See section 3.7.2 of this report.

#### 3.7.3 Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

##### 1. Test Verdict:


Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)		Refer to Plot	Limit (dBm)	Verdict
			Test Antenna Horizontal	Test Antenna Vertical			
GSM 850MHz	128	824.2	< -30	< -30	Plot A.1/A.2	-13	PASS
	190	836.6	< -30	< -30	Plot B.1/B.2		PASS
	251	848.8	< -30	< -30	Plot C.1/C.2		PASS
GSM 1900MHz	512	1850.2	< -25	< -25	Plot D.1/D.2	-13	PASS
	661	1880.0	< -25	< -25	Plot E.1/E.2		PASS
	810	1909.8	< -25	< -25	Plot F.1/F.2		PASS

##### 2. Test Plot for the Whole Measurement Frequency Range:


Note: the power of the EUT transmitting frequency should be ignored.




(Plot A.1: GSM 850MHz Channel = 128, Test Antenna Horizontal)




(Plot A.2: GSM 850MHz Channel = 128, Test Antenna Vertical)




(Plot B.1: GSM 850MHz Channel = 190, Test Antenna Horizontal)




(Plot B.2: GSM 850MHz Channel = 190, Test Antenna Vertical)




(Plot C.1: GSM 850MHz Channel = 251, Test Antenna Horizontal)




(Plot C.2: GSM 850MHz Channel = 251, Test Antenna Vertical)




(Plot D.1: GSM 1900MHz Channel = 512, Test Antenna Horizontal)




(Plot D.2: GSM 1900MHz Channel = 512, Test Antenna Vertical)




(Plot E.1: GSM 1900MHz Channel = 661, Test Antenna Horizontal)



(Plot E.2: GSM 1900MHz Channel = 661, Test Antenna Vertical)




(Plot F.1: GSM 1900MHz Channel = 810, Test Antenna Horizontal)






(Plot F.2: GSM 1900MHz Channel = 810, Test Antenna Vertical)

Appendix I: Photographs of the EUT











## Appendix II: Photographs of the Test Configuration

### 1. Conducted RF Test



## 2. Radiated RF Test



\*\* END OF REPORT \*\*