


# FCC Test Report

**APPLICANT** : ZTE CORPORATION  
**EQUIPMENT** : WCDMA/GSM(GPRS) Dual-Mode Digital Mobile Phone  
**BRAND NAME** : ZTE  
**MODEL NAME** : Z795G  
**FCC ID** : Q78-Z795G  
**STANDARD** : FCC 47 CFR FCC Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on Apr. 10, 2013 and completely tested on Apr. 18, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**

## TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT .....	4
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Feature of Equipment Under Test.....	5
1.4. Product Specification of Equipment Under Test .....	6
1.5. Test Site .....	7
1.6. Applied Standards .....	7
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1. Test Mode .....	8
2.2. Connection Diagram of Test System .....	10
2.3. Support Unit used in test configuration and system.....	12
2.4. Test Software .....	12
<b>3. TEST RESULT.....</b>	<b>13</b>
3.1. Test of AC Conducted Emission Measurement .....	13
3.2. Test of Radiated Emission Measurement .....	19
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>25</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>26</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT</b>	
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>	





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 11.97 dB at 0.580 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.17 dB at 35.820 MHz

## 1. General Description

### 1.1. Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

### 1.2. Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

### 1.3. Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA/GSM(GPRS) Dual-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z795G
FCC ID	Q78-Z795G
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSDPA/WLAN 11bgn/ Bluetooth/Bluetooth4.0 - LE
HW Version	whwA
SW Version	1.0.0
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency Range</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz
<b>Antenna Type</b>	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth BDR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK Bluetooth v4.0 - LE: GFSK GPS : BPSK

## 1.5. Test Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.		
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC/IC Registration No.</b>
	CO01-KS	03CH01-KS	149928/4086E-1

## 1.6. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2003

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 KHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.


Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	☒
2.	Data application transferred mode (EUT with PC/notebook)	☒	☒	☒

#### Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera <Fig. 1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 <Fig. 1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + GPS Rx <Fig. 2> Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with PC) + Earphone <Fig. 3>
Radiated Emissions < 1GHz	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera <Fig. 1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 <Fig. 1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + GPS Rx <Fig. 2> Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone <Fig. 4>
Radiated Emissions ≥ 1GHz	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera <Fig. 1> Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone <Fig. 4>
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>The worst case of AC Conducted Emission is mode 3; the test data of this mode was reported.</li> <li>The worst case of Radiated Emissions is mode 1, and the USB Link mode of Radiated Emissions is mode 4; the test data of these modes were reported.</li> <li>Link with PC / Notebook means data application transferred mode between EUT and PC / Notebook.</li> </ol>		


## 2.2. Connection Diagram of Test System




<Fig. 1>



<Fig. 2>



<Fig. 3>



<Fig. 4>

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
5.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
6.	Monitor	DELL	E1910Hc	FCC DoC	Shielded, 1.2 m	Unshielded, 1.8 m
7.	(USB) Mouse	DELL	N231	FCC DoC	Shielded, 1.8 m	N/A
8.	(USB) Keyboard	DELL	SK-8115	FCC DoC	Shielded, 1.8 m with core	N/A
9.	PC	DELL	MT320	FCC DoC	N/A	Unshielded, 1.8 m
10.	Printer	HP	Laser Jet 1018	FCC DoC	Shielded, 1.8 m	Unshielded, 1.8 m
11.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
12.	iPod	Apple	A1199	FCC DoC	Shielded, 1.2 m	N/A

### 2.4. Test Software

The EUT was in GSM or WCDMA idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Execute the program, "Winthrax" under WIN7 installed in notebook or PC for files transfer with EUT via USB cable.
2. Turn on GPS function to make the EUT receive continuous signals from GPS station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 KHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 3	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS  
 Condition: FCC CLASS-B LISN-L20130306 LINE  
 Project : (FC) 341002  
 mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.58	34.03	-11.97	46.00	23.20	0.20	10.63	Average
2	0.58	42.63	-13.37	56.00	31.80	0.20	10.63	QP
3	0.65	31.24	-14.76	46.00	20.40	0.20	10.64	Average
4	0.65	40.34	-15.66	56.00	29.50	0.20	10.64	QP
5	0.72	33.34	-12.66	46.00	22.51	0.19	10.64	Average
6	0.72	41.34	-14.66	56.00	30.51	0.19	10.64	QP
7	0.77	41.12	-14.88	56.00	30.30	0.18	10.64	QP
8	0.77	30.22	-15.78	46.00	19.40	0.18	10.64	Average
9	0.84	39.89	-16.11	56.00	29.09	0.15	10.65	QP
10	0.84	30.59	-15.41	46.00	19.79	0.15	10.65	Average
11	0.90	29.57	-16.43	46.00	18.80	0.12	10.65	Average
12	0.90	41.87	-14.13	56.00	31.10	0.12	10.65	QP
13	0.99	40.15	-15.85	56.00	29.40	0.10	10.65	QP
14	0.99	32.65	-13.35	46.00	21.90	0.10	10.65	Average
15	1.04	40.35	-15.65	56.00	29.60	0.10	10.65	QP
16	1.04	31.35	-14.65	46.00	20.60	0.10	10.65	Average
17	1.11	40.15	-15.85	56.00	29.40	0.10	10.65	QP
18	1.11	30.55	-15.45	46.00	19.80	0.10	10.65	Average
19	1.15	42.26	-13.74	56.00	31.50	0.10	10.66	QP
20	1.15	31.96	-14.04	46.00	21.20	0.10	10.66	Average
21	1.21	31.06	-14.94	46.00	20.30	0.10	10.66	Average
22	1.21	40.46	-15.54	56.00	29.70	0.10	10.66	QP
23	1.30	42.36	-13.64	56.00	31.60	0.10	10.66	QP
24	1.30	32.16	-13.84	46.00	21.40	0.10	10.66	Average
25	1.38	41.37	-14.63	56.00	30.60	0.10	10.67	QP
26	1.38	32.67	-13.33	46.00	21.90	0.10	10.67	Average
27	1.52	41.98	-14.02	56.00	31.20	0.10	10.68	QP



Test Mode :	Mode 3	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS  
 Condition: FCC CLASS-B LISN-L20130306 LINE  
 Project : (FC) 341002  
 mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
28	1.52	31.88	-14.12	46.00	21.10	0.10	10.68	Average
29	1.59	40.89	-15.11	56.00	30.10	0.10	10.69	QP
30	1.59	31.29	-14.71	46.00	20.50	0.10	10.69	Average
31	1.66	38.69	-17.31	56.00	27.90	0.10	10.69	QP
32	1.66	29.59	-16.41	46.00	18.80	0.10	10.69	Average
33	2.45	38.14	-17.86	56.00	27.30	0.11	10.73	QP
34	2.45	30.54	-15.46	46.00	19.70	0.11	10.73	Average
35	2.72	37.67	-18.33	56.00	26.80	0.12	10.75	QP
36	2.72	29.27	-16.73	46.00	18.40	0.12	10.75	Average
37	5.33	33.96	-16.04	50.00	22.90	0.20	10.86	Average
38	5.33	40.36	-19.64	60.00	29.30	0.20	10.86	QP
39	5.56	36.46	-13.54	50.00	25.40	0.20	10.86	Average
40	5.56	42.76	-17.24	60.00	31.70	0.20	10.86	QP
41	6.02	36.28	-13.72	50.00	25.20	0.20	10.88	Average
42	6.02	43.48	-16.52	60.00	32.40	0.20	10.88	QP
43	6.49	35.90	-14.10	50.00	24.80	0.20	10.90	Average
44	6.49	43.30	-16.70	60.00	32.20	0.20	10.90	QP
45	7.14	40.32	-19.68	60.00	29.20	0.20	10.92	QP
46	7.14	32.72	-17.28	50.00	21.60	0.20	10.92	Average



Test Mode :	Mode 3	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-KS  
 Condition: FCC CLASS-B LISN-N20130306 NEUTRAL  
 Project : (FC) 341002  
 mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.53	31.21	-14.79	46.00	20.29	0.29	10.63	Average
2	0.53	40.01	-15.99	56.00	29.09	0.29	10.63	QP
3	0.74	28.53	-17.47	46.00	17.70	0.19	10.64	Average
4	0.74	37.33	-18.67	56.00	26.50	0.19	10.64	QP
5	0.93	31.76	-14.24	46.00	21.00	0.11	10.65	Average
6	0.93	41.26	-14.74	56.00	30.50	0.11	10.65	QP
7	1.00	32.55	-13.45	46.00	21.80	0.10	10.65	Average
8	1.00	41.35	-14.65	56.00	30.60	0.10	10.65	QP
9	1.05	39.35	-16.65	56.00	28.60	0.10	10.65	QP
10	1.05	30.75	-15.25	46.00	20.00	0.10	10.65	Average
11	1.13	32.96	-13.04	46.00	22.20	0.10	10.66	Average
12	1.13	41.54	-14.46	56.00	30.78	0.10	10.66	QP
13	1.24	31.46	-14.54	46.00	20.70	0.10	10.66	Average
14	1.24	40.86	-15.14	56.00	30.10	0.10	10.66	QP
15	1.31	32.77	-13.23	46.00	22.00	0.10	10.67	Average
16	1.31	40.37	-15.63	56.00	29.60	0.10	10.67	QP
17	1.50	30.48	-15.52	46.00	19.70	0.10	10.68	Average
18	1.50	39.28	-16.72	56.00	28.50	0.10	10.68	QP
19	1.67	37.59	-18.41	56.00	26.80	0.10	10.69	QP
20	1.67	29.89	-16.11	46.00	19.10	0.10	10.69	Average
21	2.41	30.54	-15.46	46.00	19.71	0.11	10.72	Average
22	2.41	37.54	-18.46	56.00	26.71	0.11	10.72	QP
23	2.90	29.01	-16.99	46.00	18.11	0.13	10.77	Average
24	2.90	36.41	-19.59	56.00	25.51	0.13	10.77	QP
25	5.87	34.07	-15.93	50.00	23.00	0.20	10.87	Average
26	5.87	41.87	-18.13	60.00	30.80	0.20	10.87	QP
27	6.22	34.79	-15.21	50.00	23.70	0.20	10.89	Average



Test Mode :	Mode 3	Temperature :	19~20°C
Test Engineer :	Tom Wang	Relative Humidity :	39~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + GPS Rx		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS  
 Condition: FCC CLASS-B LISN-N20130306 NEUTRAL  
 Project : (FC) 341002  
 mode : Mode 3

	Freq	Level	Over	Limit	Read	LISM	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
28	6.22	41.69	-18.31	60.00	30.60	0.20	10.89	QP
29	6.70	32.81	-17.19	50.00	21.70	0.20	10.91	Average
30	6.70	40.21	-19.79	60.00	29.10	0.20	10.91	QP

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments


See list of measuring instruments of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBuV/m) = 20 log Emission level (uV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	Temperature :	21~22°C
Test Engineer :	Jun Liu	Relative Humidity :	40~41%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera		




Site : 03CH01-KS  
 Condition : FCC CLASS-B 3m LF\_ANT\_100803 HORIZONTAL  
 : RBW:100.000KHz VBW:300.000KHz SWT:Auto  
 EUT : (FC) 341002  
 Mode : mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	33.88	21.95	-18.05	40.00	39.63	15.56	0.36	33.60	100	156 Peak
2	102.75	23.26	-20.24	43.50	45.41	10.87	0.59	33.61	---	---
3	282.20	23.68	-22.32	46.00	43.40	12.70	0.97	33.39	---	---
4	451.95	22.49	-23.51	46.00	38.17	16.32	1.20	33.20	---	---
5	639.16	26.56	-19.44	46.00	39.21	18.85	1.45	32.95	---	---
6	677.96	24.37	-21.63	46.00	36.67	19.13	1.48	32.91	---	---



Test Mode :	Mode 1	Temperature :	21~22°C
Test Engineer :	Jun Liu	Relative Humidity :	40~41%
Test Distance :	3m	Polarization :	Vertical
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera		




Site : 03CH01-KS  
 Condition : FCC CLASS-B 3m LF\_ANT\_100803 VERTICAL  
 : RBW:100.000KHz VBW:300.000KHz SWT:Auto  
 EUT : (FC) 341002  
 Mode : mode 1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 !	35.82	36.83	-3.17	40.00	55.43	14.65	0.37	33.62	111	123 Peak
2	125.06	26.57	-16.93	43.50	47.77	11.75	0.65	33.60	---	---
3	225.94	25.02	-20.98	46.00	47.06	10.59	0.87	33.50	---	---
4	250.19	24.52	-21.48	46.00	45.04	12.00	0.92	33.44	---	---
5	400.54	21.85	-24.15	46.00	38.01	16.00	1.15	33.31	---	---
6	677.96	27.00	-19.00	46.00	39.30	19.13	1.48	32.91	---	---



Test Mode :	Mode 4	Temperature :	21~22°C
Test Engineer :	Jun Liu	Relative Humidity :	40~41%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone		




Site : 03CH01-KS  
 Condition : FCC CLASS-B 3m LF\_ANT\_100803 HORIZONTAL  
 EUT : (FC) 341002  
 Mode : mode 4

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	207.51	35.02	-8.48	43.50	58.40	9.34	0.83	33.55	---	---	Peak
2	239.52	38.66	-7.34	46.00	59.71	11.51	0.90	33.46	---	---	Peak
3 !	314.21	41.46	-4.54	46.00	60.45	13.36	1.02	33.37	100	0	Peak
4	345.25	39.88	-6.12	46.00	57.75	14.40	1.09	33.36	---	---	Peak
5	591.63	31.26	-14.74	46.00	44.24	18.59	1.39	32.96	---	---	Peak
6	750.71	34.07	-11.93	46.00	45.36	19.90	1.59	32.78	---	---	Peak



Test Mode :	Mode 4	Temperature :	21~22°C
Test Engineer :	Jun Liu	Relative Humidity :	40~41%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone		



Site : 03CH01-KS  
 Condition : FCC CLASS-B 3m LF\_ANT\_100803 VERTICAL  
 EUT : (FC) 341002  
 Mode : mode 4

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	34.85	31.74	-8.26	40.00	49.88	15.10	0.37	33.61	100	25 Peak
2	195.87	31.27	-12.23	43.50	55.22	8.80	0.81	33.56	---	---
3	237.58	33.67	-12.33	46.00	54.83	11.40	0.90	33.46	---	---
4	344.28	35.44	-10.56	46.00	53.34	14.37	1.09	33.36	---	---
5	480.08	35.41	-10.59	46.00	50.42	16.87	1.28	33.16	---	---
6	750.71	30.99	-15.01	46.00	42.28	19.90	1.59	32.78	---	---



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz	Jun. 01, 2012	Apr. 18, 2013	May 31, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 29, 2012	Apr. 18, 2013	Dec. 28, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Dec. 29, 2012	Apr. 18, 2013	Dec. 28, 2013	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	N/A	Nov. 15, 2012	Apr. 18, 2013	Nov. 14, 2013	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESC1	100534	9kHz~3GHz	Nov. 08, 2012	Apr. 14, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	Jun. 01, 2012	Apr. 14, 2013	May 31, 2013	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Apr. 14, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Apr. 14, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	Jun. 01, 2012	Apr. 14, 2013	May 31, 2013	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Apr. 14, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
GPS Station	ADIVIC	MP9000	MP9000-111046	N/A	N/A	Apr. 14, 2013~ Apr. 18, 2013	N/A	-
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 29, 2012	Apr. 14, 2013~ Apr. 18, 2013	Dec. 28, 2013	-

## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
-------------------------------------------------------------------------	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.54
-------------------------------------------------------------------------	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.72
-------------------------------------------------------------------------	------



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP341002 as below.