

Simultaneous Transmission SAR Evaluation for ZTE3200 and iPod Touch 2/3


Because the iPod Touch can't set it up into engineer mode for continuous transmission, we follow two steps as below to transmit a large file to evaluate the worst SAR of iPod Touch.

Step 1: The iPod Touch should NOT be mounted in the ZTE3200. Instead it should be tested by itself. It should be set to communicate with a WiFi access point at some distance away so that the iPod Touch will be operating at the maximum power level. The SAR readings should then be measured at 0 cm from the iPod Touch on the worst case frequency and in the worst case position as documented in Apple's SAR report.

Step 2: The iPod Touch should be mounted in the ZTE3200. However, the Peel should be turned off. Again the iPod Touch should be set to communicate with a WiFi access point at some distance away so that the iPod Touch will be operating at the maximum power level. The SAR readings should then be taken at 10 mm from the ZTE3200/iPod Touch on the same frequency as the Step 1. It should take these measurements using the same position as the Step 1.

The setup steps for large-file-transfer from iPod Touch to Laptop PC are as below.

1. Install FTP application software into both iPod Touch and laptop PC.
2. Set the Access Point to use 802.11b mode channel 6 only.
3. Make both iPod Touch and laptop PC linking with Access Point.
4. Execute FTP software of iPod Touch to transfer one large file (file name: test, file size: 1GB) to laptop PC through Access Point.
5. Use a Spectrum Analyzer to monitor and make sure the WLAN continuous transmission during SAR testing.



<Scaling Up Factor>

| iPod Touch Version | Apple Report (0 mm Gap) | iPod Big-File-Transfer (0 mm Gap) | Scaling Up Factor |
|--------------------------------|----------------------------|--------------------------------------|-------------------|
| iPod Touch 3 SAR _{1g} | 1.20 | 0.658 | 1.82 |
| iPod Touch 2 SAR _{1g} | 1.30 | 0.627 | 2.07 |

Note:

1. The test condition for iPod Touch WLAN SAR testing is Front Face of iPod Touch, and channel 6 of 802.11b mode.
2. Scaling Up Factor = SAR of Apple Report / SAR of iPod Big-File-Transfer

<Worst SAR Calculating for iPod Touch>

| iPod Touch Version | iPod Big-File-Transfer (10 mm Gap) | Scaling Up Factor | Calculated Worst SAR |
|--------------------------------|---------------------------------------|-------------------|----------------------|
| iPod Touch 3 SAR _{1g} | 0.063 | 1.82 | 0.115 |
| iPod Touch 2 SAR _{1g} | 0.049 | 2.07 | 0.101 |

Note:

1. Calculated Worst SAR = SAR of iPod Big-File-Transfer *Scaling Up Factor

Simultaneous Transmission SAR Evaluation for 10 mm Gap

<ZTE3200 + iPod Touch 3>

| Position | ZTE3200 CDMA2000 BC0 | ZTE3200 802.11b/g | iPod Touch 3 802.11b/g | Max. SAR Summation |
|-------------|----------------------------|----------------------|---------------------------|-----------------------|
| Front Face | 0.298 | 0 | 0.115 | 0.413 |
| Rear Face | 1.33 | | | 1.445 |
| Right Side | 0.551 | | | 0.666 |
| Left Side | 0.366 | | | 0.481 |
| Top Side | 0.075 | | | 0.19 |
| Bottom Side | 0.012 | | | 0.127 |
| | | | | |
| Position | ZTE3200 CDMA2000 BC1 | ZTE3200 802.11b/g | iPod Touch 3 802.11b/g | Max. SAR Summation |
| Front Face | 0.608 | 0 | 0.115 | 0.723 |
| Rear Face | 1.32 | | | 1.435 |
| Right Side | 1.38 | | | 1.495 |
| Left Side | 0.122 | | | 0.237 |
| Top Side | 0.244 | | | 0.359 |
| Bottom Side | 0.066 | | | 0.181 |
| | | | | |

Note: According to KDB 648474, the WLAN SAR for ZTE3200 is not required because its average power is less than 60/f.

<ZTE3200 + iPod Touch 2>

| Position | ZTE3200 CDMA2000 BC0 | ZTE3200 802.11b/g | iPod Touch 2 802.11b/g | Max. SAR Summation |
|-------------|----------------------------|----------------------|---------------------------|-----------------------|
| Front Face | 0.284 | 0 | 0.101 | 0.385 |
| Rear Face | 1.22 | | | 1.321 |
| Right Side | 0.591 | | | 0.692 |
| Left Side | 0.415 | | | 0.516 |
| Top Side | 0.077 | | | 0.178 |
| Bottom Side | 0.015 | | | 0.116 |
| | | | | |
| Position | ZTE3200 CDMA2000 BC1 | ZTE3200 802.11b/g | iPod Touch 2 802.11b/g | Max. SAR Summation |
| Front Face | 0.449 | 0 | 0.101 | 0.55 |
| Rear Face | 1.26 | | | 1.361 |
| Right Side | 1.19 | | | 1.291 |
| Left Side | 0.189 | | | 0.29 |
| Top Side | 0.23 | | | 0.331 |
| Bottom Side | 0.048 | | | 0.149 |
| | | | | |

Note: According to KDB 648474, the WLAN SAR for ZTE3200 is not required because its average power is less than 60/f.

<Conclusion>

According KDB 648474, the simultaneous transmission SAR for ZTE3200 WWAN, ZTE3200 WLAN and iPod Touch WLAN was not required, because all SAR summations are less than 1.6 W/kg.

<SAR Plots for iPod Touch Big-File-Transfer>

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 10/16/2010

#26 802.11b Ch06_iPod Touch 3 alone_Front Face_0 mm Gap_iPod Big-File-Transfer

DUT: 000802-01

Communication System: Wifi; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: MSL_2450_101014 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.91$ mho/m; $\epsilon_r = 54$; $\rho =$

1000 kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.84, 6.84, 6.84); Calibrated: 11/23/2009

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1210; Calibrated: 2009/11/16

- Phantom: SAM1; Type: SAM; Serial: TP-1477

- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

Ch6/Area Scan (61x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.462 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.54 V/m; Power Drift = -0.084 dB

Peak SAR (extrapolated) = 1.67 W/kg

SAR(1 g) = 0.658 mW/g; SAR(10 g) = 0.224 mW/g

Maximum value of SAR (measured) = 1.1 mW/g



#27 802.11b Ch06_ZTE3200 + iPod Touch 3_Front Face_10 mm Gap_iPod Big-File-Transfer

DUT: 000802-01

Communication System: Wifi; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: MSL_2450_101014 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.91$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.84, 6.84, 6.84); Calibrated: 11/23/2009

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1210; Calibrated: 2009/11/16

- Phantom: SAM1; Type: SAM; Serial: TP-1477

- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

Ch6/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.197 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.63 V/m; Power Drift = 0.024 dB

Peak SAR (extrapolated) = 0.107 W/kg

SAR(1 g) = 0.063 mW/g; SAR(10 g) = 0.032 mW/g

Maximum value of SAR (measured) = 0.065 mW/g



#28 802.11b Ch06 iPod Touch 2 alone Front Face_0 mm Gap iPod Big-File-Transfer

DUT: 000802-01

Communication System: Wifi; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: MSL_2450_101014 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.91$ mho/m; $\epsilon_r = 54$; $\rho =$

1000 kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.84, 6.84, 6.84); Calibrated: 11/23/2009

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn1210; Calibrated: 2009/11/16

- Phantom: SAM1; Type: SAM; Serial: TP-1477

- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

Ch6/Area Scan (61x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.346 mW/g


Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.02 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 0.627 mW/g; SAR(10 g) = 0.208 mW/g

Maximum value of SAR (measured) = 1 mW/g



#29 802.11b Ch06_ZTE3200 + iPod Touch 2_Front Face_10 mm Gap_iPod Big-File-Transfer

DUT: 0O0802-01

Communication System: Wifi; Frequency: 2437 MHz; Duty Cycle: 1:1
Medium: MSL_2450_101014 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.91$ mho/m; $\epsilon_r = 54$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.3 °C; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.84, 6.84, 6.84); Calibrated: 11/23/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2009/11/16
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

Ch6/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.092 mW/g

Ch6/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.15 V/m; Power Drift = -0.008 dB
Peak SAR (extrapolated) = 0.076 W/kg
SAR(1 g) = 0.049 mW/g; SAR(10 g) = 0.023 mW/g
Maximum value of SAR (measured) = 0.053 mW/g

Ch6/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.15 V/m; Power Drift = -0.008 dB
Peak SAR (extrapolated) = 0.108 W/kg
SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.021 mW/g
Maximum value of SAR (measured) = 0.045 mW/g

