

Appendix F. FCC 3G SAR Measurement Procedures

Conducted Output Power:


The EUT was tested according to the requirements of the FCC 3G procedures and the 3.1.2.3.4.

A detailed analysis of the output power verification is provided as the table below:

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Mid. Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				1013	384	777
CDMA2000 Cellular	FCH	1	1	1	55	Full	All Up	23.78	23.53	23.69
		3	3	3	55	Full	All Up	23.95	23.54	23.74
	FCH+SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	23.86	23.52	23.74
	EVDO Rev.0*	Subtype:0				RTAP 9.6	All Up	23.93	23.67	23.93
	EVDO Rev.0*	Subtype:0				RTAP 38.4	All Up	23.92	23.73	23.93
	EVDO Rev.0*	Subtype:0				RTAP 153.6	All Up	23.82	23.84	23.87
	EVDO Rev.A*	Subtype:0				RETAP 128	All Up	23.84	23.56	23.61
	EVDO Rev.A*	Subtype:0				RETAP 2048	All Up	23.91	23.89	23.94
	EVDO Rev.A*	Subtype:0				RETAP 12288	All Up	23.92	23.91	23.90

Function Type	Reverse Traffic Channel	Test Mode	Radio Configuration		Service Option	Data Rates (kbps)	Power Control	Low Ch	Mid. Ch	High Ch
			Forward Traffic Channel (Fwd)	Reverse Traffic Channel (Rvs)				25	600	1175
CDMA2000 PCS	FCH	1	1	1	55	Full	All Up	22.41	22.38	22.29
		3	3	3	55	Full	All Up	22.59	22.45	22.35
	FCH+SCH	3	3	3	32	FCH:Full,SCH 9.6	All Up	22.48	22.41	22.30
	EVDO Rev.0*	Subtype:0				RTAP 9.6	All Up	22.46	22.42	22.40
	EVDO Rev.0*	Subtype:0				RTAP 38.4	All Up	22.49	22.48	22.36
	EVDO Rev.0*	Subtype:0				RTAP 153.6	All Up	22.53	22.52	22.44
	EVDO Rev.A*	Subtype:0				RETAP 128	All Up	22.41	22.31	22.12
	EVDO Rev.A*	Subtype:0				RETAP 2048	All Up	22.57	22.50	22.48
	EVDO Rev.A*	Subtype:0				RETAP 12288	All Up	22.49	22.58	22.55

CDMA2000 Setup Configuration:



Setup Configuration

1. The EUT was connected to System Simulator, Agilent 8960. Refer to the drawing of Setup Configuration.
2. The RF path losses were compensated into the measurements.
3. A call was established between EUT and System Simulator with following setting:
 - a. For 1xRTT, set the Radio Configuration and the Service Option
 - b. For 1xEV-DO, set the Protocol Release and Data Rate
 - c. Set the Power Control to All Up Bits
4. The transmitted maximum output power was recorded.

Call Setup Screen											
Call Control		Active Cell Operating Mode								Call Parms	
Mobile Station Information ESN (Hex): ESN (Dec): NCC: NMC: NSIN: Slot Class: Slot Cycle Index: ----- Protocol Revision:										Cell Power	
										-86.00	
										dBm/1.23 MHz	
										Cell Band	
										US PCS	
										Channel	
										1175	
										Protocol Rev	
										6 (IS-2000-0)	
										Radio Config	
								(Fud1, Rvs1)			
								S055 (Loopback)			
Close Menu		FCH Service Option Setup Service Option S01 (Voice) S02 (Loopback) S03 (Voice) S06 (SMS) S055 (Loopback) S068 (Voice)								Value	
		S055 (Loopback) S09 (Loopback) S055 (Loopback) S055 (Loopback) S055 (Loopback)								S055 (Loopback)	
		Active Cell				Sys Type: IS-2000					
		Idle									
		IntRef Offset									
						1 of 4					

1xRTT setting for Radio Configuration 1 with Service Option 55

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Params		
Close Menu	Mobile Station Information ESN (Hex): ESN (Dec): MCC: MNC: MSIN: Slot Class: Slot Cycle Index: ---- Protocol Revision:						Cell Power -86.00 dBm/1.23 MHz Cell Band US PCS Channel 1175		
	FCH Service Option Setup						Value		
	Service Option for Fud3, Rvs3						S055 (Loopback)		
	Service Option for S01 (Voice)						S09 (Loopback)		
	Service Option for S02 (Loopback)						S055 (Loopback)		
	Service Option for S03 (Voice)						S055 (Loopback)		
	Service Option for S06 (SRS)						S055 (Loopback)		
	S055 (Loopback)								
	S032 (+ F-SCH)								
							Protocol Rev 6 (IS-2000-0)		
						Radio Config (Fud3, Rvs3) S055 (Loopback)			
						FCH Service Option Setup			
Active Cell Idle						Sys Type: IS-2000			
IntRef Offset						1 of 4			

1xRTT setting for Radio Configuration 3 with Service Option 55

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Params		
Close Menu	Mobile Station Information ESN (Hex): ESN (Dec): MCC: MNC: MSIN: Slot Class: Slot Cycle Index: ---- Protocol Revision:						Cell Power -86.00 dBm/1.23 MHz Cell Band US PCS Channel 1175		
	FCH Service Option Setup						Value		
	Service Option for Fud3, Rvs3						S055 (Loopback)		
	Service Option for S02 (Loopback)						S09 (Loopback)		
	Service Option for S03 (Voice)						S032 (+ SCH)		
	Service Option for S06 (SRS)						S055 (Loopback)		
	S055 (Loopback)						S055 (Loopback)		
	S032 (+ F-SCH)								
	S032 (+ SCH)								
							Protocol Rev 6 (IS-2000-0)		
						Radio Config (Fud3, Rvs3) S032 (+ SCH)			
						FCH Service Option Setup			
Active Cell Idle						Sys Type: IS-2000			
IntRef Offset						1 of 4			

1xRTT setting for Radio Configuration 3 with Service Option 32

Call Setup Screen									
Call Control		Active Cell Operating Mode					Call Params		
Operating Mode		Access Terminal Information (AT Reported) Session Seed: Hardware ID Type (Hex): Hardware ID (Hex): Hardware ID (Decimal):					Rvs Power Ctrl		
Active Cell							Rvs Power Ctrl	Active bits	
Start Data Connection		Access Terminal Information (AN Assigned) UATI 024: ---- UATI Color Code: ---- NAC Index: ----					Pur Ctrl Step	1.0 dB	
							Call Drop Timer	On	
Close Session		Protocol Release Session App: 0 (1xEV-DO) Test Applica: A (1xEV-DO-A) Limited TAP: B (1xEV-DO-B) AT Directed: DRC Value Fi: ACK Channel:					Call Limit Mode	Off	
							Protocol Rel	0 (1xEV-DO)	
Handoff Setup									
AT Max Power	23 dBm/1.23MHz								
		Active Cell		Sys Type: IS-856					
		Idle							
1 of 3		IntRef	Offset		PLSub0	RTAP	2 of 3		

1xEV-DO setting for Protocol Release (Rev.0 or Rev.A)

Call Setup Screen									
Call Control		Active Cell Operating Mode					Call Params		
Operating Mode		Access Terminal Information (AT Reported) Session Seed: Hardware ID Type (Hex): Hardware ID (Hex): Hardware ID (Decimal):					Cell Power	-86.00	
Active Cell							Cell Power	dBm/1.23 MHz	
Start Data Connection		Access Terminal Information (AN Assigned) UATI 024: ---- UATI Color Code: ---- NAC Index: ----					Cell Band	US PCS	
							Channel	1175	
Close Session		RTAP Rate Session App: 9.6 kbps Test Applica: 19.2 kbps Limited TAP: 38.4 kbps AT Directed: 76.8 kbps DRC Value Fi: 153.6 kbps ACK Channel:					Application Config		
							FTAP Rate	307.2 kbps (2 Slot, QPSK)	
Handoff Setup							RTAP Rate	9.6 kbps	
AT Max Power	23 dBm/1.23MHz								
		Active Cell		Sys Type: IS-856					
		Idle							
1 of 3		IntRef	Offset		PLSub0	RTAP	1 of 3		

1xEV-DO setting for RTAP data rate (9.6 or 38.4 or 153.6 kbps)

Call Setup Screen									
Call Control		Active Cell Operating Mode					Call Params		
Operating Mode	Active Cell	Access Terminal Information (AT Reported) Session Seed: Hardware ID Type (Hex): Hardware ID (Hex): Hardware ID (Decimal):					Cell Power -86.00 dBm/1.23 MHz		
		Access Terminal Information (AN Assigned) UATI 024: ---- UATI Color Code: ---- MAC Index: ----					Cell Band US PCS		
Start Data Connection		Application Configuration Session App: R-Data Packet Size Enhanced Te: 128 AT Directed: 256 DRC Value Fi: 512 ACK Channel: 768 Reverse Data: 1024 Expected En: 1536					Channel 1175		
Close Session		Application Capacity kbps					Application Config		
Handoff Setup							F-Traffic Format 4 (1024,2,128) (307.2k, QPSK)		
AT Max Power	23 dBm/1.23MHz						R-Data Pkt Size 128 bits		
		Active Cell		Sys Type: IS-856					
		Idle							
1 of 3		IntRef	Offset	PLSub0	RETAP		1 of 3		

1xEV-DO setting for RETAP data rate (128 or 2048 or 12288 kbps)

Reference:

- [1] SAR Measurement Procedures for 3G Devices CDMA 2000/Ev-Do/WCDMA/HSDPA, June 2006
Laboratory Division Office of Engineering and Technology Federal Communications Commission
- [2] 3.1.2.3.4 Maximum RF Output Power 3GPP2 C.S0033-0 Version 2.0, Date: 12 December 2003
Recommended Minimum Performance Standards for cdma2000 High Rate Packet Data Access Terminal