



TEST REPORT

Report No.: SRTC2011-H024-E0042

Product Name: CDMA 1X Digital Mobile Phone

Product Model: ZTE S189

Applicant: ZTE Corporation

Manufacture: ZTE Corporation

Specification: FCC Part 22H, Part 2

(October 1, 2009 edition)

FCC ID: Q78-ZTECS189

The State Radio_monitoring_center Testing Center (SRTC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-68009202 Fax: 86-10-68009205

CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory	3
1.3 Applicant's details	3
1.4 Manufacturer's details	3
1.5 Application details	4
1.6 Reference specification	4
1.7 Information of EUT	4
1.7.1 General information	4
1.7.2 EUT details	5
1.7.3 Auxiliary equipment details	5
2. Test information	6
2.1 Summary of the test results	6
2.2 Test result	7
2.2.1 RF Power Output-FCC Part2.1046	7
2.2.2 Effective Radiated Power-FCC Part22.913(a)	8
2.2.3 Occupied Bandwidth-FCC Part2.1049	10
2.2.4 Spurious Emissions at antenna terminal-FCC Part2.1051/22.917(a)	13
2.2.5 Band Edges Compliance-FCC Part2.1051/22.917(a)	19
2.2.6 Frequency Stability-FCC Part2.1055/22.355	21
2.2.7 Radiated Spurious Emissions-FCC Part2.1053/22.917(a)	22
2.3. List of test equipments	25
Appendix	26

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: No.80 Beilishi Road, Xicheng District, Beijing China
City: Beijing
Country or Region: China
Contacted person: Wang Junfeng
Tel: +86 10 68009181 +86 10 68009202
Fax: +86 10 68009195 +86 10 68009205
Email: wangjf@srrc.org.cn / wangjunfeng@srtc.org.cn

1.3 Applicant's details

Company: ZTE Corporation
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, 518057
City: Shenzhen
Country or Region: P.R.China
Grantee Code: Q78
Contacted person: Min Zhang
Tel: +86-021-68897541
Fax: +86-021-50801070
Email: zhang.min13@zte.com.cn

1.4 Manufacturer's details

Company: ZTE Corporation
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, 518057
City: Shenzhen
Country or Region: P.R.China
Contacted person: Min Zhang
Tel: +86-021-68897541
Fax: +86-021-50801070
Email: zhang.min13@zte.com.cn

1.5 Application details

Date of reception of test sample: 25th Oct 2010

Date of test: 25th Oct 2010 to 5th Nov 2010

1.6 Reference specification

FCC Part 22H, Part 2 (October 1, 2009 edition)

1.7 Information of EUT

1.7.1 General information

Name of EUT	CDMA 1X Digital Mobile Phone
FCC ID	Q78-ZTECS189
Frequency range	Tx:824~849MHz Rx:869~894MHz
Rated output power	24.0dBm
E.R.P.	22.2dBm
Modulation type	OQPSK
Emission Designator	1M25F9W
Duplex mode	FDD
Duplex spacing	45MHz
Antenna type	Integral
Power Supply	Battery or charger
Rated Power Supply Voltage	3.7V
Extreme Temperature	Lowest: -30°C Highest: +50°C
Extreme Voltage	Minimum: 3.5V Maximum: 4.2V
HW Version	cp9C
SW Version	PBTL_S189_RBTL19NV1.0.0B03

1.7.2 EUT details

Name	Model	SN
CDMA 1X Digital Mobile Phone	ZTE S189	324211460432

1.7.3 Auxiliary equipment details


Equipment	Charger
Manufacturer	Ruide Electronical Industrial Co., Ltd
Model Number	STC-A22O50USBA
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Battery
Manufacturer	ZTE Corporation
Model Number	Li3710T42P3h553457
Capacity	1000mAh
Rated Voltage	3.7V d.c.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Radiated Power	22.913(a)	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Spurious Emissions at antenna terminals	2.1051/22.917(a)	Pass
5	Band Edges Compliance	2.1051/22.917(a)	Pass
6	Frequency Stability	2.1055/22.355	Pass
7	Radiated Spurious Emissions	2.1053/22.917(a)	Pass

This Test Report Is Issued by: Mr. Song Qizhu Director of the test lab 	Checked by: Mr. Wang Junfeng Deputy director of the test lab 
Tested by: Mr. Zhao Yang Test engineer 	Issued date: 2011.6.23


2.2 Test result

2.2.1 RF Power Output-FCC Part2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

The measurement will be conducted at three channels No1013, No384 and No777 (Bottom, middle and top channels of CDMA 1X band)

Limits	$\leq 30\text{dBm}$
--------	---------------------

Test result:


Carrier frequency (MHz)	Channel No.	Test Mode	RF Power Output (dBm)
824.70	1013	RC1/SO2	23.7
		RC1/SO55	23.7
		RC3/SO2	23.8
		RC3/SO55	23.9
		RC3/SO32	23.7
836.52	384	RC1/SO2	23.6
		RC1/SO55	23.6
		RC3/SO2	23.7
		RC3/SO55	23.8
		RC3/SO32	23.5
848.31	777	RC1/SO2	23.5
		RC1/SO55	23.5
		RC3/SO2	23.5
		RC3/SO55	23.6
		RC3/SO32	23.4

2.2.2 Effective Radiated Power-FCC Part22.913(a)


Ambient condition:

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test setup



Step 1



Step 2

Test procedure:

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and

varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A RMS detector is used and RBW is set to 3MHz. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator. To repeat the same procedure as step1 and the level of signal generator will be adjusted till the same power value on the spectrum analyzer or receiver. The ERP/EIRP of the EUT can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

The measurement will be conducted at three channels No1013, No384 and No777 (Bottom, middle and top channels of CDMA 1X band) in RC3/SO55 test mode.

Limits	$\leq 38.5\text{dBm}$
--------	-----------------------

Test result:


Carrier frequency (MHz)	Channel No.	Test Mode	E.R.P. (dBm)
824.70	1013	RC3/SO55	22.2
836.52	384	RC3/SO55	22.0
848.31	777	RC3/SO55	21.9

2.2.3 Occupied Bandwidth-FCC Part2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test Setup:




Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer. The measurement will be conducted at three channels No1013, No384 and No777 (Bottom, middle and top channels of CDMA 1X band) in RC3/SO55 test mode.


Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


Carrier frequency (MHz)	Channel No.	Test Mode	Bandwidth of 99% Power (MHz)
824.70	1013	RC3/SO55	1.2628
836.52	384	RC3/SO55	1.2677
848.31	777	RC3/SO55	1.2618



Channel 1013



Channel 384




Channel 777

2.2.4 Spurious Emissions at antenna terminal-FCC Part2.1051/22.917(a)

Ambient condition:

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test Setup:



Test procedure:


After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 9GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.

The measurement will be conducted at three channels No1013, No384 and No777 (Bottom, middle and top channels of CDMA 1X band) in RC3/SO55 test mode.


Limits	$\leq -13\text{dBm}$
--------	----------------------

Test result:

Refer to the following figures.




Channel 1013, 30MHz~824MHz




Channel 1013, 824MHz~849MHz


Note: The signal beyond the limit is carrier.



Channel 1013, 849MHz~9GHz




Channel 384, 30MHz~824MHz




Channel 384, 824MHz~849MHz


Note: The signal beyond the limit is carrier.



Channel 384, 849MHz~9GHz




Channel 777, 30MHz~824MHz



Channel 777, 824MHz~849MHz

Note: The signal beyond the limit is carrier.




Channel 777, 849MHz~9GHz

2.2.5 Band Edges Compliance-FCC Part2.1051/22.917(a)

Ambient condition:

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test Setup:



Test procedure:


After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to 3KHz on spectrum analyzer.

The measurement will be conducted at two channels No1013 and No777 (Bottom and top channels of CDMA 1X band) in RC3/SO55 test mode.


Limits	$\leq -13\text{dBm}$
--------	----------------------

Test result:

Refer to the following figures.



Channel 1013




Channel 777

2.2.6 Frequency Stability-FCC Part2.1055/22.355

Ambient condition:

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test setup:



Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50° C in 10° C step size, and also the DC power supply voltage to the EUT is varied from 3.5 to 4.2 V. The measurement will be conducted at three channels No1013, No384 and No777 (Bottom, middle and top channels of CDMA 1X band) in RC3/SO55 test mode. Limits: No specific frequency stability requirements in part 2.1055 and part 22.355

Test Result:

Temperature(°C)	Test Result (ppm)@3.7V		
	Channel 1013	Channel 384	Channel 777
-30	0.004	0.004	0.004
-20	0.003	0.004	0.004
-10	0.003	0.003	0.003
0	0.002	0.003	0.003
+10	0.002	0.003	0.003
+20	0.003	0.003	0.004
+30	0.003	0.003	0.004
+40	0.003	0.002	0.003
+50	0.004	0.003	0.003


Voltage (V)	Test Result (ppm)@20°C		
	Channel 1013	Channel 384	Channel 777
3.5	0.002	0.002	0.002
4.2	0.002	0.001	0.001

2.2.7 Radiated Spurious Emissions-FCC Part2.1053/22.917(a)


Ambient condition

Temperature	Relative humidity	Pressure
24°C	53%	101.9kPa

Test Setup:



Step 1



Step 2

Test procedure:

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be

established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 9GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

Calculation procedure:

The data of cable loss, antenna gain and air loss has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss, antenna gain and air loss. The basic equation with a sample calculation is as followed:

$$P=P_R+L_C+L_A-G$$

Where

P: Power of the Radiated Spurious Emissions (dBm)

P_R: reading of the receiver (dBm)

L_C: Cable Lose (dB)

L_A: Air loss (dB)

G: Antenna Gain (dBi)


Assumed the reading of the receiver is -60dBm. A cable lose of 10dB, an air lose of 30dB and an antenna gain of 11dBi are added.

$$P=P_R+L_C+L_A-G=-60+10+30-11=-31\text{dBm}$$

The measurement will be conducted at one channel No384 (middle channel of CDMA 1X band) in RC3/SO55 test mode.


Limits	≤ -13dBm
--------	----------

Test result:



Channel 384, 30MHz~3GHz

Note: The signal beyond the limit is the base station simulator carrier.



Channel 384, 3GHz~10GHz

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date
1	E5515C(8960) Mobile Station Tester	Agilent	GB44050904	19 th Aug. 2011
2	PSA E4440A Spectrum Analyzer	Agilent	MY41000183	19 th Aug. 2011
3	66309B DC Power Supply	Agilent	MY43000461	19 th Aug. 2011
4	1506A Power Splitter	Weinschel	MN154	19 th Aug. 2011
5	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	19 th Aug. 2011
6	ESI 40 EMI test receiver	R&S	100015	19 th Aug. 2011
7	SMR 20 Signal generator	R&S	100086	19 th Aug. 2011
8	CMU 200 Radio tester	R&S	100313	19 th Aug. 2011
9	12.65m*8.03m*7.50m Fully-Anechoic Chamber	FRANKONIA	-----	19 th Aug. 2011
10	HL562 Ultra log test antenna	R&S	100016	19 th Aug. 2011
11	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	-----	19 th Aug. 2011
12	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100030	19 th Aug. 2011
13	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100029	19 th Aug. 2011
14	PS2000 Turn Table	FRANKONIA	-----	19 th Aug. 2011
15	MA260 Antenna Master	FRANKONIA	-----	19 th Aug. 2011
16	SH-241Climatic Chamber	ESPEC	92000389	19 th Aug. 2011
17	ES-K1EMI test software	R&S	-----	19 th Aug. 2011
18	HL562 Receive antenna	R&S	100167	19 th Aug. 2011

Appendix

Appendix1 Test Setup