

# FCC RF Test Report

APPLICANT : ZTE CORPORATION  
EQUIPMENT : WCDMA MESSAGE PHONE  
BRAND NAME : ZTE  
MODEL NAME : F555  
FCC ID : Q78-ZTEF555  
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)  
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)  
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /  
869.2 ~ 893.8 MHz  
GSM1900 : 1850.2 ~ 1909.8 MHz /  
1930.2 ~ 1989.8 MHz  
WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz  
2112.4 MHz ~ 2152.6 MHz  
WCDMA Band II : 1852.4 ~ 1907.6 MHz /  
1932.4 ~ 1987.6 MHz  
MAX. ERP/EIRP POWER : GSM850 (GSM) : 0.5284 W  
GSM850 (EDGE 8) : 0.1340 W  
GSM1900 (GSM) : 1.4388 W  
GSM1900 (EDGE 8) : 0.5483 W  
WCDMA Band IV (RMC 12.2Kbps) : 0.2924 W  
WCDMA Band II (RMC 12.2Kbps) : 0.2999 W

The product was received on May 04, 2012 and completely tested on Jun. 06, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Feature of Equipment Under Test..... 5

    1.4 Emission Designator and Maximum ERP/EIRP Power ..... 6

    1.5 Testing Site ..... 6

    1.6 Applied Standards ..... 6

    1.7 Ancillary Equipment List..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1 Test Mode..... 8

    2.2 Connection Diagram of Test System ..... 9

**3 TEST RESULT..... 10**

    3.1 Conducted Output Power Measurement..... 10

    3.2 Peak-to-Average Ratio ..... 12

    3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement ..... 26

    3.4 Occupied Bandwidth and 26dB Bandwidth Measurement..... 31

    3.5 Band Edge Measurement..... 50

    3.6 Conducted Emission Measurement ..... 63

    3.7 Field Strength of Spurious Radiation Measurement ..... 80

    3.8 Frequency Stability Measurement..... 95

**4 LIST OF MEASURING EQUIPMENTS ..... 100**

**5 UNCERTAINTY OF EVALUATION ..... 101**

**APPENDIX A. PHOTOGRAPHS OF EUT**

**APPENDIX B. SETUP PHOTOGRAPHS**



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§27.50(d)(4)	RSS-139 (6.4) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a) §27.53(g)	N/A	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(g)	RSS-132 (4.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a) §27.53(g)	RSS-132 (4.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Conducted Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a) §27.53(g)	RSS-132 (4.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 30.56 dB at 6930.400 MHz
3.8	§2.1055 §22.355 §24.235 §27.54	RSS-132 (4.3) RSS-133 (6.3) RSS-139 (6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

# 1 General Description

## 1.1 Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.2 Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.3 Feature of Equipment Under Test

Product Feature & Specification	
<b>Equipment</b>	WCDMA MESSAGE PHONE
<b>Brand Name</b>	ZTE
<b>Model Name</b>	F555
<b>FCC ID</b>	Q78-ZTEF555
<b>Tx Frequency</b>	GSM850 : 824.2 ~ 848.8 MHz GSM1900 : 1850.2 ~ 1909.8 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II : 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	GSM850 : 869.2 ~ 893.8 MHz GSM1900 : 1930.2 ~ 1989.8 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 32.39 dBm GSM1900 : 29.83 dBm WCDMA Band IV : 22.81 dBm WCDMA Band II : 22.81 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>HW Version</b>	w7iB
<b>SW Version</b>	TMO_US_F555V1.0.0B04
<b>Type of Modulation</b>	GSM / GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink)
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Emission Designator and Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Emission Designator	Maximum ERP/EIRP
Part 22	GSM850 GSM	GMSK	250KGXW	0.5284 W
Part 22	GSM850 EDGE 8	8PSK	250KG7W	0.1340 W
Part 24	GSM1900 GSM	GMSK	248KGXW	1.4388 W
Part 24	GSM1900 EDGE 8	8PSK	246KG7W	0.5483 W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	4M18F9W	0.2999 W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	4M14F9W	0.2924 W

### 1.5 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.		
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Registration No.</b>
	TH01-KS	03CH01-KS	149928

### 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v01
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5
- ♦ IC RSS-139 Issue 2

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



### 1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 8 Link</li> </ul>
GSM 1900	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 8 Link</li> </ul>
WCDMA Band IV	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>

**Note:**


1. The maximum power levels are GSM mode for GSM850 and GSM1900 GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band IV, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN and Bluetooth, the co-location test modes are not required.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM (1 Uplink)	32.39	32.23	32.20	29.36	29.33	29.83
GPRS 8 (1 Uplink) – CS1	32.35	32.20	32.18	29.33	29.31	29.82
GPRS 10 (2 Uplink) – CS1	30.07	29.97	29.97	26.02	26.03	26.56
EDGE 8 (8PSK, 1 Uplink) – MCS9	26.42	26.32	26.28	24.93	24.94	25.47
EDGE 10 (8PSK, 2 Uplink) – MCS9	23.95	23.86	23.80	21.98	21.96	22.46

Conducted Power (*Unit: dBm)						
Band	WCDMA Band II			WCDMA Band IV		
Tx Channel	9262	9400	9538	1312	1413	1513
Rx Channel	9662	9800	9938	1537	1638	1738
Frequency	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	22.70	22.81	22.52	22.71	22.81	22.65

## 2.2 Connection Diagram of Test System



### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

##### 3.1.4 Test Setup



### 3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE 8)		
Channel	128(Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
Conducted Power (dBm)	32.39	32.23	32.20	26.42	26.32	26.28
Conducted Power (Watts)	1.73	1.67	1.66	0.44	0.43	0.42

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.36	29.33	29.83	24.93	24.94	25.47	22.70	22.81	22.52
Conducted Power (Watts)	0.86	0.86	0.96	0.31	0.31	0.35	0.19	0.19	0.18

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.71	22.81	22.65
Conducted Power (Watts)	0.19	0.19	0.18

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. The following guidelines are offered for performing a CCDF measurement.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The CCDF (Complementary Cumulative Distribution Function) of the middle channel for the highest RF powers were measured.

### 3.2.4 Test Setup





3.2.5 Test Result of Peak-to-Average Ratio

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
<b>Peak-to-Average Ratio (dB)</b>	0.08	0.08	0.06	2.08	2.03	1.90


PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
<b>Peak-to-Average Ratio (dB)</b>	0.07	0.07	0.05	2.06	2.02	1.93	3.15	3.23	3.07

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
<b>Peak-to-Average Ratio (dB)</b>	3.11	3.23	2.97




Band :	GSM 850	Test Mode :	GSM Link
--------	---------	-------------	----------

Peak-to-Average Ratio on Channel 128



Date: 1.JUN.2012 11:51:16


Peak-to-Average Ratio on Channel 189



Date: 1.JUN.2012 11:39:42



Peak-to-Average Ratio on Channel 251




Date: 1.JUN.2012 11:38:29




<b>Band :</b>	GSM 850	<b>Test Mode :</b>	EDGE 8 Link
---------------	---------	--------------------	-------------

Peak-to-Average Ratio on Channel 128



Date: 4.JUN.2012 13:42:10


Peak-to-Average Ratio on Channel 189



Date: 4.JUN.2012 13:20:59



Peak-to-Average Ratio on Channel 251




Date: 4.JUN.2012 13:16:07




Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

Peak-to-Average Ratio on Channel 512



Date: 1.JUN.2012 21:13:32


Peak-to-Average Ratio on Channel 661



Date: 1.JUN.2012 21:14:58



Peak-to-Average Ratio on Channel 810




Date: 1.JUN.2012 21:16:29




Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

Peak-to-Average Ratio on Channel 512



Date: 4.JUN.2012 16:02:56


Peak-to-Average Ratio on Channel 661



Date: 4.JUN.2012 16:02:17



Peak-to-Average Ratio on Channel 810




Date: 4.JUN.2012 16:01:10




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

Peak-to-Average Ratio on Channel 9262



Date: 1.JUN.2012 20:50:13


Peak-to-Average Ratio on Channel 9400



Date: 1.JUN.2012 20:50:36



Peak-to-Average Ratio on Channel 9538



Complementary Cumulative Distribution Function (100000 samples)

Trace 1


Mean	22.49 dBm
Peak	25.56 dBm
Crest	3.07 dB
10 %	1.68 dB
1 %	2.44 dB
.1 %	2.80 dB
.01 %	3.00 dB

Date: 1.JUN.2012 20:51:04




<b>Band :</b>	WCDMA Band IV	<b>Test Mode :</b>	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------

Peak-to-Average Ratio on Channel 1312



Date: 1.JUN.2012 19:29:15


Peak-to-Average Ratio on Channel 1413



Date: 1.JUN.2012 19:29:47



Peak-to-Average Ratio on Channel 1513



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean    22.30 dBm  
 Peak    25.28 dBm  
 Crest    2.97 dB

10 %    1.64 dB  
 1 %    2.36 dB  
 .1 %    2.72 dB  
 .01 %    2.92 dB

Date: 1.JUN.2012 19:43:04

### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

$P_s$  (dBm) : Input power to substitution antenna.

$G_s$  (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

$AF$  (dB/m) : Receive antenna factor

$R_t$  : The highest received signal in spectrum analyzer for EUT.

$R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-19.81	-48.12	0.00	-1.08	27.23	0.5284
836.40	-20.88	-48.28	0.00	-0.93	26.47	0.4436
848.80	-21.46	-48.35	0.00	-0.76	26.13	0.4102
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-35.77	-47.97	0.00	-1.08	11.12	0.0129
836.40	-36.98	-48.01	0.00	-0.93	10.10	0.0102
848.80	-37.69	-48.05	0.00	-0.76	9.60	0.0091

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.77	-48.12	0.00	-1.08	21.27	0.1340
836.40	-26.56	-48.28	0.00	-0.93	20.79	0.1199
848.80	-27.26	-48.35	0.00	-0.76	20.33	0.1079
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-41.90	-47.97	0.00	-1.08	4.99	0.0032
836.40	-42.62	-48.01	0.00	-0.93	4.46	0.0028
848.80	-43.33	-48.05	0.00	-0.76	3.96	0.0025

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-23.24	-51.88	0.00	1.96	30.60	1.1482
1880.00	-23.79	-52.99	0.00	2.00	31.20	1.3183
1909.80	-24.84	-54.28	0.00	1.98	31.42	1.3868
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-23.61	-52.13	0.00	1.96	30.48	1.1169
1880.00	-24.07	-53.17	0.00	2.00	31.10	1.2882
1909.80	-24.53	-54.13	0.00	1.98	31.58	1.4388

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.51	-51.88	0.00	1.96	26.33	0.4295
1880.00	-28.14	-52.99	0.00	2.00	26.85	0.4842
1909.80	-29.17	-54.28	0.00	1.98	27.09	0.5117
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.89	-52.13	0.00	1.96	26.20	0.4169
1880.00	-28.33	-53.17	0.00	2.00	26.84	0.4831
1909.80	-28.72	-54.13	0.00	1.98	27.39	0.5483



WCDMA Band IV (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-30.71	-51.88	0.00	1.96	23.13	0.2056
1732.60	-31.93	-52.99	0.00	2.00	23.06	0.2023
1752.60	-31.83	-54.28	0.00	1.98	24.43	0.2773
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1712.40	-31.23	-52.13	0.00	1.96	22.86	0.1932
1732.60	-31.66	-53.17	0.00	2.00	23.51	0.2244
1752.60	-31.45	-54.13	0.00	1.98	24.66	0.2924

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.07	-51.88	0.00	1.96	24.77	0.2999
1880.00	-30.52	-52.99	0.00	2.00	24.47	0.2799
1907.60	-33.09	-54.28	0.00	1.98	23.17	0.2075
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.50	-52.13	0.00	1.96	24.59	0.2877
1880.00	-30.76	-53.17	0.00	2.00	24.41	0.2761
1907.60	-32.59	-54.13	0.00	1.98	23.52	0.2249

## 3.4 Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.4.1 Description of Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

### 3.4.4 Test Setup






### 3.4.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Test Mode :	GSM Link
--------	---------	-------------	----------

99% Occupied Bandwidth Plot on Channel 128



Date: 1.JUN.2012 11:31:15


26dB Bandwidth Plot on Channel 128



Date: 1.JUN.2012 11:29:56




99% Occupied Bandwidth Plot on Channel 189



Date: 1.JUN.2012 11:31:40


26dB Bandwidth Plot on Channel 189



Date: 1.JUN.2012 11:30:23




99% Occupied Bandwidth Plot on Channel 251



Date: 1.JUN.2012 11:32:06

26dB Bandwidth Plot on Channel 251




Date: 1.JUN.2012 11:30:49




Band :	GSM 850	Test Mode :	EDGE 8 Link
--------	---------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 128



Date: 4.JUN.2012 13:09:48


26dB Bandwidth Plot on Channel 128



Date: 4.JUN.2012 13:08:29




99% Occupied Bandwidth Plot on Channel 189



Date: 4.JUN.2012 13:10:14


26dB Bandwidth Plot on Channel 189



Date: 4.JUN.2012 13:08:56




99% Occupied Bandwidth Plot on Channel 251



Date: 4.JUN.2012 13:10:40

26dB Bandwidth Plot on Channel 251




Date: 4.JUN.2012 13:09:22




Band :	GSM 1900	Test Mode :	GSM Link
--------	----------	-------------	----------

99% Occupied Bandwidth Plot on Channel 512



Date: 1.JUN.2012 21:07:39


26dB Bandwidth Plot on Channel 512



Date: 1.JUN.2012 21:06:21




99% Occupied Bandwidth Plot on Channel 661



Date: 1.JUN.2012 21:08:05


26dB Bandwidth Plot on Channel 661



Date: 1.JUN.2012 21:06:47




99% Occupied Bandwidth Plot on Channel 810



Date: 1.JUN.2012 21:08:30

26dB Bandwidth Plot on Channel 810




Date: 1.JUN.2012 21:07:13




Band :	GSM 1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 512



Date: 4.JUN.2012 15:52:29


26dB Bandwidth Plot on Channel 512



Date: 4.JUN.2012 15:51:11




99% Occupied Bandwidth Plot on Channel 661



Date: 4.JUN.2012 15:52:55


26dB Bandwidth Plot on Channel 661



Date: 4.JUN.2012 15:51:38




99% Occupied Bandwidth Plot on Channel 810



Date: 4.JUN.2012 15:53:21

26dB Bandwidth Plot on Channel 810




Date: 4.JUN.2012 15:52:03




Band :	WCDMA Band IV	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 1312



Date: 1.JUN.2012 20:10:18


26dB Bandwidth Plot on Channel 1312



Date: 1.JUN.2012 19:54:39




99% Occupied Bandwidth Plot on Channel 1413



Date: 1.JUN.2012 20:09:10


26dB Bandwidth Plot on Channel 1413



Date: 1.JUN.2012 19:55:08




99% Occupied Bandwidth Plot on Channel 1513



Date: 1.JUN.2012 20:05:53

26dB Bandwidth Plot on Channel 1513




Date: 1.JUN.2012 19:55:54




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 9262



Date: 1.JUN.2012 20:43:46


26dB Bandwidth Plot on Channel 9262



Date: 1.JUN.2012 20:42:27




99% Occupied Bandwidth Plot on Channel 9400



Date: 1.JUN.2012 20:44:11


26dB Bandwidth Plot on Channel 9400



Date: 1.JUN.2012 20:42:54




99% Occupied Bandwidth Plot on Channel 9538



Date: 1.JUN.2012 20:44:37

26dB Bandwidth Plot on Channel 9538



Date: 1.JUN.2012 20:43:19

### 3.5 Band Edge Measurement

#### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly  $BW/100$ .


#### 3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link	Maximum 26dB Bandwidth:	0.314MHz
Correction Factor:	0.20dB	Measurement Value:	-17.42dBm
Band Edge:	-17.22dBm		

Lower Band Edge Plot on Channel 128



Date: 1.JUN.2012 11:33:31


1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	GSM850	<b>Power Stage :</b>	High
<b>Test Mode :</b>	GSM Link	<b>Maximum 26dB Bandwidth:</b>	0.314MHz
<b>Correction Factor:</b>	0.20dB	<b>Measurement Value:</b>	-15.55dBm
<b>Band Edge:</b>	-15.35dBm		

Higher Band Edge Plot on Channel 251



Date: 1.JUN.2012 11:33:57


$$1. \text{Correction Factor(dB)} = 10 \log(1\% \text{ Emission BW/RBW})$$

$$2. \text{Band Edge} = \text{Measurement Value} + \text{Correction Factor(dB)}$$



<b>Band :</b>	GSM850	<b>Power Stage :</b>	High
<b>Test Mode :</b>	EDGE 8 Link	<b>Maximum 26dB Bandwidth:</b>	0.312MHz
<b>Correction Factor:</b>	0.17dB	<b>Measurement Value:</b>	-25.13dBm
<b>Band Edge:</b>	-24.96dBm		

Lower Band Edge Plot on Channel 128



Date: 4.JUN.2012 13:12:05


1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link	Maximum 26dB Bandwidth:	0.312MHz
Correction Factor:	0.17dB	Measurement Value:	-25.43dBm
Band Edge:	-25.26dBm		

Higher Band Edge Plot on Channel 251



Date: 4.JUN.2012 13:12:31


$$1. \text{Correction Factor(dB)} = 10 \log(1\% \text{ Emission BW/RBW})$$

$$2. \text{Band Edge} = \text{Measurement Value} + \text{Correction Factor(dB)}$$



<b>Band :</b>	GSM1900	<b>Power Stage :</b>	High
<b>Test Mode :</b>	GSM Link	<b>Maximum 26dB Bandwidth:</b>	0.314MHz
<b>Correction Factor:</b>	0.20dB	<b>Measurement Value:</b>	-18.94dBm
<b>Band Edge:</b>	-18.74dBm		

Lower Band Edge Plot on Channel 512



Date: 1.JUN.2012 21:09:55


1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link	Maximum 26dB Bandwidth:	0.314MHz
Correction Factor:	0.20dB	Measurement Value:	-21.37dBm
Band Edge:	-21.17dBm		

Higher Band Edge Plot on Channel 810



Date: 1.JUN.2012 21:10:21


1. Correction Factor(dB)= 10log(1% Emission BW/RBW)

2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	GSM1900	<b>Power Stage :</b>	High
<b>Test Mode :</b>	EDGE 8 Link	<b>Maximum 26dB Bandwidth:</b>	0.310MHz
<b>Correction Factor:</b>	0.14dB	<b>Measurement Value:</b>	-22.61dBm
<b>Band Edge:</b>	-22.47dBm		

Lower Band Edge Plot on Channel 512




Date: 4.JUN.2012 15:54:45

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link	Maximum 26dB Bandwidth:	0.310MHz
Correction Factor:	0.14dB	Measurement Value:	-25.70dBm
Band Edge:	-25.56dBm		

Higher Band Edge Plot on Channel 810




Date: 4.JUN.2012 15:55:11

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band IV	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link	Maximum 26dB Bandwidth:	4.68MHz
Correction Factor:	-3.30dB	Measurement Value:	-27.25dBm
Band Edge:	-30.55dBm		

Lower Band Edge Plot on Channel 1312




Date: 6.JUN.2012 14:27:09

- 1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
- 2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	WCDMA Band IV	<b>Power Stage :</b>	High
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Maximum 26dB Bandwidth:</b>	4.68MHz
<b>Correction Factor:</b>	-3.30dB	<b>Measurement Value:</b>	-26.01dBm
<b>Band Edge:</b>	-29.31dBm		

Higher Band Edge Plot on Channel 1513



Date: 6.JUN.2012 14:27:36


$$1. \text{Correction Factor(dB)} = 10 \log(1\% \text{ Emission BW/RBW})$$

$$2. \text{Band Edge} = \text{Measurement Value} + \text{Correction Factor(dB)}$$



<b>Band :</b>	WCDMA Band II	<b>Power Stage :</b>	High
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Maximum 26dB Bandwidth:</b>	4.68MHz
<b>Correction Factor:</b>	-3.30dB	<b>Measurement Value:</b>	-27.14dBm
<b>Band Edge:</b>	-30.44dBm		

Lower Band Edge Plot on Channel 9262




Date: 1.JUN.2012 20:46:04

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



<b>Band :</b>	WCDMA Band II	<b>Power Stage :</b>	High
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Maximum 26dB Bandwidth:</b>	4.68MHz
<b>Correction Factor:</b>	-3.30dB	<b>Measurement Value:</b>	-26.30dBm
<b>Band Edge:</b>	-29.60dBm		

Higher Band Edge Plot on Channel 9538



Date: 1.JUN.2012 20:46:30

$$1. \text{Correction Factor(dB)} = 10 \log(1\% \text{ Emission BW/RBW})$$

$$2. \text{Band Edge} = \text{Measurement Value} + \text{Correction Factor(dB)}$$

## 3.6 Conducted Emission Measurement

### 3.6.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.6.3 Test Procedures

3. The EUT was connected to spectrum analyzer and base station via power divider.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.


### 3.6.4 Test Setup



### 3.6.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 4.JUN.2012 16:42:28


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 4.JUN.2012 16:44:19




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 4.JUN.2012 16:45:17

### Conducted Emission Plot between 7GHz ~ 9GHz




Date: 4.JUN.2012 16:49:59




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 4.JUN.2012 15:47:55


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 4.JUN.2012 14:13:06




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 4.JUN.2012 14:14:35

### Conducted Emission Plot between 7GHz ~ 9GHz




Date: 4.JUN.2012 14:16:04




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 1.JUN.2012 21:18:29


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 1.JUN.2012 21:19:08




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 1.JUN.2012 21:20:14


Conducted Emission Plot between 7GHz ~ 13.6G



Date: 1.JUN.2012 21:21:10



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.JUN.2012 21:22:04




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 4.JUN.2012 16:13:59


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 4.JUN.2012 16:16:46




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 4.JUN.2012 16:19:09


### Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 4.JUN.2012 16:20:00



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 4.JUN.2012 16:26:10




Band :	WCDMA Band IV	Channel :	CH1413
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 1.JUN.2012 20:13:16


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 1.JUN.2012 20:28:09




### Conducted Emission Plot between 3GHz ~ 7GHz



Date: 1.JUN.2012 20:29:25


### Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 1.JUN.2012 20:30:14



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.JUN.2012 20:30:49




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 1.JUN.2012 20:51:54


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 1.JUN.2012 20:52:44




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 1.JUN.2012 20:53:41


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 1.JUN.2012 20:54:21



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 1.JUN.2012 20:54:51

## 3.7 Field Strength of Spurious Radiation Measurement

### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$

### 3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz ~ 1000 MHz



For radiated emissions above 1000 MHz




### 3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.7.6 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	20~21°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL  
 EUT : (FG) 250401  
 Plan : E1

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-62.24	-13	-49.24	-58.02	-62.89	0.57	3.37	H	Pass
2510	-57.63	-13	-44.63	-59.88	-59.86	0.78	5.16	H	Pass
3345	-61.43	-13	-48.43	-63.37	-65.07	0.87	6.66	H	Pass
4182	-61.86	-13	-48.86	-64.60	-66.45	0.97	7.71	H	Pass
5018	-58.32	-13	-45.32	-64.52	-63.99	1.09	8.91	H	Pass
5854	-55.30	-13	-42.30	-64.01	-61.74	1.22	9.81	H	Pass



Band :	GSM850	Temperature :	20~21°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL  
 EUT : (FG) 250401  
 Plan : E1

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-64.41	-13	-51.41	-60.06	-65.06	0.57	3.37	V	Pass
2510	-57.71	-13	-44.71	-60.82	-59.94	0.78	5.16	V	Pass
3345	-61.70	-13	-48.70	-63.68	-65.34	0.87	6.66	V	Pass
4182	-61.54	-13	-48.54	-65.38	-66.13	0.97	7.71	V	Pass
5018	-60.06	-13	-47.06	-65.00	-65.73	1.09	8.91	V	Pass
5854	-56.86	-13	-43.86	-64.85	-63.30	1.22	9.81	V	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL  
 EUT : (FG) 250401  
 Plan : E1

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-66.67	-13	-53.67	-62.45	-67.32	0.57	3.37	H	Pass
2510	-59.57	-13	-46.57	-61.82	-61.80	0.78	5.16	H	Pass
3345	-61.82	-13	-48.82	-63.76	-65.46	0.87	6.66	H	Pass
4182	-61.26	-13	-48.26	-64.00	-65.85	0.97	7.71	H	Pass
5018	-58.67	-13	-45.67	-64.87	-64.34	1.09	8.91	H	Pass
5854	-56.02	-13	-43.02	-64.73	-62.46	1.22	9.81	H	Pass



<b>Band :</b>	GSM850	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL  
 EUT : (FG) 250401  
 Plan : E1

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-66.73	-13	-53.73	-62.38	-67.38	0.57	3.37	V	Pass
2510	-60.92	-13	-47.92	-64.03	-63.15	0.78	5.16	V	Pass
3345	-61.92	-13	-48.92	-63.90	-65.56	0.87	6.66	V	Pass
4182	-60.25	-13	-47.25	-64.09	-64.84	0.97	7.71	V	Pass
5018	-59.76	-13	-46.76	-64.70	-65.43	1.09	8.91	V	Pass
5854	-56.93	-13	-43.93	-64.92	-63.37	1.22	9.81	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	GSM Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL  
 EUT : (FG) 250401

Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-57.82	-13	-44.82	-58.79	-64.20	0.78	7.16	H	Pass
5640	-50.82	-13	-37.82	-57.14	-59.36	1.04	9.58	H	Pass
7520	-58.83	-13	-45.83	-63.96	-68.94	1.35	11.46	H	Pass
9400	-61.05	-13	-48.05	-64.31	-72.11	1.75	12.81	H	Pass
11280	-58.19	-13	-45.19	-69.68	-69.28	2	13.09	H	Pass
13160	-52.92	-13	-39.92	-64.22	-64.63	2.04	13.75	H	Pass



Band :	GSM1900	Temperature :	20~21°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL  
 EUT : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-60.91	-13	-47.91	-62.28	-67.29	0.78	7.16	V	Pass
5640	-58.29	-13	-45.29	-61.51	-66.83	1.04	9.58	V	Pass
7520	-60.07	-13	-47.07	-64.56	-70.18	1.35	11.46	V	Pass
9400	-61.56	-13	-48.56	-62.78	-72.62	1.75	12.81	V	Pass
11280	-58.92	-13	-45.92	-70.16	-70.01	2	13.09	V	Pass
13160	-53.13	-13	-40.13	-64.32	-64.84	2.04	13.75	V	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL  
 EUT : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-61.61	-13	-48.61	-62.58	-67.99	0.78	7.16	H	Pass
5640	-55.11	-13	-42.11	-59.29	-63.65	1.04	9.58	H	Pass
7520	-59.54	-13	-46.54	-64.67	-69.65	1.35	11.46	H	Pass
9400	-60.98	-13	-47.98	-64.24	-72.04	1.75	12.81	H	Pass
11280	-58.22	-13	-45.22	-69.71	-69.31	2	13.09	H	Pass
13160	-52.79	-13	-39.79	-64.09	-64.50	2.04	13.75	H	Pass



<b>Band :</b>	GSM1900	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	EDGE 8 Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL  
 EUT : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-57.67	-13	-44.67	-59.04	-64.05	0.78	7.16	V	Pass
5640	-56.93	-13	-43.93	-60.15	-65.47	1.04	9.58	V	Pass
7520	-60.00	-13	-47.00	-64.49	-70.11	1.35	11.46	V	Pass
9400	-63.87	-13	-50.87	-65.09	-74.93	1.75	12.81	V	Pass
11280	-60.37	-13	-47.37	-71.61	-71.46	2	13.09	V	Pass
13160	-51.63	-13	-38.63	-62.82	-63.34	2.04	13.75	V	Pass



Band :	WCDMA Band IV	Temperature :	20~21°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL  
 EUT : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3465.2	-45.85	-13	-32.85	-57.33	-38.20	1.42	7.54	H	Pass
5197.8	-57.19	-13	-44.19	-64.29	-68.60	1.58	9.80	H	Pass
6930.4	-50.12	-13	-37.12	-61.78	-67.90	1.69	11.51	H	Pass
8663	-56.52	-13	-43.52	-64.59	-58.70	2.12	12.86	H	Pass
10395.6	-52.16	-13	-39.16	-64.90	-54.80	2.31	12.90	H	Pass
12128.2	-51.25	-13	-38.25	-65.27	-53.00	2.57	13.10	H	Pass



<b>Band :</b>	WCDMA Band IV	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL  
 EUI : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3465.2	-50.83	-13	-37.83	-56.74	-43.20	1.42	7.54	V	Pass
5197.8	-55.46	-13	-42.46	-64.62	-70.30	1.58	9.80	V	Pass
6930.4	-43.56	-13	-30.56	-58.86	-64.60	1.69	11.51	V	Pass
8663	-55.91	-13	-42.91	-64.58	-56.60	2.12	12.86	V	Pass
10395.6	-50.42	-13	-37.42	-63.21	-53.60	2.31	12.90	V	Pass
12128.2	-50.70	-13	-37.70	-65.04	-52.20	2.57	13.10	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL  
 EUT : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-63.91	-13	-50.91	-64.88	-70.29	0.78	7.16	H	Pass
5640	-61.33	-13	-48.33	-65.51	-69.87	1.04	9.58	H	Pass
7520	-60.16	-13	-47.16	-65.29	-70.27	1.35	11.46	H	Pass
9400	-61.66	-13	-48.66	-64.92	-72.72	1.75	12.81	H	Pass
11280	-59.45	-13	-46.45	-70.94	-70.54	2	13.09	H	Pass
13160	-53.15	-13	-40.15	-64.45	-64.86	2.04	13.75	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	20~21°C
<b>Test Mode :</b>	RMC 12.2Kbps Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS  
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL  
 EUT : (FG) 250401  
 Plan : H

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-63.07	-13	-50.07	-64.44	-69.45	0.78	7.16	V	Pass
5640	-62.20	-13	-49.20	-65.42	-70.74	1.04	9.58	V	Pass
7520	-59.73	-13	-46.73	-64.22	-69.84	1.35	11.46	V	Pass
9400	-62.97	-13	-49.97	-64.19	-74.03	1.75	12.81	V	Pass
11280	-59.95	-13	-46.95	-71.19	-71.04	2	13.09	V	Pass
13160	-53.76	-13	-40.76	-64.95	-65.47	2.04	13.75	V	Pass

## 3.8 Frequency Stability Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at  $-30^{\circ}\text{C}$ , the testing lowest temperature will be raised in  $10^{\circ}\text{C}$  step until the EUT can be turned on.

### 3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup



### 3.8.6 Test Result of Temperature Variation

Band :	GSM 850		Channel :	189	
Limit (ppm) :	2.5				
Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-29	-0.03	-49	-0.06	PASS
-20	-31	-0.04	-42	-0.05	
-10	-25	-0.03	-45	-0.05	
0	-22	-0.03	-44	-0.05	
10	-23	-0.03	-55	-0.06	
20	-35	-0.04	-59	-0.07	
30	-21	-0.02	-65	-0.08	
40	-19	-0.02	-61	-0.07	
50	15	0.02	-54	-0.06	
55	-16	-0.02	-51	-0.06	



<b>Band :</b>	GSM 1900	<b>Channel :</b>	661
<b>Limit (ppm) :</b>	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-56	-0.03	-32	-0.02	PASS
-20	52	0.03	-36	-0.02	
-10	-53	-0.03	-42	-0.02	
0	59	0.03	-37	-0.02	
10	61	0.03	-41	-0.02	
20	68	0.04	-45	-0.02	
30	52	0.03	-49	-0.03	
40	49	0.03	-51	-0.03	
50	58	0.03	-56	-0.03	
55	55	0.03	-59	-0.03	

<b>Band :</b>	WCDMA Band IV	<b>Channel :</b>	1413
<b>Limit (ppm) :</b>	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-41	-0.02	PASS
-20	-35	-0.02	
-10	-33	-0.02	
0	-29	-0.02	
10	-27	-0.02	
20	-26	-0.02	
30	-25	-0.01	
40	-19	-0.01	
50	23	0.01	
55	-31	-0.02	



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-15	-0.01	PASS
-20	-12	-0.01	
-10	-18	-0.01	
0	-26	-0.01	
10	-31	-0.02	
20	-26	-0.01	
30	25	0.01	
40	-23	-0.01	
50	-24	-0.01	
55	-29	-0.02	

**3.8.7 Test Result of Voltage Variation**

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.7	-16	-0.02	2.5	PASS
		BEP	-21	-0.02		
		4.2	-25	-0.03		
	EDGE 8	3.7	-54	-0.06		
		BEP	-61	-0.07		
		4.2	-51	-0.06		
GSM 1900 CH661	GSM	3.7	66	0.03		
		BEP	59	0.03		
		4.2	72	0.04		
	EDGE 8	3.7	-39	-0.02		
		BEP	-35	-0.02		
		4.2	-45	-0.02		
WCDMA Band IV CH1413	RMC 12.2Kbps	3.7	-27	-0.02		
		BEP	-35	-0.02		
		4.2	-28	-0.02		
WCDMA Band II CH9400	RMC 12.2Kbps	3.7	-32	-0.02		
		BEP	-34	-0.02		
		4.2	-30	-0.02		

**Note:**

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.



## 4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Jun. 01, 2012~ Jun. 06, 2012	Dec. 29, 2012	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 30, 2011	Jun. 01, 2012~ Jun. 06, 2012	Dec. 29, 2012	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 23, 2011	Jun. 01, 2012~ Jun. 06, 2012	Aug. 22, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 30, 2011	Jun. 01, 2012~ Jun. 06, 2012	Dec. 29, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	May 11, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	May 11, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	May 11, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	May 11, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060007	30MHz~2GHz	Dec. 30, 2011	May 11, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	May 11, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
SHE-EHF Horn	Schwarzbeck	BBHA9170	BBHA170249	15GHz~40GHz	Oct. 11, 2011	May 11, 2012	Oct. 10, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00	9kHz~30 MHz	Jul. 28, 2011	May 11, 2012	Jul. 27, 2012	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 20, 2011	May 11, 2012	Sep. 19, 2012	Radiation (03CH01-KS)

## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>1.27</b>		
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>2.54</b>		

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of $X_i$		$u(X_i)$	$C_i$	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	$\pm 0.10$	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	$\pm 1.70$	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	$\pm 0.50$	Normal (k=2)	0.25	1	0.25
Receiver Correction	$\pm 2.00$	Rectangular	1.15	1	1.15
Antenna Factor Directional	$\pm 1.50$	Rectangular	0.87	1	0.87
Site Imperfection	$\pm 2.80$	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
<b>Combined Standard Uncertainty <math>U_c(y)</math></b>	<b>2.36</b>				
<b>Measuring Uncertainty for a Level of Confidence of 95% (<math>U = 2U_c(y)</math>)</b>	<b>4.72</b>				