



TEST REPORT

Report No.: SRTC2010-H024-E0034

Product Name: GSM Dual-band Digital Mobile Phone

Product Model: ZTE-G S512

Applicant: ZTE Corporation

Manufacture: ZTE Corporation

Specification: FCC Part 24E, Part 22H, Part 2

(October 1, 2009 edition)

FCC ID: Q78-ZTEGS512

The State Radio_monitoring_center Testing Center (SRTC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-68009202 Fax: 86-10-68009205

CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory.....	3
1.3 Applicant's details	3
1.4 Manufacturer's details.....	3
1.5 Application details	4
1.6 Reference specification.....	4
1.7 Information of EUT	4
1.7.1 General information.....	4
1.7.2 EUT details	5
1.7.3 Auxiliary equipment details.....	5
2. Test information	6
2.1 Summary of the test results.....	6
2.2 Test result.....	7
2.2.1 GSM850	7
2.2.1.1 RF Power Output-FCC Part2.1046.....	7
2.2.1.2 Effective Radiated Power-FCC Part22.913(a).....	8
2.2.1.3 Occupied Bandwidth-FCC Part2.1049.....	10
2.2.1.4 Spurious Emissions at antenna terminal-FCC Part2.1051/22.917(a)	13
2.2.1.5 Band Edges Compliance-FCC Part2.1051/22.917(a)	16
2.2.1.6 Frequency Stability-FCC Part2.1055/Part22.355	18
2.2.1.7 Radiated Spurious Emissions-FCC Part2.1053/22.917(a)	20
2.2.2 PCS1900.....	23
2.2.2.1 RF Power Output-FCC Part2.1046.....	23
2.2.2.2 Effective Isotropic Radiated Power-FCC Part24.232(c).....	24
2.2.2.3 Occupied Bandwidth-FCC Part2.1049.....	26
2.2.2.4 Spurious Emissions at antenna terminal-FCC Part2.1051/24.238(a)	29
2.2.2.5 Band Edges Compliance-FCC Part2.1051/24.238(a)	32
2.2.2.6 Frequency Stability-FCC Part2.1055/Part24.235	34
2.2.2.7 Radiated Spurious Emissions-FCC Part2.1053/24.238(a)	36
2.3. List of test equipments	39
Appendix.....	40

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: No.80 Beilishi Road, Xicheng District, Beijing China
City: Beijing
Country or Region: China
Contacted person: Wang Junfeng
Tel: +86 10 68009181 +86 10 68009202
Fax: +86 10 68009195 +86 10 68009205
Email: wangjf@srrc.org.cn / wangjunfeng@srtc.org.cn

1.3 Applicant's details

Company: ZTE Corporation
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, 518057
City: Shenzhen
Country or Region: P.R.China
Grantee Code: Q78
Contacted person: Min Zhang
Tel: +86-021-68897541
Fax: +86-021-50801070
Email: zhang.min13@zte.com.cn

1.4 Manufacturer's details

Company: ZTE Corporation
Address: ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park,
Nanshan District, 518057
City: Shenzhen
Country or Region: P.R.China
Contacted person: Min Zhang
Tel: +86-021-68897541
Fax: +86-021-50801070
Email: zhang.min13@zte.com.cn

1.5 Application details

Date of reception of test sample: 11th December 2010

Date of test: 11th December 2010 to 15th December 2010

1.6 Reference specification

FCC Part 24E, Part22H, Part 2 (October 1, 2009 edition)

1.7 Information of EUT

1.7.1 General information

Name of EUT	GSM Dual-band Digital Mobile Phone
FCC ID	Q78-ZTEGS512
Frequency range	GSM850: Tx:824~849MHz Rx:869~894MHz PCS1900: Tx:1850~1910MHz Rx:1930~1990MHz
Rated output power	GSM850:33.0dBm PCS1900:30.0dBm
Modulation type	GMSK
Emission Designator	300KGXW
Duplex mode	FDD
Duplex spacing:	GSM850:45MHz PCS1900:80MHz
Antenna type	Integral
Power Supply	Battery or charger
Rated Power Supply Voltage	3.7V
Extreme Temperature	Lowest: -30°C Highest: +50°C
Extreme Voltage	Minimum: 3.5V Maximum: 4.2V
HW Version	g9xA
SW Version	P118A14(U)B01-En-01\\ng9xA

1.7.2 EUT details

Name	Model	IMEI
GSM Dual-band Digital Mobile Phone	ZTE-G S512	355828040001104

1.7.3 Auxiliary equipment details



Equipment	Charger
Manufacturer	Shenzhen Dokocom Energy Technology Co., Ltd
Model Number	STC-A22O50I700M5-A
Input Voltage	100V-240V a.c.
Output Voltage	5.0V d.c.
Frequency	50/60Hz

Equipment	Battery
Manufacturer	ZTE Corporation
Model Number	Li3706T42P3h383857
Capacity	670mAh
Rated Voltage	3.7V d.c.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Isotropic Radiated Power	22.913(a)/24.232(c)	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Spurious Emissions at antenna terminals	2.1051/22.917(a)/24.238(a)	Pass
5	Band Edges Compliance	2.1051/22.917(a)/24.238(a)	Pass
6	Frequency Stability	2.1055/24.235/22.355	Pass
7	Radiated Spurious Emissions	2.1053/22.917(a)/24.238(a)	Pass

<p>This Test Report Is Issued by: Mr. Song Qizhu Director of the test lab</p> 	<p>Checked by: Mr. Wang Junfeng Deputy director of the test lab</p> 
<p>Tested by: Mr. Zhao Yang Test engineer</p> 	<p>Issued date: 2010.12.17</p>

2.2 Test result


2.2.1 GSM850

2.2.1.1 RF Power Output-FCC Part2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits	$\leq 33\text{dBm}$
--------	---------------------

Test result:

GSM MODE:


Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
824.2	128	31.9
836.4	189	32.1
848.8	251	32.6

2.2.1.2 Effective Radiated Power-FCC Part22.913(a)


Ambient condition:

Temperature	Relative humidity	Pressure
26°C	43%	101.3kPa

Test setup:



Step 1



Step 2

Test procedure:

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and

varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A RMS detector is used and RBW is set to 3MHz. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator. To repeat the same procedure as step1 and the level of signal generator will be adjusted till the same power value on the spectrum analyzer or receiver. The ERP/EIRP of the EUT can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits	$\leq 38.5\text{dBm}$
--------	-----------------------

Test result:

GSM MODE:


Carrier frequency (MHz)	Channel No.	E.R.P. (dBm)
824.2	128	27.9
836.4	189	28.2
848.8	251	28.7

2.2.1.3 Occupied Bandwidth-FCC Part2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)


Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


GSM MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	249.84
836.4	189	248.32
848.8	251	247.45


GSM MODE:



Channel 128



Channel 189




Channel 251

2.2.1.4 Spurious Emissions at antenna terminal-FCC Part2.1051/22.917(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 9GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.


The measurement will be conducted at one channel No189 (middle channel of GSM850 band)

Limits	≤ -13dBm
--------	----------


Test result:

Refer to the following figures.

GSM MODE:




Channel 189, 30MHz~824MHz



Channel 189, 824MHz~849MHz

Note: The signal beyond the limit is the base station simulator carrier.




Channel 189, 849MHz~9GHz

2.2.1.5 Band Edges Compliance-FCC Part2.1051/22.917(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to 3KHz on spectrum analyzer.


The measurement will be conducted at two channels No128 and No251 (Bottom and top channels of GSM850 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------


Test result:

Refer to the following figures.

GSM MODE:



Channel 128




Channel 251

2.2.1.6 Frequency Stability-FCC Part2.1055/Part22.355

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test setup:



Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50° C in 10° C step size, and also the DC power supply voltage to the EUT is varied from 3.5 to 4.2 V. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 22.355.

Test result:

GSM MODE:

Temperature(° C)	Test Result (ppm)@3.7V		
	Channel 128	Channel 189	Channel 251
-30	0.006	0.004	0.007
-20	0.010	0.006	0.002
-10	0.009	0.005	0.009
0	0.009	0.005	0.006
+10	0.005	0.016	0.003
+20	0.005	0.005	0.005
+30	0.010	0.005	0.004
+40	0.008	0.003	0.006
+50	0.005	0.008	0.006


Voltage (V)	Test Result (ppm)@20°C		
	Channel 128	Channel 189	Channel 251
3.5	0.005	0.002	0.004
4.2	0.012	0.008	0.002

2.2.1.7 Radiated Spurious Emissions-FCC Part2.1053/22.917(a)


Ambient condition

Temperature	Relative humidity	Pressure
26°C	43%	101.3kPa

Test Setup:



Step 1



Step 2

Test procedure:

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be

established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

Calculation procedure:

The data of cable loss, antenna gain and air loss has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss, antenna gain and air loss. The basic equation with a sample calculation is as followed:

$$P = P_R + L_C + L_A - G$$

Where

P: Power of the Radiated Spurious Emissions (dBm)

P_R: reading of the receiver (dBm)

L_C: Cable Lose (dB)

L_A: Air loss (dB)

G: Antenna Gain (dBi)


Assumed the reading of the receiver is -60dBm. A cable lose of 10dB, an air lose of 30dB and an antenna gain of 11dBi are added.

$$P = P_R + L_C + L_A - G = -60 + 10 + 30 - 11 = -31 \text{dBm}$$

The measurement will be conducted at one channel No189 (middle channels of GSM850 band)


Limits	≤ -13dBm
--------	----------

Test result:
GSM MODE:



Channel 189, 30MHz~3GHz

Note: The signal beyond the limit is the base station simulator carrier.



Channel 189, 3GHz~10GHz


2.2.2 PCS1900

2.2.2.1 RF Power Output-FCC Part2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits	≤ 30dBm

Test result:

GSM MODE:


Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
1850.2	512	28.1
1880.0	661	28.5
1909.8	810	28.3

2.2.2.2 Effective Isotropic Radiated Power-FCC Part24.232(c)


Ambient condition:

Temperature	Relative humidity	Pressure
26°C	43%	101.3kPa

Test setup:



Step 1



Step 2

Test procedure:

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meters high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and

varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A RMS detector is used and RBW is set to 3MHz. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator. To repeat the same procedure as step1 and the level of signal generator will be adjusted till the same power value on the spectrum analyzer or receiver. The ERP/EIRP of the EUT can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits	$\leq 33\text{dBm}$
--------	---------------------

Test result:

GSM MODE:


Carrier frequency (MHz)	Channel No.	E.I.R.P. (dBm)
1850.2	512	25.5
1880.0	661	25.8
1909.8	810	25.7

2.2.2.3 Occupied Bandwidth-FCC Part2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)


Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


GSM MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	248.42
1880.0	661	247.87
1909.8	810	246.05


GSM MODE:



Channel 512



Channel 661




Channel 810

2.2.2.4 Spurious Emissions at antenna terminal-FCC Part2.1051/24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.


The measurement will be conducted at one channel No661 (middle channel of PCS1900 band)

Limits	≤ -13dBm
--------	----------


Test result:

Refer to the following figures.

GSM MODE:




Channel 661, 30MHz~1850MHz



Channel 661, 1850MHz~1910MHz

Note: The signal beyond the limit is the base station simulator carrier.




Channel 661, 1910MHz~20GHz

2.2.2.5 Band Edges Compliance-FCC Part2.1051/24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to 3KHz on spectrum analyzer.


The measurement will be conducted at two channels No512 and No810 (Bottom and top channels of PCS1900 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------


Test result:

Refer to the following figures.

GSM MODE:



Channel 512




Channel 810

2.2.2.6 Frequency Stability-FCC Part2.1055/Part24.235

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test setup:



Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50° C in 10° C step size, and also the DC power supply voltage to the EUT is varied from 3.5 to 4.2 V. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 24.235.

Test result:

GSM MODE:

Temperature(°C)	Test Result (ppm)@3.7V		
	Channel 512	Channel 661	Channel 810
-30	0.008	0.003	0.002
-20	0.004	0.004	0.006
-10	0.008	0.003	0.003
0	0.010	0.005	0.005
+10	0.011	0.005	0.004
+20	0.010	0.008	0.009
+30	0.014	0.004	0.010
+40	0.013	0.006	0.004
+50	0.008	0.004	0.004


Voltage (V)	Test Result (ppm)@20°C		
	Channel 512	Channel 661	Channel 810
3.5	0.005	0.002	0.005
4.2	0.004	0.004	0.015

2.2.2.7 Radiated Spurious Emissions-FCC Part2.1053/24.238(a)


Ambient condition

Temperature	Relative humidity	Pressure
26°C	43%	101.3kPa

Test Setup:



Step 1



Step 2

Test procedure:

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be

established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

Calculation procedure:

The data of cable loss, antenna gain and air loss has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss, antenna gain and air loss. The basic equation with a sample calculation is as followed:

$$P = P_R + L_C + L_A - G$$

Where

P: Power of the Radiated Spurious Emissions (dBm)

P_R: reading of the receiver (dBm)

L_C: Cable Lose (dB)

L_A: Air loss (dB)

G: Antenna Gain (dBi)


Assumed the reading of the receiver is -60dBm. A cable lose of 10dB, an air lose of 30dB and an antenna gain of 11dBi are added.

$$P = P_R + L_C + L_A - G = -60 + 10 + 30 - 11 = -31 \text{dBm}$$

The measurement will be conducted at one channel No661 (middle channels of PCS1900 band).


Limits	≤ -13dBm
--------	----------

Test result:
GSM MODE:



Channel 661, 30MHz~3GHz

Note: The signal beyond the limit is the base station simulator carrier.



Channel 661, 3GHz~20GHz

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date
1	E5515C(8960) Mobile Station Tester	Agilent	GB44050904	19 th Aug. 2011
2	PSA E4440A Spectrum Analyzer	Agilent	MY41000183	19 th Aug. 2011
3	66309B DC Power Supply	Agilent	MY43000461	19 th Aug. 2011
4	1506A Power Splitter	Weinschel	MN154	19 th Aug. 2011
5	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	19 th Aug. 2011
6	ESI 40 EMI test receiver	R&S	100015	19 th Aug. 2011
7	SMR 20 Signal generator	R&S	100086	19 th Aug. 2011
8	CMU 200 Radio tester	R&S	100313	19 th Aug. 2011
9	12.65m*8.03m*7.50m Fully-Anechoic Chamber	FRANKONIA	-----	19 th Aug. 2011
10	HL562 Ultra log test antenna	R&S	100016	19 th Aug. 2011
11	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	-----	19 th Aug. 2011
12	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100030	19 th Aug. 2011
13	HF 906 Double-Ridged Waveguide Horn Antenna	R&S	100029	19 th Aug. 2011
14	PS2000 Turn Table	FRANKONIA	-----	19 th Aug. 2011
15	MA260 Antenna Master	FRANKONIA	-----	19 th Aug. 2011
16	SH-241 Climatic Chamber	ESPEC	92000389	19 th Aug. 2011
17	ES-K1 EMI test software	R&S	-----	19 th Aug. 2011
18	HL562 Receive antenna	R&S	100167	19 th Aug. 2011

Appendix

Appendix1 Test Setup