



RF exposure requirements – ZTE MF200

Dear Reviewer,

The maximum measured power output is

GSM 850:32.55dBm

GSM 1900:29.58dBm

UMTS 850: 24.53dBm

UMTS 1900: 24.53dBm

the maximum antenna gain for integral antenna is

GSM 850:-1.6dBi

GSM 1900:1.12dBi

UMTS 850: -1.6dBi

UMTS 1900: 1.12dBi

The maximum permissible exposure is defined in 47 CFR 1.1310 with 1 mW/cm².

The Transmitter is using external antennas that operate at 20 cm or more from nearby persons.

The maximum permitted level is calculated using the general equation:

$$S = P' / 4\pi R^2$$

$$\text{GSM 850: } P' = 32.55\text{dBm} + (-1.6\text{dBi}) = 30.95\text{dBm} = 1245\text{mW}$$

$$\text{GSM1900: } P' = 29.58\text{dBm} + 1.12\text{dBi} = 30.7\text{dBm} = 1175\text{mW}$$

$$\text{UMTS850: } P' = 24.53\text{dBm} + (-1.6\text{dBi}) = 22.93\text{dBm} = 196\text{mW}$$

$$\text{UMTS1900: } P' = 24.53\text{dBm} + 1.12\text{dBi} = 25.65\text{dBm} = 367\text{mW}$$

$$R = 20\text{cm}$$

$$\pi = 3.1416$$

Solving for S, the power density at 20 cm is

$$\text{GSM 850: } \mathbf{0.248\text{mW/ cm}^2}$$

$$\text{GSM1900: } \mathbf{0.234\text{mW/ cm}^2}$$

$$\text{UMTS850: } \mathbf{0.039\text{mW/ cm}^2}$$

$$\text{UMTS1900: } \mathbf{0.073\text{mW/ cm}^2}$$

So the limit is kept.

Best Regard.

2009-08-24

Xue Zhen

Telecommunication Metrology Center of MIIT

No 52 Huayuanbei Road, Haidian District Beijing P.R.China 100083