



MPE REPORT

No. 2013TAR211

for

ZTE CORPORATION

HSPA+ Wireless Router

Type: MF25A

with

Hardware Version: PCBMF25AV1.0.0

Software Version: EN_ZTE_MF25AV1.0.0B03

Issued Date: 2013-3-7

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633, Fax:+86(0)10-62304633 Email:welcome@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT	5
3.3. INTERNAL IDENTIFICATION OF AE	5
4. REFERENCE DOCUMENTS	6
4.1. REFERENCE DOCUMENTS FOR TESTING	6
5. RF EXPOSURE LIMIT	6
6. FRIIS FORMULA	6
7. CLASSIFICATION	7
8. TEST RESULTS	7

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 51, Xueyuan Road, Haidian District, Beijing, P.R.China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data


Project Leader: Xue Zhen
Testing Start Date: 2013-02-25
Testing End Date: 2013-03-08

1.4. Signature




Xue Zhen

(Prepared this test report)



Song Chongwen

(Reviewed this test report)



Lu Bingsong

Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
City: Shenzhen
Postal Code: 518057
Country: China
Telephone: 0086 21 68897541
Fax: 0086 21 61460600

2.2. Manufacturer Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
City: Shenzhen
Postal Code: 518057
Country: China
Telephone: 0086 21 68897541
Fax: 0086 21 61460600

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HSPA+ Wireless Router
Model	MF25A
UMTS Frequency Band	FDD Band II/Band V
GSM Frequency Band	EGSM900/DCS1800/GSM850/PCS1900
Type of modulation	GMSK, 8PSK, QPSK, 16QAM
Power Class	EGSM900:4, DCS1800:1, GSM850:4, PCS1900:1 FDD Band II:3, FDD Band V:3
GPRS Multislot Class	10
EGPRS Multislot Class	12
Extreme Temperature	-10/+55°C
Normal Voltage	4.8V
Extreme Low Voltage	5.0V
Extreme High Voltage	5.2V

Note1: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N05	869842010003577	PCBMF25AV1.0.0	EN_ZTE_MF25AV1.0.0 B03	2013-02-20
N11	869842010003551	PCBMF25AV1.0.0	EN_ZTE_MF25AV1.0.0 B03	2013-02-20
N15	869842010003593	PCBMF25AV1.0.0	EN_ZTE_MF25AV1.0.0 B03	2013-02-20

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN
AE1	RF cable	---
AE2	Charger	---

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

447498 23 D01 General RF Exposure Guidance v05: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

5. RF Exposure Limit

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz *Plane-wave equivalent power density

6. Friis Formula

Friis transmission formula : $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in **W/m²**

P_{out} = output power to antenna in **W**

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in **m**

P_d is the limit of MPE. If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

7. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

8. Test Results

8.1. the maximum antenna gain

The maximum antenna gain for internal antenna is

GSM 850: 0.5dBi

GSM1900: 1.6dBi

UMTS 850: 0.5dBi

UMTS 1900: 1.6dBi

802.11/b: 1.9dBi

802.11/g: 1.9dBi

802.11/n: 1.9dBi

8.2. Output Power Into Antenna & RF Exposure value at distance 20cm

Frequency band	Output Power (dBm)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
GSM 850	32.92	0.44	0.57
GSM 1900	29.00	0.23	1
UMTS 850	22.58	0.04	0.57
UMTS 1900	22.81	0.06	1
802.11/b	21.56	0.04	1
802.11/g	21.79	0.05	1
802.11/n	23.56	0.07	1

Considering the simultaneous transmission of cellular and WLAN, sum of two worst cases MPE ratio is

$$0.44/0.57+0.07/1=0.77+0.07=0.84<1$$

So the limit is kept.

END OF REPORT