



FCC PART 15C TEST REPORT No.2012WLN0301

for

ZTE CORPORATION

HSPA+ Wireless Router

Model: MF29A

With

FCC ID: Q78-ZTEMF29A

Hardware Version: PCBMF29AV1.0.0

Software Version: EN_ZTE_MF29AV1.0.0B05

Issued Date: 2012-02-10



No. DGA-PL-114/01-02

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

Note:The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China, 100191

Tel:+86(0)10-62304633, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com

CONTENTS

CONTENTS	2
1. TEST LABORATORY	6
1.1. TESTING LOCATION.....	6
1.2. TESTING ENVIRONMENT.....	6
1.3. PROJECT DATA	6
1.4. SIGNATURE	6
2. CLIENT INFORMATION	7
2.1. APPLICANT INFORMATION.....	7
2.2. MANUFACTURER INFORMATION.....	7
3. EQUIPMENT UNDER TEST(EUT) AND ANCILLARY EQUIPMENT(AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.....	8
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	8
3.4. GENERAL DESCRIPTION	8
4. REFERENCE DOCUMENTS	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT.....	8
4.2. REFERENCE DOCUMENTS FOR TESTING.....	9
5. LABORATORY ENVIRONMENT	10
6. SUMMARY OF TEST RESULTS	11
6.1. SUMMARY OF TEST RESULTS	11
6.2. STATEMENTS.....	11
7. TEST EQUIPMENTS UTILIZED	12
ANNEX A: MEASUREMENT RESULTS	13
A.1. MEASUREMENT METHOD	13
A.2. MAXIMUM OUTPUT POWER	14
A.2.1. MAXIMUM PEAK OUTPUT POWER-CONDUCTED	14
A.2.2. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED.....	16
A.3. PEAK POWER SPECTRAL DENSITY	17
FIG. 1 POWER SPECTRAL DENSITY (802.11B, CH 1).....	18
FIG. 2 POWER SPECTRAL DENSITY (802.11B, CH 6).....	18
FIG. 3 POWER SPECTRAL DENSITY (802.11B, CH 11).....	19
FIG. 4 POWER SPECTRAL DENSITY (802.11G, CH 1)	19
FIG. 5 POWER SPECTRAL DENSITY (802.11G, CH 6)	20
FIG. 6 POWER SPECTRAL DENSITY (802.11G, CH 11)	20
FIG. 7 POWER SPECTRAL DENSITY (802.11N-20MHZ, CH 1)	21
FIG. 8 POWER SPECTRAL DENSITY (802.11N-20MHZ, CH 6).....	21
FIG. 9 POWER SPECTRAL DENSITY (802.11N-20MHZ, CH 11).....	22

FIG. 10	POWER SPECTRAL DENSITY (802.11N-40MHZ, CH 3)	22
FIG. 11	POWER SPECTRAL DENSITY (802.11N-40MHZ, CH 6)	23
FIG. 12	POWER SPECTRAL DENSITY (802.11N-40MHZ, CH 9)	23
A.4.	OCCUPIED 6dB BANDWIDTH	24
FIG. 13	OCCUPIED 6dB BANDWIDTH (802.11B, CH 1)	25
FIG. 14	OCCUPIED 6dB BANDWIDTH (802.11B, CH 6)	25
FIG. 15	OCCUPIED 6dB BANDWIDTH (802.11B, CH 11)	26
FIG. 16	OCCUPIED 6dB BANDWIDTH (802.11G, CH 1)	26
FIG. 17	OCCUPIED 6dB BANDWIDTH (802.11G, CH 6)	27
FIG. 18	OCCUPIED 6dB BANDWIDTH (802.11G, CH 11)	27
FIG. 19	OCCUPIED 6dB BANDWIDTH (802.11N-20MHZ, CH 1)	28
FIG. 20	OCCUPIED 6dB BANDWIDTH (802.11N-20MHZ, CH 6)	28
FIG. 21	OCCUPIED 6dB BANDWIDTH (802.11N-20MHZ, CH 11)	29
FIG. 22	OCCUPIED 6dB BANDWIDTH (802.11N-40MHZ, CH 3)	29
FIG. 23	OCCUPIED 6dB BANDWIDTH (802.11N-40MHZ, CH 6)	30
FIG. 24	OCCUPIED 6dB BANDWIDTH (802.11N-40MHZ, CH 9)	30
A.5.	BAND EDGES COMPLIANCE	31
FIG. 25	BAND EDGES (802.11B, CH 1)	32
FIG. 26	BAND EDGES (802.11B, CH 11)	32
FIG. 27	BAND EDGES (802.11G, CH 1)	33
FIG. 28	BAND EDGES (802.11G, CH 11)	33
FIG. 29	BAND EDGES (802.11N-20MHZ, CH 1)	34
FIG. 30	BAND EDGES (802.11N-20MHZ, CH 11)	34
FIG. 31	BAND EDGES (802.11N-40MHZ, CH 3)	35
FIG. 32	BAND EDGES (802.11N-40MHZ, CH 9)	35
A.6.	TRANSMITTER SPURIOUS EMISSION	36
A.6.1	TRANSMITTER SPURIOUS EMISSION - CONDUCTED	36
FIG. 33	CONDUCTED SPURIOUS EMISSION (802.11B, CH1, CENTER FREQUENCY)	37
FIG. 34	CONDUCTED SPURIOUS EMISSION (802.11B, CH1, 30 MHZ-26 GHZ)	38
FIG. 35	CONDUCTED SPURIOUS EMISSION (802.11B, CH6, CENTER FREQUENCY)	38
FIG. 36	CONDUCTED SPURIOUS EMISSION (802.11B, CH6, 30 MHZ-26 GHZ)	39
FIG. 37	CONDUCTED SPURIOUS EMISSION (802.11B, CH11, CENTER FREQUENCY)	39
FIG. 38	CONDUCTED SPURIOUS EMISSION (802.11B, CH11, 30 MHZ-26 GHZ)	40
FIG. 39	CONDUCTED SPURIOUS EMISSION (802.11G, CH1, CENTER FREQUENCY)	40
FIG. 40	CONDUCTED SPURIOUS EMISSION (802.11G, CH1, 30 MHZ-26 GHZ)	41
FIG. 41	CONDUCTED SPURIOUS EMISSION (802.11G, CH6, CENTER FREQUENCY)	41
FIG. 42	CONDUCTED SPURIOUS EMISSION (802.11G, CH6, 30 MHZ-26 GHZ)	42
FIG. 43	CONDUCTED SPURIOUS EMISSION (802.11G, CH11, CENTER FREQUENCY)	42
FIG. 44	CONDUCTED SPURIOUS EMISSION (802.11G, CH11, 30 MHZ-26 GHZ)	43
FIG. 45	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH1, CENTER FREQUENCY)	43
FIG. 46	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH1, 30 MHZ-26 GHZ)	44
FIG. 47	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH6, CENTER FREQUENCY)	44
FIG. 48	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH6, 30 MHZ-26 GHZ)	45
FIG. 49	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH11, CENTER FREQUENCY)	45

FIG. 50	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH11, 30 MHZ-26 GHZ)	46
FIG. 51	CONDUCTED SPURIOUS EMISSION (802.11N-40MHZ, CH3, CENTER FREQUENCY).....	46
FIG. 52	CONDUCTED SPURIOUS EMISSION (802.11N-40MHZ, CH3, 30 MHZ-26 GHZ)	47
FIG. 53	CONDUCTED SPURIOUS EMISSION (802.11N-40MHZ, CH6, CENTER FREQUENCY).....	47
FIG. 54	CONDUCTED SPURIOUS EMISSION (802.11N-40MHZ, CH6, 30 MHZ-26 GHZ)	48
FIG. 55	CONDUCTED SPURIOUS EMISSION (802.11N-40MHZ, CH9, CENTER FREQUENCY).....	48
FIG. 56	CONDUCTED SPURIOUS EMISSION (802.11N-40MHZ, CH9, 30 MHZ-26 GHZ)	49
A.6.2	TRANSMITTER SPURIOUS EMISSION - RADIATED	50
FIG. 57	RADIATED SPURIOUS EMISSION (POWER): 802.11B, CH1, 2.38 GHZ - 245GHZ.....	57
FIG. 58	RADIATED SPURIOUS EMISSION (802.11B, CH1, 30 MHZ-1 GHZ)	57
FIG. 59	RADIATED SPURIOUS EMISSION (802.11B, CH1, 1 GHZ-4 GHZ)	58
FIG. 60	RADIATED SPURIOUS EMISSION (802.11B, CH1, 4 GHZ-18 GHZ)	58
FIG. 61	RADIATED SPURIOUS EMISSION (802.11B, CH6, 30 MHZ-1 GHZ)	59
FIG. 62	RADIATED SPURIOUS EMISSION (802.11B, CH6, 1 GHZ-4 GHZ)	59
FIG. 63	RADIATED SPURIOUS EMISSION (802.11B, CH6, 4 GHZ-18 GHZ)	60
FIG. 64	RADIATED SPURIOUS EMISSION (POWER): 802.11B, CH11, 2.45 GHZ - 2.50GHZ	60
FIG. 65	RADIATED SPURIOUS EMISSION (802.11B, CH11, 30 MHZ-1 GHZ)	61
FIG. 66	RADIATED SPURIOUS EMISSION (802.11B, CH11, 1 GHZ-4 GHZ)	61
FIG. 67	RADIATED SPURIOUS EMISSION (802.11B, CH11, 4 GHZ-18 GHZ)	62
FIG. 68	RADIATED SPURIOUS EMISSION (POWER): 802.11G, CH1, 2.38 GHZ - 2.45GHZ.....	62
FIG. 69	RADIATED SPURIOUS EMISSION (802.11G, CH1, 30 MHZ-1 GHZ)	63
FIG. 70	RADIATED SPURIOUS EMISSION (802.11G, CH1, 1 GHZ-4 GHZ)	63
FIG. 71	RADIATED SPURIOUS EMISSION (802.11G, CH1, 4 GHZ-18 GHZ)	64
FIG. 72	RADIATED SPURIOUS EMISSION (802.11G, CH6, 30 MHZ-1 GHZ)	64
FIG. 73	RADIATED SPURIOUS EMISSION (802.11G, CH6, 1 GHZ-4 GHZ)	65
FIG. 74	RADIATED SPURIOUS EMISSION (802.11G, CH6, 4 GHZ-18 GHZ)	65
FIG. 75	RADIATED SPURIOUS EMISSION (POWER): 802.11G, CH11, 2.45 GHZ - 2.50GHZ	66
FIG. 76	RADIATED SPURIOUS EMISSION (802.11G, CH11, 30 MHZ-1 GHZ)	66
FIG. 77	RADIATED SPURIOUS EMISSION (802.11G, CH11, 1 GHZ-4 GHZ)	67
FIG. 78	RADIATED SPURIOUS EMISSION (802.11G, CH11, 4 GHZ-18 GHZ)	67
FIG. 79	RADIATED SPURIOUS EMISSION (POWER): 802.11N-20MHZ, CH1, 2.38 GHZ - 2.45GHZ ..	68
FIG. 80	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH1, 30 MHZ-1 GHZ)	68
FIG. 81	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH1, 1 GHZ-4 GHZ)	69
FIG. 82	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH1, 4 GHZ-18 GHZ)	69
FIG. 83	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH6, 30 MHZ-1 GHZ)	70
FIG. 84	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH6, 1 GHZ-4 GHZ)	70
FIG. 85	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH6, 4 GHZ-18 GHZ)	71
FIG. 86	RADIATED SPURIOUS EMISSION (POWER): 802.11N-20MHZ, CH11, 2.45 GHZ - 2.50GHZ	71
FIG. 87	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH11, 30 MHZ-1 GHZ).....	72
FIG. 88	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH11, 1 GHZ-4 GHZ).....	72
FIG. 89	RADIATED SPURIOUS EMISSION (802.11N-20MHZ, CH11, 4 GHZ-18 GHZ).....	73
FIG. 90	RADIATED SPURIOUS EMISSION (POWER): 802.11N-40MHZ, CH3, 2.38 GHZ - 2.45GHZ ..	73
FIG. 91	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH3, 30 MHZ-1 GHZ)	74
FIG. 92	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH3, 1 GHZ-4 GHZ)	74

FIG. 93	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH3, 4 GHZ-18 GHZ)	75
FIG. 94	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH6, 30 MHZ-1 GHZ)	75
FIG. 95	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH6, 1 GHZ-4 GHZ)	76
FIG. 96	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH6, 4 GHZ-18 GHZ)	76
FIG. 97	RADIATED SPURIOUS EMISSION (POWER): 802.11N-40MHZ, CH9, 2.45 GHZ - 2.50GHZ ..	77
FIG. 98	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH9, 30 MHZ-1 GHZ)	77
FIG. 99	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH9, 1 GHZ-4 GHZ)	78
FIG. 100	RADIATED SPURIOUS EMISSION (802.11N-40MHZ, CH9, 4 GHZ-18 GHZ).....	78
FIG. 101	RADIATED EMISSION: 18 GHZ - 26.5 GHZ	79
A.7.	AC POWERLINE CONDUCTED EMISSION	80
FIG. 102	AC POWERLINE CONDUCTED EMISSION-802.11N	81
FIG. 103	AC POWERLINE CONDUCTED EMISSION-IDLE.....	82

1. TEST LABORATORY

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-30°C
Extreme Temperature: -20/+55°C
Relative Humidity: 30-60%
Air Pressure 990hPa-1040hPa

Note: The climatic requirements above are general exclude the special requirements for dedicated test environments listed in section 5 and some specific test cases in other parts of this report.

1.3. Project data

Testing End Date: 2012-01-17


1.4. Signature



Sun Zhenyu
(Prepared this test report)



Gao Hong
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. CLIENT INFORMATION

2.1. Applicant Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China
City: Shenzhen
Postal Code: 518057
Country: China
Contact /
Email /
Telephone: +86-21-68897541
Fax: +86-21-50801070

2.2. Manufacturer Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China
City: Shenzhen
Postal Code: 518057
Country: China
Contact /
Email /
Telephone: +86-21-68897541
Fax: +86-21-50801070

3. EQUIPMENT UNDER TEST(EUT) AND ANCILLARY EQUIPMENT(AE)

3.1. About EUT

Description	HSPA+ Wireless Router
Model	MF29A
FCC ID	Q78-ZTEMF29A
IC ID	/
With WLAN Function	Yes
Frequency Range	ISM 2400MHz~2483.5MHz
Type of Modulation	DSSS/CCK/OFDM
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	21.98dBm(OFDM)
Power Supply	12V DC

Note: Photographs of EUT are shown in ANNEX C of this test report.

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
EUT1	/	PCBMF29AV1.0.0	EN_ZTE_MF29AV1.0.0B05
EUT2	/	PCBMF29AV1.0.0	EN_ZTE_MF29AV1.0.0B05

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	SN
AE1	Power Supply	STC-A2O120150C55-C	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

Equipment Under Test (EUT) is a model of HSPA+ Wireless Router with integrated antenna. It consists of normal options: Battery and Charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. REFERENCE DOCUMENTS FOR TESTING

The following documents listed in this section are referred for testing.

FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	Oct, 2009 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2009
KDB558074	Measurement of Digital Transmission Systems Operating under Section 15.247	March 23, 2005

5. LABORATORY ENVIRONMENT

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing::

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Shielding Room2 (7.30 meters×4.00 meters×3.80 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (a)	/	P
Peak Power Spectral Density	15.247 (d)	/	P
Occupied 6dB Bandwidth	15.247 (d)	/	P
Band Edges Compliance	15.247 (b)	/	P
Transmitter Spurious Emission - Conducted	15.247	/	P
Transmitter Spurious Emission - Radiated	15.247, 15.209, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P

Please refer to **ANNEX A** for detail.

The measurement is made according to Public notice KDB558074 and ANSI C63.4.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by TMC
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

TMC has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage
V min	Low Voltage
V max	High Voltage
H nom	Norm Humidity
A nom	Norm Air Pressure

For this report, all the test case listed above are tested under Normal Temperature and Normal Voltage, and also under norm humidity, the specific conditions as following:

Temperature	T nom	26°C
Voltage	V nom	3.6V(By battery)
Humidity	H nom	44%
Air Pressure	A nom	1010hPa

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	2012-07-19
2	Spectrum Analyzer	MS2687B	6200819812	Anritsu	2012-09-22
3	Test Receiver	ESS	847151/015	Rohde & Schwarz	2012-10-30
4	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2012-08-12

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Test Receiver	ESI40	831564/002	Rohde & Schwarz	2012-08-11
2	BiLog Antenna	3142B	9908-1403	EMCO	2012-03-15
3	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO	2012-12-25

Anechoic chamber


Anechoic chamber by Frankonia German.

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to ANSI C63.4 and KDB558074

A.2. Maximum Output Power

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

The measurement is made according to ANSI C63.4 and KDB558074, and power output option 1 (RBW=20MHz) in KDB558074 is used for the test. EUT is operating in continuous transmitting mode

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

A.2.1. Maximum Peak Output Power-conducted

Measurement Results:

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	19.34	/	/
	2	19.40	/	/
	5.5	20.70	/	/
	11	21.98	21.79	21.88
802.11g	6	20.73	/	/
	9	20.86	/	/
	12	20.20	/	/
	18	20.33	/	/
	24	21.11	/	/
	36	21.07	/	/
	48	21.25	/	/
	54	21.56	21.43	21.52

The data rate 11Mbps and 54Mbps are selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20MHz mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	20.92	/	/
	MCS1	20.54	/	/
	MCS2	20.53	/	/
	MCS3	20.93	/	/
	MCS4	21.00	/	/
	MCS5	20.92	/	/

	MCS6	21.27	/	/
	MCS7	21.18	/	/
	MCS8	21.09	/	/
	MCS9	20.15	/	/
	MCS10	20.45	/	/
	MCS11	21.28	21.17	21.29
	MCS12	21.04	/	/
	MCS13	21.08	/	/
	MCS14	21.16	/	/
	MCS15	21.01	/	/

The data rate MCS11-HT20MHz is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40MHz mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n (40MHz)	MCS0	20.74	/	/
	MCS1	20.29	/	/
	MCS2	20.60	/	/
	MCS3	20.87	/	/
	MCS4	21.17	/	/
	MCS5	21.35	21.43	21.41
	MCS6	21.03	/	/
	MCS7	21.01	/	/
	MCS8	21.01	/	/
	MCS9	20.27	/	/
	MCS10	20.35	/	/
	MCS11	20.83	/	/
	MCS12	20.91	/	/
	MCS13	20.93	/	/
	MCS14	20.80	/	/
MCS15	20.90	/	/	

The data rate MCS5-HT40MHz is selected as worse condition, and the following cases are performed with this condition.

Note: the EUT have two antennas, antenna 0 and antenna 1. For SISO mode, the output power of antenna 0 is higher than other selection, and antenna 0 is selected as the worse condition. For MIMO mode, antenna 0 and antenna 1 are combined to one chain.

A.2.2. Maximum Average Output Power-conducted

802.11b/g mode

Mode	Test Result (dBm)		
	2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	16.92	14.78	15.53
802.11g	13.05	10.99	11.43

802.11n-HT20MHz mode

Mode	Test Result (dBm)		
	2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	12.67	10.53	11.23

802.11n-HT40MHz mode

Mode	Test Result (dBm)		
	2422MHz (Ch3)	2437MHz (Ch6)	2452 MHz (Ch9)
802.11n (40MHz)	12.12	9.52	10.16

Conclusion: PASS

A.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(d)	< 8 dBm/3 kHz

The measurement is made according to ANSI C63.4 and KDB558074

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Measurement Results:

802.11b/g mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
		Fig.	Value	
802.11b	1	Fig.1	2.57	P
	6	Fig.2	-1.08	P
	11	Fig.3	-1.20	P
802.11g	1	Fig.4	-15.03	P
	6	Fig.5	-14.99	P
	11	Fig.6	-14.77	P

802.11n-HT20MHz mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
		Fig.	Value	
802.11n (20MHz)	1	Fig.7	-14.33	P
	6	Fig.8	-14.32	P
	11	Fig.9	-14.15	P
802.11n (40MHz)	3	Fig.10	-21.73	P
	6	Fig.11	-22.24	P
	9	Fig.12	-22.94	P

Conclusion: PASS

Test graphs as below:




Fig. 1 Power Spectral Density (802.11b, Ch 1)




Fig. 2 Power Spectral Density (802.11b, Ch 6)




Fig. 3 Power Spectral Density (802.11b, Ch 11)




Fig. 4 Power Spectral Density (802.11g, Ch 1)




Fig. 5 Power Spectral Density (802.11g, Ch 6)




Fig. 6 Power Spectral Density (802.11g, Ch 11)




Fig. 7 Power Spectral Density (802.11n-20MHz, Ch 1)




Fig. 8 Power Spectral Density (802.11n-20MHz, Ch 6)




Fig. 9 Power Spectral Density (802.11n-20MHz, Ch 11)




Fig. 10 Power Spectral Density (802.11n-40MHz, Ch 3)




Fig. 11 Power Spectral Density (802.11n-40MHz, Ch 6)




Fig. 12 Power Spectral Density (802.11n-40MHz, Ch 9)

A.4. Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

The measurement is made according to ANSI C63.4 and KDB558074

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

802.11b/g mode

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11b	1	Fig.13	12100	P
	6	Fig.14	12100	P
	11	Fig.15	12150	P
802.11g	1	Fig.16	16400	P
	6	Fig.17	16400	P
	11	Fig.18	16400	P

802.11n mode

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11n (20MHz)	1	Fig.19	17000	P
	6	Fig.20	17000	P
	11	Fig.21	16850	P
802.11n (40MHz)	3	Fig.22	35550	P
	6	Fig.23	35550	P
	9	Fig.24	35650	P

Conclusion: PASS

Test graphs as below:



Fig. 13 Occupied 6dB Bandwidth (802.11b, Ch 1)




Fig. 14 Occupied 6dB Bandwidth (802.11b, Ch 6)



Fig. 15 Occupied 6dB Bandwidth (802.11b, Ch 11)




Fig. 16 Occupied 6dB Bandwidth (802.11g, Ch 1)




Fig. 17 Occupied 6dB Bandwidth (802.11g, Ch 6)




Fig. 18 Occupied 6dB Bandwidth (802.11g, Ch 11)




Fig. 19 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 1)




Fig. 20 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 6)



Fig. 21 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 11)




Fig. 22 Occupied 6dB Bandwidth (802.11n-40MHz, Ch 3)




Fig. 23 Occupied 6dB Bandwidth (802.11n-40MHz, Ch 6)




Fig. 24 Occupied 6dB Bandwidth (802.11n-40MHz, Ch 9)

A.5. Band Edges Compliance

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

The measurement is made according to ANSI C63.4 and KDB558074

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.25	P
	11	Fig.26	P
802.11g	1	Fig.27	P
	11	Fig.28	P

802.11n mode

Mode	Channel	Test Results	Conclusion
802.11n (20MHz)	1	Fig.29	P
	11	Fig.30	P
802.11n (40MHz)	1	Fig.31	P
	11	Fig.32	P

Conclusion: PASS

Test graphs as below:




Fig. 25 Band Edges (802.11b, Ch 1)




Fig. 26 Band Edges (802.11b, Ch 11)




Fig. 27 Band Edges (802.11g, Ch 1)




Fig. 28 Band Edges (802.11g, Ch 11)




Fig. 29 Band Edges (802.11n-20MHz, Ch 1)




Fig. 30 Band Edges (802.11n-20MHz, Ch 11)




Fig. 31 Band Edges (802.11n-40MHz, Ch 3)




Fig. 32 Band Edges (802.11n-40MHz, Ch 9)

A.6. Transmitter Spurious Emission

A.6.1 Transmitter Spurious Emission - Conducted

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

The measurement is made according to ANSI C63.4 and KDB558074

Measurement Uncertainty:

Frequency Range	Uncertainty
$30\text{MHz} \leq f \leq 2\text{GHz}$	0.63
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	0.82
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.55
$8\text{GHz} \leq f \leq 20\text{GHz}$	1.86
$20\text{GHz} \leq f \leq 22\text{GHz}$	1.90
$22\text{GHz} \leq f \leq 26\text{GHz}$	2.20

Measurement Results:

802.11b/g mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412 GHz	Fig.33	P
		30 MHz ~ 26 GHz	Fig.34	P
	6	2.437 GHz	Fig.35	P
		30 MHz ~ 26 GHz	Fig.36	P
	11	2.462 GHz	Fig.37	P
		30 MHz ~ 26 GHz	Fig.38	P
802.11g	1	2.412 GHz	Fig.39	P
		30 MHz ~ 26 GHz	Fig.40	P
	6	2.437 GHz	Fig.41	P
		30 MHz ~ 26 GHz	Fig.42	P
	11	2.462 GHz	Fig.43	P
		30 MHz ~ 26 GHz	Fig.44	P

802.11n mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n (20MHz)	1	2.412 GHz	Fig.45	P
		30 MHz ~ 26 GHz	Fig.46	P
	6	2.437 GHz	Fig.47	P
		30 MHz ~ 26 GHz	Fig.48	P
	11	2.462 GHz	Fig.49	P

		30 MHz ~ 26 GHz	Fig.50	P
802.11n (40MHz)	3	2.422 GHz	Fig.51	P
		30 MHz ~ 26 GHz	Fig.52	P
	6	2.437 GHz	Fig.53	P
		30 MHz ~ 26 GHz	Fig.54	P
	9	2.452 GHz	Fig.55	P
		30 MHz ~ 26 GHz	Fig.56	P

Conclusion: PASS

Test graphs as below:




Fig. 33 Conducted Spurious Emission (802.11b, Ch1, Center Frequency)




Fig. 34 Conducted Spurious Emission (802.11b, Ch1, 30 MHz-26 GHz)




Fig. 35 Conducted Spurious Emission (802.11b, Ch6, Center Frequency)




Fig. 36 Conducted Spurious Emission (802.11b, Ch6, 30 MHz-26 GHz)




Fig. 37 Conducted Spurious Emission (802.11b, Ch11, Center Frequency)




Fig. 38 Conducted Spurious Emission (802.11b, Ch11, 30 MHz-26 GHz)




Fig. 39 Conducted Spurious Emission (802.11g, Ch1, Center Frequency)



Fig. 40 Conducted Spurious Emission (802.11g, Ch1, 30 MHz-26 GHz)




Fig. 41 Conducted Spurious Emission (802.11g, Ch6, Center Frequency)