



TEST REPORT

No. 2011TAR556

for

ZTE CORPORATION

CDMA 1X-EVDO Digital Mobile Phone

Model Name: ZTE N762

FCC ID: Q78-ZTEN762

IC ID : 5200A- ZTEN762

with

Hardware Version: c5mA

Software Version: N762V0.0.0B01

Issued Date: Oct 20, 2011

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAR accreditation (DIN EN ISO/IEC 17025): No. DGA-PL-114/01-02

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai Dian District, Beijing, P. R. China,100191.

Tel:+86(0)10-62304633-2604, Fax:+86(0)10-62304793, Email:welcome@emcite.com, web: www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS	9
7. TEST EQUIPMENTS UTILIZED	11
ANNEX A: MEASUREMENT RESULTS.....	12
A.1 OUTPUT POWER (§22.913(A)/ §24.232(B)).....	12
A.2 EMISSION LIMIT (§2.1051/ §24.238/ §22.917).....	17
A.3 CONDUCTED EMISSION (§15.107 §15.207).....	24
A.4 FREQUENCY STABILITY (§2.1055/ §24.235)	30
A.5 OCCUPIED BANDWIDTH (§2.1049(H)(I)).....	33
A.6 EMISSION BANDWIDTH (§22.917(B)/ §24.238(B))	49
A.7 BAND EDGE COMPLIANCE (§22.917(B)/ §24.238(B))	68
A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/ §22.917/ §24.238)	71

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: 3/F Shou Xiang Technology Building, No.51 Xueyuan Road, Hai
Dian District, Beijing, P. R. China
Postal Code: 100191
Telephone: 00861062304633
Fax: 00861062304793

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Sep 27, 2011
Testing End Date: Oct 20, 2011

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
Contact: Zhang Min
Email: zhang.min13@zte.com.cn
Telephone: 0086 21 68897541
Fax: 0086 21 50801070

2.2. Manufacturer Information

Company Name: ZTE CORPORATION
Address /Post: ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
Contact: Zhang Min
Email: zhang.min13@zte.com.cn
Telephone: 0086 21 68897541
Fax: 0086 21 50801070

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	CDMA 1X-EVDO Digital Mobile Phone
Model Name	ZTE N762
FCC ID	Q78-ZTEN762
IC ID	5200A- ZTEN762
Frequency	CDMA800/1900MHz and G-band
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Output power	29.50 dBm maximum ERP measured for CDMA800
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note:Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	ESN	HW Version	SW Version
N06	a1000020ab6902	c5mA	N762V0.0.0B01
N10	a1000020ab6911	c5mA	N762V0.0.0B01

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Charger	/

AE1

Model	Li3715T42P3h415266
Manufacturer	ZTE
Capacitance	1500mAh
Nominal Voltage	3.7V

AE2

Model	STC-A22O50I700USBA-Z
Manufacturer	RUIDE
Length of DC line	120cm (length of USB cable)

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of CDMA 1X-EVDO Digital Mobile Phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.09
FCC Part 22	PUBLIC MOBILE SERVICES	V 10.1.09
RSS-Gen	RSS-Gen — General Requirements and Information for the Certification of Radiocommunication Equipment	Issue 2, June 2007
RSS139	Advanced Wireless Services Equipment Operating in the Bands 1710-1755 MHz and 2110-2155 MHz	Issue 2, February 2009
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

CDMA 1900

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS- 133	Section in this report	Verdict
1	Output Power	24.232(b)	6.4	A.1	P
2	Emission Limit	24.238, 2.1051	6.5	A.2	P
3	Frequency Stability	24.235, 2.1055	6.3	A.4	P
4	Occupied Bandwidth	2.1049(h)(i)	4.6.1	A.5	P
5	Emission Bandwidth	24.238(b)	4.6.1	A.6	P
6	Band Edge Compliance	24.238(b)	6.5	A.7	P
7	Conducted Spurious Emission	24.238, 2.1057	6.5	A.8	P

CDMA 800

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS-132	Section in this report	Verdict
1	Output Power	§2.1046(a), 22.913(a)	4.4	A.1	P
2	Emission Limit	22.917, 2.1051	4.5	A.2	P
3	Frequency Stability	22.235, 2.1055	4.3	A.4	P
4	Occupied Bandwidth	2.1049(h)(i)	4.6.1	A.5	P
5	Emission Bandwidth	22.917(b)	4.6.1	A.6	P
6	Band Edge Compliance	22.917(b)	4.5	A.7	P
7	Conducted Spurious Emission	22.917, 2.1057	4.5	A.8	P

CDMA BC14 G-BAND

Items	Test Name	Clause in FCC rules	Clause in IC rules RSS-Gen and RSS- 133	Section in this report	Verdict
1	Output Power	24.232(b)	6.4	A.1	P
2	Emission Limit	24.238, 2.1051	6.5	A.2	P
3	Frequency Stability	24.235, 2.1055	6.3	A.4	P
4	Occupied Bandwidth	2.1049(h)(i)	4.6.1	A.5	P
5	Emission Bandwidth	24.238(b)	4.6.1	A.6	P
6	Band Edge Compliance	24.238(b)	6.5	A.7	P
7	Conducted Spurious Emission	24.238, 2.1057	6.5	A.8	P

Receiver Radiated Emission

Items	Test Name	Clause in FCC rules	Clause in IC rules		Section in this report	Verdict
			RSS-132	RSS-133		
1	Receiver Radiated Emissions	15.109 2.1053	4.6	6.6	A.2	P

7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESCI	100766	R&S	2012-06-06
2	Test Receiver	ESI40	831564/002	R&S	2012-07-12
3	BiLog Antenna	VULB9163	9163-175	Schwarzbeck	2012-07-05
4	BiLog Antenna	VULB9163	9163-302	Schwarzbeck	2012-07-10
5	Signal Generator	SMB100A	102063	R&S	2012-07-05
7	LISN	ESH2-Z5	829991/012	R&S	2012-07-20
8	Spectrum Analyzer	FSU26	200030	R&S	2012-03-18
9	Spectrum Analyzer	FSU46	100054	R&S	2012-09-14
10	Universal Radio Communication Tester	CMU200	100680	R&S	2012-02-23
11	Universal Radio Communication Tester	CMU200	109914	R&S	2012-07-21
12	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS	2012-08-31
13	Dual-Ridge Waveguide Horn Antenna	3117	00119021	ETS	2013-07-09
14	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2012-07-01
15	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2012-07-01
16	Climatic chamber	PL-2G	343074	ESPEC	2012-02-15

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER (§22.913(a)/§24.232(b))

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak) These measurements were done at 3 frequencies, 848.31MHz for CDMA 800 band, (bottom, middle and top of operational frequency range).

CDMA 800

Measurement result

Channel	Frequency(MHz)	Channel power(dBm)	Target (dB)
1013	824.70	23.93	23±1
384	836.52	23.80	23±1
777	848.31	23.86	23±1

CDMA 1900

Measurement result

Channel	Frequency(MHz)	Channel power(dBm)	Target (dB)
25	1851.25	23.17	23±1
600	1880.00	23.32	23±1
1175	1908.75	23.10	23±1

CDMA BC14 G-BAND

Measurement result

Channel	Frequency(MHz)	Channel power(dBm)	Target (dB)
1225	1911.25	22.73	23±1
1250	1912.5	22.92	23±1
1275	1913.75	22.65	23±1

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is

connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna.
The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} + P_{cl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

CDMA 800 -ERP

Limits

	Burst Peak ERP (dBm)
CDMA800	≤38.45dBm (7W)

Measurement result

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Correction (dBm)	Peak ERP(dBm)	Polarization
824.70	-20.17	2.27	-53.00	0.84	2.15	27.57	H
836.52	-18.19	2.26	-53.00	0.90	2.15	29.50	V
848.31	-20.49	2.31	-53.00	0.95	2.15	27.10	V

Frequency: 836.52MHz

Peak ERP(dBm)= P_{Mea}(-18.19dBm)-P_{cl}(2.26dB)-P_{Ag}(-53.00dB)-G_a (0.90dB)-2.15dBm=29.50dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

CDMA 1900 -EIRP

Limits

	Burst Peak ERP (dBm)
CDMA1900	≤33dBm (2W)

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Peak ERP(dBm)	Polarization
1851.25	-24.56	3.91	-50.00	-4.56	26.09	H
1880.00	-25.38	3.64	-50.00	-4.43	25.41	H
1908.75	-26.77	3.61	-50.00	-4.30	23.92	H

Frequency: 1851.25MHz

Peak EIRP(dBm)= P_{Mea}(-24.56dBm)- P_{cl}(3.91dB)-P_{Ag}(-50.00dB)-G_a (-4.56dB) =26.09dBm

ANALYZER SETTINGS: RBW = VBW = 3MHz

CDMA BC14 G-BAND -EIRP

Limits

	Burst Peak ERP (dBm)
CDMA BC14 G-BAND	≤33dBm (2W)

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	Peak ERP(dBm)	Polarization
1911.25	-29.93	3.62	-53.00	-4.30	23.75	H
1912.50	-31.65	3.68	-53.00	-4.29	21.96	H

1913.75	-32.08	3.72	-53.00	-4.28	21.48	H
---------	--------	------	--------	-------	-------	---

Frequency: 1909.91MHz

Peak EIRP(dBm) = $P_{\text{Mea}}(-29.93\text{dBm}) - P_{\text{cl}}(3.62\text{dB}) - P_{\text{Ag}}(-53.00\text{dB}) - G_{\text{a}}(-4.30\text{dB}) = 23.75\text{dBm}$

ANALYZER SETTINGS: RBW = VBW = 3MHz

A.2 EMISSION LIMIT (§2.1051/§24.238/§22.917)


A.2.1 Measurement Method

The measurement procedures in TIA-603C-2004 are used.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 10GHz. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the CDMA800 band.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

A amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

A.2.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the CDMA800 band (824.7MHz, 836.52MHz, 848.31MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the CDMA800 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
CDMA800	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
CDMA1900	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
CDMA800	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
CDMA1900	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
CDMA BC14 G-BAND	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

CDMA 800 Channel 1013/824.7MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1649.78	-60.90	3.41	-5.44	2.15	-61.02	-13.00	H
3300.48	-60.49	5.41	-7.42	2.15	-60.63	-13.00	H
4293.72	-64.42	6.72	-8.68	2.15	-64.61	-13.00	V
4950.09	-61.12	6.67	-9.61	2.15	-60.33	-13.00	H
7626.41	-63.93	9.18	-11.53	2.15	-63.73	-13.00	V
8868.82	-64.95	8.76	-12.50	2.15	-63.36	-13.00	V

CDMA 800 Channel 384/836.52MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1608.96	-66.70	3.41	-5.62	2.15	-66.64	-13.00	V
2471.69	-54.85	4.20	-5.32	2.15	-55.88	-13.00	V
3325.32	-71.25	5.24	-7.48	2.15	-71.16	-13.00	V
5019.22	-57.91	6.55	-9.71	2.15	-56.90	-13.00	H
6172.24	-58.30	6.90	-10.34	2.15	-57.01	-13.00	V
8644.04	-65.38	9.35	-12.32	2.15	-64.56	-13.00	H

CDMA 800 Channel 777/848.31MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Correction	Peak ERP(dBm)	Limit (dBm)	Polarization
				(dBm)			
1710.64	-63.55	3.52	-5.17	2.15	-64.05	-13.00	V
3393.07	-57.72	5.45	-7.64	2.15	-57.68	-13.00	H
5091.68	-53.22	6.80	-9.76	2.15	-52.41	-13.00	H
5997.68	-60.46	7.26	-10.20	2.15	-59.67	-13.00	V
7901.74	-64.99	11.63	-11.80	2.15	-66.97	-13.00	H
8690.73	-62.83	9.31	-12.35	2.15	-61.94	-13.00	V

CDMA 1900 Channel 25/1851.25MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
3585.63	-66.84	5.68	-8.00	-64.52	-13.00	H
5553.54	-49.24	6.78	-10.02	-46.00	-13.00	V
8324.97	-64.37	11.61	-12.09	-63.89	-13.00	H
11105.73	-53.59	8.41	-12.40	-49.60	-13.00	V
13805.55	-61.16	8.86	-13.92	-56.10	-13.00	V
17268.74	-56.46	10.77	-12.88	-54.35	-13.00	H

CDMA 1900 Channel 600/1880.00MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
3758.92	-59.43	6.50	-8.21	-57.72	-13.00	H
5639.34	-53.67	6.78	-10.06	-50.39	-13.00	V
8601.50	-65.24	9.64	-12.28	-62.60	-13.00	H
10144.01	-62.99	8.55	-12.43	-59.11	-13.00	V
14072.20	-60.37	8.70	-13.94	-55.13	-13.00	V
16855.18	-54.99	10.49	-12.40	-53.08	-13.00	V

CDMA 1900 Channel 1175/1908.75MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
5725.25	-46.27	6.82	-10.09	-43.00	-13.00	H
7975.76	-64.63	11.99	-11.88	-64.74	-13.00	V
10130.07	-60.91	8.49	-12.43	-56.97	-13.00	H
13793.11	-60.11	8.73	-13.92	-54.92	-13.00	H
15564.53	-58.59	8.90	-13.35	-54.14	-13.00	V
17255.32	-56.53	10.80	-12.86	-54.47	-13.00	V

CDMA BC14 G-BAND Channel 1200/1910.00MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
3819.29	-57.45	6.22	-8.28	-55.39	-13.00	H
5730.38	-48.09	6.84	-10.09	-44.84	-13.00	H
8654.40	-65.88	9.36	-12.32	-62.92	-13.00	V
10887.42	-65.44	8.42	-12.42	-61.44	-13.00	H
13174.38	-61.52	8.62	-13.47	-56.67	-13.00	H
16854.88	-55.02	10.49	-12.40	-53.11	-13.00	V

CDMA BC14 G-BAND Channel 1250/1880.00MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
3825.78	-58.18	6.31	-8.29	-56.20	-13.00	V
5736.82	-51.73	6.86	-10.09	-48.50	-13.00	H
7745.95	-67.69	10.10	-11.65	-66.14	-13.00	V
9895.36	-66.61	8.22	-12.44	-62.39	-13.00	V
11472.82	-61.57	8.38	-12.40	-57.55	-13.00	H
13490.86	-62.80	8.03	-13.79	-57.04	-13.00	H


CDMA BC14 G-BAND Channel 1299/1914.95MHz

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak ERP(dBm)	Limit (dBm)	Polarization
3830.58	-52.74	6.46	-8.30	-50.90	-13.00	H
5549.76	-67.62	6.75	-10.02	-64.35	-13.00	V
8620.31	-68.01	9.35	-12.30	-65.06	-13.00	H
10348.40	-64.16	8.44	-12.47	-60.13	-13.00	V
13267.94	-62.35	8.51	-13.57	-57.29	-13.00	V
17792.69	-55.97	10.73	-13.48	-53.22	-13.00	H

MEASUREMENT RESULT: "11A07232_1C_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.528000	38.70	10.1	46	7.3	N	GND
0.550500	36.90	10.1	46	9.1	N	GND
0.573000	37.50	10.1	46	8.5	N	GND
0.618000	36.50	10.1	46	9.5	N	GND
0.946500	37.80	10.1	46	8.2	N	GND
1.954500	34.50	10.1	46	11.5	L1	GND

CDMA1900




MEASUREMENT RESULT: "11A07232_2C_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.307500	44.30	10.1	60	15.7	L1	GND
0.348000	38.90	10.1	59	20.1	N	GND
0.613500	42.00	10.1	56	14.0	L1	GND
0.991500	41.70	10.1	56	14.3	L1	GND
2.081414	45.00	10.1	56	11.0	L1	GND
2.144642	37.20	10.1	56	18.8	N	GND

MEASUREMENT RESULT: "11A07232_2C_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.528000	38.60	10.1	46	7.4	N	GND
0.550500	37.20	10.1	46	8.8	N	GND
0.573000	37.20	10.1	46	8.8	N	GND
0.595500	36.50	10.1	46	9.5	N	GND
0.946500	38.10	10.1	46	7.9	N	GND
1.999500	35.00	10.1	46	11.0	L1	GND

CDMA BC14 G-BAND




MEASUREMENT RESULT: "11A07232_3C_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.307500	44.30	10.1	60	15.8	L1	GND
0.352500	42.70	10.1	59	16.2	L1	GND
0.613500	41.40	10.1	56	14.6	N	GND
0.946500	42.10	10.1	56	13.9	N	GND
1.995000	46.10	10.1	56	9.9	L1	GND
2.133972	43.10	10.1	56	12.9	L1	GND

MEASUREMENT RESULT: "11A07232_3C_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.528000	38.30	10.1	46	7.7	N	GND
0.550500	37.30	10.1	46	8.7	N	GND
0.595500	36.70	10.1	46	9.3	N	GND
0.640500	35.40	10.1	46	10.6	N	GND
0.946500	38.00	10.1	46	8.0	N	GND
1.779000	34.40	10.1	46	11.6	L1	GND

MP3




MEASUREMENT RESULT: "11A07232_MC_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.307500	44.30	10.1	60	15.7	L1	GND
0.528000	42.00	10.1	56	14.0	N	GND
0.991500	41.30	10.1	56	14.7	L1	GND
2.000000	45.80	10.1	56	10.2	L1	GND
2.020050	39.60	10.1	56	16.4	N	GND
2.123356	38.70	10.1	56	17.3	N	GND

MEASUREMENT RESULT: "11A07232_MC_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.528000	38.50	10.1	46	7.5	N	GND
0.573000	37.10	10.1	46	8.9	N	GND
0.595500	36.10	10.1	46	9.9	N	GND
0.946500	37.90	10.1	46	8.1	N	GND
1.909500	34.30	10.1	46	11.7	L1	GND
1.999500	32.20	10.1	46	13.8	N	GND

CAMERA



MEASUREMENT RESULT: "11A07232_PHC_fin QP"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line	PE
0.307500	44.30	10.1	60	15.7	L1	GND
0.613500	42.60	10.1	56	13.4	L1	GND
0.991500	40.70	10.1	56	15.3	N	GND
1.387500	39.10	10.1	56	16.9	N	GND
2.040301	46.50	10.1	56	9.5	L1	GND
2.123356	44.30	10.1	56	11.7	L1	GND

MEASUREMENT RESULT: "11A07232_PHC_fin AV"

Frequency MHz	Level dB μ V	Transd	Limit dB	Margin dB μ V	Line dB	PE
0.528000	38.30	10.1	46	7.7	N	GND
0.550500	37.00	10.1	46	9.0	N	GND
0.613500	37.20	10.1	46	8.8	N	GND
0.636000	37.30	10.1	46	8.7	N	GND
1.032000	37.30	10.1	46	8.7	N	GND
1.383000	36.30	10.1	46	9.7	N	GND

A.4 FREQUENCY STABILITY (§2.1055/§24.235)

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 384 for CDMA 800 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

A.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 3.7VDC, with a nominal voltage of 4.2VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section

2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

A.4.3 Measurement results

CDMA 800

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	2.01	0.011
3.7	2.01	0.015
4.2	3.04	0.023

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	3.88	0.029
-20	3.04	0.023
-10	3.04	0.023
0	2.01	0.015
10	2.01	0.015
20	2.01	0.015
30	3.04	0.023
40	3.04	0.023
50	3.88	0.029

CDMA 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	2.04	0.018
3.7	3.13	0.027
4.2	3.13	0.031

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	4.02	0.035
-20	3.13	0.027
-10	3.13	0.031
0	2.04	0.018
10	2.04	0.018
20	2.04	0.018
30	3.13	0.027
40	3.13	0.031
50	4.02	0.035

CDMA BC14 G-BAND

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	12	0.036
3.7	15	0.045
4.2	15	0.045

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	16	0.048
-20	15	0.045
-10	15	0.045
0	12	0.036
10	12	0.036
20	12	0.036
30	15	0.045
40	15	0.045
50	16	0.048

A.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))

A.5.1 Occupied Bandwidth Results

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the CDMA frequency band. The table below lists the measured -20dBc BW. Spectrum analyzer plots are included on the following pages.


CDMA 800 (-20dBc BW)

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1013	1.282
384	1.282
777	1.282

ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz


CDMA 800

Channel 1013-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 05:36:19

Channel 384-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2011 05:37:17

Channel 777-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 05:38:04

CDMA 800 (-20dBc BW)-IC

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1013	1.338
384	1.346
777	1.330


ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz

Channel 1013-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 07:04:02

Channel 1013-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 07:05:17

Channel 777-Occupied Reference Level (-20dBc BW)



Date: 19.OCT.2011 07:09:09

Channel 777-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2011 07:09:42


CDMA 1900 (-20dBc BW)

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
25	1.282
600	1.274
1175	1.282

ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz


CDMA 1900

Channel 25-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 06:26:15

Channel 600-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2011 06:27:05

Channel 1175-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 06:27:50

CDMA 1900 (-20dBc BW)-IC

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
25	1.354
600	1.346
1175	1.354


ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz

Channel 25-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 07:31:43

Channel 25-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 07:33:30

Channel 600-Occupied Reference Level (-20dBc BW)




Date: 19.OCT.2011 07:34:26

Channel 600-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 07:35:32

Channel 1175-Occupied Bandwidth Reference Level



Date: 19.OCT.2011 07:36:31

Channel 1175-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2011 07:37:16


CDMA BC14 G-BAND (-20dBc BW)

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1225	1.282
1250	1.290
1275	1.282

ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz


CDMA BC14 G-BAND

Channel 1225-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 02:48:40

Channel 1250-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2011 02:49:59

Channel 1275-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 02:51:09

CDMA BC14 G-BAND (-20dBc BW)-IC

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1225	1.330
1250	1.346
1275	1.338


ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz

Channel 1225-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 05:27:21

Channel 1225-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 05:28:08

Channel 1250-Occupied Reference Level (-20dBc BW)




Date: 19.OCT.2011 05:29:23

Channel 1250-Occupied Bandwidth (-20dBc BW)




Date: 19.OCT.2011 05:30:43

Channel 1275-Occupied Bandwidth Reference Level



Date: 19.OCT.2011 05:32:01

Channel 1275-Occupied Bandwidth (-20dBc BW)



Date: 19.OCT.2011 05:32:56

A.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))

A.6.1 Emission Bandwidth Results

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the CDMA frequency band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.


CDMA 800 (-26dBc)

Channel	Occupied Bandwidth (-26dBc BW)(MHz)
1013	1.378
384	1.370
777	1.378

ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz


CDMA 800

Channel 1013-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 05:39:04

Channel 384-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2011 05:40:00

Channel 777-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 05:40:51

CDMA 800 (-26dBc BW)-IC

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1013	1.394
384	1.386
777	1.386


ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz

Channel 1013-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 07:04:02

Channel 1013-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 07:06:11

Channel 384-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 07:06:34

Channel 384-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 07:08:01

Channel 777-Occupied Reference Level



Date: 19.OCT.2011 07:09:09

Channel 777-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2011 07:10:33


CDMA 1900 (-26dBc)

Channel	Occupied Bandwidth (-26dBc BW)(MHz)
25	1.378
600	1.378
1175	1.378

ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz


CDMA 1900

Channel 25-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 06:54:13

Channel 600-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2011 06:55:27

Channel 1175-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 06:56:21

CDMA 1900 (-26dBc BW)-IC

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
25	1.402
600	1.402
1175	1.402


ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz

Channel 25-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 07:31:43

Channel 25-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 07:34:03

Channel 600-Occupied Reference Level




Date: 19.OCT.2011 07:34:26

Channel 600-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 07:36:09

Channel 1175-Occupied Bandwidth Reference Level



Date: 19.OCT.2011 07:36:31

Channel 1175-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2011 07:39:40


CDMA BC14 G-BAND (-26dBc BW)

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1225	1.394
1250	1.386
1275	1.386

ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz


CDMA BC14 G-BAND

Channel 1225-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 02:52:25

Channel 1250-Occupied Bandwidth (-26dBc BW)



Date: 19.OCT.2011 02:55:45

Channel 1275-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 02:56:56

CDMA BC14 G-BAND (-26dBc BW)-IC

Channel	Occupied Bandwidth (-20dBc BW)(MHz)
1225	1.402
1250	1.386
1275	1.402


ANALYZER SETTINGS: RBW=20 kHz, VBW=50 kHz

Channel 1225-Occupied Bandwidth Reference Level




Date: 19.OCT.2011 05:27:21

Channel 1225-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 05:28:57

Channel 1250-Occupied Reference Level (-20dBc BW)




Date: 19.OCT.2011 05:29:23

Channel 1250-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 05:31:37

Channel 1275-Occupied Bandwidth Reference Level



Date: 19.OCT.2011 05:32:01

Channel 1275-Occupied Bandwidth (-26dBc BW)




Date: 19.OCT.2011 05:33:34

A.7 BAND EDGE COMPLIANCE (§22.917(b)/§24.238(b))


CDMA 800

LOW BAND EDGE BLOCK-Channel 1013




Date: 19.OCT.2011 05:41:07

HIGH BAND EDGE BLOCK-Channel 777




Date: 19.OCT.2011 05:41:33

**CDMA 1900
LOW BAND EDGE BLOCK-Channel 25**




Date: 19.OCT.2011 06:30:42

HIGH BAND EDGE BLOCK-Channel 1175




Date: 19.OCT.2011 06:30:57

CDMA BC14 G-BAND LOW BAND EDGE BLOCK-Channel 1225



Date: 19.OCT.2011 02:59:29

HIGH BAND EDGE BLOCK-Channel 1275



Date: 19.OCT.2011 03:00:16

A.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238)

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of CDMA1900 and CDMA BC14 G-BAND, data taken from 30 MHz to 20 GHz. For CDMA800, data taken from 30 MHz to 10GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

CDMA 800 Transmitter

Channel	Frequency (MHz)
1013	824.70
384	836.52
777	848.31

CDMA 1900 Transmitter

Channel	Frequency (MHz)
25	1851.25
600	1880.00
1175	1908.75

CDMA BC14 G-BAND Transmitter

Channel	Frequency (MHz)
1225	1911.25
1250	1912.5
1275	1913.75

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.8.3 Measurement result

CDMA 1900

A. 8.3.1 Channel 25: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:31:34

A.8.3.2 Channel 25: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 19.OCT.2011 06:32:01

A.8.3.3 Channel 25: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:32:28

A.8.3.4 Channel 25: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:32:55

A.8.3.5 Channel 25: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:33:22

A.8.3.6 Channel 25: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 06:33:49

A. 8.3.7 Channel 600: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:34:38

A.8.3.8 Channel 600: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 19.OCT.2011 06:35:04

A.8.3.9 Channel 600: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:35:31

A.8.3.10 Channel 600: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:35:58

A.8.3.11 Channel 600: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:36:25

A.8.3.12 Channel 600: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 06:36:51

A. 8.3.13 Channel 1175: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:37:36

A.8.3.14 Channel 1175: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 19.OCT.2011 06:38:02

A.8.3.15 Channel 1175: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:38:28

A.8.3.16 Channel 1175: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:38:55

A.8.3.17 Channel 1175: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:39:21

A.8.3.18 Channel 1175: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 06:39:47

A. 8.3.19 Idle mode: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 07:49:53

A.8.3.20 Idle mode: 1GHz –2.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 07:50:20

A.8.3.21 Idle mode: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 07:50:46

A.8.3.22 Idle mode: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 07:51:13

A.8.3.23 Idle mode: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 07:51:40

A.8.3.24 Idle mode: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 07:52:07

CDMA 800

A. 8.3.25 Channel 1013: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 19.OCT.2011 05:42:10

A. 8.3.26 Channel 1013: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:42:37

A. 8.3.27 Channel 1013: 2.5GHz –7.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 19.OCT.2011 05:43:04

A. 8.3.28 Channel 1013: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:43:31

A. 8.3.29 Channel 384: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 19.OCT.2011 05:44:10


A.8.3.30 Channel 384: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:44:37

A. 8.3.31 Channel 384: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 05:45:04

A. 8.3.32 Channel 384: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:45:31

A. 8.3.33 Channel 777: 30MHz –1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 19.OCT.2011 05:46:05


A. 8.3.34 Channel 777: 1GHz – 2.5GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:46:32

A. 8.3.35 Channel 777: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:46:59

A. 8.3.36 Channel 777: 7.5GHz – 10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 05:47:26

A. 8.3.37 Idle mode: 30MHz – 1GHz
Spurious emission limit -13dBm.




Date: 19.OCT.2011 07:47:26

A.8.3.38 Idle mode: 1GHz – 2.5GHz
Spurious emission limit -13dBm.




Date: 19.OCT.2011 07:47:53

A.8.3.39 Idle mode: 2.5GHz – 7.5GHz
Spurious emission limit -13dBm.



Date: 19.OCT.2011 07:48:20

A.8.3.40 Idle mode: 7.5GHz – 10GHz
Spurious emission limit -13dBm.




Date: 19.OCT.2011 07:48:47

CDMA BC14 G-BAND

A. 8.3.41 Channel 1225: 30MHz –1GHz

Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:01:12

A.8.3.42 Channel 1225: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 19.OCT.2011 03:01:39

A.8.3.43 Channel 1225: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:02:06

A.8.3.44 Channel 1225: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:02:32

A.8.3.45 Channel 1225: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:02:59

A.8.3.46 Channel 1225: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 03:03:26

A. 8.3.47 Channel 1250: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:04:04

A.8.3.48 Channel 1250: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 19.OCT.2011 03:04:31

A.8.3.49 Channel 1250: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:04:58

A.8.3.50 Channel 1250: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:05:25

A.8.3.51 Channel 1250: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:05:51

A.8.3.52 Channel 1250: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 03:06:18

A. 8.3.53 Channel 1275: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:06:55

A.8.3.54 Channel 1275: 1GHz –2.5GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.




Date: 19.OCT.2011 03:07:22

A.8.3.55 Channel 1275: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:07:49

A.8.3.56 Channel 1275: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:08:16

A.8.3.57 Channel 1275: 10GHz –15GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:08:43

A.8.3.58 Channel 1275: 15GHz –20GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:09:10

A. 8.3.59 Idle mode: 30MHz –1GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:09:46

A.8.3.60 Idle mode: 1GHz –2.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:10:12

A.8.3.61 Idle mode: 2.5GHz –7.5GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:10:39

A.8.3.62 Idle mode: 7.5GHz –10GHz
Spurious emission limit –13dBm.




Date: 19.OCT.2011 03:11:06

A.8.3.63 Idle mode: 10GHz –15GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 03:11:33

A.8.3.64 Idle mode: 15GHz –20GHz
Spurious emission limit –13dBm.



Date: 19.OCT.2011 03:12:00

END OF REPORT