

#59 LTE Band II_QPSK_RB(1 0)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.445 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.125 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.632 W/kg

SAR(1 g) = 0.410 mW/g; SAR(10 g) = 0.258 mW/g

Maximum value of SAR (measured) = 0.441 mW/g



#60 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.044 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.662 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.596 W/kg

SAR(1 g) = 0.919 mW/g; SAR(10 g) = 0.496 mW/g

Maximum value of SAR (measured) = 1.038 mW/g



#60 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.044 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 7.662 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.596 W/kg

SAR(1 g) = 0.919 mW/g; SAR(10 g) = 0.496 mW/g

Maximum value of SAR (measured) = 1.038 mW/g

1g/10g Averaged SAR



#61 LTE Band II_QPSK_RB(1 0)_Left Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.201 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.371 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.306 W/kg

SAR(1 g) = 0.177 mW/g; SAR(10 g) = 0.101 mW/g

Maximum value of SAR (measured) = 0.196 mW/g



#62 LTE Band II_QPSK_RB(1 0)_Right Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.237 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.621 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.357 W/kg

SAR(1 g) = 0.218 mW/g; SAR(10 g) = 0.131 mW/g

Maximum value of SAR (measured) = 0.235 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.621 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.335 W/kg

SAR(1 g) = 0.203 mW/g; SAR(10 g) = 0.117 mW/g

Maximum value of SAR (measured) = 0.223 mW/g



#63 LTE Band II_QPSK_RB(1 0)_Top Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.893 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.338 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.379 W/kg

SAR(1 g) = 0.796 mW/g; SAR(10 g) = 0.430 mW/g

Maximum value of SAR (measured) = 0.892 mW/g



#67 LTE Band II_QPSK_RB(1 99)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.474 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.603 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.682 W/kg

SAR(1 g) = 0.432 mW/g; SAR(10 g) = 0.269 mW/g

Maximum value of SAR (measured) = 0.464 mW/g



#68 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.277 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.981 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.976 W/kg

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.569 mW/g

Maximum value of SAR (measured) = 1.259 mW/g



#68 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.277 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 6.981 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.976 W/kg

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.569 mW/g

Maximum value of SAR (measured) = 1.259 mW/g

1g/10g Averaged SAR



#69 LTE Band II_QPSK_RB(1 99)_Left Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.235 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.018 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.370 W/kg

SAR(1 g) = 0.210 mW/g; SAR(10 g) = 0.119 mW/g

Maximum value of SAR (measured) = 0.233 mW/g



#70 LTE Band II_QPSK_RB(1 99)_Right Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.288 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.344 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.418 W/kg

SAR(1 g) = 0.255 mW/g; SAR(10 g) = 0.153 mW/g

Maximum value of SAR (measured) = 0.279 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.344 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.375 W/kg

SAR(1 g) = 0.226 mW/g; SAR(10 g) = 0.131 mW/g

Maximum value of SAR (measured) = 0.248 mW/g



#71 LTE Band II_QPSK_RB(1 99)_Top Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.967 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.970 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.500 W/kg

SAR(1 g) = 0.862 mW/g; SAR(10 g) = 0.464 mW/g

Maximum value of SAR (measured) = 0.959 mW/g



#75 LTE Band II_16QAM_RB(50 25)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.317 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.300 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.458 W/kg

SAR(1 g) = 0.284 mW/g; SAR(10 g) = 0.175 mW/g

Maximum value of SAR (measured) = 0.304 mW/g



#76 LTE Band II_16QAM_RB(50 25)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.729 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.078 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.156 W/kg

SAR(1 g) = 0.642 mW/g; SAR(10 g) = 0.334 mW/g

Maximum value of SAR (measured) = 0.732 mW/g



#76 LTE Band II_16QAM_RB(50 25)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.729 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.078 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.156 W/kg

SAR(1 g) = 0.642 mW/g; SAR(10 g) = 0.334 mW/g

Maximum value of SAR (measured) = 0.732 mW/g



#77 LTE Band II_16QAM_RB(50 25)_Left Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.121 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.946 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.177 W/kg

SAR(1 g) = 0.101 mW/g; SAR(10 g) = 0.057 mW/g

Maximum value of SAR (measured) = 0.113 mW/g



#78 LTE Band II_16QAM_RB(50 25)_Right Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.149 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.936 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.239 W/kg

SAR(1 g) = 0.142 mW/g; SAR(10 g) = 0.084 mW/g

Maximum value of SAR (measured) = 0.152 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.936 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.206 W/kg

SAR(1 g) = 0.123 mW/g; SAR(10 g) = 0.070 mW/g

Maximum value of SAR (measured) = 0.136 mW/g



#79 LTE Band II_16QAM_RB(50 25)_Top Side_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.543 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.075 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.890 W/kg

SAR(1 g) = 0.503 mW/g; SAR(10 g) = 0.268 mW/g

Maximum value of SAR (measured) = 0.562 mW/g



#81 LTE Band II_16QAM_RB(1 0)_Front_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.407 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.244 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.576 W/kg

SAR(1 g) = 0.358 mW/g; SAR(10 g) = 0.221 mW/g

Maximum value of SAR (measured) = 0.382 mW/g



#82 LTE Band II_16QAM_RB(1 0)_Back_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.909 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.938 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.468 W/kg

SAR(1 g) = 0.808 mW/g; SAR(10 g) = 0.422 mW/g

Maximum value of SAR (measured) = 0.916 mW/g



#82 LTE Band II_16QAM_RB(1 0)_Back_1cm_Ch19100_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.909 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.938 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.468 W/kg

SAR(1 g) = 0.808 mW/g; SAR(10 g) = 0.422 mW/g

Maximum value of SAR (measured) = 0.916 mW/g



#83 LTE Band II_16QAM_RB(1 0)_Left Side_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.154 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.640 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.249 W/kg

SAR(1 g) = 0.141 mW/g; SAR(10 g) = 0.078 mW/g

Maximum value of SAR (measured) = 0.156 mW/g



#84 LTE Band II_16QAM_RB(1 0)_Right Side_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.201 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.050 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.320 W/kg

SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.112 mW/g

Maximum value of SAR (measured) = 0.211 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.050 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.270 W/kg

SAR(1 g) = 0.161 mW/g; SAR(10 g) = 0.092 mW/g

Maximum value of SAR (measured) = 0.177 mW/g



#85 LTE Band II_16QAM_RB(1 0)_Top Side_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.736 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.071 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.196 W/kg

SAR(1 g) = 0.674 mW/g; SAR(10 g) = 0.361 mW/g

Maximum value of SAR (measured) = 0.757 mW/g



#87 LTE Band II_16QAM_RB(1 99)_Front_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.364 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.062 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.493 W/kg

SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.190 mW/g

Maximum value of SAR (measured) = 0.332 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.062 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.175 mW/g; SAR(10 g) = 0.104 mW/g

Maximum value of SAR (measured) = 0.184 mW/g



#88 LTE Band II_16QAM_RB(1 99)_Back_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.876 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.248 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.319 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.388 mW/g

Maximum value of SAR (measured) = 0.833 mW/g



#88 LTE Band II_16QAM_RB(1 99)_Back_1cm_Ch19100_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.876 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.248 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.319 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.388 mW/g

Maximum value of SAR (measured) = 0.833 mW/g



#89 LTE Band II_16QAM_RB(1 99)_Left Side_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.157 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.700 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.240 W/kg

SAR(1 g) = 0.140 mW/g; SAR(10 g) = 0.082 mW/g

Maximum value of SAR (measured) = 0.152 mW/g



#90 LTE Band II_16QAM_RB(1 99)_Right Side_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (31x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.181 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.861 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.173 mW/g; SAR(10 g) = 0.105 mW/g

Maximum value of SAR (measured) = 0.187 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.861 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.242 W/kg

SAR(1 g) = 0.149 mW/g; SAR(10 g) = 0.087 mW/g

Maximum value of SAR (measured) = 0.164 mW/g



#91 LTE Band II_16QAM_RB(1 99)_Top Side_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.682 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.463 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.081 W/kg

SAR(1 g) = 0.613 mW/g; SAR(10 g) = 0.332 mW/g

Maximum value of SAR (measured) = 0.682 mW/g



#239 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900_19

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r =$

52.569 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.626 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.962 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.021 W/kg

SAR(1 g) = 0.572 mW/g; SAR(10 g) = 0.302 mW/g

Maximum value of SAR (measured) = 0.640 mW/g



#219 802.11B_Front_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.024 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.716 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.024 W/kg

SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00797 mW/g

Maximum value of SAR (measured) = 0.017 mW/g


Ch11/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.716 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.023 W/kg

SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00368 mW/g

Maximum value of SAR (measured) = 0.014 mW/g



#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g



Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.630 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.114 mW/g

Maximum value of SAR (measured) = 0.250 mW/g



#220 802.11B_Back_1cm_1M_Ch11_2D

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g


Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.630 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.114 mW/g

Maximum value of SAR (measured) = 0.250 mW/g



#221 802.11B_Right Side_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (41x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.145 mW/g



Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.494 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.243 W/kg

SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.066 mW/g

Maximum value of SAR (measured) = 0.145 mW/g



#222 802.11B_Top Side_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.023 mW/g



Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.788 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.025 W/kg

SAR(1 g) = 0.017 mW/g; SAR(10 g) = 0.00743 mW/g

Maximum value of SAR (measured) = 0.019 mW/g



#31 CDMA2000 BC0_RC3 SO32_Front_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.459$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.716 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.529 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.898 W/kg

SAR(1 g) = 0.680 mW/g; SAR(10 g) = 0.520 mW/g

Maximum value of SAR (measured) = 0.717 mW/g



#32 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.459$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.342 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 35.880 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.624 W/kg

SAR(1 g) = 1.29 mW/g; SAR(10 g) = 0.968 mW/g

Maximum value of SAR (measured) = 1.351 mW/g



#32 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_2D

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.459$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.342 mW/g


Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 35.880 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.624 W/kg

SAR(1 g) = 1.29 mW/g; SAR(10 g) = 0.968 mW/g

Maximum value of SAR (measured) = 1.351 mW/g



#36 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch384

DUT: 1N0701

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.37$; ρ

$= 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch384/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.204 mW/g


Ch384/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 35.568 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.394 W/kg

SAR(1 g) = 1.08 mW/g; SAR(10 g) = 0.800 mW/g

Maximum value of SAR (measured) = 1.166 mW/g



#37 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch777

DUT: 1N0701

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 848.31$ MHz; $\sigma = 0.988$ mho/m; $\epsilon_r =$

54.276 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch777/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.093 mW/g



Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.729 V/m; Power Drift = 0.0089 dB

Peak SAR (extrapolated) = 1.322 W/kg

SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.784 mW/g

Maximum value of SAR (measured) = 1.099 mW/g



#38 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.459$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.974 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.097 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.211 W/kg

SAR(1 g) = 0.944 mW/g; SAR(10 g) = 0.705 mW/g

Maximum value of SAR (measured) = 0.989 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.097 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.289 W/kg

SAR(1 g) = 0.915 mW/g; SAR(10 g) = 0.640 mW/g

Maximum value of SAR (measured) = 0.997 mW/g



#39 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch384_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 837$ MHz; $\sigma = 0.978$ mho/m; $\epsilon_r = 54.37$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch384/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.943 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.654 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.239 W/kg

SAR(1 g) = 0.884 mW/g; SAR(10 g) = 0.606 mW/g

Maximum value of SAR (measured) = 0.951 mW/g



Ch384/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.654 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.065 W/kg

SAR(1 g) = 0.867 mW/g; SAR(10 g) = 0.644 mW/g

Maximum value of SAR (measured) = 0.909 mW/g



#40 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch777_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: MSL_835_120105 Medium parameters used: $f = 848.31$ MHz; $\sigma = 0.988$ mho/m; $\epsilon_r =$

54.276 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch777/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.853 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.332 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.029 W/kg

SAR(1 g) = 0.802 mW/g; SAR(10 g) = 0.592 mW/g

Maximum value of SAR (measured) = 0.845 mW/g



Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.332 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.193 W/kg

SAR(1 g) = 0.766 mW/g; SAR(10 g) = 0.533 mW/g

Maximum value of SAR (measured) = 0.833 mW/g



#232 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_15.5

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120120 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.451$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.194 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.862 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.226 W/kg

SAR(1 g) = 0.178 mW/g; SAR(10 g) = 0.134 mW/g

Maximum value of SAR (measured) = 0.187 mW/g



#246 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_18.5

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120120 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.451$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.264 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.442 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.322 W/kg

SAR(1 g) = 0.253 mW/g; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.267 mW/g



#233 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_15.5_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120120 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.451$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.153 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.017 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.217 W/kg

SAR(1 g) = 0.148 mW/g; SAR(10 g) = 0.111 mW/g

Maximum value of SAR (measured) = 0.155 mW/g



#247 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_18.5_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120120 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.451$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.224 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.761 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.279 W/kg

SAR(1 g) = 0.212 mW/g; SAR(10 g) = 0.159 mW/g

Maximum value of SAR (measured) = 0.222 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.761 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.306 W/kg

SAR(1 g) = 0.206 mW/g; SAR(10 g) = 0.149 mW/g

Maximum value of SAR (measured) = 0.218 mW/g



#262 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_15_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120120 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.451$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.136 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.629 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.163 W/kg

SAR(1 g) = 0.128 mW/g; SAR(10 g) = 0.097 mW/g

Maximum value of SAR (measured) = 0.135 mW/g



Ch1013/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.629 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.173 W/kg

SAR(1 g) = 0.120 mW/g; SAR(10 g) = 0.085 mW/g

Maximum value of SAR (measured) = 0.131 mW/g



#264 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_15

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120120 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.451$;

$\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.171 mW/g


Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.282 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.224 W/kg

SAR(1 g) = 0.162 mW/g; SAR(10 g) = 0.120 mW/g

Maximum value of SAR (measured) = 0.176 mW/g



#41 CDMA2000 BC15_RC3 SO32_Front_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1711.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1711.25$ MHz; $\sigma = 1.471$ mho/m; $\epsilon_r =$

55.564 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.862 mW/g


Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.067 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.321 W/kg

SAR(1 g) = 0.816 mW/g; SAR(10 g) = 0.491 mW/g

Maximum value of SAR (measured) = 0.884 mW/g



#42 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1711.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1711.25$ MHz; $\sigma = 1.471$ mho/m; $\epsilon_r =$

55.564 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.323 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.330 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.962 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.738 mW/g

Maximum value of SAR (measured) = 1.315 mW/g



#46 CDMA2000 BC15_RC3 SO32_Front_1cm_Ch425

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1731.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1731.25$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.529 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.821 mW/g


Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.088 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.315 W/kg

SAR(1 g) = 0.798 mW/g; SAR(10 g) = 0.475 mW/g

Maximum value of SAR (measured) = 0.866 mW/g



#47 CDMA2000 BC15_RC3 SO32_Front_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r =$

55.493 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.875 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.469 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.366 W/kg

SAR(1 g) = 0.841 mW/g; SAR(10 g) = 0.506 mW/g

Maximum value of SAR (measured) = 0.910 mW/g



#48 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch425

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1731.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1731.25$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.529 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.304 mW/g



Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.864 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.996 W/kg

SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.738 mW/g

Maximum value of SAR (measured) = 1.326 mW/g



#49 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r =$

55.493 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.419 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.351 V/m; Power Drift = 0.0017 dB

Peak SAR (extrapolated) = 2.191 W/kg

SAR(1 g) = 1.34 mW/g; SAR(10 g) = 0.796 mW/g

Maximum value of SAR (measured) = 1.450 mW/g



#49 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875_2D

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r =$

55.493 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.419 mW/g

Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 12.351 V/m; Power Drift = 0.0017 dB

Peak SAR (extrapolated) = 2.191 W/kg

SAR(1 g) = 1.34 mW/g; SAR(10 g) = 0.796 mW/g

Maximum value of SAR (measured) = 1.450 mW/g

1g/10g Averaged SAR



#50 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r =$

55.493 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.377 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.782 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 2.124 W/kg

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.771 mW/g

Maximum value of SAR (measured) = 1.395 mW/g



#57 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch25_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1711.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1711.25$ MHz; $\sigma = 1.471$ mho/m; $\epsilon_r =$

55.564 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.220 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.831 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.888 W/kg

SAR(1 g) = 1.15 mW/g; SAR(10 g) = 0.685 mW/g

Maximum value of SAR (measured) = 1.216 mW/g



#58 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch425_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1731.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120105 Medium parameters used: $f = 1731.25$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.529 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.254 mW/g



Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.043 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.939 W/kg

SAR(1 g) = 1.2 mW/g; SAR(10 g) = 0.714 mW/g

Maximum value of SAR (measured) = 1.287 mW/g



#248 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875_15.5

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.195 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.420 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.295 W/kg

SAR(1 g) = 0.179 mW/g; SAR(10 g) = 0.100 mW/g

Maximum value of SAR (measured) = 0.198 mW/g



#249 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875_Earphone_15.5

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.161 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.328 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.244 W/kg

SAR(1 g) = 0.148 mW/g; SAR(10 g) = 0.083 mW/g

Maximum value of SAR (measured) = 0.166 mW/g



#263 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875_15_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.122 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.011 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.172 W/kg

SAR(1 g) = 0.103 mW/g; SAR(10 g) = 0.059 mW/g

Maximum value of SAR (measured) = 0.113 mW/g



#265 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875_15

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.177 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.050 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.258 W/kg

SAR(1 g) = 0.158 mW/g; SAR(10 g) = 0.094 mW/g

Maximum value of SAR (measured) = 0.173 mW/g



#01 CDMA2000 BC15_RTAP 153.6_Front_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1711.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1711.25$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

55.651 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.590 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.764 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.809 W/kg

SAR(1 g) = 0.527 mW/g; SAR(10 g) = 0.330 mW/g

Maximum value of SAR (measured) = 0.572 mW/g



#02 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1711.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1711.25$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

55.651 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.071 mW/g


Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.508 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.536 W/kg

SAR(1 g) = 0.939 mW/g; SAR(10 g) = 0.537 mW/g

Maximum value of SAR (measured) = 1.071 mW/g



#06 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch425

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1731.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1731.25$ MHz; $\sigma = 1.492$ mho/m; $\epsilon_r =$

55.617 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.110 mW/g



Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.583 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.673 W/kg

SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.581 mW/g

Maximum value of SAR (measured) = 1.150 mW/g



#07 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.517$ mho/m; $\epsilon_r =$

55.58 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.392 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.641 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.042 W/kg

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.681 mW/g

Maximum value of SAR (measured) = 1.377 mW/g



#08 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875_Earphone

DUT: 1N0701



Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1
Medium: MSL_1750_120104 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.517$ mho/m; $\epsilon_r = 55.58$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.497 mW/g

Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.465 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 2.172 W/kg
SAR(1 g) = 1.28 mW/g; SAR(10 g) = 0.693 mW/g
Maximum value of SAR (measured) = 1.476 mW/g



#08 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875_Earphone_2D

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.517$ mho/m; $\epsilon_r =$

55.58 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.497 mW/g

Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 8.465 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.172 W/kg

SAR(1 g) = 1.28 mW/g; SAR(10 g) = 0.693 mW/g

Maximum value of SAR (measured) = 1.476 mW/g

1g/10g Averaged SAR



#09 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch25_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1711.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1711.25$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

55.651 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.146 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.039 V/m; Power Drift = 0.0034 dB

Peak SAR (extrapolated) = 1.638 W/kg

SAR(1 g) = 0.974 mW/g; SAR(10 g) = 0.543 mW/g

Maximum value of SAR (measured) = 1.116 mW/g



#10 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch425_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1731.25 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120104 Medium parameters used: $f = 1731.25$ MHz; $\sigma = 1.492$ mho/m; $\epsilon_r =$

55.617 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.249 mW/g


Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.002 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.825 W/kg

SAR(1 g) = 1.08 mW/g; SAR(10 g) = 0.591 mW/g

Maximum value of SAR (measured) = 1.241 mW/g



#234 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875_17

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.382 mW/g


Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.871 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.544 W/kg

SAR(1 g) = 0.322 mW/g; SAR(10 g) = 0.178 mW/g

Maximum value of SAR (measured) = 0.368 mW/g



#235 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875_17_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.624 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.184 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.692 W/kg

SAR(1 g) = 0.394 mW/g; SAR(10 g) = 0.190 mW/g

Maximum value of SAR (measured) = 0.462 mW/g



#252 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875_23

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120' Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.158 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.788 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.760 W/kg

SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.575 mW/g

Maximum value of SAR (measured) = 1.178 mW/g



#253 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875_Earphone_23

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120' Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r =$

55.567 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.253 mW/g



Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.455 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.844 W/kg

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.576 mW/g

Maximum value of SAR (measured) = 1.220 mW/g



#21 CDMA2000 BC1_RC3 SO32_Front_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r =$

52.602 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.695 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.235 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.038 W/kg

SAR(1 g) = 0.637 mW/g; SAR(10 g) = 0.395 mW/g

Maximum value of SAR (measured) = 0.674 mW/g



#22 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r =$

52.602 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.154 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.951 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.718 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.647 mW/g

Maximum value of SAR (measured) = 1.174 mW/g



#22 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25_2D

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r =$

52.602 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.154 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 11.951 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.718 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.647 mW/g

Maximum value of SAR (measured) = 1.174 mW/g

1g/10g Averaged SAR



#26 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch600

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.903 mW/g



Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.003 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.362 W/kg

SAR(1 g) = 0.839 mW/g; SAR(10 g) = 0.505 mW/g

Maximum value of SAR (measured) = 0.903 mW/g



#27 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch1175

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1909$ MHz; $\sigma = 1.542$ mho/m; $\epsilon_r =$

52.376 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.909 mW/g



Ch1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.518 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.553 W/kg

SAR(1 g) = 0.875 mW/g; SAR(10 g) = 0.521 mW/g

Maximum value of SAR (measured) = 0.961 mW/g



#28 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r =$

52.602 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.109 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.432 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.673 W/kg

SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.615 mW/g

Maximum value of SAR (measured) = 1.087 mW/g



#29 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch600_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.869 mW/g



Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.645 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.398 W/kg

SAR(1 g) = 0.835 mW/g; SAR(10 g) = 0.498 mW/g

Maximum value of SAR (measured) = 0.900 mW/g



#30 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch1175_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1909$ MHz; $\sigma = 1.542$ mho/m; $\epsilon_r =$

52.376 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.939 mW/g



Ch1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.460 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.418 W/kg

SAR(1 g) = 0.864 mW/g; SAR(10 g) = 0.511 mW/g

Maximum value of SAR (measured) = 0.937 mW/g



#250 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25_15.5

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r =$

52.574 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.155 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.633 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.233 W/kg

SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.080 mW/g

Maximum value of SAR (measured) = 0.161 mW/g



#251 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25_earphone_15.5

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r =$

52.574 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.125 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.830 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.201 W/kg

SAR(1 g) = 0.122 mW/g; SAR(10 g) = 0.066 mW/g

Maximum value of SAR (measured) = 0.136 mW/g



#11 CDMA2000 BC1_RTAP 153.6_Front_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.442$ mho/m; $\epsilon_r =$

53.85 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.614 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.790 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.931 W/kg

SAR(1 g) = 0.573 mW/g; SAR(10 g) = 0.357 mW/g

Maximum value of SAR (measured) = 0.611 mW/g



#12 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.442$ mho/m; $\epsilon_r =$

53.85 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.468 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.209 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.282 W/kg

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.692 mW/g

Maximum value of SAR (measured) = 1.480 mW/g



#12 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_2D

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.442$ mho/m; $\epsilon_r =$

53.85 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.468 mW/g


Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.209 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.282 W/kg

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.692 mW/g

Maximum value of SAR (measured) = 1.480 mW/g



#16 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch600

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.479$ mho/m; $\epsilon_r =$

53.835 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.428 mW/g


Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.676 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.263 W/kg

SAR(1 g) = 1.27 mW/g; SAR(10 g) = 0.677 mW/g

Maximum value of SAR (measured) = 1.457 mW/g



#17 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch1175

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1909$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r =$

53.822 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.337 mW/g


Ch1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.545 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 2.178 W/kg

SAR(1 g) = 1.21 mW/g; SAR(10 g) = 0.638 mW/g

Maximum value of SAR (measured) = 1.387 mW/g



#18 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.442$ mho/m; $\epsilon_r =$

53.85 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.487 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.239 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.316 W/kg

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.686 mW/g

Maximum value of SAR (measured) = 1.492 mW/g



#19 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch600_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.479$ mho/m; $\epsilon_r =$

53.835 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.331 mW/g



Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.397 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.174 W/kg

SAR(1 g) = 1.22 mW/g; SAR(10 g) = 0.646 mW/g

Maximum value of SAR (measured) = 1.393 mW/g



#20 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch1175_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120104 Medium parameters used: $f = 1909$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r =$

53.822 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch1175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.187 mW/g


Ch1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.485 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.006 W/kg

SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.584 mW/g

Maximum value of SAR (measured) = 1.266 mW/g



#236 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_17

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r =$

52.574 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.426 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.978 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.665 W/kg

SAR(1 g) = 0.373 mW/g; SAR(10 g) = 0.196 mW/g

Maximum value of SAR (measured) = 0.413 mW/g



#237 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_17_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r =$

52.574 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.407 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.718 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.643 W/kg

SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.189 mW/g

Maximum value of SAR (measured) = 0.412 mW/g



#254 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_23

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120206 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.453$ mho/m; $\epsilon_r =$

53.923 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.225 mW/g


Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.170 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.899 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.574 mW/g

Maximum value of SAR (measured) = 1.215 mW/g



#255 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_Earphone_23

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120206 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.453$ mho/m; $\epsilon_r =$

53.923 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.318 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.234 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 2.048 W/kg

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.599 mW/g

Maximum value of SAR (measured) = 1.297 mW/g



#93 LTE Band IV_QPSK_RB(50 25)_Front_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120106 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.494$ mho/m; $\epsilon_r =$

55.527 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.389 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.457 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.577 W/kg

SAR(1 g) = 0.363 mW/g; SAR(10 g) = 0.223 mW/g

Maximum value of SAR (measured) = 0.391 mW/g



#94 LTE Band IV_QPSK_RB(50 25)_Back_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120106 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.494$ mho/m; $\epsilon_r =$

55.527 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.650 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.250 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.951 W/kg

SAR(1 g) = 0.570 mW/g; SAR(10 g) = 0.317 mW/g

Maximum value of SAR (measured) = 0.639 mW/g



#94 LTE Band IV_QPSK_RB(50 25)_Back_1cm_Ch20175_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120106 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.494$ mho/m; $\epsilon_r =$

55.527 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.650 mW/g

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 5.250 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.951 W/kg

SAR(1 g) = 0.570 mW/g; SAR(10 g) = 0.317 mW/g

Maximum value of SAR (measured) = 0.639 mW/g

1g/10g Averaged SAR



#98 LTE Band IV_QPSK_RB(50 25)_Back_1cm_Ch20175_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120106 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.494$ mho/m; $\epsilon_r =$

55.527 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.632 mW/g


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.038 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.897 W/kg

SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.299 mW/g

Maximum value of SAR (measured) = 0.611 mW/g



#99 LTE Band IV_QPSK_RB(1 0)_Front_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.457 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.523 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.660 W/kg

SAR(1 g) = 0.413 mW/g; SAR(10 g) = 0.254 mW/g

Maximum value of SAR (measured) = 0.450 mW/g



#100 LTE Band IV_QPSK_RB(1 0)_Back_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.750 mW/g


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.867 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.110 W/kg

SAR(1 g) = 0.655 mW/g; SAR(10 g) = 0.368 mW/g

Maximum value of SAR (measured) = 0.736 mW/g



#104 LTE Band IV_QPSK_RB(1 0)_Back_1cm_Ch20175_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.739 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.444 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.116 W/kg

SAR(1 g) = 0.664 mW/g; SAR(10 g) = 0.369 mW/g

Maximum value of SAR (measured) = 0.746 mW/g



#104 LTE Band IV_QPSK_RB(1 0)_Back_1cm_Ch20175_Earphone_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.739 mW/g


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.444 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.116 W/kg

SAR(1 g) = 0.664 mW/g; SAR(10 g) = 0.369 mW/g

Maximum value of SAR (measured) = 0.746 mW/g



#105 LTE Band IV_QPSK_RB(1 99)_Front_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.525 mW/g


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.922 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.760 W/kg

SAR(1 g) = 0.481 mW/g; SAR(10 g) = 0.298 mW/g

Maximum value of SAR (measured) = 0.520 mW/g



#106 LTE Band IV_QPSK_RB(1 99)_Back_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.954 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.986 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.468 W/kg

SAR(1 g) = 0.872 mW/g; SAR(10 g) = 0.481 mW/g

Maximum value of SAR (measured) = 0.984 mW/g



#106 LTE Band IV_QPSK_RB(1 99)_Back_1cm_Ch20175_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.954 mW/g


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.986 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.468 W/kg

SAR(1 g) = 0.872 mW/g; SAR(10 g) = 0.481 mW/g

Maximum value of SAR (measured) = 0.984 mW/g



#110 LTE Band IV_QPSK_RB(1 99)_Back_1cm_Ch20175_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.825 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.424 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.314 W/kg

SAR(1 g) = 0.763 mW/g; SAR(10 g) = 0.419 mW/g

Maximum value of SAR (measured) = 0.864 mW/g



#112 LTE Band IV_16QAM_RB(50 25)_Front_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.330 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.133 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.480 W/kg

SAR(1 g) = 0.300 mW/g; SAR(10 g) = 0.184 mW/g

Maximum value of SAR (measured) = 0.324 mW/g



#113 LTE Band IV_16QAM_RB(50 25)_Back_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.575 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.205 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.810 W/kg

SAR(1 g) = 0.480 mW/g; SAR(10 g) = 0.267 mW/g

Maximum value of SAR (measured) = 0.546 mW/g



#113 LTE Band IV_16QAM_RB(50 25)_Back_1cm_Ch20175_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.575 mW/g

Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 5.205 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.810 W/kg

SAR(1 g) = 0.480 mW/g; SAR(10 g) = 0.267 mW/g

Maximum value of SAR (measured) = 0.546 mW/g

1g/10g Averaged SAR



#117 LTE Band IV_16QAM_RB(50 25)_Back_1cm_Ch20175_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.483$ mho/m; $\epsilon_r =$

51.051 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.496 mW/g



Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.620 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.743 W/kg

SAR(1 g) = 0.437 mW/g; SAR(10 g) = 0.240 mW/g

Maximum value of SAR (measured) = 0.498 mW/g



#119 LTE Band IV_16QAM_RB(1 0)_Front_1cm_Ch20050

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.338 mW/g



Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.986 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.485 W/kg

SAR(1 g) = 0.309 mW/g; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.333 mW/g



#120 LTE Band IV_16QAM_RB(1 0)_Back_1cm_Ch20050

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.664 mW/g


Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.937 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.954 W/kg

SAR(1 g) = 0.564 mW/g; SAR(10 g) = 0.316 mW/g

Maximum value of SAR (measured) = 0.641 mW/g



#120 LTE Band IV_16QAM_RB(1 0)_Back_1cm_Ch20050_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.664 mW/g

Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 5.937 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.954 W/kg

SAR(1 g) = 0.564 mW/g; SAR(10 g) = 0.316 mW/g

Maximum value of SAR (measured) = 0.641 mW/g

1g/10g Averaged SAR



#124 LTE Band IV_16QAM_RB(1 0)_Back_1cm_Ch20050_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.585 mW/g


Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.788 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.889 W/kg

SAR(1 g) = 0.518 mW/g; SAR(10 g) = 0.288 mW/g

Maximum value of SAR (measured) = 0.592 mW/g



#126 LTE Band IV_16QAM_RB(1 99)_Front_1cm_Ch20050

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.398 mW/g



Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.001 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.576 W/kg

SAR(1 g) = 0.366 mW/g; SAR(10 g) = 0.225 mW/g

Maximum value of SAR (measured) = 0.396 mW/g



#127 LTE Band IV_16QAM_RB(1 99)_Back_1cm_Ch20050

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.709 mW/g



Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.851 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.025 W/kg

SAR(1 g) = 0.611 mW/g; SAR(10 g) = 0.338 mW/g

Maximum value of SAR (measured) = 0.699 mW/g



#127 LTE Band IV_16QAM_RB(1 99)_Back_1cm_Ch20050_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.709 mW/g


Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.851 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.025 W/kg

SAR(1 g) = 0.611 mW/g; SAR(10 g) = 0.338 mW/g

Maximum value of SAR (measured) = 0.699 mW/g



#131 LTE Band IV_16QAM_RB(1 99)_Back_1cm_Ch20050_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120107 Medium parameters used: $f = 1720$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r =$

51.085; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20050/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.637 mW/g


Ch20050/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.164 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.838 W/kg

SAR(1 g) = 0.545 mW/g; SAR(10 g) = 0.291 mW/g

Maximum value of SAR (measured) = 0.634 mW/g



#238 LTE Band IV_QPSK_RB(1 99)_Back_1cm_Ch20175_19

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1750_120120 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r =$

55.607 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch20175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.541 mW/g


Ch20175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.375 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.808 W/kg

SAR(1 g) = 0.486 mW/g; SAR(10 g) = 0.273 mW/g

Maximum value of SAR (measured) = 0.542 mW/g



#51 LTE Band II_QPSK_RB(50 25)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.355 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.337 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.710 W/kg

SAR(1 g) = 0.337 mW/g; SAR(10 g) = 0.204 mW/g

Maximum value of SAR (measured) = 0.367 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.337 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.395 W/kg

SAR(1 g) = 0.167 mW/g; SAR(10 g) = 0.086 mW/g

Maximum value of SAR (measured) = 0.187 mW/g



#52 LTE Band II_QPSK_RB(50 25)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.785 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.796 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.270 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.386 mW/g

Maximum value of SAR (measured) = 0.865 mW/g



#52 LTE Band II_QPSK_RB(50 25)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.785 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.796 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.270 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.386 mW/g

Maximum value of SAR (measured) = 0.865 mW/g



#56 LTE Band II_QPSK_RB(50 25)_Back_1cm_Ch18900_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.754 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.515 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.213 W/kg

SAR(1 g) = 0.672 mW/g; SAR(10 g) = 0.357 mW/g

Maximum value of SAR (measured) = 0.766 mW/g



#59 LTE Band II_QPSK_RB(1 0)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.445 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.125 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.632 W/kg

SAR(1 g) = 0.410 mW/g; SAR(10 g) = 0.258 mW/g

Maximum value of SAR (measured) = 0.441 mW/g



#60 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.044 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.662 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.596 W/kg

SAR(1 g) = 0.919 mW/g; SAR(10 g) = 0.496 mW/g

Maximum value of SAR (measured) = 1.038 mW/g



#60 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.044 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 7.662 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.596 W/kg

SAR(1 g) = 0.919 mW/g; SAR(10 g) = 0.496 mW/g

Maximum value of SAR (measured) = 1.038 mW/g

1g/10g Averaged SAR



#64 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch18900_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.934 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.321 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.457 W/kg

SAR(1 g) = 0.818 mW/g; SAR(10 g) = 0.433 mW/g

Maximum value of SAR (measured) = 0.899 mW/g



#65 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch18700_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1860$ MHz; $\sigma = 1.486$ mho/m; $\epsilon_r =$

52.541 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18700/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.012 mW/g



Ch18700/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.807 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 1.549 W/kg

SAR(1 g) = 0.876 mW/g; SAR(10 g) = 0.466 mW/g

Maximum value of SAR (measured) = 0.990 mW/g



#66 LTE Band II_QPSK_RB(1 0)_Back_1cm_Ch19100_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.532$ mho/m; $\epsilon_r =$

52.397 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.957 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.036 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.554 W/kg

SAR(1 g) = 0.866 mW/g; SAR(10 g) = 0.455 mW/g

Maximum value of SAR (measured) = 0.955 mW/g



#67 LTE Band II_QPSK_RB(1 99)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.474 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.603 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.682 W/kg

SAR(1 g) = 0.432 mW/g; SAR(10 g) = 0.269 mW/g

Maximum value of SAR (measured) = 0.464 mW/g



#68 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.277 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.981 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.976 W/kg

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.569 mW/g

Maximum value of SAR (measured) = 1.259 mW/g



#68 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.277 mW/g

Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 6.981 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.976 W/kg

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.569 mW/g

Maximum value of SAR (measured) = 1.259 mW/g

1g/10g Averaged SAR



#72 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.509$ mho/m; $\epsilon_r =$

52.468 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.992 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.102 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.582 W/kg

SAR(1 g) = 0.881 mW/g; SAR(10 g) = 0.462 mW/g

Maximum value of SAR (measured) = 0.971 mW/g



#73 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18700_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1860$ MHz; $\sigma = 1.486$ mho/m; $\epsilon_r =$

52.541 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18700/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.958 mW/g



Ch18700/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.345 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.527 W/kg

SAR(1 g) = 0.853 mW/g; SAR(10 g) = 0.449 mW/g

Maximum value of SAR (measured) = 0.934 mW/g



#74 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch19100_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120105 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.532$ mho/m; $\epsilon_r =$

52.397 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.866 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.818 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.394 W/kg

SAR(1 g) = 0.768 mW/g; SAR(10 g) = 0.402 mW/g

Maximum value of SAR (measured) = 0.850 mW/g



#75 LTE Band II_16QAM_RB(50 25)_Front_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.317 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.300 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.458 W/kg

SAR(1 g) = 0.284 mW/g; SAR(10 g) = 0.175 mW/g

Maximum value of SAR (measured) = 0.304 mW/g



#76 LTE Band II_16QAM_RB(50 25)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.729 mW/g



Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.078 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.156 W/kg

SAR(1 g) = 0.642 mW/g; SAR(10 g) = 0.334 mW/g

Maximum value of SAR (measured) = 0.732 mW/g



#76 LTE Band II_16QAM_RB(50 25)_Back_1cm_Ch18900_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.729 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.078 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.156 W/kg

SAR(1 g) = 0.642 mW/g; SAR(10 g) = 0.334 mW/g

Maximum value of SAR (measured) = 0.732 mW/g



#80 LTE Band II_16QAM_RB(50 25)_Back_1cm_Ch18900_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.489$ mho/m; $\epsilon_r =$

53.955 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.667 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.902 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.070 W/kg

SAR(1 g) = 0.592 mW/g; SAR(10 g) = 0.309 mW/g

Maximum value of SAR (measured) = 0.677 mW/g



#81 LTE Band II_16QAM_RB(1 0)_Front_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.407 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.244 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.576 W/kg

SAR(1 g) = 0.358 mW/g; SAR(10 g) = 0.221 mW/g

Maximum value of SAR (measured) = 0.382 mW/g



#82 LTE Band II_16QAM_RB(1 0)_Back_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.909 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.938 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.468 W/kg

SAR(1 g) = 0.808 mW/g; SAR(10 g) = 0.422 mW/g

Maximum value of SAR (measured) = 0.916 mW/g



#82 LTE Band II_16QAM_RB(1 0)_Back_1cm_Ch19100_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.909 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.938 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.468 W/kg

SAR(1 g) = 0.808 mW/g; SAR(10 g) = 0.422 mW/g

Maximum value of SAR (measured) = 0.916 mW/g



#86 LTE Band II_16QAM_RB(1 0)_Back_1cm_Ch19100_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.868 mW/g


Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.596 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.398 W/kg

SAR(1 g) = 0.781 mW/g; SAR(10 g) = 0.410 mW/g

Maximum value of SAR (measured) = 0.887 mW/g



#87 LTE Band II_16QAM_RB(1 99)_Front_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.364 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.062 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.493 W/kg

SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.190 mW/g

Maximum value of SAR (measured) = 0.332 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.062 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.175 mW/g; SAR(10 g) = 0.104 mW/g

Maximum value of SAR (measured) = 0.184 mW/g



#88 LTE Band II_16QAM_RB(1 99)_Back_1cm_Ch19100

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.876 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.248 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.319 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.388 mW/g

Maximum value of SAR (measured) = 0.833 mW/g



#88 LTE Band II_16QAM_RB(1 99)_Back_1cm_Ch19100_2D

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.876 mW/g

Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 7.248 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.319 W/kg

SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.388 mW/g

Maximum value of SAR (measured) = 0.833 mW/g

1g/10g Averaged SAR



#92 LTE Band II_16QAM_RB(1 99)_Back_1cm_Ch19100_Earphone

DUT: 1N0701

Communication System: LTE; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120106 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.512$ mho/m; $\epsilon_r =$

53.903 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch19100/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.815 mW/g



Ch19100/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.962 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.223 W/kg

SAR(1 g) = 0.695 mW/g; SAR(10 g) = 0.370 mW/g

Maximum value of SAR (measured) = 0.737 mW/g



#239 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900_19

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r =$

52.569 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch18900/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.626 mW/g


Ch18900/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.962 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.021 W/kg

SAR(1 g) = 0.572 mW/g; SAR(10 g) = 0.302 mW/g

Maximum value of SAR (measured) = 0.640 mW/g



#219 802.11B_Front_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.024 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.716 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.024 W/kg

SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00797 mW/g

Maximum value of SAR (measured) = 0.017 mW/g


Ch11/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.716 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.023 W/kg

SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00368 mW/g

Maximum value of SAR (measured) = 0.014 mW/g



#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g



Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.630 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.114 mW/g

Maximum value of SAR (measured) = 0.250 mW/g



#220 802.11B_Back_1cm_1M_Ch11_2D

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g


Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.630 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.400 W/kg

SAR(1 g) = 0.222 mW/g; SAR(10 g) = 0.114 mW/g

Maximum value of SAR (measured) = 0.250 mW/g



#223 802.11B_Back_1cm_1M_Ch11_Earphone

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120116 Medium parameters used: $f = 2462$ MHz; $\sigma = 2.027$ mho/m; $\epsilon_r =$

53.408 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 21.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM1; Type: SAM; Serial: TP-1479
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch11/Area Scan (61x111x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.180 mW/g



Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.620 V/m; Power Drift = 0.0067 dB

Peak SAR (extrapolated) = 0.329 W/kg

SAR(1 g) = 0.158 mW/g; SAR(10 g) = 0.077 mW/g

Maximum value of SAR (measured) = 0.175 mW/g



#269 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25_15

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r =$

52.574 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.132 mW/g


Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.714 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.196 W/kg

SAR(1 g) = 0.122 mW/g; SAR(10 g) = 0.073 mW/g

Maximum value of SAR (measured) = 0.132 mW/g



0 dB = 0.130mW/g

#270 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25_Earphone_15

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r =$

52.574 ; $\rho = 1000$ kg/m³

Ambient Temperature : 23.6 °C ; Liquid Temperature : 21.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011-9-2
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2011-11-18
- Phantom: SAM2; Type: SAM; Serial: TP-1477
- Measurement SW: DASY52, Version 52.8 (0); SEMCAD X Version 14.4.5 (3634)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.116 mW/g



Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.939 V/m; Power Drift = 0.046 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.109 mW/g; SAR(10 g) = 0.064 mW/g

Maximum value of SAR (measured) = 0.120 mW/g



0 dB = 0.120mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/3/12

#234 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1800_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r = 55.567$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM2; Type: SAM; Serial: TP-1477
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#32 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120119 Medium parameters used: $f = 825$ MHz; $\sigma = 0.97$ mho/m; $\epsilon_r = 54.453$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)


- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2

- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.49 mW/g; SAR(10 g) = 1.12 mW/g

Maximum value of SAR (interpolated) = 1.938 mW/g



0 dB = 1.940mW/g = 5.76 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/3/12

#236 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used : $f = 1851.25$ MHz; $\sigma = 1.476$ mho/m; $\epsilon_r = 52.574$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#32 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120119 Medium parameters used: $f = 825$ MHz; $\sigma = 0.958$ mho/m; $\epsilon_r = 54.451$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)


- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2

- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.48 mW/g; SAR(10 g) = 1.11 mW/g

Maximum value of SAR (interpolated) = 1.928 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#12 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120119 Medium parameters used : $f = 1851.25$ MHz; $\sigma = 1.461$ mho/m; $\epsilon_r = 53.588$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2
- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM1; Type: SAM; Serial: TP-1479
- ε Measurement SW: DASYS2, Version 52.8 (0)

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/2/7

#260 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120207 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.44$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM1; Type: SAM; Serial: TP-1479
- ε Measurement SW: DASYS2, Version 52.8 (0)

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)


- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2
- ε Sensor-Surface: 4mm (Mechanical Surface Detection)

ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
ε Phantom: SAM2; Type: SAM; Serial: TP-1477
ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.32 mW/g; SAR(10 g) = 0.684 mW/g

Maximum value of SAR (interpolated) = 2.480 mW/g



0 dB = 2.480mW/g = 7.89 dB mW/g

Date: 2012/1/19

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#12 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120119 Medium parameters used : $f = 1851.25$ MHz; $\sigma = 1.461$ mho/m; $\epsilon_r =$

53.588 ; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/2/6

#258 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1

Medium: MSL_1800_120206 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.506$ mho/m; $\epsilon_r =$

55.558 ; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM2; Type: SAM; Serial: TP-1477
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r =$

53.795 ; $\rho = 1000$ kg/m³

Phantom section: Flat Section


Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2
- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.31 mW/g; SAR(10 g) = 0.680 mW/g

Maximum value of SAR (interpolated) = 2.447 mW/g



0 dB = 2.450mW/g = 7.78 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#12 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120119 Medium parameters used : $f = 1851.25$ MHz; $\sigma = 1.461$ mho/m; $\epsilon_r =$

53.588 ; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2

ε Sensor-Surface: 4mm (Mechanical Surface Detection)

ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18

ε Phantom: SAM1; Type: SAM; Serial: TP-1479

ε Measurement SW: DASY52, Version 52.8 (0)

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/2/6

#256 CDMA2000 BC1_RC3 SO32_Back_1cm_Ch25

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120206 Medium parameters used : $f = 1851.25$ MHz; $\sigma = 1.453$ mho/m; $\epsilon_r =$

53.923 ; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2

ε Sensor-Surface: 4mm (Mechanical Surface Detection)

ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18

ε Phantom: SAM1; Type: SAM; Serial: TP-1479

ε Measurement SW: DASY52, Version 52.8 (0)

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r =$

53.795 ; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2

- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.32 mW/g; SAR(10 g) = 0.688 mW/g

Maximum value of SAR (interpolated) = 2.451 mW/g



0 dB = 2.450mW/g = 7.78 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/3/42

#238 LTE Band IV_QPSK_RB(1 99)_Back_1cm_Ch20175

DUT: 1N0701

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: MSL_1800_120120 Medium parameters used : $f = 1732.5$ MHz; $\sigma = 1.493$ mho/m; $\epsilon_r = 55.607$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM2; Type: SAM; Serial: TP-1477
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#32 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120119 Medium parameters used: $f = 825$ MHz; $\sigma = 0.958$ mho/m; $\epsilon_r = 54.451$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³

Phantom section: Flat Section


Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2
- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.51 mW/g; SAR(10 g) = 1.13 mW/g

Maximum value of SAR (interpolated) = 1.976 mW/g



0 dB = 1.980mW/g = 5.93 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/3/42

#239 LTE Band II_QPSK_RB(1 99)_Back_1cm_Ch18900

DUT: 1N0701

Communication System: LTE; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL_1900_120120 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.518$ mho/m; $\epsilon_r = 52.569$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#32 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: MSL_835_120119 Medium parameters used: $f = 825$ MHz; $\sigma = 0.958$ mho/m; $\epsilon_r = 54.451$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Date/Time: 2012/1/19 LUL□ 07:16:24

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³

Phantom section: Flat Section


Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2
- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.5 mW/g; SAR(10 g) = 1.12 mW/g

Maximum value of SAR (interpolated) = 1.966 mW/g



0 dB = 1.970mW/g = 5.89 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#18 CDMA2000 BC1_RTAP 153.6_Back_1cm_Ch25_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1851.25 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_1900_120119 Medium parameters used : $f = 1851.25$ MHz; $\sigma = 1.461$ mho/m; $\epsilon_r = 53.588$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(6.96, 6.96, 6.96); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASY52, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/2/7

#262 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013_Earphone

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_835_120207 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.44$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASY52, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#223 802.11B_Back_1cm_1M_Ch11_Earphone

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)


- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2

- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.26 mW/g; SAR(10 g) = 0.666 mW/g

Maximum value of SAR (interpolated) = 2.111 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/20

#07 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_1800_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r = 55.567$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM2; Type: SAM; Serial: TP-1477
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/2/7

#264 CDMA2000 BC0_RC3 SO32_Back_1cm_Ch1013

DUT: 1N0701

Communication System: CDMA2000; Frequency: 824.7 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_835_120207 Medium parameters used: $f = 825$ MHz; $\sigma = 0.967$ mho/m; $\epsilon_r = 54.44$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM1; Type: SAM; Serial: TP-1479
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)


- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2

- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.26 mW/g; SAR(10 g) = 0.702 mW/g

Maximum value of SAR (interpolated) = 2.175 mW/g



0 dB = 2.170mW/g = 6.73 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/20

#07 CDMA2000 BC15_RTAP 153.6_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_1800_120120 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.516$ mho/m; $\epsilon_r = 55.567$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM2; Type: SAM; Serial: TP-1477
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/2/6

#265 CDMA2000 BC15_RC3 SO32_Back_1cm_Ch875

DUT: 1N0701

Communication System: CDMA2000; Frequency: 1753.75 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_1800_120206 Medium parameters used: $f = 1754$ MHz; $\sigma = 1.506$ mho/m; $\epsilon_r = 55.558$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

- ε Probe: EX3DV4 - SN3697; ConvF(7.16, 7.16, 7.16); Calibrated: 2011/9/2
 - ε Sensor-Surface: 4mm (Mechanical Surface Detection)
 - ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
 - ε Phantom: SAM2; Type: SAM; Serial: TP-1477
 - ε Measurement SW: DASYS2, Version 52.8 (0)
-

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2012/1/19

#220 802.11B_Back_1cm_1M_Ch11

DUT: 1N0701

Communication System: WIFI; Frequency: 2462 MHz; Duty Cycle: 1:1; PMF: 1
Medium: MSL_2450_120119 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.977$ mho/m; $\epsilon_r = 53.795$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)


- ε Probe: EX3DV4 - SN3697; ConvF(6.73, 6.73, 6.73); Calibrated: 2011/9/2

- ε Sensor-Surface: 4mm (Mechanical Surface Detection)
- ε Electronics: DAE4 Sn1210; Calibrated: 2011/11/18
- ε Phantom: SAM2; Type: SAM; Serial: TP-1477
- ε Measurement SW: DASY52, Version 52.8 (0)

Multi Band Result:

SAR(1 g) = 1.26 mW/g; SAR(10 g) = 0.696 mW/g

Maximum value of SAR (interpolated) = 2.142 mW/g



0 dB = 2.140mW/g = 6.61 dB mW/g