



## ***Appendix B. Plots of RF Emission Measurement***

The plots are shown as follows.

**#01 HAC\_E\_CDMA2000 BC10\_RC1\_SO3\_1/8Rate\_Ch476**

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 817.9 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch476/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 27.97 V/m; Power Drift = -0.18 dB

Applied MIF = 0.74 dB

RF audio interference level = 27.76 dB V/m

**Emission category: M4**

MIF scaled E-field


Grid 1 M4 <b>26.15 dB V/m</b>	Grid 2 M4 <b>26.91 dB V/m</b>	Grid 3 M4 <b>26.55 dB V/m</b>
Grid 4 M4 <b>26.56 dB V/m</b>	Grid 5 M4 <b>27.76 dB V/m</b>	Grid 6 M4 <b>26.77 dB V/m</b>
Grid 7 M4 <b>26.42 dB V/m</b>	Grid 8 M4 <b>27 dB V/m</b>	Grid 9 M4 <b>26.63 dB V/m</b>

**Cursor:**

Total = 27.76 dB V/m

E Category: M4

Location: -4.5, -4.5, 8.7 mm



0 dB = 24.44 V/m = 27.76 dB V/m

**#02 HAC\_E\_CDMA2000 BC10\_RC1\_SO3\_1/8Rate\_Ch580**

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 820.5 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch580/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 29.70 V/m; Power Drift = 0.07 dB

Applied MIF = 0.74 dB

RF audio interference level = 28.68 dB V/m

**Emission category: M4**

MIF scaled E-field



<b>Grid 1 M4</b> <b>26.61 dB V/m</b>	<b>Grid 2 M4</b> <b>27.32 dB V/m</b>	<b>Grid 3 M4</b> <b>26.87 dB V/m</b>
<b>Grid 4 M4</b> <b>27 dB V/m</b>	<b>Grid 5 M4</b> <b>28.68 dB V/m</b>	<b>Grid 6 M4</b> <b>27.21 dB V/m</b>
<b>Grid 7 M4</b> <b>27.13 dB V/m</b>	<b>Grid 8 M4</b> <b>27.77 dB V/m</b>	<b>Grid 9 M4</b> <b>27.11 dB V/m</b>

**Cursor:**

Total = 28.68 dB V/m

E Category: M4

Location: 0, 5, 8.7 mm



0 dB = 27.18 V/m = 28.68 dB V/m

### #03 HAC\_E\_CDMA2000 BC10\_RC1\_SO3\_1/8Rate\_Ch684

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 823.1 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

### Ch684/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 30.15 V/m; Power Drift = 0.05 dB

Applied MIF = 0.74 dB

RF audio interference level = 27.89 dB V/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>26.79 dB V/m</b>	Grid 2 <b>M4</b> <b>27.51 dB V/m</b>	Grid 3 <b>M4</b> <b>26.78 dB V/m</b>
Grid 4 <b>M4</b> <b>27.19 dB V/m</b>	Grid 5 <b>M4</b> <b>27.89 dB V/m</b>	Grid 6 <b>M4</b> <b>27.27 dB V/m</b>
Grid 7 <b>M4</b> <b>27.29 dB V/m</b>	Grid 8 <b>M4</b> <b>27.77 dB V/m</b>	Grid 9 <b>M4</b> <b>27.18 dB V/m</b>

**Cursor:**

Total = 27.89 dB V/m

E Category: M4

Location: -2.5, 2, 8.7 mm



0 dB = 24.82 V/m = 27.90 dB V/m

### #04 HAC\_E\_CDMA2000 BC0\_RC1\_SO3\_1/8Rate\_Ch1013

#### DUT: 2D2016

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 824.7 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

#### DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

#### Ch1013/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 29.31 V/m; Power Drift = -0.08 dB

Applied MIF = 0.74 dB

RF audio interference level = 27.50 dB V/m

**Emission category: M4**

MIF scaled E-field


Grid 1 M4 <b>26.19 dB V/m</b>	Grid 2 M4 <b>26.98 dB V/m</b>	Grid 3 M4 <b>26.62 dB V/m</b>
Grid 4 M4 <b>26.68 dB V/m</b>	Grid 5 M4 <b>27.5 dB V/m</b>	Grid 6 M4 <b>26.94 dB V/m</b>
Grid 7 M4 <b>26.7 dB V/m</b>	Grid 8 M4 <b>27.29 dB V/m</b>	Grid 9 M4 <b>26.79 dB V/m</b>

**Cursor:**

Total = 27.50 dB V/m

E Category: M4

Location: -0.5, 0.5, 8.7 mm



0 dB = 23.72 V/m = 27.50 dB V/m

**#05 HAC\_E\_CDMA2000 BC0\_RC1\_SO3\_1/8Rate\_Ch384**

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 836.52 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch384/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 28.09 V/m; Power Drift = 0.01 dB

Applied MIF = 0.74 dB

RF audio interference level = 27.36 dB V/m

**Emission category: M4**

MIF scaled E-field


<b>Grid 1 M4</b> <b>26.4 dB V/m</b>	<b>Grid 2 M4</b> <b>27.03 dB V/m</b>	<b>Grid 3 M4</b> <b>26.59 dB V/m</b>
<b>Grid 4 M4</b> <b>26.79 dB V/m</b>	<b>Grid 5 M4</b> <b>27.36 dB V/m</b>	<b>Grid 6 M4</b> <b>26.85 dB V/m</b>
<b>Grid 7 M4</b> <b>26.76 dB V/m</b>	<b>Grid 8 M4</b> <b>27.25 dB V/m</b>	<b>Grid 9 M4</b> <b>26.81 dB V/m</b>

**Cursor:**

Total = 27.36 dB V/m

E Category: M4

Location: -1.5, 2, 8.7 mm



0 dB = 23.33 V/m = 27.36 dB V/m

**#06 HAC\_E\_CDMA2000 BC0\_RC1\_SO3\_1/8Rate\_Ch777**

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 848.31 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch777/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 25.59 V/m; Power Drift = -0.04 dB

Applied MIF = 0.74 dB

RF audio interference level = 26.33 dB V/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>25.03 dB V/m</b>	Grid 2 <b>M4</b> <b>26.16 dB V/m</b>	Grid 3 <b>M4</b> <b>25.74 dB V/m</b>
Grid 4 <b>M4</b> <b>25.36 dB V/m</b>	Grid 5 <b>M4</b> <b>26.33 dB V/m</b>	Grid 6 <b>M4</b> <b>25.97 dB V/m</b>
Grid 7 <b>M4</b> <b>25.39 dB V/m</b>	Grid 8 <b>M4</b> <b>26.19 dB V/m</b>	Grid 9 <b>M4</b> <b>25.88 dB V/m</b>

**Cursor:**

Total = 26.33 dB V/m

E Category: M4

Location: -3.5, 4.5, 8.7 mm



0 dB = 20.73 V/m = 26.33 dB V/m

**#07 HAC\_E\_CDMA2000 BC0\_RC1\_SO3\_1/8Rate\_Ch25**

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 1851.25 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch25/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 10.37 V/m; Power Drift = -0.15 dB

Applied MIF = 0.74 dB

RF audio interference level = 19.75 dB V/m

**Emission category: M4**

MIF scaled E-field


<b>Grid 1 M4</b> <b>19.4 dB V/m</b>	<b>Grid 2 M4</b> <b>18.97 dB V/m</b>	<b>Grid 3 M4</b> <b>19.16 dB V/m</b>
<b>Grid 4 M4</b> <b>18.62 dB V/m</b>	<b>Grid 5 M4</b> <b>19.75 dB V/m</b>	<b>Grid 6 M4</b> <b>19.66 dB V/m</b>
<b>Grid 7 M4</b> <b>20.18 dB V/m</b>	<b>Grid 8 M4</b> <b>20.34 dB V/m</b>	<b>Grid 9 M4</b> <b>20.11 dB V/m</b>

**Cursor:**

Total = 20.34 dB V/m

E Category: M4

Location: -3.5, 24.5, 8.7 mm



0 dB = 10.40 V/m = 20.34 dB V/m

**#08 HAC\_E\_CDMA2000 BC0\_RC1\_SO3\_1/8Rate\_Ch600**

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 1880 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch600/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 9.543 V/m; Power Drift = -0.12 dB

Applied MIF = 0.74 dB

RF audio interference level = 19.85 dB V/m

**Emission category: M4**

MIF scaled E-field


Grid 1 M4 <b>19.85 dB V/m</b>	Grid 2 M4 <b>18.8 dB V/m</b>	Grid 3 M4 <b>18.79 dB V/m</b>
Grid 4 M4 <b>18.33 dB V/m</b>	Grid 5 M4 <b>19.56 dB V/m</b>	Grid 6 M4 <b>19.32 dB V/m</b>
Grid 7 M4 <b>20.2 dB V/m</b>	Grid 8 M4 <b>20.63 dB V/m</b>	Grid 9 M4 <b>19.85 dB V/m</b>

**Cursor:**

Total = 20.63 dB V/m

E Category: M4

Location: 3.5, 25, 8.7 mm



0 dB = 10.75 V/m = 20.63 dB V/m

### #09 HAC\_E\_CDMA2000 BC0\_RC1\_SO3\_1/8Rate\_Ch1175

**DUT: 2D2016**

Communication System: CDMA2000 (1xRTT, RC1, 1/8 Rate); Frequency: 1908.75 MHz; Duty Cycle: 1:19.8153

Medium: Air Medium parameters used:  $\sigma = 0$  mho/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4 °C

DASY5 Configuration:

- Probe: ER3DV6 - SN2476; ConvF(1, 1, 1); Calibrated: 2012/12/12;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn910; Calibrated: 2012/12/5
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

### Ch1175/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Measurement grid: dx=5mm, dy=5mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 9.170 V/m; Power Drift = -0.08 dB

Applied MIF = 0.74 dB

RF audio interference level = 20.19 dB V/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>20.22 dB V/m</b>	Grid 2 <b>M4</b> <b>19.47 dB V/m</b>	Grid 3 <b>M4</b> <b>18.86 dB V/m</b>
Grid 4 <b>M4</b> <b>19.38 dB V/m</b>	Grid 5 <b>M4</b> <b>19.54 dB V/m</b>	Grid 6 <b>M4</b> <b>19.4 dB V/m</b>
Grid 7 <b>M4</b> <b>20.19 dB V/m</b>	Grid 8 <b>M4</b> <b>20.19 dB V/m</b>	Grid 9 <b>M4</b> <b>19.39 dB V/m</b>

**Cursor:**

Total = 20.22 dB V/m

E Category: M4

Location: 25, -25, 8.7 mm



0 dB = 10.25 V/m = 20.21 dB V/m