



TEST REPORT

No. 2012EEB00355-EMC

For

ZTE Corporation

WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone

Model Name: ZTE V790/Movistar Motion/V790/ZTE V790S

Marketing Name: ZTE V790/Movistar Motion/V790/ZTE V790S

FCC ID: Q78-ZTEV790

with

Hardware Version: p8rA

Software Version: MOVISTAR_P752D03V1.0.0B01

Issued Date: 2012-08-29

Test Laboratory:

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2678 , Fax:+86(0)10-62304633-2504 Email:welcome@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. EUT SET-UPS	5
4. REFERENCE DOCUMENTS	6
4.1. REFERENCE DOCUMENTS FOR TESTING.....	6
5. LABORATORY ENVIRONMENT.....	7
6. SUMMARY OF TEST RESULTS	8
7. TEST EQUIPMENTS UTILIZED	9
ANNEX A: MEASUREMENT RESULTS.....	10

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52 Hua Yuanbei Road, Haidian District, Beijing, P.R.China
Postal Code: 100191
Telephone: +86(0)10-62304633-2678
Fax: +86(0)10-62304633-2504


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data


Testing Start Date: Apr 24th, 2012
Testing End Date: Apr 27th, 2012

1.4. Signature




Du Zhaoxuan

(Prepared this test report)



Zhou Yi

(Reviewed this test report)



Lu Minniu

Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: ZTE Corporation
Address /Post: ZTE Plaza, Hi-tech Park, Nanshan District
City: Shenzhen, Guangdong
Postal Code: 518057
Country: China
Telephone: +86-21-68897541
Fax: +86-21-50801070

2.2. Manufacturer Information

Company Name: ZTE Corporation
Address /Post: ZTE Plaza, Hi-tech Park, Nanshan District
City: Shenzhen, Guangdong
Postal Code: 518057
Country: China
Telephone: +86-21-68897541
Fax: +86-21-50801070

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	WCDMA/GSM (GPRS) Dual-Mode Digital Mobile Phone
Model Name	ZTE V790/Movistar Motion/V790/ZTE V790S
Marketing Name	ZTE V790/Movistar Motion/V790/ZTE V790S
FCC ID	Q78-ZTEV790

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	866302010001793	p8rA	MOVISTAR_P752D03V1.0.0B01

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Travel charger	/
AE3	USB cable	/

AE1

Model	Li3712T42P3h654246h
Manufacturer	ZTE Corporation
Capacitance	1200mAh
Nominal voltage	3.7V

AE2

Model	STC-A22O50I500USBA
Manufacturer	DOKOCOM
Length of cable	118cm

AE3

Model	/
Manufacturer	/
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1 + AE2	Charging mode
Set.2	EUT1+ AE1 + AE3	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-2011 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (11.20 meters×6.10meters×5.60meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 70 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 1 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. =35 %, Max. = 80 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 1 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. =35 %, Max. = 80 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 1 Ω

Fully-anechoic chamber (11.20 meters×6.10 meters×6.60 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 70 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 1 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 6 GHz, 3 m distance

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Radiated Emission	15.109(a)	A.1	P
2	Conducted Emission	15.107(a)	A.2	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1	Test Receiver	ESCI	100701	R&S	2013.08.03
2	Test Receiver	ESCI	100702	R&S	2013.08.03
3	Test Receiver	FSP 40	100378	R&S	2012.12.22
4	BiLog Antenna	VULB9163	9163 330	Schwarzbeck	2014.02.24
5	LISN	ESH2-Z5	100196	R&S	2013.01.25
6	Dual-Ridge Waveguide Horn Antenna	3117	00066585	ETS-Lindgren	2013.04

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

Reference

FCC: CFR Part 15.109(a)

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Limit from CFR Part 15.109(a)

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

*Note: The original limit is defined at 10m test distance. This limit is calculated according to CISPR requirements.

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz (IF bandwidth)	5
1000-4000	1MHz/1MHz	15

A.1.5 Measurement Results




Figure A.1 Radiated Emission from 30MHz to 1GHz (Set.1, Charging mode)




Figure A.2 Radiated Emission from 1GHz to 4GHz (Set.1, Charging mode)




Figure A.3 Radiated Emission from 30MHz to 1GHz (Set.2, USB mode)




Figure A.4 Radiated Emission from 1GHz to 4GHz (Set.2, USB mode)

A.2 Conducted Emission (§15.107(a))

Reference

FCC: CFR Part 15.107(a)

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results




Figure A.5 Conducted Emission (Set.1, Charging mode)

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
0.303000	42.2	FLO	L1	10.0	18.0	60.2
0.312000	48.3	FLO	L1	10.0	11.6	59.9
1.468500	37.2	FLO	L1	10.1	18.8	56.0
1.684500	40.5	FLO	L1	10.1	15.5	56.0
1.693500	40.8	FLO	L1	10.1	15.2	56.0
1.851000	40.8	FLO	L1	10.1	15.2	56.0

Final Measurement Detector 2

Frequency (MHz)	Average (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
0.312000	41.3	FLO	L1	10.0	8.6	49.9
1.684500	30.9	FLO	L1	10.1	15.1	46.0
1.734000	32.3	FLO	L1	10.1	13.7	46.0
1.765500	32.7	FLO	L1	10.1	13.3	46.0
1.815000	33.0	FLO	L1	10.1	13.0	46.0
1.833000	33.0	FLO	L1	10.1	13.0	46.0




Figure A.6 Conducted Emission (Set.2, USB mode)

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
7.881000	15.6	FLO	N	10.3	44.4	60.0
10.126500	25.6	FLO	N	10.3	34.4	60.0
10.878000	20.1	FLO	N	10.4	39.9	60.0
12.376500	23.2	FLO	L1	10.4	36.8	60.0
13.128000	26.0	FLO	L1	10.4	34.0	60.0
16.129500	24.3	FLO	L1	10.4	35.7	60.0

Final Measurement Detector 2

Frequency (MHz)	Average (dB µV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB µV)
0.676500	25.6	FLO	N	10.0	20.4	46.0
1.351500	25.4	FLO	L1	10.1	20.6	46.0
2.026500	25.3	FLO	L1	10.1	20.7	46.0
2.800500	23.4	FLO	N	10.1	22.6	46.0
3.187500	21.8	FLO	L1	10.2	24.2	46.0
4.632000	24.8	FLO	L1	10.2	21.2	46.0

END OF REPORT