

# AFAR COMMUNICATIONS, INC

## PULSAR WIRELESS ETHERNET BRIDGE

Model: AR-9027E

02/08/2010

Report No.: SL09121701-AFA-001(AR-9027E)  
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

David Zhang  
Compliance Engineer

Leslie Bai  
Director of Certification

This test report may be reproduced in full only.  
All Test Data Presented in this report is only applicable to presented Test sample.

**EMC Test Report**

**SIEMIC, INC.**  
Accessing global markets



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 2 of 65  
www.siemic.com

## Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management through out a project. Our extensive experience with China, Asia Pacific, North America, European, and international compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless , Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety

### Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom



**SIEMIC, INC.**  
Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 3 of 65  
[www.siemic.com](http://www.siemic.com)

This page has been left blank intentionally.

## CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION.....	6
2	TECHNICAL DETAILS.....	7
3	MODIFICATION .....	8
4	TEST SUMMARY .....	9
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	10
	ANNEX A. TEST INSTRUMENT & METHOD .....	40
	ANNEX B EUT AND TEST SETUP PHOTOGRAPHS.....	44
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT .....	44
	ANNEX D USER MANUAL, BLOCK DIAGRAM, CIRCUIT DIAGRAM.....	48
	ANNEX E. SIEMIC ACCREDITATION CERTIFICATES .....	49



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 5 of 65  
[www.siemic.com](http://www.siemic.com)

This page has been left blank intentionally.

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model: AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 6 of 65  
www.siemic.com

## 1 Executive Summary & EUT information

The purpose of this test programmed was to demonstrate compliance of the AFAR Communications, Inc Model: AR-9027E against the current Stipulated Standards. The PulsAR Wireless Ethernet Bridge have demonstrated compliance with the FCC 15.247:2009 & RSS-210 Issue 7 : 2007.

The test has demonstrated that this unit complies with stipulated standards.

### EUT Information

<b>EUT Description</b>	: The family of pulsAR Wireless Ethernet Bridges consist of license free radios that can be used to bridge Ethernet LANs (Local Area Networks) across distances ranging from a few hundred feet to 50miles (80 km) and beyond. You can deploy them in a variety of topologies from a simple point-to-point link to a general mesh "tree" topology where any subscriber node can also be used as an access point to nodes further downstream. For mobile applications you can configure subscriber nodes to autonomously roam between multiple access points, keeping the mobile nodes connected to the network at all times.
	All radios use Direct Sequence Spread Spectrum and operate in the "Industrial Scientific and Medical" (ISM) bands, at 900 MHz.
<b>Model No</b>	: AR-9027E
<b>Serial No</b>	: AF030007
<b>Input Power</b>	: Power over Ethernet compatible ( +48VDC) Or +10 to +58 VDC or 110 to 220VAC ( with external supply)
<b>Classification Per Stipulated Test Standard</b>	: Spread Spectrum System / Device

## 2 TECHNICAL DETAILS

<b>Purpose</b>	Compliance testing of PulsAR Wireless Ethernet Bridge model AR-9027E with stipulated standard
<b>Applicant / Client</b>	AFAR Communications, Inc
<b>Manufacturer</b>	AFAR Communications, Inc 81 David Love Place Santa Barbara , CA 93117
<b>Laboratory performing the tests</b>	SIEMIC Laboratories
<b>Test report reference number</b>	SL09121701-AFA-001(AR-9027E)
<b>Date EUT received</b>	January 26 <sup>th</sup> 2010
<b>Standard applied</b>	See Page 9
<b>Dates of test (from – to)</b>	Jan 26 <sup>th</sup> – Feb 5 <sup>th</sup> 2010
<b>No of Units:</b>	1
<b>Equipment Category:</b>	DTS
<b>Trade Name:</b>	AFAR Communications, Inc
<b>Model Name:</b>	AR-9027E
<b>RF Operating Frequency (ies)</b>	905MHz - 925MHz
<b>Number of Channels:</b>	21
<b>Modulation:</b>	DSSS
<b>FCC ID:</b>	Q7N-9027E
<b>IC ID:</b>	4733A-9027E

### **3 MODIFICATION**

**NONE**

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 9 of 65  
www.siemic.com

## 4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

**Spread Spectrum System / Device**

### Test Results Summary

Test Standard	Description	Pass / Fail	
CFR 47 Part 15.247: 2009	RSS 210 Issue 7: 2007		
15.203	Antenna Requirement	Pass	
15.205	Restricted Band of Operation	Pass	
15.207(a)	RSSGen(7.2.2)	Conducted Emissions Voltage	Pass
15.247(a)(1)	RSS210(A8.1)	Channel Separation	N/A
15.247(a)(1)	RSS210(A8.1)	Occupied Bandwidth	N/A
15.247(a)(2)	RSS210 (A8.2)	6 dB Bandwidth	Pass
15.247(a)(1)	RSS210(A8.1)	Number of Hopping Channels	N/A
15.247(a)(1)	RSS210(A8.1)	Time of Occupancy	N/A
15.247(b)	RSS210(A8.4)	Output Power	Pass
15.247(c)	RSS210(A8.4)	Antenna Gain > 6 dBi	Pass
15.247(d)	RSS210(A8.5)	Conducted Spurious Emissions	Pass
15.209; 15.247(d)	RSS210(A8.5)	Radiated Spurious Emissions	Pass
15.247(e)	RSS210(A8.3)	Power Spectral Density	Pass
15.247(f)	RSS210(A8.3)	Hybrid System Requirement	N/A
15.247(g)	RSS210(A8.1)	Hopping Capability	N/A
15.247(h)	RSS210(A8.1)	Hopping Coordination Requirement	N/A
15.247(i)	RSSGen(5.5)	RF Exposure requirement	Pass
	RSSGen(4.8)	Receiver Spurious Emissions	Pass

ANSI C63.4: 2003/ RSS-Gen Issue 2: 2007

PS: All measurement uncertainties are not taken into consideration for all presented test result.



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 10 of 65  
www.siemic.com

## **5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS**

### **5.1 Antenna Requirement**

**Requirement(s):** 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

AR-9027E can work with 2 different types of antenna , of which antenna gain are 5dBi and 15dBi . The antenna connector is N type and the maximum gain is 15dBi for 905MHz – 925MHz band.

This is subject to professional installation. For detail, please see user manual.

**Results:** PASS

## 5.2 Conducted Emissions Voltage

Requirement:

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

\*Decreases with the logarithm of the frequency.

**Procedures:**


1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty  
 All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is  $\pm 3.86$ dB.
4. Environmental Conditions
 

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Jan 26th to Feb 5th 2010

Tested By :David Zhang

**Results:** Pass




Quasi-Peak Limit

Average Limit

Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	QP Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
0.60	52.75	56.00	PASS	-3.25	38.39	46.00	PASS	-7.61	Phase
0.72	43.37	56.00	PASS	-12.63	33.06	46.00	PASS	-12.94	Phase
0.73	42.69	56.00	PASS	-13.31	31.76	46.00	PASS	-14.24	Phase
8.27	45.23	60.00	PASS	-14.77	40.89	50.00	PASS	-9.11	Phase
8.87	43.07	60.00	PASS	-16.93	36.79	50.00	PASS	-13.21	Phase
8.94	41.54	60.00	PASS	-18.46	33.27	50.00	PASS	-16.73	Phase



Quasi-Peak Limit

Average Limit

Neutral Line Plot at 120Vac, 60Hz

Frequency (MHz)	QP Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
0.60	53.49	56.00	PASS	-2.51	40.13	46.00	PASS	-5.87	Neutral
0.73	43.16	56.00	PASS	-12.84	32.21	46.00	PASS	-13.79	Neutral
0.50	43.40	56.03	PASS	-12.63	34.89	46.03	PASS	-11.14	Neutral
8.65	42.62	60.00	PASS	-17.38	34.71	50.00	PASS	-15.29	Neutral
0.67	38.63	56.00	PASS	-17.37	28.80	46.00	PASS	-17.20	Neutral
0.32	41.47	59.72	PASS	-18.25	34.30	49.72	PASS	-15.42	Neutral

## 5.3 6dB & 99% Occupied Bandwidth


**Requirement(s): 47 CFR §15.247(a)(1)**

**Procedures:** The 6dB bandwidths were measured conducted using a spectrum analyzer at low, mid, and hi channels. 6 dB Bandwidth Limit: > 500 kHz.


## Results: Pass

Channel	Channel Frequency (MHz)	6 dB Channel Bandwidth (MHz)	99% Channel Bandwidth (MHz)	6 dB Occupied Bandwidth Limit (MHz)
Low	905	3.02	3.920	0.5
Mid	915	3.05	3.920	0.5
High	925	3.00	3.917	0.5


Refer to the attached plots.




6 dB Bandwidth - Low Channel




99% dB Bandwidth - Low Channel




6 dB Bandwidth - Middle Channel



99% dB Bandwidth - Mid Channel



6 dB Bandwidth – High Channel



99% dB Bandwidth - High Channel

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 18 of 65  
www.siemic.com

## **5.4 Peak Spectral Density**

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5$ dB.
3. Environmental Conditions  
Temperature 23°C  
Relative Humidity 50%  
Atmospheric Pressure 1019mbar
4. Test Date : Jan 26th to Feb 5th 2010  
Tested By :David Zhang

**Standard Requirement:** 47 CFR §15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission


**Procedures:** The Peak Spectral density measurement was taken conducted using a spectrum analyzer with average measurement method

RBW=3KHz, VBW > RBW, Sweep time atuo


**Test Result:** Pass

Channel	Channel Frequency (MHz)	Peak Spectral Density Limit (dBm/3KHz)	Peak Spectral Density (dBm/3KHz)
Low	905	8	-6.41
Mid	915	8	-5.82
High	925	8	-6.40


Refer to the attached plots.



### PSD Low Channel



### PSD Mid Channel



Date: 2.FEB.2010 09:16:10

PSD High Channel

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 21 of 65  
www.siemic.com

## 5.11 Peak Output Power

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5$ dB.
3. Environmental Conditions  
Temperature 23°C  
Relative Humidity 50%  
Atmospheric Pressure 1019mbar
4. Test Date : Jan 26th to Feb 5th 2010  
Tested By :David Zhang



Standard Requirement: 47 CFR §15.247(b)



**Procedures:** The peak output power was measured conducted using a spectrum analyzer at low, mid, and hi channels. Peak detector was set to measure the power output. The power is converted from watt to dBm, therefore, 1 watt = 30 dBm. The highest antenna gain that will be used is 15 dBi.


**Test Result:** Pass

Antenna Gain	Channel	Channel Frequency (MHz)	Peak Output Power Limit (dBm)	Measured Output Power(dBm)
5dBi	Low	905	30	21.50
5dBi	Mid	915	30	26.60
5dBi	High	925	30	26.50
15dBi	Low	905	21	20.30
15dBi	Mid	915	21	20.20
15dBi	High	925	21	20.00


Note : AR-9027E can be configured by internal hardware register . Permitted maximum output power setting for AR-9027E is 24dBm for 905MHz , and 28dBm for other higher channel up to 925MHz if using 5dBi antenna ; the permitted maximum output power setting is 23dBm for all channels if using 15dBi antenna.







Output Power Middle Channel (Antenna Gain 15dBi)



Output Power High Channel (Antenna Gain 15dBi)


## 5.11 Antenna Port Emission

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. Environmental Conditions      Temperature      23°C  
    Relative Humidity      50%  
    Atmospheric Pressure      1019mbar
4. Test Date : Jan 26th to Feb 5th 2010  
Tested By :David Zhang


**Standard Requirement:** 47 CFR §15.247(d)

**Procedures:** The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels. The limit was determined by attenuating 20 dB of the RF peak power output


**Test Result:** Pass




Low Channel -1




Low Channel -2




Mid Channel -1



Mid Channel -2



High Channel -1



High Channel -2



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 29 of 65  
www.siemic.com

## **5.11 Radiated Spurious Emission < 1GHz**

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m & 10m) is +6.0dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions      Temperature      23°C  
    Relative Humidity      50%  
    Atmospheric Pressure      1019mbar

Test Date : Jan 26th to Feb 5th 2010

Tested By :David Zhang

**Standard Requirement:** 47 CFR §15.247(d)


**Procedures:** Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set to transmit at mid channel. Note that setting the channel other than middle, the spurious emissions are the same.

The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dB $\mu$ V/m) + ACF (dB) + Cable Loss ( dB)

**Test Result:** Pass

### Radiated Emission Plot – Antenna 5dBi




### 30MHz ~1000MHz

Frequency (MHz)	Quasi-Peak (dBµV/m)	Antenna height (cm)	Polarity	Turntable position (deg)	Limit (dBµV/m)	Margin (dB)
42.804	36.10	188	H	323	40.00	-3.90
47.50	46.99	395	H	293	40.00	-0.51
83.78	23.12	119	V	217	46.00	-16.88
269.97	30.71	100	V	151	46.00	-15.29
400.13	30.43	396	H	288	43.50	-15.57
190.04	29.08	105	H	129	40.00	-14.42

Note:

Emission at 915MHz is normal fundamental signal

### Radiated Emission Plot – Antenna 15dBi



### 30MHz ~1000MHz

Frequency (MHz)	Quasi-Peak (dB $\mu$ V/m)	Antenna height (cm)	Polarity	Turntable position (deg)	Limit (dB $\mu$ V/m)	Margin (dB)
42.80	43.47	102	H	17	46.00	-2.53
47.75	39.66	131	V	6	40.00	-0.34
33.98	34.57	107	V	88	40.00	-5.43
399.85	22.82	271	H	281	46.00	-23.18
106.47	37.08	114	V	125	43.50	-6.42
827.14	30.91	396	V	39	46.00	-15.09

Note:

Emission at 915MHz is normal fundamental signal

## 5.11 Radiated Spurious Emissions > 1GHz & Band Edge

1. 

All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. 

A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. 

Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 1GHz – 40GHz is +6.0dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. 

Environmental Conditions	Temperature	23°C
	Relative Humidity	50%
	Atmospheric Pressure	1019mbar

Test Date : Jan 26th to Feb 5th 2010

Tested By :David Zhang

Standard Requirement: 47 CFR §15.247(d)

**Procedures:** Equipment was setup in a semi-anechoic chamber. For measurements above 1 GHz an average measurement was taken with a 10Hz video bandwidth. The EUT was tested at low, mid and high with the highest output power. An emission was scan up to 10<sup>th</sup> harmonic of the operating frequency.

### Sample Calculation:

EUT Field Strength = Raw Amplitude (dB $\mu$ V/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)

### Test Result: Pass

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
 Model : AR-9027E  
 To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
 Issue Date 02/08/2010  
 Page 33 of 65  
 www.siemic.com

**Antenna Gain 5dBi****Low Channel @ 905MHz @ 3 Meter**

Frequency (GHz)	Reading (dBuV/m)	Direction (degree)	Height (m)	Polarity (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBuV/m)	15.247/15.209 Limit @ 3m (dBuV/m)	Margin (dBuV/m)	Detector (pk/avg)
1.810	53.8	152	100	H	25.7	2.16	31.98	49.68	74	-24.32	Peak
1.810	62.85	152	120	V	25.7	2.16	31.98	58.73	74	-15.27	Peak
1.810	44.22	152	100	H	25.7	2.16	31.98	40.1	54	-13.90	Ave
1.810	56.53	163	121	V	25.7	2.16	31.98	52.41	54	-1.59	Ave
2.715	43.63	130	120	H	28.8	2.72	32.08	43.07	74	-30.93	Peak
2.715	60.55	137	120	V	28.8	2.72	32.08	59.99	74	-14.01	Peak
2.715	29.1	130	120	H	28.8	2.72	32.08	28.54	54	-25.46	Ave
2.715	53.59	137	120	V	28.8	2.72	32.08	53.03	54	-0.97	Ave
3.620	48.59	169	125	V	31.2	3.435	32.37	50.855	74	-23.15	Peak
3.620	43.46	166	126	H	31.2	3.435	32.37	45.725	74	-28.28	Peak
3.620	42.32	169	125	V	31.2	3.435	32.37	44.585	54	-9.42	Ave
3.620	37.85	166	126	H	31.2	3.435	32.37	40.115	54	-13.89	Ave
4.525	37.87	190	110	V	32.2	4.125	32.49	41.705	74	-32.30	Peak
4.525	38.48	271	170	H	32.2	4.125	32.49	42.315	74	-31.69	Peak
4.525	25.36	190	110	V	32.2	4.125	32.49	29.195	54	-24.81	Ave
4.525	25.34	271	170	H	32.2	4.125	32.49	29.175	54	-24.83	Ave

**Note:** Emission was scanned up to 10GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**Mid Channel @ 915MHz @ 3 Meter**

Frequency (GHz)	Reading (dBuV/m)	Direction (degree)	Height (m)	Polarity (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBuV/m)	15.247/15.209 Limit @ 3m (dBuV/m)	Margin (dBuV/m)	Detector (pk/avg)
1.830	54.5	163	100	H	25.7	2.16	31.98	50.38	74	-23.62	Peak
1.830	54.69	163	121	V	25.7	2.16	31.98	50.57	74	-23.43	Peak
1.830	46.3	163	100	H	25.7	2.16	31.98	42.18	54	-11.82	Ave
1.830	46.67	163	121	V	25.7	2.16	31.98	42.55	54	-11.45	Ave
2.745	56.96	160	103	V	28.8	2.72	32.08	56.4	74	-17.60	Peak
2.745	57.53	360	133	H	28.8	2.72	32.08	56.97	74	-17.03	Peak
2.745	47.88	160	103	V	28.8	2.72	32.08	47.32	54	-6.68	Ave
2.745	48.34	360	133	H	28.8	2.72	32.08	47.78	54	-6.22	Ave
3.660	51.53	160	125	V	31.2	3.435	32.37	53.795	74	-20.21	Peak
3.660	46.79	211	126	H	31.2	3.435	32.37	49.055	74	-24.95	Peak
3.660	46.25	160	125	V	31.2	3.435	32.37	48.515	54	-5.48	Ave
3.660	40.41	211	126	H	31.2	3.435	32.37	42.675	54	-11.33	Ave
4.575	38.15	190	110	V	32.2	4.125	32.49	41.985	74	-32.02	Peak
4.575	25.63	271	170	H	32.2	4.125	32.49	29.465	74	-44.54	Peak
4.575	38.02	190	110	V	32.2	4.125	32.49	41.855	54	-12.15	Ave
4.575	25.4	271	170	H	32.2	4.125	32.49	29.235	54	-24.77	Ave

**Note:** Emission was scanned up to 10GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### High Channel @ 925MHz @ 3 Meter

Frequency (GHz)	Reading (dBuV/m)	Direction (degree)	Height (m)	Polarity (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBuV/m)	15.247/15.209 Limit @ 3m (dBuV/m)	Margin (dBuV/m)	Detector (pk/avg)
1.850	42.35	210	100	H	25.7	2.16	31.98	38.23	74	-35.77	Peak
1.850	45.89	143	121	V	25.7	2.16	31.98	41.77	74	-32.23	Peak
1.850	27.39	210	100	H	25.7	2.16	31.98	23.27	54	-30.73	Ave
1.850	28.27	163	121	V	25.7	2.16	31.98	24.15	54	-29.85	Ave
2.775	46.74	158	120	V	28.8	2.72	32.08	46.18	74	-27.82	Peak
2.775	45.24	200	124	H	28.8	2.72	32.08	44.68	74	-29.32	Peak
2.775	35.37	158	120	V	28.8	2.72	32.08	34.81	54	-19.19	Ave
2.775	27.56	200	124	H	28.8	2.72	32.08	27	54	-27.00	Ave
3.700	44.47	158	125	V	31.2	3.435	32.37	46.735	74	-27.27	Peak
3.700	42.12	211	126	H	31.2	3.435	32.37	44.385	74	-29.62	Peak
3.700	36.43	158	125	V	31.2	3.435	32.37	38.695	54	-15.31	Ave
3.700	34.89	211	126	H	31.2	3.435	32.37	37.155	54	-16.85	Ave
4.625	38.3	190	110	V	32.2	4.125	32.49	42.135	74	-31.87	Peak
4.625	25.3	271	170	H	32.2	4.125	32.49	29.135	74	-44.87	Peak
4.625	38.12	190	110	V	32.2	4.125	32.49	41.955	54	-12.05	Ave
4.625	24.8	271	170	H	32.2	4.125	32.49	28.635	54	-25.37	Ave

**Note:** Emission was scanned up to 10GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
 Model : AR-9027E  
 To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
 Issue Date 02/08/2010  
 Page 35 of 65  
 www.siemic.com

**Antenna Gain 15dBi****Low Channel @ 905MHz @ 3 Meter**

Frequency (GHz)	Reading (dBuV/m)	Direction (degree)	Height (m)	Polarity (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBuV/m)	15.247/15.209 Limit @ 3m (dBuV/m)	Margin (dBuV/m)	Detector (pk/avg)
1.810	47.14	204	100	H	25.7	2.16	31.98	43.02	74	-30.98	Peak
1.810	53.622	3	117	V	25.7	2.16	31.98	49.502	74	-24.50	Peak
1.810	36.15	204	100	H	25.7	2.16	31.98	32.03	54	-21.97	Ave
1.810	45.45	3	117	V	25.7	2.16	31.98	41.33	54	-12.67	Ave
2.715	44.99	164	100	H	28.8	2.72	32.08	44.43	74	-29.57	Peak
2.715	53.55	352	171	V	28.8	2.72	32.08	52.99	74	-21.01	Peak
2.715	30.48	164	100	H	28.8	2.72	32.08	29.92	54	-24.08	Ave
2.715	44.52	352	171	V	28.8	2.72	32.08	43.96	54	-10.04	Ave
3.620	52.55	355	171	V	31.2	3.435	32.37	54.815	74	-19.19	Peak
3.620	45.359	158	144	H	31.2	3.435	32.37	47.624	74	-26.38	Peak
3.620	43.12	355	171	V	31.2	3.435	32.37	45.385	54	-8.62	Ave
3.620	39.02	158	144	H	31.2	3.435	32.37	41.285	54	-12.72	Ave
4.525	41.81	125	113	V	32.2	4.125	32.49	45.645	74	-28.36	Peak
4.525	42.81	56	100	H	32.2	4.125	32.49	46.645	74	-27.36	Peak
4.525	27.83	125	113	V	32.2	4.125	32.49	31.665	54	-22.34	Ave
4.525	27.83	56	100	H	32.2	4.125	32.49	31.665	54	-22.34	Ave

**Note:** Emission was scanned up to 10GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**Mid Channel @ 915MHz @ 3 Meter**

Frequency (GHz)	Reading (dBuV/m)	Direction (degree)	Height (m)	Polarity (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBuV/m)	15.247/15.209 Limit @ 3m (dBuV/m)	Margin (dBuV/m)	Detector (pk/avg)
1.830	53.99	357	100	H	25.7	2.16	31.98	49.87	74	-24.13	Peak
1.830	52.273	358	109	V	25.7	2.16	31.98	48.153	74	-25.85	Peak
1.830	47.53	357	100	H	25.7	2.16	31.98	43.41	54	-10.59	Ave
1.830	47.86	358	109	V	25.7	2.16	31.98	43.74	54	-10.26	Ave
2.745	53.204	351	161	V	28.8	2.72	32.08	52.644	74	-21.36	Peak
2.745	53.842	350	164	H	28.8	2.72	32.08	53.282	74	-20.72	Peak
2.745	44.91	351	161	V	28.8	2.72	32.08	44.35	54	-9.65	Ave
2.745	43.31	350	164	H	28.8	2.72	32.08	42.75	54	-11.25	Ave
3.660	52.2	320	166	V	31.2	3.435	32.37	54.465	74	-19.54	Peak
3.660	53.912	350	166	H	31.2	3.435	32.37	56.177	74	-17.82	Peak
3.660	43.2	320	166	V	31.2	3.435	32.37	45.465	54	-8.53	Ave
3.660	42.1	350	166	H	31.2	3.435	32.37	44.365	54	-9.64	Ave
4.575	44.21	353	155	V	32.2	4.125	32.49	48.045	74	-25.96	Peak
4.575	47.04	355	159	H	32.2	4.125	32.49	50.875	74	-23.13	Peak
4.575	37.4	353	155	V	32.2	4.125	32.49	41.235	54	-12.77	Ave
4.575	39.32	355	159	H	32.2	4.125	32.49	43.155	54	-10.85	Ave

**Note:** Emission was scanned up to 10GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007


Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 36 of 65  
www.siemic.com

### High Channel @ 925MHz @ 3 Meter


Frequency (GHz)	Reading (dBuV/m)	Direction (degree)	Height (m)	Polarity (H/V)	Antenna Loss (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBuV/m)	15.247/15.209 Limit @ 3m (dBuV/m)	Margin (dBuV/m)	Detector (pk/avg)
1.850	47.486	135	166	H	25.7	2.16	31.98	43.366	74	-30.63	Peak
1.850	58.513	6	112	V	25.7	2.16	31.98	54.393	74	-19.61	Peak
1.850	36.89	135	166	H	25.7	2.16	31.98	32.77	54	-21.23	Ave
1.850	50.89	6	112	V	25.7	2.16	31.98	46.77	54	-7.23	Ave
2.775	44.928	129	101	V	28.8	2.72	32.08	44.368	74	-29.63	Peak
2.775	47.2	164	116	H	28.8	2.72	32.08	46.64	74	-27.36	Peak
2.775	34.33	129	101	V	28.8	2.72	32.08	33.77	54	-20.23	Ave
2.775	36.69	164	116	H	28.8	2.72	32.08	36.13	54	-17.87	Ave
3.700	44.47	158	125	V	31.2	3.435	32.37	46.735	74	-27.27	Peak
3.700	44.17	350	183	H	31.2	3.435	32.37	46.435	74	-27.57	Peak
3.700	36.43	158	125	V	31.2	3.435	32.37	38.695	54	-15.31	Ave
3.700	33.52	350	183	H	31.2	3.435	32.37	35.785	54	-18.22	Ave
4.625	42.82	356	100	V	32.2	4.125	32.49	46.655	74	-27.35	Peak
4.625	42.908	62	100	H	32.2	4.125	32.49	46.743	74	-27.26	Peak
4.625	28.69	356	100	V	32.2	4.125	32.49	32.525	54	-21.48	Ave
4.625	27.67	62	100	H	32.2	4.125	32.49	31.505	54	-22.50	Ave

**Note:** Emission was scanned up to 10GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

## Band Edge Plots



Low Channel



High Channel

## 5.11 Receiver Spurious Emissions

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. Environmental Conditions      Temperature 23°C  
    Relative Humidity 50%  
    Atmospheric Pressure 1019mbar
4. Test Date : Jan 26th to Feb 5th 2010  
Tested By :David Zhang

Standard Requirement: RSSGen(4.8)

**Procedures:** The conducted spurious emissions were measured conducted using a spectrum analyzer at mid channels. the search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is the higher, to at least 3 times the highest tuneable or local oscillator frequency, whichever is the higher, without exceeding 40 GHz. Receiver spurious emissions at any discrete frequency shall not exceed 2 nanowatts in the band 30-1000 MHz, or 5 nanowatts above 1 GHz.

**Test Result:** Pass




**SIEMIC, INC.**


Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 39 of 65  
www.siemic.com



**Receiver Spurious Emission Plot- 1**



**Receiver Spurious Emission Plot- 2**

## **Annex A. TEST INSTRUMENT & METHOD**

### **Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES**

Instrument	Model	Calibration Due
<b>AC Conducted Emissions</b>		
R&S EMI Test Receiver	ESIB40	04/25/2010
R&S LISN	ESH2-Z5	04/24/2010
CHASE LISN	MN2050B	04/24/2010
<b>Radiated Emissions</b>		
Spectrum Analyzer	8564E	04/26/2010
EMI Receiver	ESIB 40	04/25/2010
R&S LISN	ESH2-Z5	04/24/2010
CHASE LISN	MN2050B	04/24/2010
Antenna(1 ~18GHz)	3115	01/04/2011
Antenna (30MHz~2GHz)	JB1	01/04/2011
Chamber	3m	04/18/2010
Pre-Amplifier(1 ~ 26GHz)	8449	04/24/2010
Horn Antenna (18~40GHz)	AH-840	03/19/2010
Microwave Pre-Amp (18~40GHz)	PA-840	03/19/2010*

Note: Functional Verification

## Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

### Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a  $50\Omega/50\mu\text{H}$  EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

### Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

### Sample Calculation Example

At 20 MHz

limit =  $250 \mu\text{V} = 47.96 \text{ dB}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = 40.00 dB $\mu\text{V}$

(Calibrated for system losses)

Therefore, Q-P margin =  $47.96 - 40.00 = 7.96$

i.e. **7.96 dB below limit**

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 42 of 65  
www.siemic.com

## Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION


### EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 1GHz (for FCC tests, until the 5<sup>th</sup> harmonic for operating frequencies  $\geq$  108MHz), was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer / receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

### **Test Set-up**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table as shown in Annex B.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



## Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

### Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

## Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

Where:

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz}, \text{VBW} = 10\text{Hz}.$$

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

## **Annex B EUT AND TEST SETUP PHOTOGRAPHS**

Please see the attachment


## **Annex C. TEST SETUP AND SUPPORTING EQUIPMENT**

### **EUT TEST CONDITIONS**


#### **Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION**

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
PC Laptop / DELL	Latitude D600	Shielded RJ45 Cable < 1 meter (From PC to EUT)

**Block Configuration Diagram for Radiated Emission**

## Block Configuration Diagram for Conducted Emission



### Note:

A 50ohm termination is used to replace external antenna to simulate normal system function which will not impact the Conducted Emission test.

### **Annex C.ii. EUT OPERATING CONDITIONS**

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
<b>Emissions Testing</b>	The EUT was continuously transmitting controlled via serial connection to PC Laptop using Hyper Terminal commands
<b>Others Testing</b>	The EUT was continuously transmitting controlled via serial connection to PC Laptop using Hyper Terminal commands



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 48 of 65  
[www.siemic.com](http://www.siemic.com)

## **Annex D User Manual, Block Diagram, Circuit Diagram**

**Please see attachment**

## Annex E. SIEMIC ACCREDITATION CERTIFICATES

### SIEMIC ACCREDITATION DETAILS: A2LA Certificate Number: 2742.01



THE AMERICAN ASSOCIATION FOR  
LABORATORY ACCREDITATION

#### ACCREDITED LABORATORY

A2LA has accredited

#### **SIEMIC LABORATORIES**

**San Jose, CA**

for technical competence in the field of

#### **Electrical Testing**

The laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-LAF Communiqué dated 18 June 2005).

Presented this 11th day of July 2008.

Peter Abrey  
 President  
 For the Accreditation Council  
 Certificate Number 2742.01  
 Valid to September 30, 2010



For the tests or types of tests to which this accreditation applies,  
 please refer to the laboratory's Electrical Scope of Accreditation.



THE AMERICAN ASSOCIATION FOR  
LABORATORY ACCREDITATION

#### ACCREDITED PRODUCT CERTIFICATION BODY

A2LA has accredited

#### **SIEMIC INC.**

**San Jose, CA**

for technical competence as a  
**Product Certification Body**

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), IDA (Singapore) and IC (Canada) requirements.

Presented this 9<sup>th</sup> day of January 2009.

Peter Abrey  
 President  
 For the Accreditation Council  
 Certificate Number 2742.02  
 Valid to: September 30, 2010



For the product certification schemes to which this accreditation applies,  
 please refer to the certification body's Scope of Accreditation.

### SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 65:1996

SIEMIC INC  
 2206 Ringwood Ave  
 San Jose, CA 95131  
 Mr. Snell Leong (Authorized Representative) Phone: 408 526 1188  
[www.siemic.com](http://www.siemic.com)

### PRODUCT CERTIFICATION CONFORMITY ASSESSMENT BODY (CAB)

Valid to: September 30, 2010

Certificate Number: 2742.02

In recognition of the successful completion of the A2LA Certification Body Accreditation Program evaluation, including the US Federal Communications Commission (FCC), Industry Canada (IC) and Singapore (IDA) requirements for the indicated types of product certifications, accreditation is granted to this organization to perform the following product certification schemes:

<u>Economy</u>	<u>Scope</u>
----------------	--------------

#### Federal Communication Commission - (FCC)

Unlicensed Radio Frequency Devices	A1, A2, A3, A4
Licensed Radio Frequency Devices	B1, B2, B3, B4
Telephone Terminal Equipment	C

\*Please refer to FCC TCB Program Roles and Responsibilities, v04, released February 14, 2009 detailing scope, roles and responsibilities: <http://www.fcc.gov/oet/ea/FCC-Overview-TCB-Program.pdf>

#### Industry Canada - (IC)

Radio	All Radio Standards Specifications (RSS) in Category I Equipment Standards List Radio
-------	--

\*Please refer to Industry Canada (IC) website at: [http://www.ic.gc.ca/eic/certificat-gst/nfim/1\\_1831542e.html](http://www.ic.gc.ca/eic/certificat-gst/nfim/1_1831542e.html)

#### IDA – Singapore

Line Terminal Equipment	All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2008, Annex 2
Radio-Communication Equipment	All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2008, Annex 2

\*Please refer to Info-Communication Development Authority (IDA) Singapore website at: [http://www.ida.gov.sg/Doc/Policy%20and%20Regulation/Policy\\_and\\_Regulation\\_Level2/20080809145518/01N4RacSelhen.pdf](http://www.ida.gov.sg/Doc/Policy%20and%20Regulation/Policy_and_Regulation_Level2/20080809145518/01N4RacSelhen.pdf)

**SIEMIC ACCREDITATION DETAILS: FCC Test Site Registration No. 783147****FEDERAL COMMUNICATIONS COMMISSION**

Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046

December 20, 2007

Registration Number: 783147

SIEMIC Laboratories  
2206 Ringwood Avenue,  
San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose  
3 & 10 meter site  
Date of Renewal: December 20, 2007

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish  
Industry Analyst



## SIEMIC, INC.

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 52 of 65  
www.siemic.com

### SIEMIC ACCREDITATION DETAILS: Industry of Canada CAB ID : US0160



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

March 4, 2009

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by Industry Canada (IC), under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131 USA  
Identification No.: US0160  
Recognized Scope: CS-03 Part I, II, V, VI, VII and VIII

You may submit test data to IC to verify that the equipment to be imported into Canada satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have any questions.


Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: CAB Program Manager

## SIEMIC ACCREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842-1



May 23rd, 2008

OUR FILE: 46405-4842  
 Submission No: 126429

Siemic Inc.  
 2206 Ringwood Ave.  
 San Jose CA 95131  
 USA

*Attention:* Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration / renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**4842A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please be informed that the Bureau is now utilizing a **new site numbering scheme** in order to simplify the electronic filing process. Our goal is to reduce the number of secondary codes associated to one particular company. The following changes have been made to your record.

- Your primary code is: **4842**
- The company number associated to the site(s) located at the above address is: **4842A**.
- The table below is a summary of the changes made to the unique site registration number(s):

New Site Number	Obsolete Site Number	Description of Site	Expiry Date (YYYY-MM-DD)
4842A-1	4842-1	3m Chamber	2010-05-23

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL: [http://strategis.ic.gc.ca/epic/internet/ineeb-bhst.nsf/en/h\\_1100052e.html](http://strategis.ic.gc.ca/epic/internet/ineeb-bhst.nsf/en/h_1100052e.html).

If you have any questions, you may contact the Bureau by e-mail at [certification.bureau@ic.gc.ca](mailto:certification.bureau@ic.gc.ca). Please reference our file and submission number above for all correspondence.

Yours sincerely,

S. Proulx  
 Test & Measurement Specialist  
 Certification and Engineering Bureau  
 3701 Carling Ave., Building 94  
 Ottawa, Ontario K2H 1S2

**SIEMIC ACCREDITATION DETAILS: FCC DOC CAB Recognition : US1109**

**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbin, MD 21046**

August 28, 2008

Siemic Laboratories  
2206 Ringwood Ave.,  
San Jose, CA 95131

Attention: Leslie Bai

Re: Accreditation of Siemic Laboratories  
Designation Number: US1109  
Test Firm Registration #: 540430


Dear Sir or Madam:

We have been notified by American Association for Laboratory Accreditation that Siemic Laboratories has been accredited as a Conformity Assessment Body (CAB).

At this time Siemic Laboratories is hereby designated to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Parts 15 and 18 of the Commission's Rules.

This designation will expire upon expiration of the accreditation or notification of withdrawal of designation.

Sincerely,

  
George Tannahill  
George Tannahill  
Electronics Engineer

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 55 of 65  
www.siemic.com

**SIEMIC ACCREDITATION DETAILS: Australia CAB ID : US0160**

**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I Procedures**, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4  
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771  
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have questions.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

## SIEMIC ACCREDITATION DETAILS: Korea CAB ID: US0160



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
 Gaithersburg, Maryland 20899

October 1, 2008

Mr. Leslie Bai  
 SIEMIC, Inc.  
 2206 Ringwood Avenue  
 San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
 Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
 Identification No.: US0160  
 Recognized Scope: **EMI:** KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI  
 KN22: Test Method for EMI  
**EMS:** KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS  
 KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS  
**Wireless:** RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,  
 RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,  
 RRL Notice 2007-80, RRL Notice 2004-68  
**Wired:** President Notice 20664, RRL Notice 2007-30,  
 RRL Notice 2008-7 with attachments 1, 3, 5, 6  
 President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,

*David F. Alderman*

David F. Alderman  
 Group Leader, Standards Coordination and Conformity Group  
 Standards Services Division

Enclosure

cc: Ramona Saar

**NIST**

**SIEMIC ACCREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R**

**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20883

May 3, 2006

Mr. Leslie Bai  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S. Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group

cc: Jagminder Dhillon



# SIEMIC, INC.

Accessing global markets

Title: RF Test Report of AFAR Communications, Inc  
Model : AR-9027E  
To FCC 15.247:2009 & RSS-210 Issue 7 : 2007

Serial# SL09121701-AFA-001(AR-9027E)  
Issue Date 02/08/2010  
Page 58 of 65  
www.siemic.com

## SIEMIC ACCREDITATION DETAILS: Taiwan NCC CAB ID: US0160



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

November 25, 2008

Mr. LeslieBai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Current Scope: LP0002  
Additional Scope: PSTN01, ADSL01, ID0002, IS6100 and CNS 14336

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Ramona Saar

**SIEMIC ACCREDITATION DETAILS: Mexico NOM Recognition**

CÁMARA NACIONAL  
DE LA INDUSTRIA  
ELECTRÓNICA, DE  
TELECOMUNICACIONES  
E INFORMÁTICA

**Laboratorio Valentín V. Rivero**

Méjico D.F. a 16 de octubre de 2009.

LESLIE BAI  
DIRECTOR OF CERTIFICATION  
SIEMIC LABORATORIES, INC.  
ACCEESSING GLOBAL MARKETS  
P R E S E N T E

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español prellenado de los cuales le pido sea revisado y en su caso corregido, para que si esto de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediano gestor será la empresa Isotel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestión de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me deseo de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:

Ing. Faustino Sánchez González  
Gerente Técnico del Laboratorio de  
CANIETI

## SIEMIC ACCREDITATION DETAILS: Hong Kong OFTA CAB ID : US0160



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
 Gaithersburg, Maryland 20899

December 8, 2008

Mr. Leslie Bai  
 SIEMIC, Inc.  
 2206 Ringwood Avenue  
 San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I Procedures**, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
 Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA  
 Identification No.: US0160  
 Recognized Scope: **Radio:** HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026, 1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041, 1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051  
**Telecom:** HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,

*David T. Alderman*

David F. Alderman  
 Group Leader, Standards Coordination and Conformity Group  
 Standards Services Division

Enclosure

cc: Ramona Saar

## SIEMIC ACCREDITATION DETAILS: Australia ACMA CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE  
**National Institute of Standards and Technology**  
 Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai  
 SIEMIC, Inc.  
 2206 Ringwood Avenue  
 San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.  
 Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
 Identification No.: US0160  
 Recognized Scope: **EMC:** AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4  
**Radiocommunications:** AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771  
**Telecommunications:** AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have questions.

Sincerely,

David F. Alderman  
 Group Leader, Standards Coordination and Conformity Group  
 Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

**SIEMIC ACCREDITATION DETAILS: Australia NATA Recognition**

Leslie Bal  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

November 4, 2008

Under Australian government legislation, the Australian Communications and Media Authority (ACMA) has determined the National Association of Testing Authorities, Australia (NATA) as an accreditation body as per Section 409(1) of the Telecommunications Act 1997 (Cth). Pursuant to Section 409(2) of the Telecommunications Act 1997 (Cth), I am pleased to advise that your laboratory has been determined as a Recognised Testing Authority (RTA).

This determination has been made on the basis of your accreditation by A2LA accreditation no. 2742.01 and the Mutual Recognition Agreement between NATA and A2LA. It is effective from 11 July 2008. RTA status applies only to the following standards and is contingent upon their continued inclusion in your laboratory's scope of accreditation.

**AS/ACIF S002, AS/ACIF S003, AS/ACIF S004,  
AS/ACIF S006, AS/ACIF S016, AS/ACIF S031,  
AS/ACIF S038, AS/ACIF S041 and  
AS/ACIF S043.2**

As an RTA, your laboratory has the following obligations.

1. the laboratory shall continue to meet all of the accreditation criteria of A2LA;
2. the authorised representative of the laboratory shall notify NATA of changes to the staff or operations of the laboratory which would affect the performance of the tests for which the laboratory has been determined;
3. compliance of equipment shall be reported on test reports bearing the A2LA logo/endorsement.

Current information on the Australian Communications and Media Authority and regulatory requirements for telecommunications products within Australia can be obtained from the ACMA's web-site at "<http://www.acma.gov.au>". Further information about NATA may be gained by visiting "<http://www.nata.asn.au>".

Please note that AS/ACIF S040 and New Zealand standards do not form part of the RTA scheme.

Your RTA listing will appear on the NATA website shortly.

Kind Regards

Chris Norton  
Senior Scientific Officer  
Measurement Science and Technology  
National Association of Testing Authorities (NATA)  
71-73 Flemington Road  
North Melbourne Vic 3051  
Australia  
Ph: +61 3 9329 1633 Fx: +61 3 9326 5148  
E-Mail: [Christopher.Norton@nata.asn.au](mailto:Christopher.Norton@nata.asn.au)  
Internet: [www.nata.asn.au](http://www.nata.asn.au)

**SIEMIC ACCREDITATION DETAILS: VCCI Radiated Test Site Registration No. R-3083**



# CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Radiation 3 meter site)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility  
has been registered in accordance with the Rules  
for Voluntary Control Measures*

Registration No.: R-3083

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010

*VCCI Council*



**SIEMIC ACCREDITATION DETAILS: VCCI Conducted (Main Port) Test Site Registration No. C-3421**



*VCCI Council*

# CERTIFICATE

**Company: SIEMIC Inc.**

*<Member No. 3081 >*

**Facility: SIEMIC Inc.**

(Main Ports Conducted Interference Measurement)

**Location of Facility:**

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility  
has been registered in accordance with the Rules  
for Voluntary Control Measures*

Registration No.: C-3421

Date of Registration: June 12 , 2009

This Certificate is valid until September 30 , 2010

*VCCI Council*



**SIEMIC ACCREDITATION DETAILS: VCCI Conducted (Telecom Port) Test Site Registration No. T-1597**



*VCCI Council*

# CERTIFICATE

**Company: SIEMIC Inc.**

*<Member No. 3081 >*

**Facility: SIEMIC Inc.**

*(Telecominication Ports Conducted Interference Measurement)*

**Location of Facility:**

**2206 Ringwood Avenue, San Jose, CA 95131 USA**

*This is to certify that the following measuring facility  
has been registered in accordance with the Rules  
for Voluntary Control Measures*

**Registration No.: T-1597**

**Date of Registration: June 12, 2009**

**This Certificate is valid until September 30, 2010**

*VCCI Council*

