

RF-031 WIRELESS HEADPHONE

INSTRUCTION MANUAL

KIWA TECHNOLOGY CO., LTD

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATIONS IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED. INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION.

INSTALLATION:

A. TRANSMITTER

1. POWER SUPPLY : PLUG THE ADAPTOR TO MAINS SOCKET AND THE DC CONNECTOR TO DC 9 VOLT INPUT CONNECTOR LOCATED ON THE REAR PANEL OF THE TRANSMITTER.
2. AUDIO CONNECTIONS:
 - a. CONNECT THE 2.0mm BLACK COLOR CONNECTOR OF THE AUDIO CABLE TO AUDIO IN JACK ON THE REAR PANEL OF THE TRANSMITTER.
 - b. CONNECT THE 3.5mm GREEN COLOR CONNECTOR TO AUDIO SOURCE SUCH AS PHONE JACK OF THE COMPUTER.
 - c. CONNECT THE 3.5mm RED COLOR CONNECTOR TO MICROPHONE JACK OF THE COMPUTER.
 - d. PUSH DOWN THE POWER BUTTON ON THE TRANSMITTER, THE POWER LED WILL ON .

B. RECEIVER

1. REMOVE THE BATTERY COVERY OF THE RECEIVER UNIT.
2. ACCORDING TO THE POLARITY INSTRUCTION ON THE RECEIVER UNIT,PUT THE BATTERY (AAA X 2)TO THE RECEIVER THEN PUT BACK THE BATTERY COVERY.
3. PLUG IN THE HEADPHONE CONNECTOR TO RECEIVER UNIT.
4. SWITCH ON THE ON/OFF SWITCH, LED WILL ON.
5. ADJUSTING THE VOLUME TO THE DESIRED LEVEL WITH THE VOLUME CONTROL.

NOTICE : THE CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

INSTALLATION