

FCC TEST REPORT

REPORT NO.: RF121204E06 R1

MODEL NO.: RE1000

VERSION : 2

FCC ID: Q87-RE1000V2

RECEIVED: Dec. 04, 2012

TESTED: Dec. 06 to 20, 2012

ISSUED: Feb. 26, 2013

APPLICANT: Cisco Consumer Products LLC

ADDRESS: 121 Theory Drive Irvine, CA 92617(USA)

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

Table of Contents

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.4 DESCRIPTION OF SUPPORT UNITS.....	15
3.5 CONFIGURATION OF SYSTEM UNDER TEST	15
4. TEST TYPES AND RESULTS	16
4.1 CONDUCTED EMISSION MEASUREMENT	16
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	16
4.1.2 TEST INSTRUMENTS.....	16
4.1.3 TEST PROCEDURES	17
4.1.4 DEVIATION FROM TEST STANDARD	17
4.1.5 TEST SETUP	18
4.1.6 EUT OPERATING CONDITIONS	18
4.1.7 TEST RESULTS	19
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	21
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	21
4.2.2 TEST INSTRUMENTS.....	22
4.2.3 TEST PROCEDURES	23
4.2.4 DEVIATION FROM TEST STANDARD	23
4.2.5 TEST SETUP	24
4.2.6 EUT OPERATING CONDITIONS	24
4.2.7 TEST RESULTS	25
4.3 6dB BANDWIDTH MEASUREMENT	38
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	38
4.3.2 TEST INSTRUMENTS.....	38
4.3.3 TEST PROCEDURE.....	38
4.3.4 DEVIATION FROM TEST STANDARD	38
4.3.5 TEST SETUP	38
4.3.6 EUT OPERATING CONDITIONS	38
4.3.7 TEST RESULTS	39
4.4 CONDUCTED OUTPUT POWER MEASUREMENT	40
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	40
4.4.2 INSTRUMENTS.....	40
4.4.3 TEST PROCEDURES	40



A D T

4.4.4	DEVIATION FROM TEST STANDARD	40
4.4.5	TEST SETUP	40
4.4.6	EUT OPERATING CONDITIONS	40
4.4.7	TEST RESULTS	41
4.5	POWER SPECTRAL DENSITY MEASUREMENT	42
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	42
4.5.2	TEST INSTRUMENTS.....	42
4.5.3	TEST PROCEDURE.....	42
4.5.4	DEVIATION FROM TEST STANDARD	42
4.5.5	TEST SETUP	42
4.5.6	EUT OPERATING CONDITION.....	42
4.5.7	TEST RESULTS	43
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT	44
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	44
4.6.2	TEST INSTRUMENTS.....	44
4.6.3	TEST PROCEDURE.....	44
4.6.4	DEVIATION FROM TEST STANDARD	45
4.6.5	TEST SETUP	45
4.6.6	EUT OPERATING CONDITION.....	45
4.6.7	TEST RESULTS	45
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	52
6.	INFORMATION ON THE TESTING LABORATORIES	53
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	54




RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF121204E06	Original release	Jan. 17, 2013
RF121204E06 R1	Added version information on page 1, 5 & 8	Feb. 26, 2013

1. CERTIFICATION

PRODUCT: Wireless-N Range Extender
BRAND NAME: Cisco
MODEL NO.: RE1000
VERSION: 2
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: Cisco Consumer Products LLC
TESTED: Dec. 06 to 20, 2012
STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2009

The above equipment (Model: RE1000) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE:** Feb. 26, 2013
(Lori Chung, Specialist)

APPROVED BY : , **DATE:** Feb. 26, 2013
(May Chen, Deputy Manager)



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -11.01Db at 0.52109MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.5Db at 2384.00MHz & 2483.50MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6Db bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.98 Db
Radiated emissions (30MHz-1GHz)	5.59 Db
Radiated emissions (1GHz -6GHz)	3.56 Db
Radiated emissions (6GHz -18GHz)	4.10 Db
Radiated emissions (18GHz -40GHz)	4.24 Db

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless-N Range Extender
MODEL NO.	RE1000
VERSION	2
POWER SUPPLY	DC 12V from Internal power supply
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11n (20MHz, 800ns GI): up to 130Mbps 802.11n (20MHz, 400ns GI): up to 144.444Mbps 802.11n (40MHz, 800ns GI) : up to 270Mbps 802.11n (40MHz, 400ns GI) : up to 300Mbps
OPERATING FREQUENCY	2.412 ~ 2.462GHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
MAXIMUM OUTPUT POWER	802.11b: 208.930mW 802.11g: 363.078mW 802.11n (HT20): 526.193mW 802.11n (HT40): 586.621mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	RJ-45 cable (Unshielded, 1.5m) x 1
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT has two colors of the housing which are identical to each other in all aspects except for the following table:

Brand	Model Name	Color	Description
Cisco	RE1000	black	For marketing requirement
		white	

2. The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Antenna Type	Gain (dBi)	Connector type	Frequency range (MHz to MHz)
Chain (0)	PIFA	2.8	NA	2400-2500
Chain (1)	PIFA	2.8	NA	2400-2500

3. The EUT must be supplied with an internal power supply and following two different models could be chosen as following table:

No	Brand	Model No.	Spec.
1	HON-KWANG	HK-XX06-A12	Input: 100-240V, 0.8A, 50/60Hz AC input cable (Unshielded, 1.5m) Output: 12V, 0.5A
2	solytech	UOP0612A	Input: 100-240V, 0.5A, 50/60Hz AC input cable (Unshielded, 1.5m) Output: 12V, 0.5A

From the above power supply, the worse case was found in **power 1**. Therefore only the test data of the mode was recorded in this report.

4. The EUT incorporates a MIMO function without beam forming.

MODULATION MODE	Tx/Rx FUNCTION
802.11b	1Tx/1Rx
802.11g	1Tx/1Rx
802.11n (HT20)	2Tx/2Rx
802.11n (HT40)	2Tx/2Rx

5. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
6. For more detailed product features, please refer to manufacturer's specification or user's manual.

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC:** Power Line Conducted Emission

RE < 1G: Radiated Emission below 1GHz

RE ³ 1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

OB: Conducted Out-Band Emission Measurement

NOTE: 1. "-" means no effect.

2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane (for below 1GHz) and Y-plane (for above 1GHz).

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATIO N TYPE	DATA RATE (Mbps)
802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	22deg. C, 53%RH	120Vac, 60Hz	Timmy Hu
RE<1G	22deg. C, 68%RH	120Vac, 60Hz	Amos Chuang
RE ³ 1G	20deg. C, 68%RH	120Vac, 60Hz	Amos Chuang
APCM	25deg. C, 60%RH	120Vac, 60Hz	Amos Chuang
OB	25deg. C, 60%RH	120Vac, 60Hz	Amos Chuang

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
558074 D01 DTS Meas Guidance
662911 D01 Multiple Transmitter Output
ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP cable (10m)

NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 12, 2012	Mar. 11, 2013
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK8127	8127-522	Sep. 06, 2012	Sep. 05, 2013
Line-Impedance Stabilization Network (for Peripheral)	ENV216	100072	June 08, 2012	June 07, 2013
RF Cable (JYEBAO)	5DFB	COCCAB-001	Aug. 28, 2012	Aug. 27, 2013
50 ohms Terminator	50	EMC-3	Sep. 25, 2012	Sep. 24, 2013
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Dec. 06, 2012

4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


NOTE:

1. The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Turn on the power of EUT.
2. The communication partner run test program “RT5x9xQA.exe” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


4.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
-------	----------	----------------------	-----------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.25547	0.13	41.33	27.96	41.46	28.09	61.58	51.58	-20.12	-23.49
2	0.36875	0.15	40.37	23.09	40.52	23.24	58.53	48.53	-18.01	-25.29
3	0.52109	0.17	44.82	26.24	44.99	26.41	56.00	46.00	-11.01	-19.59
4	0.60313	0.17	42.20	31.21	42.37	31.38	56.00	46.00	-13.63	-14.62
5	0.99375	0.19	35.11	24.74	35.30	24.93	56.00	46.00	-20.70	-21.07
6	1.65234	0.22	34.03	24.93	34.25	25.15	56.00	46.00	-21.75	-20.85
7	3.79688	0.27	40.30	31.68	40.57	31.95	56.00	46.00	-15.43	-14.05
8	5.54688	0.34	33.08	24.93	33.42	25.27	60.00	50.00	-26.58	-24.73

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)
-------	-------------	----------------------	-----------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.40781	0.15	39.51	31.01	39.66	31.16	57.69	47.69	-18.03	-16.53
2	0.59141	0.16	43.08	31.83	43.24	31.99	56.00	46.00	-12.76	-14.01
3	0.73203	0.16	36.14	21.99	36.30	22.15	56.00	46.00	-19.70	-23.85
4	3.16016	0.23	33.19	23.02	33.42	23.25	56.00	46.00	-22.58	-22.75
5	4.21094	0.25	37.29	28.22	37.54	28.47	56.00	46.00	-18.46	-17.53
6	5.32813	0.28	39.36	31.12	39.64	31.40	60.00	50.00	-20.36	-18.60

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250254	July 09, 2012	July 08, 2013
Pre-Selector Agilent	N9039A	MY46520311	July 09, 2012	July 08, 2013
Signal Generator Agilent	N5181A	MY49060517	July 09, 2012	July 08, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A02578	June 26, 2012	June 25, 2013
Pre-Amplifier SPACEK LABS	SLKKA-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Apr. 09, 2012	Apr. 08, 2013
Horn_Antenna AISI	AIH.8018	000032009111 0	Nov. 19, 2012	Nov. 20, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 26, 2011	Dec. 25, 2012
RF Cable	NA	CHGCAB_001	Oct. 06, 2012	Oct. 05, 2013
Software	ADT_Radiated V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
- 5 The VCCI Site Registration No. is G-137.
- 6 The CANADA Site Registration No. is IC 7450H-2.
- 7 Tested Date: Dec. 12 to 18, 2012

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11n (HT20)

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	160.03	36.1 QP	43.5	-7.4	2.00 H	84	21.76	14.33
2	239.96	41.1 QP	46.0	-4.9	1.00 H	64	28.18	12.91
3	320.02	39.8 QP	46.0	-6.3	1.00 H	47	23.94	15.81
4	500.02	36.4 QP	46.0	-9.7	2.00 H	204	15.96	20.39
5	700.04	35.9 QP	46.0	-10.1	1.00 H	360	11.96	23.97
6	999.88	34.6 QP	54.0	-19.4	1.50 H	304	6.15	28.46
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	50.49	38.2 QP	40.0	-1.8	1.00 V	346	24.16	14.07
2	239.96	39.7 QP	46.0	-6.3	2.00 V	0	26.75	12.91
3	320.02	35.4 QP	46.0	-10.6	1.50 V	241	19.60	15.81
4	399.95	36.0 QP	46.0	-10.0	1.00 V	33	18.13	17.86
5	500.02	33.3 QP	46.0	-12.8	2.00 V	360	12.86	20.39
6	700.04	34.8 QP	46.0	-11.2	2.00 V	0	10.82	23.97
7	999.88	35.9 QP	54.0	-18.1	1.00 V	54	7.45	28.46

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2373.70	61.8 PK	74.0	-12.2	1.10 H	37	29.47	32.33
2	2373.70	53.3 AV	54.0	-0.7	1.10 H	37	20.97	32.33
3	*2412.00	109.4 PK			1.10 H	41	76.96	32.44
4	*2412.00	106.9 AV			1.10 H	41	74.46	32.44
5	2490.00	60.8 PK	74.0	-13.2	1.05 H	40	28.16	32.64
6	2490.00	51.8 AV	54.0	-2.2	1.05 H	40	19.16	32.64
7	4824.00	52.0 PK	74.0	-22.0	1.00 H	101	10.06	41.94
8	4824.00	45.1 AV	54.0	-8.9	1.00 H	101	3.16	41.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2373.70	58.3 PK	74.0	-15.7	1.00 V	221	25.97	32.33
2	2373.70	45.1 AV	54.0	-8.9	1.00 V	221	12.77	32.33
3	*2412.00	95.8 PK			1.00 V	69	63.36	32.44
4	*2412.00	93.2 AV			1.00 V	69	60.76	32.44
5	2490.00	58.2 PK	74.0	-15.8	1.00 V	236	25.56	32.64
6	2490.00	45.2 AV	54.0	-8.8	1.00 V	236	12.56	32.64
7	4824.00	55.4 PK	74.0	-18.6	1.10 V	82	13.46	41.94
8	4824.00	52.2 AV	54.0	-1.8	1.10 V	82	10.26	41.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2358.00	61.1 PK	74.0	-12.9	1.09 H	43	28.82	32.28
2	2358.00	52.9 AV	54.0	-1.1	1.09 H	43	20.62	32.28
3	*2437.00	109.4 PK			1.07 H	35	76.89	32.51
4	*2437.00	106.7 AV			1.07 H	35	74.19	32.51
5	4874.00	56.1 PK	74.0	-17.9	1.28 H	36	14.11	41.99
6	4874.00	46.5 AV	54.0	-7.5	1.28 H	36	4.51	41.99
7	7311.00	56.5 PK	74.0	-17.5	1.31 H	23	9.97	46.53
8	7311.00	46.9 AV	54.0	-7.1	1.31 H	23	0.37	46.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2358.00	58.4 PK	74.0	-15.6	1.04 V	60	26.12	32.28
2	2358.00	46.1 AV	54.0	-7.9	1.04 V	60	13.82	32.28
3	*2437.00	97.1 PK			1.00 V	65	64.59	32.51
4	*2437.00	94.1 AV			1.00 V	65	61.59	32.51
5	4874.00	56.5 PK	74.0	-17.5	1.05 V	81	14.51	41.99
6	4874.00	53.3 AV	54.0	-0.7	1.05 V	81	11.31	41.99
7	7311.00	58.3 PK	74.0	-15.7	1.00 V	67	11.77	46.53
8	7311.00	45.9 AV	54.0	-8.1	1.00 V	67	-0.63	46.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2380.00	61.7 PK	74.0	-12.3	1.12 H	41	29.35	32.35
2	2380.00	52.9 AV	54.0	-1.1	1.12 H	41	20.55	32.35
3	*2462.00	109.3 PK			1.08 H	42	76.73	32.57
4	*2462.00	106.7 AV			1.08 H	42	74.13	32.57
5	2483.50	60.8 PK	74.0	-13.2	1.08 H	42	28.17	32.63
6	2483.50	51.3 AV	54.0	-2.7	1.08 H	42	18.67	32.63
7	4924.00	56.1 PK	74.0	-17.9	1.30 H	39	14.09	42.01
8	4924.00	46.4 AV	54.0	-7.6	1.30 H	39	4.39	42.01
9	7386.00	57.0 PK	74.0	-17.0	1.35 H	32	10.27	46.73
10	7386.00	47.4 AV	54.0	-6.6	1.35 H	32	0.67	46.73
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2380.00	57.9 PK	74.0	-16.1	1.01 V	226	25.55	32.35
2	2380.00	44.9 AV	54.0	-9.1	1.01 V	226	12.55	32.35
3	*2462.00	96.6 PK			1.00 V	58	64.03	32.57
4	*2462.00	93.7 AV			1.00 V	58	61.13	32.57
5	2483.50	58.1 PK	74.0	-15.9	1.02 V	212	25.47	32.63
6	2483.50	45.2 AV	54.0	-8.8	1.02 V	212	12.57	32.63
7	4924.00	56.0 PK	74.0	-18.0	1.02 V	80	13.99	42.01
8	4924.00	52.9 AV	54.0	-1.1	1.02 V	80	10.89	42.01
9	7386.00	58.5 PK	74.0	-15.5	1.05 V	75	11.77	46.73
10	7386.00	45.9 AV	54.0	-8.1	1.05 V	75	-0.83	46.73

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2339.30	70.1 PK	74.0	-3.9	1.07 H	40	37.88	32.22
2	2339.30	53.1 AV	54.0	-0.9	1.07 H	40	20.88	32.22
3	*2412.00	110.5 PK			1.07 H	40	78.06	32.44
4	*2412.00	99.6 AV			1.07 H	40	67.16	32.44
5	2489.00	63.8 PK	74.0	-10.2	1.05 H	43	31.16	32.64
6	2489.00	52.8 AV	54.0	-1.2	1.05 H	43	20.16	32.64
7	4824.00	55.4 PK	74.0	-18.6	1.28 H	34	13.46	41.94
8	4824.00	46.0 AV	54.0	-8.0	1.28 H	34	4.06	41.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2339.30	57.6 PK	74.0	-16.4	1.00 V	217	25.38	32.22
2	2339.30	44.9 AV	54.0	-9.1	1.00 V	217	12.68	32.22
3	*2412.00	95.3 PK			1.00 V	288	62.86	32.44
4	*2412.00	85.0 AV			1.00 V	288	52.56	32.44
5	2489.00	57.8 PK	74.0	-16.2	1.00 V	222	25.16	32.64
6	2489.00	44.5 AV	54.0	-9.5	1.00 V	222	11.86	32.64
7	4824.00	57.0 PK	74.0	-17.0	1.00 V	101	15.06	41.94
8	4824.00	40.1 AV	54.0	-13.9	1.00 V	101	-1.84	41.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2384.00	64.3 PK	74.0	-9.7	1.09 H	41	31.94	32.36
2	2384.00	53.5 AV	54.0	-0.5	1.09 H	41	21.14	32.36
3	*2437.00	108.4 PK			1.08 H	41	75.89	32.51
4	*2437.00	98.9 AV			1.08 H	41	66.39	32.51
5	2489.30	63.7 PK	74.0	-10.3	1.05 H	42	31.06	32.64
6	2489.30	53.4 AV	54.0	-0.6	1.05 H	42	20.76	32.64
7	4874.00	55.7 PK	74.0	-18.3	1.34 H	42	13.71	41.99
8	4874.00	46.2 AV	54.0	-7.8	1.34 H	42	4.21	41.99
9	7311.00	56.7 PK	74.0	-17.3	1.36 H	29	10.17	46.53
10	7311.00	46.9 AV	54.0	-7.1	1.36 H	29	0.37	46.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2364.10	57.8 PK	74.0	-16.2	1.00 V	216	25.50	32.30
2	2364.10	45.0 AV	54.0	-9.0	1.00 V	216	12.70	32.30
3	*2437.00	95.4 PK			1.00 V	295	62.89	32.51
4	*2437.00	85.1 AV			1.00 V	295	52.59	32.51
5	2489.30	57.8 PK	74.0	-16.2	1.00 V	231	25.16	32.64
6	2489.30	44.7 AV	54.0	-9.3	1.00 V	231	12.06	32.64
7	4874.00	57.0 PK	74.0	-17.0	1.00 V	95	15.01	41.99
8	4874.00	40.0 AV	54.0	-14.0	1.00 V	95	-1.99	41.99
9	7311.00	57.9 PK	74.0	-16.1	1.01 V	75	11.37	46.53
10	7311.00	45.6 AV	54.0	-8.4	1.01 V	75	-0.93	46.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.17	61.8 PK	74.0	-12.2	1.11 H	40	29.44	32.36
2	2383.17	50.2 AV	54.0	-3.8	1.11 H	40	17.84	32.36
3	*2462.00	108.2 PK			1.07 H	41	75.63	32.57
4	*2462.00	97.5 AV			1.07 H	41	64.93	32.57
5	2483.50	73.4 PK	74.0	-0.6	1.07 H	41	40.77	32.63
6	2483.50	53.1 AV	54.0	-0.9	1.07 H	41	20.47	32.63
7	4924.00	56.3 PK	74.0	-17.7	1.34 H	24	14.29	42.01
8	4924.00	46.6 AV	54.0	-7.4	1.34 H	24	4.59	42.01
9	7386.00	56.7 PK	74.0	-17.3	1.39 H	44	9.97	46.73
10	7386.00	47.2 AV	54.0	-6.8	1.39 H	44	0.47	46.73
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.17	57.5 PK	74.0	-16.5	1.06 V	213	25.14	32.36
2	2383.17	44.3 AV	54.0	-9.7	1.06 V	213	11.94	32.36
3	*2462.00	95.5 PK			1.05 V	298	62.93	32.57
4	*2462.00	85.2 AV			1.05 V	298	52.63	32.57
5	2483.50	58.0 PK	74.0	-16.0	1.06 V	201	25.37	32.63
6	2483.50	45.3 AV	54.0	-8.7	1.06 V	201	12.67	32.63
7	4924.00	57.6 PK	74.0	-16.4	1.01 V	93	15.59	42.01
8	4924.00	40.4 AV	54.0	-13.6	1.01 V	93	-1.61	42.01
9	7386.00	57.7 PK	74.0	-16.3	1.00 V	78	10.97	46.73
10	7386.00	45.4 AV	54.0	-8.6	1.00 V	78	-1.33	46.73

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.8 PK	74.0	-5.2	1.09 H	4	36.42	32.38
2	2390.00	53.1 AV	54.0	-0.9	1.09 H	4	20.72	32.38
3	*2412.00	110.1 PK			1.09 H	4	77.66	32.44
4	*2412.00	99.3 AV			1.09 H	4	66.86	32.44
5	2488.80	62.6 PK	74.0	-11.4	1.30 H	69	29.96	32.64
6	2488.80	51.9 AV	54.0	-2.1	1.30 H	69	19.26	32.64
7	4824.00	56.7 PK	74.0	-17.3	1.38 H	8	14.76	41.94
8	4824.00	46.9 AV	54.0	-7.1	1.38 H	8	4.96	41.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2339.47	57.5 PK	74.0	-16.5	1.05 V	206	25.28	32.22
2	2339.47	45.1 AV	54.0	-8.9	1.05 V	206	12.88	32.22
3	*2412.00	100.0 PK			1.03 V	63	67.56	32.44
4	*2412.00	88.1 AV			1.03 V	63	55.66	32.44
5	2488.80	57.4 PK	74.0	-16.6	1.03 V	197	24.76	32.64
6	2488.80	44.2 AV	54.0	-9.8	1.03 V	197	11.56	32.64
7	4824.00	57.4 PK	74.0	-16.6	1.07 V	80	15.46	41.94
8	4824.00	40.1 AV	54.0	-13.9	1.07 V	80	-1.84	41.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2362.30	65.5 PK	74.0	-8.5	1.11 H	4	33.21	32.29
2	2362.30	53.3 AV	54.0	-0.7	1.11 H	4	21.01	32.29
3	*2437.00	111.2 PK			1.11 H	4	78.69	32.51
4	*2437.00	99.8 AV			1.11 H	4	67.29	32.51
5	2488.70	64.1 PK	74.0	-9.9	1.11 H	4	31.46	32.64
6	2488.70	51.7 AV	54.0	-2.3	1.11 H	4	19.06	32.64
7	4874.00	56.2 PK	74.0	-17.8	1.32 H	13	14.21	41.99
8	4874.00	46.3 AV	54.0	-7.7	1.32 H	13	4.31	41.99
9	7311.00	56.4 PK	74.0	-17.6	1.34 H	41	9.87	46.53
10	7311.00	46.9 AV	54.0	-7.1	1.34 H	41	0.37	46.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2362.30	58.3 PK	74.0	-15.7	1.10 V	210	26.01	32.29
2	2362.30	45.6 AV	54.0	-8.4	1.10 V	210	13.31	32.29
3	*2437.00	100.3 PK			1.00 V	67	67.79	32.51
4	*2437.00	89.1 AV			1.00 V	67	56.59	32.51
5	2488.70	57.5 PK	74.0	-16.5	1.04 V	203	24.86	32.64
6	2488.70	44.5 AV	54.0	-9.5	1.04 V	203	11.86	32.64
7	4874.00	58.0 PK	74.0	-16.0	1.00 V	98	16.01	41.99
8	4874.00	40.8 AV	54.0	-13.2	1.00 V	98	-1.19	41.99
9	7311.00	57.9 PK	74.0	-16.1	1.00 V	80	11.37	46.53
10	7311.00	45.6 AV	54.0	-8.4	1.00 V	80	-0.93	46.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.50	63.2 PK	74.0	-10.8	1.10 H	32	30.84	32.36
2	2383.50	51.3 AV	54.0	-2.7	1.10 H	32	18.94	32.36
3	*2462.00	110.1 PK			1.08 H	4	77.53	32.57
4	*2462.00	99.2 AV			1.08 H	4	66.63	32.57
5	2483.50	73.4 PK	74.0	-0.6	1.08 H	4	40.77	32.63
6	2483.50	52.2 AV	54.0	-1.8	1.08 H	4	19.57	32.63
7	4924.00	56.8 PK	74.0	-17.2	1.37 H	23	14.79	42.01
8	4924.00	46.7 AV	54.0	-7.3	1.37 H	23	4.69	42.01
9	7386.00	56.4 PK	74.0	-17.6	1.28 H	52	9.67	46.73
10	7386.00	46.9 AV	54.0	-7.1	1.28 H	52	0.17	46.73
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.50	57.9 PK	74.0	-16.1	1.06 V	193	25.54	32.36
2	2383.50	44.6 AV	54.0	-9.4	1.06 V	193	12.24	32.36
3	*2462.00	100.3 PK			1.00 V	66	67.73	32.57
4	*2462.00	88.5 AV			1.00 V	66	55.93	32.57
5	2483.50	57.7 PK	74.0	-16.3	1.02 V	220	25.07	32.63
6	2483.50	45.5 AV	54.0	-8.5	1.02 V	220	12.87	32.63
7	4924.00	57.8 PK	74.0	-16.2	1.05 V	106	15.79	42.01
8	4924.00	40.5 AV	54.0	-13.5	1.05 V	106	-1.51	42.01
9	7386.00	57.6 PK	74.0	-16.4	1.00 V	71	10.87	46.73
10	7386.00	45.3 AV	54.0	-8.7	1.00 V	71	-1.43	46.73

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.6 PK	74.0	-3.4	1.07 H	356	38.22	32.38
2	2390.00	53.4 AV	54.0	-0.6	1.07 H	356	21.02	32.38
3	*2422.00	104.5 PK			1.07 H	356	72.03	32.47
4	*2422.00	93.1 AV			1.07 H	356	60.63	32.47
5	4844.00	56.6 PK	74.0	-17.4	1.40 H	10	14.64	41.96
6	4844.00	46.6 AV	54.0	-7.4	1.40 H	10	4.64	41.96
7	7266.00	55.9 PK	74.0	-18.1	1.30 H	56	9.50	46.40
8	7266.00	46.7 AV	54.0	-7.3	1.30 H	56	0.30	46.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	1.00 V	220	25.42	32.38
2	2390.00	45.6 AV	54.0	-8.4	1.00 V	220	13.22	32.38
3	*2422.00	96.2 PK			1.00 V	81	63.73	32.47
4	*2422.00	83.9 AV			1.00 V	81	51.43	32.47
5	4844.00	57.3 PK	74.0	-16.7	1.05 V	105	15.34	41.96
6	4844.00	40.2 AV	54.0	-13.8	1.05 V	105	-1.76	41.96
7	7266.00	57.8 PK	74.0	-16.2	1.00 V	68	11.40	46.40
8	7266.00	45.6 AV	54.0	-8.4	1.00 V	68	-0.80	46.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.1 PK	74.0	-4.9	1.12 H	4	36.72	32.38
2	2390.00	53.1 AV	54.0	-0.9	1.12 H	4	20.72	32.38
3	*2437.00	105.0 PK			1.10 H	7	72.49	32.51
4	*2437.00	93.6 AV			1.10 H	7	61.09	32.51
5	2483.50	72.4 PK	74.0	-1.6	1.02 H	46	39.77	32.63
6	2483.50	52.3 AV	54.0	-1.7	1.02 H	46	19.67	32.63
7	4874.00	56.9 PK	74.0	-17.1	1.36 H	20	14.91	41.99
8	4874.00	46.9 AV	54.0	-7.1	1.36 H	20	4.91	41.99
9	7311.00	56.0 PK	74.0	-18.0	1.30 H	64	9.47	46.53
10	7311.00	46.7 AV	54.0	-7.3	1.30 H	64	0.17	46.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2341.80	57.7 PK	74.0	-16.3	1.00 V	230	25.48	32.22
2	2341.80	45.6 AV	54.0	-8.4	1.00 V	230	13.38	32.22
3	*2437.00	96.0 PK			1.00 V	67	63.49	32.51
4	*2437.00	83.7 AV			1.00 V	67	51.19	32.51
5	2483.50	57.6 PK	74.0	-16.4	1.07 V	189	24.97	32.63
6	2483.50	44.4 AV	54.0	-9.6	1.07 V	189	11.77	32.63
7	4874.00	57.5 PK	74.0	-16.5	1.08 V	108	15.51	41.99
8	4874.00	40.4 AV	54.0	-13.6	1.08 V	108	-1.59	41.99
9	7311.00	57.9 PK	74.0	-16.1	1.00 V	83	11.37	46.53
10	7311.00	45.8 AV	54.0	-8.2	1.00 V	83	-0.73	46.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2356.80	62.6 PK	74.0	-11.4	1.32 H	67	30.33	32.27
2	2356.80	51.5 AV	54.0	-2.5	1.32 H	67	19.23	32.27
3	*2452.00	104.5 PK			1.12 H	2	71.95	32.55
4	*2452.00	93.4 AV			1.12 H	2	60.85	32.55
5	2483.50	73.5 PK	74.0	-0.5	1.12 H	2	40.87	32.63
6	2483.50	52.8 AV	54.0	-1.2	1.12 H	2	20.17	32.63
7	4904.00	57.4 PK	74.0	-16.6	1.41 H	20	15.38	42.02
8	4904.00	47.1 AV	54.0	-6.9	1.41 H	20	5.08	42.02
9	7356.00	56.6 PK	74.0	-17.4	1.25 H	60	9.95	46.65
10	7356.00	47.0 AV	54.0	-7.0	1.25 H	60	0.35	46.65
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2356.80	58.1 PK	74.0	-15.9	1.10 V	206	25.83	32.27
2	2356.80	44.7 AV	54.0	-9.3	1.10 V	206	12.43	32.27
3	*2452.00	95.9 PK			1.00 V	94	63.35	32.55
4	*2452.00	83.4 AV			1.00 V	94	50.85	32.55
5	2483.50	58.0 PK	74.0	-16.0	1.00 V	227	25.37	32.63
6	2483.50	45.8 AV	54.0	-8.2	1.00 V	227	13.17	32.63
7	4904.00	57.8 PK	74.0	-16.2	1.04 V	99	15.78	42.02
8	4904.00	40.8 AV	54.0	-13.2	1.04 V	99	-1.22	42.02
9	7356.00	58.2 PK	74.0	-15.8	1.00 V	84	11.55	46.65
10	7356.00	46.1 AV	54.0	-7.9	1.00 V	84	-0.55	46.65

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100060	May 09, 2012	May 10, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Dec. 20, 2012


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	10.24	0.5	PASS
6	2437	9.76	0.5	PASS
11	2462	9.77	0.5	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.40	0.5	PASS
6	2437	16.37	0.5	PASS
11	2462	16.40	0.5	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	17.08	17.09	0.5	PASS
6	2437	17.02	17.05	0.5	PASS
11	2462	17.06	17.04	0.5	PASS

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
3	2422	35.67	35.81	0.5	PASS
6	2437	35.62	35.61	0.5	PASS
9	2452	35.75	36.01	0.5	PASS

4.4 CONDUCTED OUTPUT POWER MEASUREMENT

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v01r02 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $NANT \leq 4$;
Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;
Array Gain = $5 \log(NANT/NSS)$ dB or 3 dB, whichever is less for 20-MHz channel widths with $NANT \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(NANT/NSS)$ dB.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 10, 2012	May 09, 2013
Peak Power Sensor	MA2411B	0738172	May 10, 2012	May 09, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Dec. 20, 2012


4.4.3 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	173.780	22.4	30	PASS
6	2437	208.930	23.2	30	PASS
11	2462	114.815	20.6	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	257.040	24.1	30	PASS
6	2437	363.078	25.6	30	PASS
11	2462	263.027	24.2	30	PASS

802.11n (HT20)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	24.2	24.0	514.216	27.11	30	PASS
6	2437	24.3	24.1	526.193	27.21	30	PASS
11	2462	24.2	23.7	497.450	26.97	30	PASS

802.11n (HT40)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
3	2422	20.3	19.6	198.353	22.97	30	PASS
6	2437	24.2	25.1	586.621	27.68	30	PASS
9	2452	19.7	20.1	195.654	22.91	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100060	May 09, 2012	May 10, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Dec. 20, 2012


4.5.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-3.98	8	PASS
6	2437	-3.24	8	PASS
11	2462	-5.18	8	PASS

802.11g

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-12.10	8	PASS
6	2437	-11.23	8	PASS
11	2462	-13.33	8	PASS

802.11n (HT20)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-10.14	3.01	-7.13	8	PASS
	6	2437	-13.02	3.01	-10.01	8	PASS
	11	2462	-13.57	3.01	-10.56	8	PASS
1	1	2412	-11.55	3.01	-8.54	8	PASS
	6	2437	-12.58	3.01	-9.57	8	PASS
	11	2462	-13.94	3.01	-10.93	8	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.81\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11n (HT40)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	3	2422	-18.83	3.01	-15.82	8	PASS
	6	2437	-13.76	3.01	-10.75	8	PASS
	9	2452	-18.98	3.01	-15.97	8	PASS
1	3	2422	-18.74	3.01	-15.73	8	PASS
	6	2437	-14.67	3.01	-11.66	8	PASS
	9	2452	-18.03	3.01	-15.02	8	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.81\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.



A D T

4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100060	May 09, 2012	May 10, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Dec. 20, 2012

4.6.3 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

802.11b


CH 1



CH 6



CH 11









A D T

802.11g



CH 1



CH 6



CH 11







A D T



802.11n (HT20)

Chain 0



CH 1



CH 6



CH 11









A D T

Chain 1



CH 1



CH 6



CH 11







A D T



802.11n (HT40)

Chain 0



CH 3



CH 6




CH 9






A D T


Chain 1 CH 3



CH 6



CH 9



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---