



RF EXPOSURE REPORT

REPORT NO.: SA970807L10

MODEL NO.: WET610N

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Cisco-Linksys LLC

ADDRESS: 121 Theory Drive Irvine, CA 92617 (USA)

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.



RF EXPOSURE MEASUREMENT (MOBILE DEVICE)

1. INTRODUCTION

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF EXPOSURE LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
(A)LIMITS FOR OCCUPATIONAL / CONTROL EXPOSURES				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz



3. FRIIS FORMULA

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance r .

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4. EUT OPERATING CONDITION

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**.



6. TEST RESULTS

6.1 ANTENNA GAIN

The maximum Gain measured in Fully Anechoic Chamber is 1.0dBi or 1.2589 (numeric)(2.4GHz) & 1.28dBi or 1.3428 (numeric)(5.0GHz).

6.2 OUTPUT POWER INTO ANTENNA & RF EXPOSURE VALUE AT DISTANCE 20cm:

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER OUTPUT (mW)	POWER DENSITY (mW/cm ²)	LIMIT OF POWER DENSITY (mW/cm ²)
1	2412	21.11	129.122	0.032	1.0
6	2437	21.09	128.529	0.032	1.0
11	2462	21.05	127.350	0.032	1.0

802.11g OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
1	2412	22.06	22.11	322.130	25.08	0.081	1.000
6	2437	22.08	22.11	342.857	25.35	0.086	1.000
11	2462	22.56	22.0	323.619	25.10	0.081	1.000

DRAFT 802.11n (20MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
1	2412	19.05	19.09	161.449	22.08	0.040	1.000
6	2437	19.09	19.08	162.006	22.10	0.041	1.000
11	2462	19.03	19.03	159.967	22.04	0.040	1.000

DRAFT 802.11n (40MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
1	2422	19.04	19.11	161.638	22.09	0.040	1.000
4	2437	19.59	19.62	182.613	22.62	0.046	1.000
7	2452	19.06	19.07	161.261	22.08	0.040	1.000

**802.11a OFDM MODULATION:**

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
36	5180	11.11	11.08	25.735	14.11	0.007	1.000
40	5200	11.54	11.05	26.991	14.31	0.007	1.000
48	5240	11.07	11.09	25.647	14.09	0.007	1.000
52	5260	11.10	11.11	25.795	14.12	0.007	1.000
60	5300	9.63	10.63	20.744	13.17	0.006	1.000
64	5320	11.05	11.03	25.412	14.05	0.007	1.000
100	5500	11.06	11.15	25.796	14.12	0.007	1.000
120	5600	11.10	11.10	25.765	14.11	0.007	1.000
140	5700	10.56	10.01	21.399	13.30	0.006	1.000
149	5745	22.11	22.03	322.143	25.08	0.086	1.000
157	5785	22.03	22.04	319.544	25.05	0.085	1.000
165	5825	22.07	22.13	324.370	25.11	0.087	1.000

DRAFT 802.11n (20MHz) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)	LIMIT OF POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
36	5180	9.58	9.59	18.177	12.60	0.005	1.000
40	5200	10.06	9.52	19.093	12.81	0.005	1.000
48	5240	9.54	9.56	18.031	12.56	0.005	1.000
52	5260	9.53	9.63	18.158	12.59	0.005	1.000
60	5300	9.07	9.02	16.052	12.06	0.004	1.000
64	5320	9.60	9.55	18.136	12.59	0.005	1.000
100	5500	9.15	9.53	17.197	12.35	0.005	1.000
120	5600	9.58	9.53	18.052	12.57	0.005	1.000
140	5700	10.07	9.59	19.262	12.85	0.005	1.000
149	5745	20.56	20.53	226.742	23.56	0.061	1.000
157	5785	20.54	20.13	216.279	23.35	0.058	1.000
165	5825	20.60	20.56	228.578	23.59	0.061	1.000


DRAFT 802.11N (40MHZ) OFDM MODULATION:

CHAN.	CHAN. FREQ. (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	POWER DENSITY (mW/CM ²)
		CHAIN 0	CHAIN 1				
38	5190	9.04	9.10	16.145	12.08	0.004	1.000
46	5230	9.08	9.13	16.276	12.12	0.004	1.000
54	5270	9.51	9.53	17.907	12.53	0.005	1.000
62	5310	9.13	9.07	16.257	12.11	0.004	1.000
102	5510	9.08	9.07	17.197	12.35	0.004	1.000
118	5590	10.11	9.11	18.052	12.57	0.005	1.000
134	5670	9.09	10.14	19.262	12.85	0.005	1.000
151	5755	19.54	19.58	180.732	22.57	0.048	1.000
159	5795	19.55	19.57	180.730	22.57	0.048	1.000