



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Linksys LLC
Applicant Address	131 Theory Drive, Irvine Ca., 92617
FCC ID	Q87-WUSB6300
Manufacturer's company	Linksys LLC
Manufacturer Address	131 Theory Drive, Irvine Ca., 92617

Product Name	Linksys Dual Band Wireless-AC USB Adapter
Brand Name	Linksys
Model Name	WUSB6300
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Nov. 01, 2012
Final Test Date	May 29, 2013
Submission Type	Original Equipment

Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a/ac (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009**,

47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03 and KDB 662911 D01 v01r02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE.....	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION.....	3
3.1. Product Details	3
3.2. Accessories	6
3.3. Table for Filed Antenna	7
3.4. Table for Carrier Frequencies	8
3.5. Table for Test Modes	9
3.6. Table for Testing Locations.....	11
3.7. Table for Supporting Units	11
3.8. Table for Parameters of Test Software Setting	11
3.9. Test Configurations.....	13
4. TEST RESULT.....	15
4.1. AC Power Line Conducted Emissions Measurement	15
4.2. Maximum Conducted Output Power Measurement.....	19
4.3. Power Spectral Density Measurement.....	22
4.4. 6dB Spectrum Bandwidth Measurement	31
4.5. Radiated Emissions Measurement.....	41
4.6. Band Edge Emissions Measurement.....	73
4.7. Antenna Requirements	93
5. LIST OF MEASURING EQUIPMENTS	94
6. TEST LOCATION.....	96
APPENDIX A. TEST PHOTOS.....	A1 ~ A5


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR2N0801-01AB	Rev. 01	Initial issue of report	May 31, 2013

1. CERTIFICATE OF COMPLIANCE

Product Name : Linksys Dual Band Wireless-AC USB Adapter
Brand Name : Linksys
Model Name : WUSB6300
Applicant : Linksys LLC
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 01, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	7.19 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	8.05 dB
4.3	15.247(e)	Power Spectral Density	Complies	10.68 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.17 dB
4.6	15.247(d)	Band Edge Emissions	Complies	1.00 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1GHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth ; 1 for 80MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS8 (20MHz): 17.76 MHz ; MCS8 (40MHz): 36.32 MHz For 5GHz Band: MCS8 (20MHz): 23.68 MHz ; MCS8 (40MHz): 42.24 MHz ; MCS8 (80MHz): 84.48 MHz
Maximum Conducted Output Power	For 2.4GHz Band: MCS8 (20MHz): 18.86 dBm ; MCS8 (40MHz): 18.38 dBm For 5GHz Band: MCS8 (VHT 20MHz): 21.87 dBm ; MCS8 (VHT 40MHz): 21.14 dBm ; MCS8 (VHT 80MHz): 21.29 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11a/b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 14.88 MHz ; 11g: 18.00 MHz ; 11a: 28.24 MHz
Maximum Conducted Output Power	11b: 17.30 dBm ; 11g: 16.60 dBm ; 11a: 15.79 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)			Two (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X	X	X	X
IEEE 802.11b	V	X	X	X	X	X
IEEE 802.11g	X	X	X	V	X	X
IEEE 802.11n	X	X	X	V	V	X
IEEE 802.11ac	X	X	X	V	V	V

IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

IEEE 802. 11a, 11n and 11ac Spec.

Worst Modulation Used for Conformance Testing				
Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS	Worst Data Rate / MCS	Worst Modulation Mode
802.11a	1	6-54 Mbps	6Mbps	11A5.8G-20M
802.11n 20MHz	2	MCS 0-15	MCS 8	11N5.8G-20M
802.11n 40MHz	2	MCS 0-15	MCS 8	11N5.8G-40M
802.11ac 20MHz	2	MCS 0-9	MCS 0-Nss2	11AC5.8G-20M
802.11ac 40MHz	2	MCS 0-9	MCS 0-Nss2	11AC5.8G-40M
802.11ac 80MHz	2	MCS 0-9	MCS 0-Nss2	11AC5.8G-80M
Note 1: IEEE 802.11 modulation consists of IEEE 802.11a.				
Note 2: IEEE 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Worst modulation mode of Guard Interval (GI) is 400ns.				
Note 3: IEEE 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160. Then EUT support VHT20, VHT40, VHT80. (VHT: Very High Throughput).				
20M/40M/80M: Channel Bandwidth 20MHz/40MHz/80MHz				

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)		
					2.4GHz	5GHz	
1	SERCOMM	AC-950	Printed Antenna	I-PEX	2.31	Band 1	3.84
						Band 4	4.15
2	SERCOMM	AC-950	Printed Antenna	I-PEX	1.72	Band 1	4.29
						Band 4	3.07

Note: The EUT has two antennas

For 2.4GHz Band:

For IEEE 802.11b/g mode (1TX/1RX):

It fixed Ant. 2 as transmitting and receiving antenna.

For IEEE 802.11n mode (2TX/2RX):

Ant. 1 and Ant. 2 could transmit / receive simultaneously.


For 5GHz Band:

For IEEE 802.11a mode (1TX/1RX):

It fixed Ant. 2 as transmitting and receiving antenna.

For IEEE 802.11n/ac mode (2TX/2RX):

Ant. 1 and Ant. 2 could transmit / receive simultaneously.



3.4. Table for Carrier Frequencies

For 2.4GHz Band:

There are two bandwidth systems.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	Auto	-	-
Maximum Conducted Output Power	MCS8/20MHz	15 Mbps	1/6/11	1+2
	MCS8/40MHz	30 Mbps	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	2
	11g/BPSK	6 Mbps	1/6/11	2
Power Spectral Density	MCS8/20MHz	15 Mbps	1/6/11	1 and 2
	MCS8/40MHz	30 Mbps	3/6/9	1 and 2
	11b/CCK	1 Mbps	1/6/11	2
	11g/BPSK	6 Mbps	1/6/11	2
6dB Spectrum Bandwidth	MCS8/20MHz	15 Mbps	1/6/11	1+2
	MCS8/40MHz	30 Mbps	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	2
	11g/BPSK	6 Mbps	1/6/11	2
Radiated Emissions Below 1GHz	CTX	Auto	-	-
Radiated Emissions Above 1GHz	MCS8/20MHz	15 Mbps	1/6/11	1+2
	MCS8/40MHz	30 Mbps	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	2
	11g/BPSK	6 Mbps	1/6/11	2
Band Edge Emissions	MCS8/20MHz	15 Mbps	1/6/11	1+2
	MCS8/40MHz	30 Mbps	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	2
	11g/BPSK	6 Mbps	1/6/11	2

For 5GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	Auto	-	-
Maximum Conducted Output Power	11n 20MHz	15 Mbps	149/157/165	1+2
	11n 40MHz	30 Mbps	151/159	1+2
	11ac 20MHz	Nss2	155	1+2
	11ac 40MHz	Nss2	149/157/165	1+2
	11ac 80MHz	Nss2	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	2
Power Spectral Density	11n 20MHz	15 Mbps	149/157/165	1 and 2
	11n 40MHz	30 Mbps	151/159	1 and 2
	11ac 80MHz	Nss2	155	1 and 2
	11a/BPSK	6 Mbps	149/157/165	2
6dB Spectrum Bandwidth	11n 20MHz	15 Mbps	149/157/165	1+2
	11n 40MHz	30 Mbps	151/159	1+2
	11ac 80MHz	Nss2	155	1+2
	11a/BPSK	6 Mbps	149/157/165	2
Radiated Emissions Below 1GHz	CTX	Auto	-	-
Radiated Emissions Above 1GHz	11n 20MHz	15 Mbps	149/157/165	1+2
	11n 40MHz	30 Mbps	151/159	1+2
	11ac 80MHz	Nss2	155	1+2
	11a/BPSK	6 Mbps	149/157/165	2
Band Edge Emissions	11n 20MHz	15 Mbps	149/157/165	1+2
	11n 40MHz	30 Mbps	151/159	1+2
	11ac 20MHz	Nss2	149/157/165	1+2
	11ac 40MHz	Nss2	151/159	1+2
	11ac 80MHz	Nss2	155	1+2
	11a/BPSK	6 Mbps	149/157/165	2

The following test modes were performed for all tests:

For Radiated Emission test:

Mode 1: EUT in X-axis

Mode 2: EUT in Y-axis

Mode 3: EUT in Z-axis

Mode 1 generated the worst test result, so it was recorded in this report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	1340	E2K4965AGNM

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For 2.4GHz Band

Power Parameters of IEEE 802.11n MCS8 20MHz

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS8 20MHz	46/46	46/47	47/49

Power Parameters of IEEE 802.11n MCS8 40MHz

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS8 40MHz	46/46	46/47	47/48

Power Parameters of IEEE 802.11b/g

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	36	37	38
IEEE 802.11g	47	48	49

For 5GHz Band

Power Parameters of IEEE 802.11ac MCS8 20MHz

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS8 20MHz	48/52	48/52	48/52

Power Parameters of IEEE 802.11ac MCS8 40MHz

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102	
Frequency	5755 MHz	5795 MHz
MCS8 40MHz	48/52	48/52

Power Parameters of IEEE 802.11ac MCS8 80MHz

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102	
Frequency	5775 MHz	
MCS8 80MHz	48/52	


Power Parameters of IEEE 802.11a

Test Software Version	Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	40	41	42

During the test, "Realtek 11ac 8812A USB WLAN MP Diagnostic Program 0.0027.20121102" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.


3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration



Item	Connection	Shield	Length	Remark
1	Power cable	No	2.6m	-
2	USB cable	No	1.8m	-

3.9.2. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length	Remark
1	Power cable	No	2.6m	-
2	USB cable	No	1.8m	-

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	58%
Test Engineer	Sollo Luo	Phase	Line
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.17678	57.45	-7.19	64.64	57.10	0.15	0.20	LINE	QP
2	0.17678	41.81	-12.83	54.64	41.46	0.15	0.20	LINE	AVERAGE
3	0.18739	56.49	-7.66	64.15	56.14	0.15	0.20	LINE	QP
4	0.18739	41.48	-12.67	54.15	41.13	0.15	0.20	LINE	AVERAGE
5	0.23910	49.66	-12.47	62.13	49.31	0.15	0.20	LINE	QP
6	0.23910	35.76	-16.37	52.13	35.41	0.15	0.20	LINE	AVERAGE
7	0.25211	44.50	-17.19	61.69	44.15	0.15	0.20	LINE	QP
8	0.25211	28.19	-23.50	51.69	27.84	0.15	0.20	LINE	AVERAGE
9	0.29712	42.23	-18.09	60.32	41.88	0.15	0.20	LINE	QP
10	0.29712	28.20	-22.12	50.32	27.85	0.15	0.20	LINE	AVERAGE
11	0.30509	40.73	-19.37	60.10	40.38	0.15	0.20	LINE	QP
12	0.30509	29.01	-21.09	50.10	28.66	0.15	0.20	LINE	AVERAGE
13	3.436	29.49	-26.51	56.00	28.99	0.21	0.29	LINE	QP
14	3.436	22.78	-23.22	46.00	22.28	0.21	0.29	LINE	AVERAGE
15	14.986	38.03	-21.97	60.00	37.22	0.41	0.40	LINE	QP
16	14.986	28.05	-21.95	50.00	27.24	0.41	0.40	LINE	AVERAGE

Temperature	24°C	Humidity	58%
Test Engineer	Sollo Luo	Phase	Neutral
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.17772	56.02	-8.57	64.59	55.74	0.08	0.20	NEUTRAL	QP
2	0.17772	40.99	-13.60	54.59	40.71	0.08	0.20	NEUTRAL	AVERAGE
3	0.18249	55.47	-8.90	64.37	55.19	0.08	0.20	NEUTRAL	QP
4	0.18249	43.29	-11.08	54.37	43.01	0.08	0.20	NEUTRAL	AVERAGE
5	0.18541	55.37	-8.87	64.24	55.09	0.08	0.20	NEUTRAL	QP
6	0.18541	41.63	-12.61	54.24	41.35	0.08	0.20	NEUTRAL	AVERAGE
7	0.23784	33.63	-18.54	52.17	33.35	0.08	0.20	NEUTRAL	AVERAGE
8	0.23784	47.94	-14.23	62.17	47.66	0.08	0.20	NEUTRAL	QP
9	3.399	29.02	-26.98	56.00	28.61	0.12	0.28	NEUTRAL	QP
10	3.399	25.15	-20.85	46.00	24.74	0.12	0.28	NEUTRAL	AVERAGE
11	14.828	36.80	-23.20	60.00	36.09	0.31	0.40	NEUTRAL	QP
12	14.828	28.97	-21.03	50.00	28.26	0.31	0.40	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n/ac
Test Date	Nov. 24, 2012		

For 2.4GHz Band

Configuration IEEE 802.11n MCS8 20MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	15.36	15.47	18.43	30.00	Complies
6	2437 MHz	16.03	15.67	18.86	30.00	Complies
11	2462 MHz	15.71	15.73	18.73	30.00	Complies

Configuration IEEE 802.11n MCS8 40MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
3	2422 MHz	15.16	14.67	17.93	30.00	Complies
6	2437 MHz	15.18	14.63	17.92	30.00	Complies
9	2452 MHz	15.61	15.12	18.38	30.00	Complies

For 5GHz Band

Configuration IEEE 802.11ac MCS8 20MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
149	5745 MHz	19.32	18.20	21.81	30.00	Complies
157	5785 MHz	19.28	18.14	21.76	30.00	Complies
165	5825 MHz	19.35	18.30	21.87	30.00	Complies

Configuration IEEE 802.11ac MCS8 40MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
151	5755 MHz	18.79	17.34	21.14	30.00	Complies
159	5795 MHz	18.55	17.61	21.12	30.00	Complies

Configuration IEEE 802.11ac MCS8 80MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
155	5775 MHz	18.74	17.77	21.29	30.00	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11a/b/g
Test Date	Nov. 24, 2012		

Configuration IEEE 802.11b / Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.70	30.00	Complies
6	2437 MHz	17.00	30.00	Complies
11	2462 MHz	17.30	30.00	Complies

Configuration IEEE 802.11g / Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	15.72	30.00	Complies
6	2437 MHz	16.00	30.00	Complies
11	2462 MHz	16.60	30.00	Complies

Configuration IEEE 802.11a / Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	15.56	30.00	Complies
157	5785 MHz	15.79	30.00	Complies
165	5825 MHz	15.65	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add 10 log (NANT) dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
1	2412 MHz	-10.23	-10.76	4.99	Complies
6	2437 MHz	-10.17	-10.81	4.99	Complies
11	2462 MHz	-9.50	-9.90	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
3	2422 MHz	-14.33	-15.46	4.99	Complies
6	2437 MHz	-14.21	-14.73	4.99	Complies
9	2452 MHz	-13.47	-14.85	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

For 5GHz Band

Configuration IEEE 802.11ac MCS8 20MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
149	5745 MHz	-7.63	-6.93	4.99	Complies
157	5785 MHz	-8.08	-8.51	4.99	Complies
165	5825 MHz	-9.24	-8.78	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

Configuration IEEE 802.11ac MCS8 40MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
151	5755 MHz	-12.04	-13.17	4.99	Complies
159	5795 MHz	-12.40	-12.55	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

Configuration IEEE 802.11ac MCS8 80MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
155	5775 MHz	-5.69	-9.75	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

Temperature	23°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 2

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-12.73	8.00	Complies
6	2437 MHz	-11.88	8.00	Complies
11	2462 MHz	-11.32	8.00	Complies

Configuration IEEE 802.11g / Ant. 2

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-11.10	8.00	Complies
6	2437 MHz	-11.06	8.00	Complies
11	2462 MHz	-10.14	8.00	Complies


Configuration IEEE 802.11a / Ant. 2

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
149	5745 MHz	-10.00	8.00	Complies
157	5785 MHz	-9.53	8.00	Complies
165	5825 MHz	-9.09	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11n MCS8 20MHz / Ant. 1 / 2462 MHz



Date: 29.MAY.2013 04:23:03

Power Density Plot on Configuration IEEE 802.11n MCS8 40MHz / Ant. 1 / 2452 MHz



Date: 29.MAY.2013 04:31:52



Ref 20 dBm Att 30 dB RBW 3 kHz VEW 30 kHz SWT 3.4 s Marker 1 [T1] -6.93 dBm 5.738340000 GHz

20 Offset 1.0 dB

1 PK

MAXH

1

LVL

SDB

Center 5.745 GHz 3 MHz/ Span 30 MHz

Ref 20 dBm Att 30 dB REW 3 kHz VEW 30 kHz SWT 6.8 s Marker 1 [T1] -12.04 dBm 5.756320000 GHz

20 Offset 1.0 dB

1. PK
MAX

Center 5.755 GHz 6 MHz/ Span 60 MHz

Report Format Version: 01
FCC ID: Q87-WUSB6300



Ref 20 dBm Att 30 dB RBW 3 kHz VEW 30 kHz SWT 13.5 s Marker 1 [T1] -5.69 dBm 5.775000000 GHz

20 Offset 1.0 dB

1 PK MAX

Center 5.775 GHz 12 MHz/ Span 120 MHz

Ref 20 dBm *Att 30 dB *REW 3 kHz *VEW 30 kHz SWT 3.4 s Marker 1 [T1] -11.32 dBm 2.461280000 GHz


20 Offset 1.0 dB

1.00 dBm MAX

Center 2.462 GHz 3 MHz/ Span 30 MHz


Page No. : 29 of 96
Issued Date : May 31, 2013

Power Density Plot on Configuration IEEE 802.11g / Ant. 2 / 2462 MHz



Date: 29.MAY.2013 04:12:47

Power Density Plot on Configuration IEEE 802.11a / Ant. 2 / 5825 MHz



Date: 29.MAY.2013 04:35:51

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.4.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add $10 \log (\text{NANT})$ dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n/ac

For 2.4GHz Band

Configuration IEEE 802.11n MCS8 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.60	17.60	500	Complies
6	2437 MHz	17.36	17.76	500	Complies
11	2462 MHz	17.36	17.60	500	Complies

Configuration IEEE 802.11n MCS8 40MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.48	36.32	500	Complies
6	2437 MHz	36.48	36.32	500	Complies
9	2452 MHz	36.48	36.16	500	Complies

For 5GHz Band

Configuration IEEE 802.11ac MCS8 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.60	23.44	500	Complies
157	5785 MHz	17.52	23.68	500	Complies
165	5825 MHz	17.52	23.44	500	Complies

Configuration IEEE 802.11ac MCS8 40MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.48	42.08	500	Complies
159	5795 MHz	36.48	42.24	500	Complies

Configuration IEEE 802.11ac MCS8 80MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	74.56	84.48	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Robert Chang	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.08	14.88	500	Complies
6	2437 MHz	10.16	14.64	500	Complies
11	2462 MHz	10.08	14.80	500	Complies

Configuration IEEE 802.11g / Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.48	16.48	500	Complies
6	2437 MHz	16.40	18.00	500	Complies
11	2462 MHz	16.48	16.48	500	Complies


Configuration IEEE 802.11a / Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	28.16	500	Complies
157	5785 MHz	16.40	28.24	500	Complies
165	5825 MHz	16.40	27.28	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS8 20MHz / Ant. 1 + Ant. 2 / 2437 MHz




Date: 24.NOV.2012 13:37:17

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS8 40MHz / Ant. 1 + Ant. 2 / 2437 MHz




Date: 24.NOV.2012 13:44:27

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS8 20MHz / Ant. 1 + Ant. 2 / 5785MHz




Date: 24.NOV.2012 13:32:08

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS8 40MHz / Ant. 1 + Ant. 2 / 5795 MHz




Date: 24.NOV.2012 13:34:56

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS8 80MHz / Ant. 1 + Ant. 2 / 5775 MHz




Date: 24.NOV.2012 13:49:41

6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 2 / 2412 MHz




Date: 24.NOV.2012 13:17:28

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 2 / 2437 MHz



Date: 24.NOV.2012 13:20:39

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 2 / 5785 MHz



Date: 24.NOV.2012 13:23:24

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1GHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RB 120kHz for QP

4.5.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	CTX / Mode 1
Test Date	Nov. 23, 2012		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	CTX / Mode 1

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	30.97	32.83	40.00	-7.17	40.66	0.85	27.98	19.30	Peak	0	400	HORIZONTAL
2	139.61	32.14	43.50	-11.36	45.89	1.71	27.56	12.10	Peak	0	400	HORIZONTAL
3	189.08	31.61	43.50	-11.89	47.07	2.05	27.32	9.81	Peak	0	400	HORIZONTAL
4	232.73	31.68	46.00	-14.32	44.86	2.29	27.01	11.54	Peak	0	400	HORIZONTAL
5	687.66	31.88	46.00	-14.12	35.08	4.10	27.20	19.90	Peak	0	400	HORIZONTAL
6	866.14	33.28	46.00	-12.72	34.38	4.48	26.88	21.30	Peak	0	400	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	30.00	29.47	40.00	-10.53	36.71	0.83	27.97	19.90	Peak	0	100	VERTICAL
2	165.80	23.56	43.50	-19.94	38.63	1.92	27.41	10.42	Peak	0	100	VERTICAL
3	191.99	23.17	43.50	-20.33	38.49	2.06	27.30	9.92	Peak	0	100	VERTICAL
4	229.82	25.12	46.00	-20.88	38.57	2.28	27.03	11.30	Peak	0	100	VERTICAL
5	663.41	31.42	46.00	-14.58	35.17	3.97	27.43	19.71	Peak	0	100	VERTICAL
6	711.91	31.50	46.00	-14.50	34.37	4.17	27.09	20.05	Peak	0	100	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz Ch 1 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.32	32.14	54.00	-21.86	30.80	3.31	33.06	35.03	Average	100	247	HORIZONTAL
2	4823.35	45.48	74.00	-28.52	44.14	3.31	33.06	35.03	Peak	100	247	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.05	33.74	54.00	-20.26	32.40	3.31	33.06	35.03	Average	100	265	VERTICAL
2	4825.25	46.27	74.00	-27.73	44.93	3.31	33.06	35.03	Peak	100	265	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz Ch 6 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.11	41.16	74.00	-32.84	39.70	3.33	33.16	35.03	Peak	100	333	HORIZONTAL
2	4875.32	27.61	54.00	-26.39	26.15	3.33	33.16	35.03	Average	100	333	HORIZONTAL
3	7309.19	43.27	74.00	-30.73	38.65	4.06	35.96	35.40	Peak	100	170	HORIZONTAL
4	7312.57	30.04	54.00	-23.96	25.42	4.06	35.96	35.40	Average	100	170	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4872.61	51.53	74.00	-22.47	50.07	3.33	33.16	35.03	Peak	100	266	VERTICAL
2	4874.84	40.28	54.00	-13.72	38.82	3.33	33.16	35.03	Average	100	266	VERTICAL
3	7310.47	29.99	54.00	-24.01	25.37	4.06	35.96	35.40	Average	100	217	VERTICAL
4	7310.80	42.83	74.00	-31.17	38.21	4.06	35.96	35.40	Peak	100	217	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz Ch11 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4922.05	28.82	54.00	-25.18	27.22	3.35	33.26	35.01	Average	100	14	HORIZONTAL
2	4922.13	41.11	74.00	-32.89	39.51	3.35	33.26	35.01	Peak	100	14	HORIZONTAL
3	7384.28	44.48	74.00	-29.52	39.73	4.06	36.09	35.40	Peak	100	135	HORIZONTAL
4	7386.41	31.38	54.00	-22.62	26.63	4.06	36.09	35.40	Average	100	135	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4922.45	40.53	74.00	-33.47	38.93	3.35	33.26	35.01	Peak	100	250	VERTICAL
2	4923.63	32.62	54.00	-21.38	31.02	3.35	33.26	35.01	Average	100	250	VERTICAL
3	7383.62	44.77	74.00	-29.23	40.02	4.06	36.09	35.40	Peak	100	165	VERTICAL
4	7384.43	31.47	54.00	-22.53	26.72	4.06	36.09	35.40	Average	100	165	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 40MHz Ch 3 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4822.09	28.71	54.00	-25.29	27.37	3.31	33.06	35.03	Average	100	332	HORIZONTAL
2	4822.96	41.94	74.00	-32.06	40.60	3.31	33.06	35.03	Peak	100	332	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.29	41.03	74.00	-32.97	39.69	3.31	33.06	35.03	Peak	100	259	VERTICAL
2	4825.76	29.54	54.00	-24.46	28.20	3.31	33.06	35.03	Average	100	259	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 40MHz Ch 6 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4875.57	45.05	74.00	-28.95	43.59	3.33	33.16	35.03	Peak	100	248	HORIZONTAL
2	4876.05	31.08	54.00	-22.92	29.62	3.33	33.16	35.03	Average	100	248	HORIZONTAL
3	7309.44	43.31	74.00	-30.69	38.69	4.06	35.96	35.40	Peak	100	121	HORIZONTAL
4	7310.43	30.64	54.00	-23.36	26.02	4.06	35.96	35.40	Average	100	121	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.58	32.06	54.00	-21.94	30.60	3.33	33.16	35.03	Average	100	329	VERTICAL
2	4875.19	43.63	74.00	-30.37	42.17	3.33	33.16	35.03	Peak	100	329	VERTICAL
3	7310.12	30.02	54.00	-23.98	25.40	4.06	35.96	35.40	Average	100	279	VERTICAL
4	7310.22	43.30	74.00	-30.70	38.68	4.06	35.96	35.40	Peak	100	279	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 40MHz Ch 9 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4904.59	30.21	54.00	-23.79	28.70	3.34	33.19	35.02	Average	100	261	HORIZONTAL
2	4904.59	42.97	74.00	-31.03	41.46	3.34	33.19	35.02	Peak	100	261	HORIZONTAL
3	7354.42	44.23	74.00	-29.77	39.55	4.06	36.02	35.40	Peak	100	216	HORIZONTAL
4	7358.10	31.20	54.00	-22.80	26.52	4.06	36.02	35.40	Average	100	216	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4904.05	42.62	74.00	-31.38	41.11	3.34	33.19	35.02	Peak	100	30	VERTICAL
2	4904.28	34.12	54.00	-19.88	32.61	3.34	33.19	35.02	Average	100	30	VERTICAL
3	7356.36	44.38	74.00	-29.62	39.70	4.06	36.02	35.40	Peak	100	97	VERTICAL
4	7357.51	31.02	54.00	-22.98	26.34	4.06	36.02	35.40	Average	100	97	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz CH 149 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11490.13	45.21	54.00	-8.79	31.08	9.71	39.50	35.08	Average	100	176 HORIZONTAL
2	11490.16	56.44	74.00	-17.56	42.31	9.71	39.50	35.08	Peak	100	176 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11488.75	56.33	74.00	-17.67	42.20	9.71	39.50	35.08	Peak	100	187 VERTICAL
2	11490.16	46.72	54.00	-7.28	32.59	9.71	39.50	35.08	Average	100	187 VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz CH 157 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11570.13	47.51	54.00	-6.49	33.48	9.65	39.47	35.09	Average	100	157 HORIZONTAL
2	11570.16	57.02	74.00	-16.98	42.99	9.65	39.47	35.09	Peak	100	157 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11569.84	56.68	74.00	-17.32	42.65	9.65	39.47	35.09	Peak	100	188 VERTICAL
2	11570.03	47.22	54.00	-6.78	33.19	9.65	39.47	35.09	Average	100	188 VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz CH 165 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11650.13	45.14	54.00	-8.86	31.18	9.59	39.44	35.07	Average	100	153	HORIZONTAL
2	11650.32	56.18	74.00	-17.82	42.22	9.59	39.44	35.07	Peak	100	153	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11650.03	56.22	74.00	-17.78	42.26	9.59	39.44	35.07	Peak	100	165	VERTICAL
2	11650.16	45.89	54.00	-8.11	31.93	9.59	39.44	35.07	Average	100	165	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 40MHz CH 151 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11510.19	46.39	54.00	-7.61	32.28	9.71	39.50	35.10	Average	100	152 HORIZONTAL
2	11510.32	56.48	74.00	-17.52	42.37	9.71	39.50	35.10	Peak	100	152 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11510.22	47.33	54.00	-6.67	33.22	9.71	39.50	35.10	Average	100	187 VERTICAL
2	11510.54	55.42	74.00	-18.58	41.31	9.71	39.50	35.10	Peak	100	187 VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 40MHz CH 159 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11589.07	54.72	74.00	-19.28	40.70	9.63	39.47	35.08	Peak	100	174 HORIZONTAL
2	11590.13	44.18	54.00	-9.82	30.16	9.63	39.47	35.08	Average	100	174 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11590.10	45.46	54.00	-8.54	31.44	9.63	39.47	35.08	Average	100	149 VERTICAL
2	11590.22	54.62	74.00	-19.38	40.60	9.63	39.47	35.08	Peak	100	149 VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS8 20MHz CH 149 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11490.16	46.59	54.00	-7.41	32.46	9.71	39.50	35.08	Average	100	141	HORIZONTAL
2	11490.16	57.15	74.00	-16.85	43.02	9.71	39.50	35.08	Peak	100	141	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11490.16	46.72	54.00	-7.28	32.59	9.71	39.50	35.08	Average	100	175	VERTICAL
2	11490.42	56.17	74.00	-17.83	42.04	9.71	39.50	35.08	Peak	100	175	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS8 20MHz CH 157 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11570.00	56.95	74.00	-17.05	42.92	9.65	39.47	35.09	Peak	100	150	HORIZONTAL
2	11570.22	46.87	54.00	-7.13	32.84	9.65	39.47	35.09	Average	100	150	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.94	56.65	74.00	-17.35	42.62	9.65	39.47	35.09	Peak	100	175	VERTICAL
2	11570.19	47.32	54.00	-6.68	33.29	9.65	39.47	35.09	Average	100	175	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS8 20MHz CH 165 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11650.22	45.05	54.00	-8.95	31.09	9.59	39.44	35.07 Average	100	151	HORIZONTAL
2	11657.24	54.79	74.00	-19.21	40.83	9.59	39.44	35.07 Peak	100	151	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11640.10	55.96	74.00	-18.04	42.00	9.59	39.44	35.07 Peak	100	186	VERTICAL
2	11650.13	45.73	54.00	-8.27	31.77	9.59	39.44	35.07 Average	100	186	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS8 40MHz CH 151 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11510.13	55.78	74.00	-18.22	41.67	9.71	39.50	35.10	Peak	100	161	HORIZONTAL
2	11510.22	45.52	54.00	-8.48	31.41	9.71	39.50	35.10	Average	100	161	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11509.90	56.40	74.00	-17.60	42.29	9.71	39.50	35.10	Peak	100	175	VERTICAL
2	11510.16	47.16	54.00	-6.84	33.05	9.71	39.50	35.10	Average	100	175	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS8 40MHz CH 159 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11590.13	44.68	54.00	-9.32	30.66	9.63	39.47	35.08	Average	100	149 HORIZONTAL
2	11599.97	54.60	74.00	-19.40	40.58	9.63	39.47	35.08	Peak	100	149 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11584.42	54.75	74.00	-19.25	40.71	9.65	39.47	35.08	Peak	100	182 VERTICAL
2	11590.10	45.13	54.00	-8.87	31.11	9.63	39.47	35.08	Average	100	182 VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11ac MCS8 80MHz CH 155 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11550.22	45.59	54.00	-8.41	31.52	9.67	39.49	35.09	Average	100	149	HORIZONTAL
2	11550.42	55.83	74.00	-18.17	41.77	9.67	39.48	35.09	Peak	100	149	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11550.03	46.32	54.00	-7.68	32.25	9.67	39.49	35.09	Average	100	170	VERTICAL
2	11551.15	55.96	74.00	-18.04	41.90	9.67	39.48	35.09	Peak	100	170	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 6 / Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.94	46.24	54.00	-7.76	44.90	3.31	33.06	35.03	Average	101	75	HORIZONTAL
2	4823.95	49.77	74.00	-24.23	48.43	3.31	33.06	35.03	Peak	101	75	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.92	52.59	74.00	-21.41	51.25	3.31	33.06	35.03	Peak	103	307	VERTICAL
2	4823.94	50.45	54.00	-3.55	49.11	3.31	33.06	35.03	Average	103	307	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 6 / Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.97	42.82	54.00	-11.18	41.36	3.33	33.16	35.03	Average	172	280	HORIZONTAL
2	4874.01	47.26	74.00	-26.74	45.80	3.33	33.16	35.03	Peak	172	280	HORIZONTAL
3	7309.93	46.91	74.00	-27.09	42.29	4.06	35.96	35.40	Peak	145	260	HORIZONTAL
4	7311.68	37.57	54.00	-16.43	32.95	4.06	35.96	35.40	Average	145	260	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.97	50.83	54.00	-3.17	49.37	3.33	33.16	35.03	Average	103	327	VERTICAL
2	4874.00	52.60	74.00	-21.40	51.14	3.33	33.16	35.03	Peak	103	327	VERTICAL
3	7309.34	43.43	74.00	-30.57	38.81	4.06	35.96	35.40	Peak	100	40	VERTICAL
4	7312.04	31.22	54.00	-22.78	26.60	4.06	35.96	35.40	Average	100	40	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 11 / Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.83	48.16	74.00	-25.84	46.56	3.35	33.26	35.01	Peak	158	283	HORIZONTAL
2	4923.96	43.51	54.00	-10.49	41.91	3.35	33.26	35.01	Average	158	283	HORIZONTAL
3	7385.02	49.69	74.00	-24.31	44.94	4.06	36.09	35.40	Peak	150	214	HORIZONTAL
4	7387.73	40.45	54.00	-13.55	35.70	4.06	36.09	35.40	Average	150	214	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.94	48.92	54.00	-5.08	47.32	3.35	33.26	35.01	Average	102	17	VERTICAL
2	4923.96	51.38	74.00	-22.62	49.78	3.35	33.26	35.01	Peak	102	17	VERTICAL
3	7386.67	34.35	54.00	-19.65	29.60	4.06	36.09	35.40	Average	138	228	VERTICAL
4	7386.82	46.81	74.00	-27.19	42.06	4.06	36.09	35.40	Peak	138	228	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1 / Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4822.96	41.61	74.00	-32.39	40.27	3.31	33.06	35.03	Peak	100	44	HORIZONTAL
2	4823.71	32.31	54.00	-21.69	30.97	3.31	33.06	35.03	Average	100	44	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4822.96	41.09	74.00	-32.91	39.75	3.31	33.06	35.03	Peak	100	195	VERTICAL
2	4823.91	34.61	54.00	-19.39	33.27	3.31	33.06	35.03	Average	100	195	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 6 / Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4871.81	44.99	74.00	-29.01	43.53	3.33	33.16	35.03	Peak	100	285	HORIZONTAL
2	4873.86	32.71	54.00	-21.29	31.25	3.33	33.16	35.03	Average	100	285	HORIZONTAL
3	7309.25	44.77	74.00	-29.23	40.15	4.06	35.96	35.40	Peak	100	229	HORIZONTAL
4	7310.22	33.06	54.00	-20.94	28.44	4.06	35.96	35.40	Average	100	229	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.05	40.55	54.00	-13.45	39.09	3.33	33.16	35.03	Average	129	321	VERTICAL
2	4875.64	53.04	74.00	-20.96	51.58	3.33	33.16	35.03	Peak	129	321	VERTICAL
3	7311.45	43.26	74.00	-30.74	38.64	4.06	35.96	35.40	Peak	100	103	VERTICAL
4	7312.98	30.66	54.00	-23.34	26.04	4.06	35.96	35.40	Average	100	103	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 11 / Ant. 2 / Mode 1
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4921.72	40.51	74.00	-33.49	38.94	3.35	33.23	35.01	Peak	100	112	HORIZONTAL
2	4923.94	29.09	54.00	-24.91	27.49	3.35	33.26	35.01	Average	100	112	HORIZONTAL
3	7385.24	44.62	74.00	-29.38	39.87	4.06	36.09	35.40	Peak	100	70	HORIZONTAL
4	7386.22	31.31	54.00	-22.69	26.56	4.06	36.09	35.40	Average	100	70	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4925.73	30.27	54.00	-23.73	28.67	3.35	33.26	35.01	Average	100	360	VERTICAL
2	4925.89	42.05	74.00	-31.95	40.45	3.35	33.26	35.01	Peak	100	360	VERTICAL
3	7384.35	31.52	54.00	-22.48	26.77	4.06	36.09	35.40	Average	100	279	VERTICAL
4	7387.97	44.14	74.00	-29.86	39.39	4.06	36.09	35.40	Peak	100	279	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11a CH 149 / Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11489.90	48.17	54.00	-5.83	34.04	9.71	39.50	35.08	Average	100	157	HORIZONTAL
2	11489.90	58.18	74.00	-15.82	44.05	9.71	39.50	35.08	Peak	100	157	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos		
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	11489.87	47.66	54.00	-6.34	33.53	9.71	39.50	35.08	Average	100	174	VERTICAL
2	11490.00	57.16	74.00	-16.84	43.03	9.71	39.50	35.08	Peak	100	174	VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11a CH 157 / Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	11569.97	57.01	74.00	-16.99	42.98	9.65	39.47	35.09	Peak	100	158 HORIZONTAL
2	11570.03	47.41	54.00	-6.59	33.38	9.65	39.47	35.09	Average	100	158 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	11569.94	47.33	54.00	-6.67	33.30	9.65	39.47	35.09	Average	100	187 VERTICAL
2	11570.13	57.53	74.00	-16.47	43.50	9.65	39.47	35.09	Peak	100	187 VERTICAL

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11a CH 165 / Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	11647.60	56.21	74.00	-17.79	42.25	9.59	39.44	35.07	Peak	100	164	HORIZONTAL
2	11650.00	45.49	54.00	-8.51	31.53	9.59	39.44	35.07	Average	100	164	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	11649.94	45.77	54.00	-8.23	31.81	9.59	39.44	35.07	Average	100	176	VERTICAL
2	11650.80	56.14	74.00	-17.86	42.18	9.59	39.44	35.07	Peak	100	176	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 KHz / 300 KHz for Peak

4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 20MHz Ch 1, 6, 11 / Ant. 1 + Ant. 2 / Mode 1
Test date	Nov. 22, 2012		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	52.93	54.00	-1.07	22.54	2.22	28.17	0.00	Average	199	91	HORIZONTAL
2	2390.00	69.78	74.00	-4.22	39.39	2.22	28.17	0.00	Peak	199	91	HORIZONTAL
3	2406.40	112.00			81.57	2.22	28.21	0.00	Peak	199	91	HORIZONTAL
4	2407.00	100.92			70.49	2.22	28.21	0.00	Average	199	91	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.20	60.89	74.00	-13.11	30.51	2.21	28.17	0.00	Peak	100	122	HORIZONTAL
2	2390.00	48.97	54.00	-5.03	18.58	2.22	28.17	0.00	Average	100	122	HORIZONTAL
3	2442.20	102.41			71.88	2.24	28.29	0.00	Average	100	122	HORIZONTAL
4	2443.80	113.26			82.73	2.24	28.29	0.00	Peak	100	122	HORIZONTAL
5	2483.50	52.04	54.00	-1.96	21.40	2.26	28.38	0.00	Average	100	122	HORIZONTAL
6	2485.90	67.19	74.00	-6.81	36.51	2.26	28.42	0.00	Peak	100	122	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2467.20	111.56			80.97	2.26	28.33	0.00	Peak	197	74	HORIZONTAL
2	2468.20	101.30			70.66	2.26	28.38	0.00	Average	197	74	HORIZONTAL
3	2483.50	52.16	54.00	-1.84	21.52	2.26	28.38	0.00	Average	197	74	HORIZONTAL
4	2483.50	67.14	74.00	-6.86	36.50	2.26	28.38	0.00	Peak	197	74	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS8 40MHz Ch 3, 6, 9 / Ant. 1 + Ant. 2 / Mode 1
Test date	Nov. 22, 2012		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.60	65.44	74.00	-8.56	35.06	2.21	28.17	0.00	Peak	101	122	HORIZONTAL
2	2390.00	52.99	54.00	-1.01	22.60	2.22	28.17	0.00	Average	101	122	HORIZONTAL
3	2430.00	105.15			74.67	2.23	28.25	0.00	Peak	101	122	HORIZONTAL
4	2435.20	94.37			63.85	2.23	28.29	0.00	Average	101	122	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	50.71	54.00	-3.29	20.32	2.22	28.17	0.00	Average	100	121	HORIZONTAL
2	2390.00	63.18	74.00	-10.82	32.79	2.22	28.17	0.00	Peak	100	121	HORIZONTAL
3	2434.20	96.08			65.56	2.23	28.29	0.00	Average	100	121	HORIZONTAL
4	2439.40	106.39			75.87	2.23	28.29	0.00	Peak	100	121	HORIZONTAL
5	2483.50	53.00	54.00	-1.00	22.36	2.26	28.38	0.00	Average	100	121	HORIZONTAL
6	2483.50	67.33	74.00	-6.67	36.69	2.26	28.38	0.00	Peak	100	121	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2437.60	103.71			73.19	2.23	28.29	0.00	Peak	100	119	HORIZONTAL
2	2438.40	93.72			63.20	2.23	28.29	0.00	Average	100	119	HORIZONTAL
3	2484.70	52.16	54.00	-1.84	21.52	2.26	28.38	0.00	Average	100	119	HORIZONTAL
4	2484.70	66.12	74.00	-7.88	35.48	2.26	28.38	0.00	Peak	100	119	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2385.80	55.67	74.00	-18.33	25.29	2.21	28.17	0.00	Peak	155	122	HORIZONTAL
2	2386.40	44.27	54.00	-9.73	13.89	2.21	28.17	0.00	Average	155	122	HORIZONTAL
3	2410.20	100.62			70.19	2.22	28.21	0.00	Average	155	122	HORIZONTAL
4	2411.00	104.50			74.07	2.22	28.21	0.00	Peak	155	122	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.80	46.70	54.00	-7.30	16.32	2.21	28.17	0.00	Average	100	218	HORIZONTAL
2	2389.20	57.02	74.00	-16.98	26.64	2.21	28.17	0.00	Peak	100	218	HORIZONTAL
3	2436.20	104.99			74.47	2.23	28.29	0.00	Average	100	218	HORIZONTAL
4	2436.20	108.83			78.31	2.23	28.29	0.00	Peak	100	218	HORIZONTAL
5	2485.10	45.68	54.00	-8.32	15.00	2.26	28.42	0.00	Average	100	218	HORIZONTAL
6	2485.10	56.69	74.00	-17.31	26.01	2.26	28.42	0.00	Peak	100	218	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2463.00	108.64			78.07	2.24	28.33	0.00	Peak	100	224	HORIZONTAL
2	2463.80	104.62			74.05	2.24	28.33	0.00	Average	100	224	HORIZONTAL
3	2487.70	52.91	54.00	-1.09	22.23	2.26	28.42	0.00	Average	100	224	HORIZONTAL
4	2487.90	60.84	74.00	-13.16	30.16	2.26	28.42	0.00	Peak	100	224	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	60%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1 + Ant. 2 / Mode 1
Test Date	Nov. 23, 2012		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	52.55	54.00	-1.45	22.16	2.22	28.17	0.00	Average	158	123	HORIZONTAL
2	2390.00	71.76	74.00	-2.24	41.37	2.22	28.17	0.00	Peak	158	123	HORIZONTAL
3	2405.60	106.64			76.21	2.22	28.21	0.00	Peak	158	123	HORIZONTAL
4	2405.80	97.19			66.76	2.22	28.21	0.00	Average	158	123	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.60	65.32	74.00	-8.68	34.94	2.21	28.17	0.00	Peak	100	217	HORIZONTAL
2	2390.00	51.05	54.00	-2.95	20.66	2.22	28.17	0.00	Average	100	217	HORIZONTAL
3	2430.60	111.41			80.93	2.23	28.25	0.00	Peak	100	217	HORIZONTAL
4	2431.80	101.16			70.68	2.23	28.25	0.00	Average	100	217	HORIZONTAL
5	2483.50	50.18	54.00	-3.82	19.54	2.26	28.38	0.00	Average	100	217	HORIZONTAL
6	2484.70	64.66	74.00	-9.34	34.02	2.26	28.38	0.00	Peak	100	217	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2467.40	106.67			76.08	2.26	28.33	0.00	Peak	100	223	HORIZONTAL
2	2468.20	97.44			66.80	2.26	28.38	0.00	Average	100	223	HORIZONTAL
3	2483.50	52.71	54.00	-1.29	22.07	2.26	28.38	0.00	Average	100	223	HORIZONTAL
4	2483.50	70.37	74.00	-3.63	39.73	2.26	28.38	0.00	Peak	100	223	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS8 20MHz / Reference Level




Date: 24.NOV.2012 11:54:57

Plot on Configuration IEEE 802.11n MCS8 20MHz / CH 1 (down 30dBc)




Date: 24.NOV.2012 12:35:50

Plot on Configuration IEEE 802.11n MCS8 20MHz / CH 6 (down 30dBc)




Date: 24.NOV.2012 12:34:26

Plot on Configuration IEEE 802.11n MCS8 20MHz / CH 11 (down 30dBc)




Date: 24.NOV.2012 12:33:24

Plot on Configuration IEEE 802.11n MCS8 40MHz / Reference Level




Date: 24.NOV.2012 11:52:05

Plot on Configuration IEEE 802.11n MCS8 40MHz / CH 3 (down 30dBc)




Date: 24.NOV.2012 12:38:26

Plot on Configuration IEEE 802.11n MCS8 40MHz / CH 6 (down 30dBc)




Date: 24.NOV.2012 12:39:33

Plot on Configuration IEEE 802.11n MCS8 40MHz / CH 9 (down 30dBc)




Date: 24.NOV.2012 12:40:32

Plot on Configuration IEEE 802.11n MCS8 20MHz / Reference Level




Date: 24.NOV.2012 12:48:07

Plot on Configuration IEEE 802.11n MCS8 20MHz / CH 149 (down 30dBc)




Date: 24.NOV.2012 13:05:43

Plot on Configuration IEEE 802.11n MCS8 20MHz / CH 157 (down 30dBc)




Date: 24.NOV.2012 13:03:52

Plot on Configuration IEEE 802.11n MCS8 20MHz / CH 165 (down 30dBc)




Date: 24.NOV.2012 13:02:17

Plot on Configuration IEEE 802.11n MCS8 40MHz / Reference Level




Date: 24.NOV.2012 12:49:26

Plot on Configuration IEEE 802.11n MCS8 40MHz / CH 151 (down 30dBc)




Date: 24.NOV.2012 13:07:44

Plot on Configuration IEEE 802.11n MCS8 40MHz / CH 159 (down 30dBc)




Date: 24.NOV.2012 13:08:42

Plot on Configuration IEEE 802.11ac MCS8 80MHz / Reference Level




Date: 24.NOV.2012 13:54:03

Plot on Configuration IEEE 802.11ac MCS8 80MHz / CH 155 (down 30dBc)




Date: 24.NOV.2012 13:55:26

Plot on Configuration IEEE 802.11b / Reference Level




Date: 24.NOV.2012 11:01:15

Plot on Configuration IEEE 802.11b / CH 1 (down 30dBc)




Date: 24.NOV.2012 11:08:27

Plot on Configuration IEEE 802.11b / CH 6 (down 30dBc)




Date: 24.NOV.2012 11:07:25

Plot on Configuration IEEE 802.11b / CH 11 (down 30dBc)




Date: 24.NOV.2012 11:06:27

Plot on Configuration IEEE 802.11g / Reference Level




Date: 24.NOV.2012 11:12:35

Plot on Configuration IEEE 802.11g / CH 1 (down 30dBc)




Date: 24.NOV.2012 11:15:17

Plot on Configuration IEEE 802.11g / CH 6 (down 30dBc)




Date: 24.NOV.2012 11:14:02

Plot on Configuration IEEE 802.11g / CH 11 (down 30dBc)




Date: 24.NOV.2012 11:15:54

Plot on Configuration IEEE 802.11a / Reference Level




Date: 24.NOV.2012 11:22:31

Plot on Configuration IEEE 802.11a / CH 149 (down 30dBc)




Date: 24.NOV.2012 11:26:21

Plot on Configuration IEEE 802.11a / CH 157 (down 30dBc)



Date: 24.NOV.2012 11:25:32

Plot on Configuration IEEE 802.11a / CH 165 (down 30dBc)



Date: 24.NOV.2012 11:24:17

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 03, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2011	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 22, 2011	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 22, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 03, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz ~ 26.5 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz ~ 26.5 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: “*” Calibration Interval of instruments listed above is two years.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085