



Labels Exemplary

G-Wave, Inc.
MODEL: BDA-PS7W-37/37-90-R
FCC ID Q8KPS7W3790R IC: 4901A-PS7W3790R
SER.No: 15051002


**This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received,
that may cause undesired operation.**

**WARNING. This is NOT a CONSUMER device. It is designed for installation
by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC
LICENSE or express consent of an FCC Licensee to operate this device. You
MUST register Class B signal boosters (as defined in 47 CFR 90.219) online
at www.fcc.gov/signal-boosters/registration. Unauthorized use may result
in significant forfeiture penalties, including penalties in excess of \$100,000
for each continuing violation.**

**This device is a Part 90
Signal Booster and a
90.219 Class B device.**

*The labels having adhesive back.

This device is a Part 90
Signal Booster and a
90.219 Class B device.



BASE



MOBILE

WARNING:

Input Signal Level
above -30 dBm may cause
damage to system

This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received,
that may cause undesired operation.

WARNING: This is NOT a CONSUMER device. It is designed for installation
by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC
LICENSE or express consent of an FCC Licensee to operate this device. You
MUST register Class B signal boosters (as defined in 47 CFR 90.219) online
at www.fcc.gov/signal-boosters/registration. Unauthorized use may result
in significant forfeiture penalties, including penalties in excess of \$100,000
for each continuing violation.

G-Wave, Inc.

MODEL: BDA-PS7W-37/37-90-R

FCC ID Q8KPS7W3790R IC: 4901A-PS7W3790R

SER.No: 15051002

WARNING:

THE WARRANTY IS VOID IF THE ISOLATION BETWEEN THE BASE
ANTENNA AND THE MOBILE ANTENNA IS NOT CONFIGURED AT
LEAST 12dB HIGHER THAN THE BDA GAIN. ISOLATION EQUAL OR
LESS THAN THE BDA GAIN WILL RESULT IN DAMAGE TO THE BDA.