

## Test Report

Prepared for: G-Way Solutions, LLC

Model: 1BOX-PS7W/PS8W-33/33-90-N

**Description:** Patented 1-BOX(tm) system which includes a Bi-Directional Amplifier (BDA), Annunciator, and Battery backup unit in a single enclosure

FCC ID: Q8KPS7W83790N

Serial Number: 24101001

Project No: p2490008

To

FCC Part 1.1310

Date of Issue: February 5, 2025

On the behalf of the applicant:

**G-Way Solutions, LLC**  
17-01 Pollitt Drive, Suite 6  
Fair Lawn, NJ 07410

Attention of:

**Gregory Tsvika Blekher, Head of Engineering**  
Ph: (201) 343- 6388  
E-Mail: t\_blekher@gwaverf.com

Prepared By:

Compliance Testing, LLC Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
ANAB Cert#: AT-2901  
FCC Site Reg. #US2901  
ISED Site Reg. #2044A-2

Reviewed / Authorized By:



**Greg Corbin**  
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested

### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	2/5/2025	Greg Corbin	Original Document

**ANAB**

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliantesting.com/labscope.html> for current scope of accreditation.



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

## EUT Description

<b>Model:</b>	1BOX-PS7W/PS8W-33/33-90-N
<b>Serial:</b>	24101001
<b>Firmware:</b>	GWY20190111
<b>Software:</b>	N/A
<b>Description:</b>	Public Safety 700/800 MHz Band Bi-Directional Amplifier Patented 1-BOX(tm) system which includes a Bi-Directional Amplifier (BDA), Annunciator, and Battery backup unit in a single enclosure
<b>Additional Information:</b>	This test report is to support a C2PC. The manufacturer installed a battery, battery monitoring circuitry and digital alarm circuitry. The RF portion of the EUT was not changed from the original design. Spot testing was performed to verify no change in RF performance. All tests were performed with the EUT gain set to maximum. Uplink gain = 86 dB Downlink Gain = 85 dB
<b>Receipt of Sample(s):</b>	October 24, 2024
<b>EUT Condition:</b>	<b>Visual Damage No</b> <b>State of Development</b> Production/Production Equivalent

## Frequency of operation

The EUT is patented 1-BOX(tm) system which includes a B-Directional Amplifier(BDA), Annunciator, and Battery backup unit in a single enclosure, that operates in the frequency range listed in Table 1. The emission designators listed in Table 1 are representative emission designators used by transmitters whose signal is amplified by this booster.

Table 1

Frequency		Emission Designators
Base to Mobile	Mobile to Base	
758 – 775 851 - 869	788 - 824	F3E, G1D, G1E, W7W, F2D

Per the user manual, the composite output power for the uplink and downlink is 33 dBm.

For the uplink, the user manual states the maximum antenna gain is 10.1 dBi and a cable loss of 1 – 10 dB. This makes the maximum antenna gain = 10.1 dB – 1 dB = 9.1 dBi.

For the downlink, the user manual states the maximum antenna gain is 2.0 dBi and a cable loss of 1 – 10 dB. This makes the maximum antenna gain = 2.0 dB – 1 dB = 1 dBi.

## MPE Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

**Limits Uncontrolled Exposure**  
**47 CFR 1.1310**  
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

## Test Data

For the **Uplink**, MPE was calculated using the lowest frequency in the band (758 MHz), the composite output power (+33 dBm) and the maximum antenna gain minus the cable loss (9.1 dBi).

Test Frequency, MHz	758
Power, Conducted, mW (P)	1995.2
Antenna Gain Isotropic	9.1 dBi
Antenna Gain Numeric (G)	8.13
Distance (R)	20 cm
$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm <sup>2</sup>	3.227

Power Density (S) = 3.227 mw/cm <sup>2</sup>
Limit =(from above table) = 0.505 mw/cm <sup>2</sup>

With the output power set to **manufacturer rated output power (+33 dBm)** using a 9.1 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

## Minimum Safe Distance Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

Test Frequency, MHz	758
Power, Conducted, mW (P)	1995.2
Antenna Gain Isotropic	9.1 dBi
Antenna Gain Numeric (G)	8.13
Limit (L)	0.505

R = $\sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
50.6 cm	1995.2	8.13	0.505

With the output power set to the manufacturer's (Mfr) rated output power (+33 dBm) using an antenna with 9.1 dBi gain, the minimum safe distance is 50.6 cm.

For the **Downlink**, MPE was calculated using the lowest frequency in the band (758 MHz), the composite output power (+33 dBm) and the maximum antenna gain minus the cable loss (1.0 dBi).

Test Frequency, MHz	758
Power, Conducted, mW (P)	1995.2
Antenna Gain Isotropic	1.0 dBi
Antenna Gain Numeric (G)	1.26
Distance (R)	20 cm
$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm <sup>2</sup>	0.500

Power Density (S) = 0.500 mw/cm <sup>2</sup>
Limit =(from above table) = 0.505 mw/cm <sup>2</sup>

With the output power set to **manufacturer rated output power (+33 dBm)** using a 1.0 dBi antenna, the EUT meets the power density requirements at 20 cm for the Downlink.

END OF TEST REPORT