



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: G-Way Incorporated

Model: BDA-PS7W/PS8NEPS-37/37-90-R

Description: Public Safety 700/800 MHz Band Bi-Directional Amplifier

Serial Number: 16061003

FCC ID: Q8KPS7W83790R

To

FCC Part 1.1310

Date of Issue: July 7, 2016

On the behalf of the applicant:

**G-Way Incorporated
38 Leuning St.
South Hackensack, NJ 07606**

Attention of:

**Gregory Tsvika Blekher, Project Engineer
Ph: (201)343-6388
E-Mail: tech-support@gwaverf.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1660016**

**Greg Corbin
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	July 1, 2016	Greg Corbin	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description**Model:** BDA-PS7W/PS8NEPS-37/37-90-R**Description:** The industrial booster is a Bi-Directional amplifier (BDA), used to amplify DL and UL frequencies in the PS 700/800 MHz band.**Firmware:** N/A**Serial Number:** 16061003**Additional Information:**The EUT is classified as a Part 90 PS **Class B** industrial signal booster.

The EUT is a Bi-directional Amplifier that operates in the Frequency ranges listed in Table 1.

System Power is 120 VAC @ 60 Hz.

Frequency - MHz	
Base to Mobile	Mobile to Base
758 - 775	788 - 805
851 - 862	806 - 817

Antennas specified for the EUT:

Antenna type	Model	Gain - dBi
Wideband High Gain Ceiling Antenna	TQI-4FC-5	2
Full Band Directional Antenna	TDJ-700/2500YG	8.5

EUT Operation during Tests

The EUT was tested under normal operating conditions with the front panel attenuators set to 0 dB for all measurements.

30 dB, 50 watt attenuators were installed on both RF ports for all tests.

MPE calculations were performed at the manufacturer's rated output of +37 dBm using an antenna with 8.5 dBi gain.

MPE calculations were performed at the manufacturer's rated output of +37 dBm +20% using an antenna with 8.5 dBi gain.

MPE Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 8.5 dBi gain

Test Frequency, MHz	758
Power, Conducted, mW (P)	5011
Antenna Gain Isotropic	8.5 dBi
Antenna Gain Numeric (G)	7.08
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
7.058

Power Density (S) = 7.058 mw/cm ²
Limit =(from above table) = 0.505 mw/cm ²

With the output power set to **manufacturer rated output power (+37 dBm)** using a 8.5 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

Minimum Safe Distance Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

Test Data

Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 8.5 dBi gain

Test Frequency, MHz	758
Power, Conducted, mW (P)	5011
Antenna Gain Isotropic	8.5 dBi
Antenna Gain Numeric (G)	7.08
Limit (L)	0.505

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
74.8 cm	5011	7.08	0.505

With the output power set to the manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 8.5 dBi gain, the minimum safe distance is 74.8 cm.

MPE Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) + 20% using an antenna with 8.5 dBi gain

Test Frequency, MHz	758
Power, Conducted, mW (P)	6013.2 (37 dBm + 20%)
Antenna Gain Isotropic	8.5 dBi
Antenna Gain Numeric (G)	7.08
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
8.469

Power Density (S) = 8.469 mw/cm ²
Limit =(from above table) = 0.505 mw/cm ²

With the output power set to **manufacturer rated output power (+37 dBm)** using a 8.5 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

Minimum Safe Distance Evaluation

This is a Fixed device used in Uncontrolled Exposure environment.

Test Data

Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) + 20% using an antenna with 8.5 dBi gain

Test Frequency, MHz	758
Power, Conducted, mW (P)	6013.2 (37 dBm + 20%)
Antenna Gain Isotropic	8.5 dBi
Antenna Gain Numeric (G)	7.08
Limit (L)	0.505

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
81.9 cm	6013.2	7.08	0.505

With the output power set to the manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 8.5 dBi gain, the minimum safe distance is 81.9 cm.

END OF TEST REPORT