



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 1 of 41



TEST REPORT

Product Name : Tablet PC

Model Number : V300

Applicant : Global Brands Manufacture Ltd.

Address : 9th Plant, Yue Yuen Industrial Estate Huang Jiang Zhen,
Dong Guan City, Guang Dong Province, China Zip : 53758

Date Received : JUN. 5. 2003

Date Tested : JUN.5~JUN. 21, 2003

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as separately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.
5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.



**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 2 of 41

Test Report Certification

Product Name : Table PC
Model Number : V300
Applicant : Global Brands Manufacture Ltd.

Measurement Standard :

47 CFR Part 15, Subpart B and Subpart C (Section 15.247),
ANSI C63.4-2001

Tested By : Y. H. Liu , **Date** : Jul, 5, 2003
(Y. H. Liu)

Reviewed By : Roger Sheng , **Date** : Jul 15, 2003
(Roger Sheng)

Approved By : C. F. Wu , **Date** : July 09, 2003
(C. F. Wu , Manager)



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 3 of 41

TABLE OF CONTENTS

TITLE	PAGE NO.
1. GENERAL INFORMATION	5
1.1 General Statement.....	5
1.2 General Description of EUT & Power.....	5
1.3 Description of EUT	5
1.4 EUT Information	6
1.5 Description of Peripherals	7
1.6 EUT & Peripherals Setup Diagram	8
1.7 EUT Operating Condition	9
1.8 Description of Test Site	9
1.9 Summary of Test Results.....	10
2. CONDUCTED POWERLINE TEST	11
2.1 Test Equipments	11
2.2 Test Setup	11
2.3 Conducted Power Line Emission Limit.....	12
2.4 Test Procedure	12
2.5 Uncertainty of Conducted Emission.....	12
2.6 Conducted Power Line Emission	13
2.7 Photos of Conduction Test	14
3. RADIATED EMISSION TEST.....	15
3.1 Test Equipments	15
3.2 Test Setup	15
3.3 Radiation Limit.....	16
3.4 Test Procedures.....	17
3.5 Uncertainty of Radiated Emission.....	17
3.6 Radiated Rf Noise Measurement	18-27
3.7 Photos of Open Site	28-29
4. 6dB BANDWIDTH MEASUREMENT	30
4.1 Test Equipments	30
4.2 Test Setup	30
4.3 Limits of 6db Bandwidth Measurement	30
4.4 Test Procedure	30
4.5 Uncertainty of Conducted Emission.....	30
4.6 Test Results.....	31
4.7 Photo of 6db Bandwidth Measurement.....	32
5. MAXIMUM PEAK OUTPUT POWER.....	33
5.1 Test Equipments	33
5.2 Test Setup	33
5.3 Limits of Maximum Peak Output Power.....	33
5.4 Test Procedure	34
5.5 Uncertainty of Conducted Emission.....	34
5.6 Test Results.....	34



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 4 of 41

TABLE OF CONTENTS

TITLE	PAGE NO.
6. POWER SPECTRAL DENSITY MEASUREMENT	35
6.1 Test Equipments	35
6.2 Test Setup	35
6.3 Limits of Power Spectral Density Measurement	35
6.4 Test Procedure	36
6.5 Uncertainty of Conducted Emission.....	36
6.6 Test Results.....	36
6.7 Photo of Power Spectral Density Measurment.....	37
7. OUT OF BAND MEASUREMENT	38
7.1 Test Equipments	38
7.2 Test Setup	38
7.3 Limits of Out of Band Emissions Measurement.....	38
7.4 Test Procedure	39
7.5 Uncertainty of Conducted Emission.....	39
7.6 Test Results.....	39
7.7 Photo of Out Of Band Measurement	40
8. ANTENNA REQUIREMENT	41
8.1 Standard Applicable.....	41
8.2 Antenna Connected Construction	41



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 5 of 41

1. GENERAL INFORMATION

1.1 General Statement

MEASUREMENT DEVIATION : Comply with standard in full

TRACEABILITY : This test result is traceable to national or international std.

1.2 General Description of EUT & Power

1.3 Description of EUT

Manufacturer	: Global Brands Manufacture Ltd.
Sample Name	: Tablet PC
Model Name	: V300
Frequency Range	: 2412 MHz to 2462mhz
Channel Number	: 11
Air Data Rate	: 11Mbps (Highest Mode)
Type Of Modulation	: Direct Sequence Spread Spectrum
Frequency Selection	: By Software
Antenna Type	: Inverted F Type Antenna, IFTA



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 6 of 41

1.4 EUT Information

CPU Manufacturer : Transmeta Model : TM5800 867MHz
DDRAM Type : DDR 512MB
LCD Manufacturer : AU Model : AU B084SN02
HDD Manufacturer : Hitachi Model : IC25N020AT
Modem Manufacturer : Actiontech Model : MD560LMI-2
Wireless Manufacturer : Airvast Model : WM168B
Antenna Manufacturer : Favor Tron Model : Short : 14-211-F25011
Long : 14-211-F25021
Keyboard Manufacturer : VAC Model : V300 external USB KB
Power Adapter :
Manufacturer : DELTA Corp.
Model Number : ADP-50HH
Input Power : 100-240VAC, 1.5A, 50-60Hz
Output Power : 19VDC, 2.64A

I/O Port for EUT :

No.	I/O PORT TYPES	Q.TY	TESTED WITH
1	Video Port	1	1
2	LAN Port	1	1
3	RJ11 Port	1	1
4	Audio Jack Line in Port	1	1
5	Audio Jack Line out Port	1	1
6	USB Port	2	2
7	Card Read Port	1	1
8	External Contact USB port	1	1



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720


FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 7 of 41

1.5 Description of Peripherals

No.	Product	Manufacture	Model No.	Serial No.	FCC ID
1	Notebook PC	DELL	PP01L	CN-09C748-4815 5-1AP-6081	DOC
2	Monitor	HP	D8894A	CN00905269	DOC
3	Keyboard	BTC	7932M	G91400390	DOC
4	Mouse	Logitechm	M-BJ58	LNA14607310	DOC
5	Headset with Micphone	Fujiei	SBZ-33	-----	
6	Wireless Ethernet Bridge	ASKEY	RTW026	-----	

No.	Type	Connector	Shielded	Length
1	Cat5 twisted-pair	RJ-45, Plastic	NO	15m
2	-----	RJ-11, Plastic	NO	15m

1.6 EUT & Peripherals Setup Diagram





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 9 of 41

1.7 EUT Operating Condition

1. Set up all equipments like the setup diagram.
2. NB (1) ping 192.168.1.10 -t -l 5000 to EUT.
3. EUT ping 192.168.1.11 -t -l 5000 to NB (1).
4. EUT ping 192.168.1.1 -t -l 5000 to AP.
5. Modem connection internet and download data
6. EUT run Emitest.
7. EUT run Media play mood music
8. All of the function are under run.

1.8 Description of Test Site

SITE DESCRIPTION : FCC certificate NO. : 90585
BSMI certificate NO. : SL2-IN-E-0002
NVLAP Lab code : 200118-0
CNLA certificate NO. : CNLA-ZL97018
VCCI certificate NO. : R-1229, C-1250

NAME OF SITE : Ecom Sertech Corp. Hsinchu
(Spin-off from ITRI / ERSO on April. 01, 2003)

SITE LOCATION : Rm.258, Bldg.17, NO.195, Sec. 4, Chung Hsing Rd.,
Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 10 of 41

1.9 Summary of Test Results

The EUT has been tested according to the following specifications :

APPLIED STANDARD : 47 CFR Part 15, Subpart B and Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.107 15.207	AC Power Conducted Emission Limit : sec 15.107	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : 6dB bandwidth > 500KHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit : max. 30dBm	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(d)	Power Spectral Density Limit : max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band Limit: Table 15.209	PASS	Meet the requirement of limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 11 of 41


2. CONDUCTED POWERLINE TEST

2.1 Test Equipments

The following test equipments are used during the conducted powerline tests :

Manufacturer or Type	Model No	Serial No.	Date of Calibration	Calibration Period	Remark
SPECTRUM ANALYZER & DISPLAY	HP 8568A	2235A02320	APR. 01, 2003	1 Year	PRETEST
QUASI-PEAK ADAPTER	HP 85650 A	2341A00672	APR. 01, 2003	1 Year	PRETEST
ISOLATION TRANSFORMER	SOLAR 7032-1	N/A	N/A	N/A	FINAL
L.I.S.N.	EMCO 3850/2	9311-1025 9401-1028	JAN. 08, 2003 For Characteristic impedance MAY 18, 2003 For Insertion loss	1 Year	FINAL
TEST RECEIVER	R/S ESHS30	838550/003	JUN. 07, 2003	1 Year	FINAL
SHIELDED ROOM	KEENE 5983	NO.1	N/A	N/A	FINAL
PULSE LIMIT	R/S EHS3Z2	357.8810.52	JUL. 10, 2002	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	JUL. 10, 2002	1 Year	FINAL
50Ω TERMINATOR	-----	-----	JUL. 10, 2002	1 Year	FINAL

2.2 Test Setup





2.3 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Maximum Rf Line Voltage (Db μ v)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56	56-46
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

2.4 Test Procedure

The test procedure is performed in a 12ft×12ft×8ft(L×W×H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

2.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.36 dB.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 13 of 41

2.6 Conducted Power Line Emission

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 26 °C

Humidity : 65 % RH

Frequency (MHz)	Loss(dB)		MEASUREMENT				L1 Emission (dB μ V)		L2 Emission (dB μ V)		LIMITS (dB μ V)	
			L1(dB μ V)		L2(dB μ V)							
	L1	L2	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
0.150	0.1	0.2	*	*	*	*	*	*	*	*	66.00	56.00
0.210	0.1	0.2	41.30	*	*	*	41.40	*	*	*	63.21	53.21
0.492	0.1	0.2	35.00	*	*	*	35.10	*	*	*	56.13	46.13
0.630	0.1	0.2	27.30	*	*	*	27.40	*	*	*	56.00	46.00
0.699	0.1	0.2	*	*	26.50	*	*	*	26.70	*	56.00	46.00
2.106	0.11	0.2	27.30	*	*	*	27.41	*	*	*	56.00	46.00
2.589	0.16	0.2	*	*	25.90	*	*	*	26.10	*	56.00	46.00
3.156	0.2	0.2	28.60	*	*	*	28.80	*	*	*	56.00	46.00
6.243	0.3	0.3	25.50	*	*	*	25.80	*	*	*	60.00	50.00
6.297	0.3	0.3	*	*	22.30	*	*	*	22.60	*	60.00	50.00
9.615	0.46	0.46	23.80	*	*	*	24.26	*	*	*	60.00	50.00
9.945	0.49	0.49	*	*	21.20	*	*	*	21.69	*	60.00	50.00
19.866	0.9	0.99	30.90	*	39.20	*	*	*	40.19	*	60.00	50.00
24.195	1.04	1.0	*	*	35.50	*	*	*	*	*	60.00	50.00
30.000	1.4	1.8	*	*	*	*	*	*	*	*	60.00	50.00

REMARKS : 1. * Undetectable or the Q.P. value is lower than the limits of Ave.

2. According to technical experiences, the power line emissions of the EUT in transmitting and receiving mode are almost the same. The EUT was set to transmitting mode at channel 1 (2412MHz) while performing final test.

2.7 Photos of Conduction Test



3. RADIATED EMISSION TEST


3.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.

Manufacturer or Type	Model No	Serial No	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2421	MAY 07, 2003	1 Year	FINAL
R/S TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002	1 Year	FINAL
OPEN SITE	-----	No.1	JUL. 10~12, 2002	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	JUL. 13, 2002	1 Year	FINAL
Horn Antenna	AH-118	10089	FEB. 25, 2003	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	OCT. 11, 2002	1 Year	FINAL
HP High pass filter	84300/80038	011	cal. on use	1 Year	FINAL
Horn Antenna	AH-840	03077	FEB. 25, 2003	1 Year	FINAL


3.2 Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



Antenna Elevation Variable

The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



Antenna Elevation Variable

3.3 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class B digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (M)	Field Strength Limit (dB μ V/M)		
		Q.P.	AVG	PK
30~230	10	30	-----	-----
230~1G	10	37	-----	-----
Above 1G	3	-----	54	74

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.



3.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

3.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is $\pm 2.72\text{dB}$.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 18 of 41

3.6 Radiated Rf Noise Measurement

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 25 °C

Humidity : 65 %RH

FREQ- UENCY (MHz)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	METER READING AT10m(dB μ V)		LIMITS (dB μ V/m)	EMISSION LEVEL AT10m(dB μ V/m)	
			HORIZON- TAL	VERTICAL		HORIZON- TAL	VERTICAL
30.00	18.11	0.90	*	*	30.00	*	*
83.25	8.79	1.73	8.90	8.70	30.00	19.42	19.22
118.65	12.42	2.09	4.80	5.70	30.00	19.31	20.21
123.50	12.27	2.17	5.10	6.50	30.00	19.54	20.94
200.46	10.13	2.60	13.10	11.90	30.00	25.83	24.63
217.25	11.28	2.77	7.80	9.70	30.00	21.85	23.75
454.75	17.76	4.12	13.10	10.30	37.00	34.98	32.18
720.42	19.82	5.42	4.00	4.00	37.00	29.24	29.24
1000.00	21.34	6.40	*	*	37.00	*	*

REMARKS : 1. *Undetectable

2. Emission level (dB μ V/M) = Antenna Factor (dB/m) + Cable loss (dB)
+ Meter Reading (dB μ V).

3. The EUT was operated in stand-by, receiving and transmitting mode, after a preliminary scan, we found the EUT in transmitting mode generate the highest emission power. The EUT is set transmitting mode at final test to get the worst-case emission.

4. Mode : Transmitting test



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 19 of 41

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/6
Fundamental Frequency	2412MHz (CH 1)	Test By:	Y. H. Liu
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4823.83	51.09	34.44	2.77	35.38	9.5	0	43.42	74	-30.58	P	H	1.0
4823.83	48.73	34.44	2.77	35.38	9.5	0	41.06	54	-12.94	A	H	1.1
7236.94	40.04	39.81	3.94	35.56	9.5	0	38.73	74	-35.27	P	H	1.0
7236.94	27.93	39.81	3.94	35.56	9.5	0	26.62	54	-27.38	A	H	1.2
9647.22	45.17	38.54	4.10	35.67	9.5	0	42.63	74	-31.37	P	H	1.0
9647.22	38.31	38.54	4.10	35.67	9.5	0	35.77	54	-18.23	A	H	1.0
4823.82	51.19	34.44	2.77	35.38	9.5	0	43.52	74	-30.48	P	V	1.1
4823.82	49.16	34.44	2.77	35.38	9.5	0	41.49	54	-12.51	A	V	1.1
7235.68	40.67	39.81	3.94	35.56	9.5	0	39.36	74	-34.64	P	V	1.0
7235.68	29.47	39.81	3.94	35.56	9.5	0	28.16	54	-25.84	A	V	1.0
9647.83	45.33	38.54	4.10	35.67	9.5	0	42.79	74	-31.21	P	V	1.2
9647.83	38.04	38.54	4.10	35.67	9.5	0	35.50	54	-18.50	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB

5. The result basic equation calculation as follow :

$$\text{Level} = \text{Reading} + \text{AF} + \text{Closs} - \text{Preamp} + \text{Filter} - \text{Dist}, \text{Margin} = \text{Level} - \text{Limit}$$



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 20 of 41

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/6
Fundamental Frequency	2437MHz (CH 6)	Test By:	Y. H. Liu
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4873.82	52.81	34.767	2.80	35.40	9.5	0	45.48	74	-28.52	P	H	1.0
4873.82	50.48	34.767	2.80	35.40	9.5	0	43.15	54	-10.85	A	H	1.1
7310.91	41.02	39.776	4.00	35.57	9.5	0	39.73	74	-34.27	P	H	1.0
7310.91	28.67	39.776	4.00	35.57	9.5	0	27.38	54	-26.62	A	H	1.2
9747.81	47.94	38.525	4.02	35.72	9.5	0	45.26	74	-28.74	P	H	1.0
9747.81	42.12	38.525	4.02	35.72	9.5	0	39.44	54	-14.56	A	H	1.0
4873.82	51.67	34.767	2.80	35.40	9.5	0	44.34	74	-29.66	P	V	1.1
4873.82	48.93	34.767	2.80	35.40	9.5	0	41.60	54	-12.40	A	V	1.1
7310.81	41.96	39.776	4.00	35.57	9.5	0	40.67	74	-33.33	P	V	1.0
7310.81	30.86	39.776	4.00	35.57	9.5	0	29.57	54	-24.43	A	V	1.0
9747.79	45.50	38.525	4.02	35.72	9.5	0	42.82	74	-31.18	P	V	1.2
9747.79	39.07	38.525	4.02	35.72	9.5	0	36.39	54	-17.61	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, "----" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 21 of 41

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Receiving	Test Date :	2003/6/6
Fundamental Frequency	2462MHz (CH 11)	Test By:	Y. H. Liu
Temperature :	27 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
4873.82	52.81	34.77	2.80	35.40	9.5	0	45.48	74	-28.52	P	H	1.0
4873.82	50.48	34.77	2.80	35.40	9.5	0	43.15	54	-10.85	A	H	1.1
7310.91	41.02	39.78	4.00	35.57	9.5	0	39.73	74	-34.27	P	H	1.0
7310.91	28.67	39.78	4.00	35.57	9.5	0	27.38	54	-26.62	A	H	1.2
9747.81	47.94	38.53	4.02	35.72	9.5	0	45.26	74	-28.74	P	H	1.0
9747.81	42.12	38.53	4.02	35.72	9.5	0	39.44	54	-14.56	A	H	1.0
4873.82	51.67	34.77	2.80	35.40	9.5	0	44.34	74	-29.66	P	V	1.1
4873.82	48.93	34.77	2.80	35.40	9.5	0	41.60	54	-12.40	A	V	1.1
7310.81	41.96	39.78	4.00	35.57	9.5	0	40.67	74	-33.33	P	V	1.0
7310.81	30.86	39.78	4.00	35.57	9.5	0	29.57	54	-24.43	A	V	1.0
9747.79	45.50	38.53	4.02	35.72	9.5	0	42.82	74	-31.18	P	V	1.2
9747.79	39.07	38.53	4.02	35.72	9.5	0	36.39	54	-17.61	A	V	1.0

Note :

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss,
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 22 of 41

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/6
Fundamental Frequency:	2412MHz (CH 1)	Test By:	Y. H. Liu
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	(dB)	(P/Q/A)	(H/V)	(Meter)
2390.25	63.24	31.81	2.30	35.31	9.5	0	41.64	74	-32.36	P	H	1.0
2390.25	51.03	31.81	2.30	35.31	9.5	0	32.61	54	-21.39	A	H	1.0
2412	104.20	31.788	2.36	35.31	9.5	0	93.53	Fundamental frequency		P	H	1.0
2412	101.43	31.788	2.36	35.31	9.5	0	90.76			A	H	1.0
4823.84	52.00	34.437	2.77	35.38	9.5	1	45.33	74	-28.67	P	H	1.0
4823.84	49.08	34.437	2.77	35.38	9.5	1	42.41	54	-11.59	A	H	1.0
7235.29	40.73	39.806	3.94	35.56	9.5	1	40.42	74	-33.58	P	H	1.0
7235.29	29.01	39.806	3.94	35.56	9.5	1	28.70	54	-25.30	A	H	1.0
9647.81	47.56	38.535	4.10	35.67	9.5	1	46.02	74	-27.98	P	H	1.0
9647.81	42.15	38.535	4.10	35.67	9.5	1	40.61	54	-13.39	A	H	1.0
12059.93*	---	42.60	15.20	35.30	9.5	1	---	---	---	---	H	1.0
14471.97*	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
16884.01	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19296.05*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
21708.09	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24120.13	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark "----" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 23 of 41

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/6
Fundamental Frequency:	2412MHz (CH 1)	Test By:	Y. H. Liu
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2390.25	62.08	31.81	2.30	35.31	9.5	0	43.54	74	-30.46	P	V	1.0
2390.25	50.18	31.81	2.30	35.31	9.5	0	31.55	54	-22.45	A	V	1.0
2412.72	107.07	31.787	2.36	35.31	9.5	0	96.40	Fundamental frequency		P	V	1.0
2412.72	102.08	31.787	2.36	35.31	9.5	0	91.41			A	V	1.0
4823.77	50.02	34.437	2.77	35.38	9.5	1	43.35	74	-30.65	P	V	1.0
4823.77	46.62	34.437	2.77	35.38	9.5	1	39.95	54	-14.05	A	V	1.0
7235.38	41.03	39.806	3.94	35.56	9.5	1	40.72	74	-33.28	P	V	1.0
7235.38	28.92	39.806	3.94	35.56	9.5	1	28.61	54	-25.39	A	V	1.0
9647.73	44.06	38.535	4.10	35.67	9.5	1	42.52	74	-31.48	P	V	1.0
9647.73	34.99	38.535	4.10	35.67	9.5	1	33.45	54	-20.55	A	V	1.0
12059.93*	---	42.60	15.20	35.30	9.5	1	---	---	---	---	V	1.0
14471.97*	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
16884.01	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19296.05*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
21708.09	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24120.13	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs+Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 24 of 41

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/6
Fundamental Frequency:	2437MHz (CH 6)	Test By:	Y. H. Liu
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2435.77	105.01	31.7642	2.42	35.32	9.5	0	94.38	Fundamental frequency		P	H	1.0
2435.77	103.02	31.7642	2.42	35.32	9.5	0	92.39			A	H	1.0
4873.81	51.11	34.7671	2.80	35.40	9.5	1	44.78	74	-29.22	P	H	1.0
4873.81	48.42	34.7671	2.80	35.40	9.5	1	42.09	54	-11.91	A	H	1.0
7311.62	41.29	39.7754	4.00	35.57	9.5	1	41.00	74	-33.00	P	H	1.0
7311.62	29.48	39.7754	4.00	35.57	9.5	1	29.19	54	-24.81	A	H	1.0
9747.83	47.08	38.5252	4.02	35.72	9.5	1	45.40	74	-28.60	P	H	1.0
9747.83	41.79	38.5252	4.02	35.72	9.5	1	40.11	54	-13.89	A	H	1.0
12185.10*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	H	1.0
14622.12	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
17059.14	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19496.16*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
21933.18	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24370.2	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “—” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 25 of 41

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/6
Fundamental Frequency:	2437MHz (CH 6)	Test By:	Y. H. Liu
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2435.77	108.65	31.764	2.42	35.32	9.5	0	98.02	Fundamental frequency		P	V	1.0
2435.77	105.74	31.764	2.42	35.32	9.5	0	95.11			A	V	1.0
4873.82	51.11	34.767	2.80	35.40	9.5	1	44.78	74	-29.22	P	V	1.1
4873.82	47.99	34.767	2.80	35.40	9.5	1	41.66	54	-12.34	A	V	1.1
7311.24	41.42	39.776	4.00	35.57	9.5	1	41.13	74	-32.87	P	V	1.0
7311.24	29.38	39.776	4.00	35.57	9.5	1	29.09	54	-24.91	A	V	1.0
9747.82	45.17	38.525	4.02	35.72	9.5	1	43.49	74	-30.51	P	V	1.2
9747.82	36.66	38.525	4.02	35.72	9.5	1	34.98	54	-19.02	A	V	1.0
12185.10*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	V	1.0
14622.12	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
17059.14	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19496.16*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
21933.18	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24370.20	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extrea plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 26 of 41

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/6
Fundamental Frequency:	2462MHz (CH 11)	Test By:	Y. H. Liu
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2461.05	103.25	31.739	2.49	35.32	9.5	0	92.65	Fundamental frequency	74	P	H	1.0
2461.05	100.66	31.739	2.49	35.32	9.5	0	90.06			A	H	2.0
4923.81	51.29	35.097	2.83	35.41	9.5	1	45.31	74	-28.69	P	H	1.0
4923.81	48.22	35.097	2.83	35.41	9.5	1	42.24	54	-11.76	A	H	1.0
7385.24	40.17	39.746	4.06	35.57	9.5	1	39.90	74	-34.10	P	H	1.0
7385.24	29.33	39.746	4.06	35.57	9.5	1	29.06	54	-24.94	A	H	1.0
9847.77	48.19	38.515	3.93	35.77	9.5	1	46.37	74	-27.63	P	H	1.0
9847.77	43.55	38.515	3.93	35.77	9.5	1	41.73	54	-12.27	A	H	1.0
14772.06	---	43.40	16.80	34.00	9.5	1	---	---	---	---	H	1.0
17234.08	---	45.20	17.60	34.30	9.5	1	---	---	---	---	H	1.0
19696.1*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	H	1.0
22158.12*	---	36.20	19.20	34.60	9.5	1	---	---	---	---	H	1.0
24620.14	---	36.80	21.00	34.20	9.5	1	---	---	---	---	H	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark "----" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 27 of 41

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Operation Mode:	Transmitting	Test Date :	2003/6/6
Fundamental Frequency:	2462MHz (CH 11)	Test By:	Y. H. Liu
Temperature :	30 °C	Humidity :	65%

Freq.	Reading	AF	Closs	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Pol.	Height
MHz	dBuV	dBuV	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	P/Q/A	H/V	Meter
2461.66	107.68	31.738	2.49	35.32	9.5	0	97.08	Fundamental frequency		P	V	1.0
2461.66	104.48	31.738	2.49	35.32	9.5	0	93.88			A	V	1.0
2483.7	103.21	31.74	2.49	35.32	9.5	0	106.76	74	32.76	P	V	1.0
2483.7	94.30	31.74	2.49	35.32	9.5	0	93.62	54	39.62	A	V	1.0
4923.81	50.63	35.097	2.83	35.41	9.5	1	44.65	74	-29.35	P	V	1.0
4923.81	47.15	35.097	2.83	35.41	9.5	1	41.17	54	-12.83	A	V	1.0
7385.33	40.22	39.746	4.06	35.57	9.5	1	39.95	74	-34.05	P	V	1.0
7385.33	28.69	39.746	4.06	35.57	9.5	1	28.42	54	-25.58	A	V	1.0
9847.78	48.12	38.515	3.93	35.77	9.5	1	46.30	74	-27.70	P	V	1.0
9847.78	42.78	38.515	3.93	35.77	9.5	1	40.96	54	-13.04	A	V	1.0
12310.04*	---	32.14	4.53	35.24	9.5	1	---	---	---	---	V	1.0
14772.06	---	43.40	16.80	34.00	9.5	1	---	---	---	---	V	1.0
17234.08	---	45.20	17.60	34.30	9.5	1	---	---	---	---	V	1.0
19696.1*	---	36.30	18.50	34.30	9.5	1	---	---	---	---	V	1.0
22158.12*	---	36.20	19.20	34.60	9.5	1	---	---	---	---	V	1.0
24620.14	---	36.80	21.00	34.20	9.5	1	---	---	---	---	V	1.0

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamp gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement
distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs+Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit

3.7 Photos of Open Site



For 10M test



For 10M test

3.7 Photos of Open Site



For 10M test



For 3M test



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 30 of 41

4. 6dB BANDWIDTH MEASUREMENT


4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2 Test Setup



4.3 Limits of 6db Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is $>500\text{KHz}$

4.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 200\text{KHz}$.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 31 of 41

4.6 Test Results

INPUT POWER (SYSTEM)	19VDC	ENVIRONMENTAL CONDITIONS	27°C, 70%RH,
TESTED BY : Y. H. Liu			

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.48	0.5	PASS
6	2437	8.33	0.5	PASS
11	2462	7.37	0.5	PASS




Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 32 of 41


4.7 Photo of 6db Bandwidth Measurement



Channel 1



Channel 6



Channel 11



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 33 of 41

5. MAXIMUM PEAK OUTPUT POWER


5.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.2 Test Setup



5.3 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 34 of 41

5.4 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

5.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

5.6 Test Results

INPUT POWER (SYSTEM)	19VDC	ENVIRONMENTAL CONDITIONS	27°C, 70%RH,
TESTED BY : Y. H. Liu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	15.68	30	PASS
6	2437	15.93	30	PASS
11	2462	15.43	30	PASS



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 35 of 41

6. POWER SPECTRAL DENSITY MEASUREMENT


6.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

6.2 Test Setup



6.3 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 36 of 41

6.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 30KHz VBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

6.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

6.6 Test Results

INPUT POWER (SYSTEM)	19VDC	ENVIRONMENTAL CONDITIONS	27°C, 70%RH,
TESTED BY : Y. H. Liu			

CHANNEL	CHANNEL FREQUENCY (MHz)	Final RF Power Level IN 3KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	0.27	8	PASS
6	2437	0.10	8	PASS
11	2462	-0.82	8	PASS

Note:

1. The measurement value of RF Power Level + 10dB attenuator = Final RF Power Level




Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 37 of 41


6.7 Photo of Power Spectral Density Measurement



Channel 1



Channel 6



Channel 11



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 38 of 41

7. OUT OF BAND MEASUREMENT


7.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ TEST RECEIVER	ESMI	842088/005 841978/008	SEPT. 3, 2002
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

3. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
4. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

7.2 Test Setup



7.3 Limits of Out of Band Emissions Measurement

1. Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 39 of 41

7.4 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100KHz with suitable frequency span including 100KHz bandwidth from band edge. The band edges were measured and recorded.

7.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

7.6 Test Results

A. Conducted

Refer to 7.7 photo of out band Emission measurement

B. Radiated

NOTE1: The band edge emission plot on the following first figure shows 51.10dB delta between carrier maximum power and local maximum emission in restrict band (2.3857GHz). The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 91.41dBuV/m, so the maximum field strength in restrict band is $91.41 - 51.10 = 40.31\text{ dBuV/m}$ which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second figure shows 59.06dB delta between carrier maximum power and local maximum emission in restrict band (2.4846GHz). The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 93.88dBuV/m, so the maximum field strength in restrict band is $93.88 - 46.7 = 47.17\text{ dBuV/m}$ which is under 54 dBuV/m limit.

INPUT POWER (SYSTEM)	19VDC	ENVIRONMENTAL CONDITIONS	27°C, 70%RH,
TESTED BY : Y. H. Liu			

CHANNEL FREQUENCY (MHz)	Required Limit (dBc)	PASS / FAIL
<2400	>20	PASS
>2483.5	>20	PASS




Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : Q8XV300TM
Report No. : EC03-06-030FRF
Page 40 of 41

7.7 Photo of Out Of Band Measurement



FRONT



BACK



8. ANTENNA REQUIREMENT

8.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.2 Antenna Connected Construction

The antenna used in this product is invert F type antenna. The invert F type antenna connector is U-FL-R-SMT And the maximum Gain of these antennas are only 3dBi.