



## FCC PART 15B

### MEASUREMENT AND TEST REPORT

For

## NINGBO BAIHUANG ELECTRIC APPLIANCES CO., LTD.

NO. 180, YANSHAN RD, HUXIMEN, HENGHE TOWN, CIXI, NINGBO, China

**FCC ID: Q92-BHD9829U**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Remote Control Lamp Holder
<b>Test Engineer:</b> <u>Phil Zhu</u> <i>Phil.zhu</i>	
<b>Report Number:</b> <u>RKS170103004-00A</u>	
<b>Report Date:</b> <u>2017-01-06</u> <i>Kamp Chen</i> <u>Kamp.chen</u>	
<b>Reviewed By:</b> <u>EMC Manager</u>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EUT EXERCISE SOFTWARE .....	5
SPECIAL ACCESSORIES.....	5
EQUIPMENT MODIFICATIONS .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF RADIATED TEST SETUP.....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>FCC §15.107 –CONDUCTED EMISSIONS .....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
MEASUREMENT UNCERTAINTY .....	8
EUT SETUP .....	8
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE .....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
CORRECTED FACTOR & MARGIN CALCULATION .....	9
TEST RESULTS SUMMARY.....	10
TEST DATA .....	10
<b>FCC §15.109 - RADIATED EMISSIONS .....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
MEASUREMENT UNCERTAINTY .....	13
EUT SETUP .....	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE .....	14
TEST EQUIPMENT LIST AND DETAILS.....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	15
TEST RESULTS SUMMARY.....	16
TEST DATA .....	16

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Manufacturer	NINGBO BAIHUANG ELECTRIC APPLIANCES CO., LTD.
Model	BHD9829U (FCC ID: Q92-BHD9829U)
Product	Remote Control Lamp Holder
Power input	AC :120V, rated power :60W
Output Voltage	AC :120V
Operation frequency	433.92MHz
Dimension	50mm×50mm×86.6mm

*Note: The product's series model number: BHD0312U-RF. The difference between them was explained in the attached declaration letter.*

*\*All measurement and test data in this report was gathered from production sample serial number: 20170103005 (Assigned by BACL, Kunshan). The EUT was received on 2017-01-03.*

### Objective

This report is prepared on behalf of NINGBO BAIHUANG ELECTRIC APPLIANCES CO., LTD. in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15, Class B.

### Related Submittal(s)/Grant(s)

FCC Part 15.231 submission with FCC ID: Q92-BH-V.  
FCC Part 15.231 submission with FCC ID: Q92-BH-U.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## **Test Facility**

The test site A used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## **SYSTEM TEST CONFIGURATION**

### **Justification**

The system was configured for testing in a typical fashion (as normally used by a typical user).

Test Mode : Normal operation

### **EUT Exercise Software**

No exercise software was used.

### **Special Accessories**

No special accessory was used.

### **Equipment Modifications**

No modification was made to the EUT tested.


### **Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number
NA	Lamp	Oppel 13III 90W	/
/	Testfixture	/	/

### **External I/O Cable**

Cable Description	Length (m)	From/Port	To
/	/	/	/

**Block Diagram of Radiated Test Setup**



## **SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Results</b>
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

## FCC §15.107 –CONDUCTED EMISSIONS

### Applicable Standard


According to FCC§15.107

### Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Item	Measurement Uncertainty	$U_{cispr}$
AMN	150kHz~30MHz	3.26 dB

### EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2016-11-25	2017-11-24
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2016-10-10	2017-10-09
ROHDE&SCHWARZ	LISN	ENV216	3560655016	2016-11-25	2017-11-24
Rohde & Schwarz	CE Test software	EMC 32	100357	--	--
MICRO-COAX	Coaxial Cable	Cable-6	006	2016-09-08	2017-09-07

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107 Class B, the worst margin reading as below:

**8.54 dB at 0.160000 MHz** in the **Line** conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## Test Data


### Environmental Conditions

<b>Temperature:</b>	22°C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Phil Zhu on 2017-01-04.*

Test Mode : Normal operation

**Line**



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Corr. (dB)
0.160000	---	38.70	55.46	16.76	L1	10.3
0.160000	56.92	---	65.46	8.54	L1	10.3
0.260000	---	34.38	51.43	17.05	L1	10.3
0.260000	47.53	---	61.43	13.90	L1	10.3
0.345000	---	26.77	49.08	22.31	L1	10.3
0.345000	39.74	---	59.08	19.34	L1	10.3
0.510000	---	19.00	46.00	27.00	L1	10.3
0.510000	35.85	---	56.00	20.15	L1	10.3
0.675000	---	18.09	46.00	27.91	L1	10.3
0.675000	37.35	---	56.00	18.65	L1	10.3
0.810000	---	22.03	46.00	23.97	L1	10.3
0.810000	40.94	---	56.00	15.06	L1	10.3

**Neutral**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Corr. (dB)
0.160000	---	38.46	55.46	17.00	N	10.3
0.160000	56.84	---	65.46	8.62	N	10.3
0.260000	---	34.31	51.43	17.12	N	10.3
0.260000	47.53	---	61.43	13.90	N	10.3
0.430000	---	23.07	47.25	24.18	N	10.3
0.430000	37.31	---	57.25	19.94	N	10.3
0.510000	---	18.90	46.00	27.10	N	10.3
0.510000	36.98	---	56.00	19.02	N	10.3
0.675000	---	17.41	46.00	28.59	N	10.3
0.675000	37.90	---	56.00	18.10	N	10.3
0.810000	---	23.87	46.00	22.13	N	10.3
0.810000	43.16	---	56.00	12.84	N	10.3

## FCC §15.109 - RADIATED EMISSIONS

### Applicable Standard

FCC §15.109


### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Item		Measurement Uncertainty	$U_{cisp}$
Radiated Emission	30MHz~1GHz	5.91dB	6.3 dB
	1GHz~6GHz	4.68dB	5.2 dB
	6 GHz ~18 GHz	4.92dB	5.5 dB
	18GHz up	4.88dB	NA

### EUT Setup

#### Below 1G



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

**Above 1GHz:****EMI Test Receiver Setup**

The system was investigated from 30 MHz to 2 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
1GHz-2GHz	1MHz	3MHz	-	PK
	1MHz	1Hz	-	AV

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz, Peak and average detection mode above 1 GHz.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	330	171377	2016-12-12	2017-12-11
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-24
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Champrotek	Chamber	Chamber A	T-KSEMC049	-	-
R&S	Auto test Software	EMC32	100361	-	-
ETS	Horn Antenna	3115	6229	2016-01-11	2019-01-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-12-12	2017-12-11
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-11
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-11
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-11
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-11
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-11

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, with the worst margin reading of:

**14.38 dB at 30.955850 MHz** in the **Vertical** polarization mode

Refer to CISPR16-4-2:2011+A1-2014 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\lim} + U_{\text{cisp}}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{\text{cisp}}$ , if  $L_m$  is less than  $L_{\lim}$ , it implies that the EUT complies with the limit.

## Test Data


### Environmental Conditions

<b>Temperature:</b>	27 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Phil Zhu on 2017-01-04.*

*Test Mode: Normal operation*

**30MHz ~ 1GHz**



Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
30.955850	25.62	40.00	14.38	100.0	V	211.0	-5.5
38.658350	19.56	40.00	20.44	100.0	V	259.0	-9.6
45.092050	11.97	40.00	28.03	100.0	H	273.0	-13.4
49.537300	20.90	40.00	19.10	100.0	V	22.0	-16.2
57.573350	10.08	40.00	29.92	199.0	V	148.0	-16.7
725.613300	14.92	46.00	31.08	100.0	V	246.0	-2.3

**Above 1GHz**

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB /m)
1294.619238	34.21	---	74.00	39.79	149.0	V	0.0	-10.2
1294.619238	---	20.79	54.00	33.21	149.0	V	0.0	-10.2
1308.026052	---	23.56	54.00	30.44	149.0	V	39.0	-7.0
1308.026052	37.00	---	74.00	37.00	149.0	V	39.0	-7.0
1338.026052	40.07	---	74.00	33.93	149.0	V	49.0	-3.5
1338.026052	---	25.85	54.00	28.15	149.0	V	49.0	-3.5
1557.905811	---	28.90	54.00	25.10	149.0	V	104.0	0.3
1557.905811	42.32	---	74.00	31.68	149.0	V	104.0	0.3
1872.126107	43.91	---	74.00	30.09	149.0	H	216.0	1.7
1872.126107	---	30.07	54.00	23.93	149.0	H	216.0	1.7
1958.066133	50.18	---	74.00	23.82	149.0	V	30.0	8.1
1958.066133	---	36.17	54.00	17.83	149.0	V	30.0	8.1

**\*\*\*\*\* END OF REPORT \*\*\*\*\***