



TEST REPORT

Report No. : AF001283-001 Date : 2005 January 18

Application No.: LF200153(0)

Applicant : AVC Technology Limited
6/F., Enterprise Square Three,
39 Wang Chiu Road,
Kowloon Bay, Hong Kong

Sample Description : One(1) submitted sample stated to be:
Model Name : Digital Audio Player
Model No. : DFP3011 (128 MB) / DFP3012 (256 MB)
Rating : 3.7V Internal rechargeable battery / DC 5V (USB)
No. of sample(s) : Two (2) piece(s) ***

Date Received : 2004 November 30

Test Period : 2004 December 01 – 2005 January 14

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 18.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart B.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Danny Chui
EMC Engineer - EL. Division

Page 1 of 18

FCC ID: Q93-F023

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Related Submittal Grants	3
1.3	Location of the test site	4
1.4	List of measuring equipment	5
1.5	List of support equipment	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Result	7
2.3	Radiated Emission Measurement Data	8
2.3	Radiated Emission Measurement Data	9
2.3	Radiated Emission Measurement Data	10
2.3	Radiated Emission Measurement Data	11
2.3	Radiated Emission Measurement Data	12
2.3	Radiated Emission Measurement Data	13
2.3	Radiated Emission Measurement Data	14
2.3	Radiated Emission Measurement Data	15
3	Description of the Line-conducted Test	16
3.1	Test Procedure	16
3.2	Test Result	16
3.3	Graph and Table of Conducted Emission Measurement Data	16
4	Photograph	17
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	17
4.2	Photographs of the External and Internal Configurations of the EUT	17
5	Supplementary document	17
6	Appendices	18



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

1 General Information

1.1 General Description

The equipment under test (EUT) is a standalone multi-function product and is powered by one 1.5 V AAA size battery with built-in 128 MB/ 256MB memory. Controlled by a 24.000 MHz crystal, the digital audio player has three different features:

1. Music Player (supports MP3, WMA and WAV file formats)
2. Voice recording
3. USB interface for uploading and downloading files and as mass storage through a USB connection cable

A brief circuit description is saved with filename : OpDes.pdf

1.2 Related Submittal Grants

This is a single application for certification of a computer peripheral product.



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6112B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
LISN	R&S	ESH3-Z5	100010	20-70405
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

1.5 List of support equipment

1. Intel CPU PIII 800EB / 256 cache / 133MHz
Model: L103A455-0041 SL4MB
2. Intel Mother Board
Model: Intel Type: D815EEA
3. IBM Hard-disk
Model: DTLA-30720, 20.5GB
4. Proview LCD Monitor
Model: 568
S/N: FYUJ240040133
5. IBM Mouse
Model: 12J3618
S/N: 23-005077
6. Acer Keyboard
Model: 6511-VA
7. Hewlett Packard LaserJet 2100TN
Model: C4172A
S/N: SGGS038577
8. PenPower Handwriting System
Model: PP403N
S/N: PT9122239
9. Panasonic 64 MB SD Memory Card
Model: RP_SD064B
S/N: BP3 AA 014349
10. USB cable
(Provided by Applicant)



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

2.2 Test Result

All modes had been test. The measurement data based on measurements employing the CISPR quasi-peak detector were indicated in next page.

All other measurement were 20 dB below the 15.109 limits. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP 3011
Mode : MP3 playback

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
184.507	H	23.1	10.5	33.6	43.5	-9.9
189.008	H	25.5	10.5	36.0	43.5	-7.5
193.508	H	25.9	10.5	36.4	43.5	-7.1
198.008	H	23.2	10.5	33.7	43.5	-9.8
202.508	H	23.9	10.1	34.0	43.5	-9.5
205.509	H	19.3	10.1	29.4	43.5	-14.1
285.012	H	13.8	14.2	28.0	46.0	-18.0
300.012	H	11.4	15.6	27.0	46.0	-19.0
312.013	H	10.3	15.6	25.9	46.0	-20.1
336.013	H	10.2	15.6	25.8	46.0	-20.2



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3011
Mode : Voice recording

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
180.007	H	19.4	10.5	29.9	43.5	-13.6
184.507	H	23.2	10.5	33.7	43.5	-9.8
189.008	H	24.7	10.5	35.2	43.5	-8.3
193.508	H	25.1	10.5	35.6	43.5	-7.9
198.008	H	22.3	10.5	32.8	43.5	-10.7
201.009	H	20.5	10.1	30.6	43.5	-12.9
205.509	H	19.1	10.1	29.2	43.5	-14.3
288.012	H	18.6	14.2	32.8	46.0	-13.2
388.516	H	20.1	15.6	35.7	46.0	-10.3
396.016	H	22.7	15.6	38.3	46.0	-7.7



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3011
Mode : USB (PC connected)

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
72.010	H	24.5	6.3	30.8	40.0	-9.2
84.012	H	22.0	8.0	30.0	40.0	-10.0
144.012	H	18.9	12.4	31.3	43.5	-12.2
204.008	H	19.7	10.1	29.8	43.5	-13.7
216.009	H	19.4	10.1	29.5	46.0	-16.5
228.011	H	18.2	10.1	28.3	46.0	-17.7
254.412	H	12.9	14.2	27.1	46.0	-18.9
288.047	H	15.7	14.2	29.9	46.0	-16.1
360.021	H	15.6	15.6	31.2	46.0	-14.8
480.024	H	13.7	18.7	32.4	46.0	-13.6



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3011
Mode : FM

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
152.453	H	10.3	11.8	22.1	43.5	-21.4
184.432	H	20.4	10.5	30.9	43.5	-12.6
216.443	H	26.4	10.1	36.5	46.0	-9.5
304.908	H	17.7	15.6	33.3	46.0	-12.7
368.864	H	26.4	15.6	42.0	46.0	-4.0
432.884	H	23.5	18.7	42.2	46.0	-3.8
457.361	H	1.4	18.7	20.1	46.0	-25.9
553.296	H	9.6	20.6	30.2	46.0	-15.8
649.329	H	8.2	22.0	30.2	46.0	-15.8



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3012
Mode : MP3 playback

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
181.499	H	19.3	10.5	29.8	43.5	-13.7
182.999	H	17.4	10.5	27.9	43.5	-15.6
184.498	H	22.5	10.5	33.0	43.5	-10.5
188.999	H	24.6	10.5	35.1	43.5	-8.4
209.998	H	17.7	10.1	27.8	43.5	-15.7
230.999	H	15.1	10.1	25.2	46.0	-20.8
263.999	H	11.1	14.2	25.3	46.0	-20.7
272.998	H	10.3	14.2	24.5	46.0	-21.5
335.997	H	12.8	15.6	28.4	46.0	-17.6
356.997	H	14.6	15.6	30.2	46.0	-15.8



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3012
Mode : PC connected (USB)

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
72.012	H	26.9	6.3	33.2	40.0	-6.8
84.013	H	20.0	8.0	28.0	40.0	-12.0
144.026	H	16.6	12.4	29.0	43.5	-14.5
204.010	H	20.3	10.1	30.4	43.5	-13.1
216.033	H	21.7	10.1	31.8	46.0	-14.2
239.998	H	25.9	10.1	36.0	46.0	-10.0
252.011	H	20.5	14.2	34.7	46.0	-11.3
288.047	H	19.7	14.2	33.9	46.0	-12.1
360.063	H	17.3	15.6	32.9	46.0	-13.1
479.997	H	16.2	18.7	34.9	46.0	-11.1



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3012
Mode : FM

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
152.454	H	11.2	11.8	23.0	43.5	-20.5
184.825	H	16.5	10.5	27.0	43.5	-16.5
216.442	H	28.5	10.1	38.6	46.0	-7.4
304.909	H	13.2	15.6	28.8	46.0	-17.2
369.653	H	21.6	15.6	37.2	46.0	-8.8
432.888	H	23.8	18.7	42.5	46.0	-3.5
457.364	H	1.6	18.7	20.3	46.0	-25.7
554.475	H	9.5	20.6	30.1	46.0	-15.9
649.331	H	10.6	22.0	32.6	46.0	-13.4



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Model : DFP3012
Mode : Voice recording

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
184.499	H	21.5	10.5	32.0	43.5	-11.5
188.999	H	24.6	10.5	35.1	43.5	-8.4
190.499	H	18.4	10.5	28.9	43.5	-14.6
215.999	H	14.4	10.1	24.5	43.5	-19.0
217.500	H	17.2	10.1	27.3	46.0	-18.7
239.996	H	15.9	10.1	26.0	46.0	-20.0
242.000	H	16.0	10.1	26.1	46.0	-19.9
283.500	H	15.3	14.2	29.5	46.0	-16.5
288.000	H	14.8	14.2	29.0	46.0	-17.0
323.999	H	9.7	15.6	25.3	46.0	-20.7



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The PC connected mode had been tested. The EUT connecting with an USB cable and earphone produced the maximum emission. The measurement data was indicated in Appendix.

The result showed that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the document are saved with filename TestRpt2.pdf



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp1.jpg, LabelSmp2jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf



TEST REPORT

Report No. : AF001283-001

Date : 2005 January 18

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of the set-up of Conducted Emissions	2 pages
A3.	Photos of External Configurations	1 page
A4.	Photos of Internal Configurations	1 page
A5.	ID Label/Location	1 page
A6.	Conducted Emission Measurement Data	4 pages
A7.	Block Diagram	1 page
A8.	Schematics Diagram	1 page
A9.	User Manual	14 pages
A10.	Operation Description	1 page

***** End of Report *****