

Appendix B

Highest Test Plots

Table of Contents

1. 2.4G Head-worn 0mm SAR 3

1. 2.4G Head-worn 0mm SAR

Date: 17.04.2025

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q25030625-1E

Serial: S25030625-004

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz;Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): f = 2480 MHz; $\sigma = 1.74 \text{ S/m}$; $\epsilon_r = 37.94$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ComF(7.95, 7.95, 7.95) @ 2402 MHz; Calibrated: 29.04.2024
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), z = 1.0, 31.0
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/Top side 3DHS 2480 MHz/Area Scan (5x9x1): Measurement grid: dx=10mm, dy=10mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.361 W/kg

Configuration/Top side 3DHS 2480 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.887 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.731 W/kg

SAR(1 g) = 0.255 W/kg; SAR(10 g) = 0.092 W/kg

Smallest distance from peaks to all points 3 dB below = 5.8 mm

Ratio of SAR at M2 to SAR at M1 = 37.4%

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.526 W/kg

