

Radio Exposure Evaluation Report

FCC ID : Q9DAPEX0565567

Equipment : Wireless Access Point

Brand Name : aruba 、 Hewlett Packard Enterprise

Model Name : APEX0565,APEX0567

Applicant : Hewlett Packard Enterprise Company
3333 Scott Blvd Santa Clara, CA. 95054

Manufacturer : Hewlett Packard Enterprise Company
3333 Scott Blvd Santa Clara, CA. 95054

Standard : 47 CFR Part 2.1091

The product was received on Apr. 30, 2020, and testing was started from May 15, 2020 and completed on Jun. 30, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
1 GENERAL DESCRIPTION	5
1.1 EUT General Information	5
1.2 Table for Multiple Listing	5
1.3 Testing Location	5
2 MAXIMUM PERMISSIBLE EXPOSURE	6
2.1 Limit of Maximum Permissible Exposure	6
2.2 MPE Calculation Method	6
2.3 Calculated Result and Limit	7
Photographs of EUT V02	



History of this test report

Report No.	Version	Description	Issued Date
FA042903	01	Initial issue of report	Jul. 31, 2020
FA042903	02	1. The Model Name was changed 2. Photographs of EUT was updated This report is the latest version replacing for the report issued on Jul. 31, 2020	Aug. 07, 2020
FA042903	03	The section 2.3 was updated This report is the latest version replacing for the report issued on Jul. 31, 2020	Aug. 10, 2020
FA042903	04	Change to outdoor use only This report is the latest version replacing for the report issued on Aug. 10, 2020	Aug. 21, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None.

Reviewed by: Sam Tsai

Report Producer: Jenny Yang

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)
ZigBee	2400-2483.5	2405-2480	DSSS (O-QPSK)

1.2 Table for Multiple Listing

Sample Number	Model Name	Description
1	APEX0565	There are two Samples for EUT. The only difference between Sample 1 and Sample 2 is the Antenna.
2	APEX0567	

1.3 Testing Location

Testing Location			
☒	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
☐	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

WLAN 2.4GHz + WLAN 5GHz + Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;G1D	6.80	21.98	28.78	1.00	29.78	0.95060	20	0.18912	1.00000	0.18912
5.8G;D1D	7.10	21.98	29.08	1.00	30.08	1.01859	20	0.20264	1.00000	0.20264
2.4G;BT-LE	3.30	7.54	10.84	1.00	11.84	0.01528	20	0.00304	1.00000	0.00304
									Sum Ratio	0.39480
									Ratio Limit	1

Note: Tune-up EIRP = Power + Tolerance + DG

ZigBee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;G1D	3.01	7.54	10.55	1.00	11.55	0.01429	20	0.00284	1.00000

Note: Tune-up EIRP = Power + Tolerance + DG

—————THE END—————