


### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2403.784 MHz : -1.579 dBm M2 : 2412.040 MHz : 5.789 dBm Delta1 : 16.433 MHz : 3.221 dB T1 : 2403.784 MHz : -1.579 dBm T2 : 2420.297 MHz : -1.182 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.433 MHz Limit: $\geq 0.5$ MHz Margin: -15.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2428.784 MHz : -1.404 dBm M2 : 2438.323 MHz : 6.043 dBm Delta1 : 16.433 MHz : 1.952 dB T1 : 2428.784 MHz : -1.404 dBm T2 : 2445.297 MHz : -1.632 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.433 MHz Limit: $\geq 0.5$ MHz Margin: -15.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2428.784 MHz : -1.274 dBm M2 : 2437.040 MHz : 7.217 dBm Delta1 : 16.353 MHz : 2.518 dB T1 : 2428.784 MHz : -1.274 dBm T2 : 2445.297 MHz : -1.575 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.353 MHz Limit: $\geq 0.5$ MHz Margin: -15.85 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2428.784 MHz : -1.713 dBm M2 : 2437.040 MHz : 6.412 dBm Delta1 : 16.433 MHz : 3.455 dB T1 : 2428.784 MHz : -1.713 dBm T2 : 2445.297 MHz : -1.089 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.433 MHz Limit: $\geq 0.5$ MHz Margin: -15.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2453.784 MHz : -1.579 dBm M2 : 2463.323 MHz : 5.938 dBm Delta1 : 16.433 MHz : 2.455 dB T1 : 2453.784 MHz : -1.579 dBm T2 : 2470.297 MHz : -1.646 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.433 MHz Limit: $\geq 0.5$ MHz Margin: -15.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2453.784 MHz : -1.447 dBm M2 : 2462.040 MHz : 6.639 dBm Delta1 : 16.433 MHz : 2.725 dB T1 : 2453.784 MHz : -1.447 dBm T2 : 2470.297 MHz : -1.189 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.433 MHz Limit: $\geq 0.5$ MHz Margin: -15.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2453.784 MHz : -1.622 dBm M2 : 2462.040 MHz : 5.980 dBm Delta1 : 16.433 MHz : 3.014 dB T1 : 2453.784 MHz : -1.622 dBm T2 : 2470.297 MHz : -1.479 dBm OBW : 16.513 MHz	Measured 6 dB Bandwidth: 16.433 MHz Limit: $\geq 0.5$ MHz Margin: -15.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2403.804 MHz : -4.345 dBm M2 : 2425.768 MHz : 1.783 dBm Delta1 : 36.393 MHz : 1.060 dB T1 : 2403.964 MHz : -4.093 dBm T2 : 2440.196 MHz : -3.285 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.393 MHz Limit: $\geq 0.5$ MHz Margin: -35.89 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2404.285 MHz : -4.257 dBm M2 : 2422.080 MHz : 3.998 dBm Delta1 : 35.271 MHz : 5.235 dB T1 : 2403.964 MHz : -4.471 dBm T2 : 2440.196 MHz : -2.982 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 35.271 MHz Limit: $\geq 0.5$ MHz Margin: -34.77 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2404.285 MHz : -4.196 dBm M2 : 2422.080 MHz : 2.798 dBm Delta1 : 35.591 MHz : 1.243 dB T1 : 2403.964 MHz : -5.152 dBm T2 : 2440.196 MHz : -3.552 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 35.591 MHz Limit: $\geq 0.5$ MHz Margin: -35.09 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2418.643 MHz : -6.659 dBm M2 : 2442.050 MHz : 3.143 dBm Delta1 : 36.553 MHz : 5.206 dB T1 : 2418.964 MHz : -2.506 dBm T2 : 2455.196 MHz : -1.453 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2419.285 MHz : -0.957 dBm M2 : 2437.080 MHz : 5.667 dBm Delta1 : 35.591 MHz : 0.700 dB T1 : 2418.964 MHz : -2.136 dBm T2 : 2455.196 MHz : -0.737 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 35.591 MHz Limit: $\geq 0.5$ MHz Margin: -35.09 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2419.285 MHz : -1.953 dBm M2 : 2437.080 MHz : 4.268 dBm Delta1 : 35.912 MHz : 0.972 dB T1 : 0 Hz : 500.000 dBm T2 : 0 Hz : 500.000 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 35.912 MHz Limit: $\geq 0.5$ MHz Margin: -35.41 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2433.643 MHz : -6.554 dBm M2 : 2469.555 MHz : 3.251 dBm Delta1 : 36.553 MHz : 5.265 dB T1 : 2433.964 MHz : -2.142 dBm T2 : 2470.196 MHz : -1.288 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2434.285 MHz : -1.010 dBm M2 : 2452.080 MHz : 5.932 dBm Delta1 : 35.591 MHz : 1.037 dB T1 : 2433.964 MHz : -1.872 dBm T2 : 2470.196 MHz : -0.542 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 35.591 MHz Limit: $\geq 0.5$ MHz Margin: -35.09 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2434.285 MHz : -1.730 dBm M2 : 2452.080 MHz : 4.856 dBm Delta1 : 35.591 MHz : 0.671 dB T1 : 2433.964 MHz : -2.862 dBm T2 : 2470.196 MHz : -1.412 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 35.591 MHz Limit: $\geq 0.5$ MHz Margin: -35.09 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.501 dBm M2 : 5747.525 MHz : 7.483 dBm Delta1 : 17.715 MHz : 1.562 dB T1 : 5736.142 MHz : 0.501 dBm T2 : 5753.938 MHz : 0.485 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5745.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.662 dBm M2 : 5747.525 MHz : 8.268 dBm Delta1 : 17.715 MHz : 2.621 dB T1 : 5736.142 MHz : 0.662 dBm T2 : 5753.938 MHz : 1.378 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5745.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.504 dBm M2 : 5746.242 MHz : 8.053 dBm Delta1 : 17.715 MHz : 1.859 dB T1 : 5736.142 MHz : 0.504 dBm T2 : 5753.938 MHz : 0.495 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5785.000 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 1.012 dBm M2 : 5787.525 MHz : 7.664 dBm Delta1 : 17.715 MHz : 1.033 dB T1 : 5776.142 MHz : 1.012 dBm T2 : 5793.938 MHz : 0.851 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5785.000 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 0.782 dBm M2 : 5787.525 MHz : 8.002 dBm Delta1 : 17.715 MHz : 2.286 dB T1 : 5776.142 MHz : 0.782 dBm T2 : 5793.938 MHz : 1.036 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5785.000 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 1.321 dBm M2 : 5786.242 MHz : 8.085 dBm Delta1 : 17.715 MHz : 1.440 dB T1 : 5776.142 MHz : 1.321 dBm T2 : 5793.938 MHz : 1.195 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.658 dBm M2 : 5827.525 MHz : 7.752 dBm Delta1 : 17.715 MHz : 1.810 dB T1 : 5816.142 MHz : 0.658 dBm T2 : 5833.938 MHz : 1.287 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5825.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.941 dBm M2 : 5830.010 MHz : 7.750 dBm Delta1 : 17.715 MHz : 2.028 dB T1 : 5816.142 MHz : 0.941 dBm T2 : 5833.938 MHz : 1.297 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11a, Channel: 5825.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.955 dBm M2 : 5826.242 MHz : 8.136 dBm Delta1 : 17.715 MHz : 1.961 dB T1 : 5816.062 MHz : -0.180 dBm T2 : 5834.018 MHz : -3.379 dBm OBW : 17.956 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.188 dBm M2 : 5747.525 MHz : 7.479 dBm Delta1 : 17.715 MHz : 1.381 dB T1 : 5736.142 MHz : 0.188 dBm T2 : 5753.938 MHz : 0.388 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.788 dBm M2 : 5747.525 MHz : 8.252 dBm Delta1 : 17.715 MHz : 2.766 dB T1 : 5736.142 MHz : 0.788 dBm T2 : 5753.938 MHz : 1.433 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.182 dBm M2 : 5746.242 MHz : 8.006 dBm Delta1 : 17.715 MHz : 2.068 dB T1 : 5736.142 MHz : 0.182 dBm T2 : 5753.938 MHz : 0.534 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 0.786 dBm M2 : 5787.525 MHz : 7.632 dBm Delta1 : 17.715 MHz : 1.391 dB T1 : 5776.142 MHz : 0.786 dBm T2 : 5793.938 MHz : 0.855 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 1.045 dBm M2 : 5787.525 MHz : 7.949 dBm Delta1 : 17.715 MHz : 2.131 dB T1 : 5776.142 MHz : 1.045 dBm T2 : 5793.938 MHz : 1.177 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 0.699 dBm M2 : 5786.242 MHz : 8.071 dBm Delta1 : 17.715 MHz : 1.826 dB T1 : 5776.142 MHz : 0.699 dBm T2 : 5793.938 MHz : 0.965 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.774 dBm M2 : 5823.758 MHz : 7.727 dBm Delta1 : 17.715 MHz : 1.706 dB T1 : 5816.062 MHz : -0.495 dBm T2 : 5833.938 MHz : 1.307 dBm OBW : 17.876 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.123 dBm M2 : 5830.010 MHz : 7.422 dBm Delta1 : 17.715 MHz : 2.992 dB T1 : 5816.142 MHz : 0.123 dBm T2 : 5833.938 MHz : 0.548 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.589 dBm M2 : 5823.758 MHz : 7.937 dBm Delta1 : 17.715 MHz : 2.927 dB T1 : 5816.062 MHz : -0.934 dBm T2 : 5834.098 MHz : -5.291 dBm OBW : 18.036 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.188 dBm M2 : 5747.525 MHz : 7.479 dBm Delta1 : 17.715 MHz : 1.381 dB T1 : 5736.142 MHz : 0.188 dBm T2 : 5753.938 MHz : 0.388 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.788 dBm M2 : 5747.525 MHz : 8.252 dBm Delta1 : 17.715 MHz : 2.766 dB T1 : 5736.142 MHz : 0.788 dBm T2 : 5753.938 MHz : 1.433 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.142 MHz : 0.182 dBm M2 : 5746.242 MHz : 8.006 dBm Delta1 : 17.715 MHz : 2.068 dB T1 : 5736.142 MHz : 0.182 dBm T2 : 5753.938 MHz : 0.534 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 0.786 dBm M2 : 5787.525 MHz : 7.632 dBm Delta1 : 17.715 MHz : 1.391 dB T1 : 5776.142 MHz : 0.786 dBm T2 : 5793.938 MHz : 0.855 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 1.045 dBm M2 : 5787.525 MHz : 7.949 dBm Delta1 : 17.715 MHz : 2.131 dB T1 : 5776.142 MHz : 1.045 dBm T2 : 5793.938 MHz : 1.177 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.142 MHz : 0.699 dBm M2 : 5786.242 MHz : 8.071 dBm Delta1 : 17.715 MHz : 1.826 dB T1 : 5776.142 MHz : 0.699 dBm T2 : 5793.938 MHz : 0.965 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.774 dBm M2 : 5823.758 MHz : 7.727 dBm Delta1 : 17.715 MHz : 1.706 dB T1 : 5816.062 MHz : -0.495 dBm T2 : 5833.938 MHz : 1.307 dBm OBW : 17.876 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.123 dBm M2 : 5830.010 MHz : 7.422 dBm Delta1 : 17.715 MHz : 2.992 dB T1 : 5816.142 MHz : 0.123 dBm T2 : 5833.938 MHz : 0.548 dBm OBW : 17.796 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.142 MHz : 0.589 dBm M2 : 5823.758 MHz : 7.937 dBm Delta1 : 17.715 MHz : 2.927 dB T1 : 5816.062 MHz : -0.934 dBm T2 : 5834.098 MHz : -5.291 dBm OBW : 18.036 MHz	Measured 6 dB Bandwidth: 17.715 MHz Limit: $\geq 0.5$ MHz Margin: -17.22 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.643 MHz : -8.008 dBm M2 : 5758.768 MHz : 1.289 dBm Delta1 : 36.553 MHz : 4.340 dB T1 : 5736.964 MHz : -4.166 dBm T2 : 5773.196 MHz : -3.668 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.643 MHz : -7.599 dBm M2 : 5749.950 MHz : 2.462 dBm Delta1 : 36.553 MHz : 5.701 dB T1 : 5736.964 MHz : -2.537 dBm T2 : 5773.196 MHz : -1.898 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.643 MHz : -9.055 dBm M2 : 5749.950 MHz : 1.250 dBm Delta1 : 36.553 MHz : 6.010 dB T1 : 5736.964 MHz : -4.530 dBm T2 : 5773.196 MHz : -3.045 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.643 MHz : -8.215 dBm M2 : 5798.768 MHz : 1.093 dBm Delta1 : 36.553 MHz : 4.029 dB T1 : 5776.964 MHz : -4.054 dBm T2 : 5813.196 MHz : -4.186 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.643 MHz : -7.137 dBm M2 : 5789.950 MHz : 2.220 dBm Delta1 : 36.553 MHz : 4.678 dB T1 : 5776.804 MHz : -2.319 dBm T2 : 5813.196 MHz : -2.460 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.643 MHz : -8.052 dBm M2 : 5789.950 MHz : 1.498 dBm Delta1 : 36.553 MHz : 5.363 dB T1 : 5776.964 MHz : -4.436 dBm T2 : 5813.196 MHz : -2.689 dBm OBW : 36.232 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.643 MHz : -4.070 dBm M2 : 5758.768 MHz : 5.098 dBm Delta1 : 36.553 MHz : 3.964 dB T1 : 5736.804 MHz : -0.408 dBm T2 : 5773.196 MHz : -0.107 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-40, Channel: 5755.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.643 MHz : -3.533 dBm M2 : 5749.950 MHz : 6.090 dBm Delta1 : 36.553 MHz : 4.698 dB T1 : 5736.804 MHz : 1.199 dBm T2 : 5773.196 MHz : 1.164 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-40, Channel: 5755.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.643 MHz : -3.916 dBm M2 : 5749.950 MHz : 5.429 dBm Delta1 : 36.553 MHz : 5.147 dB T1 : 5736.804 MHz : 0.811 dBm T2 : 5773.196 MHz : 1.232 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.643 MHz : -3.759 dBm M2 : 5798.768 MHz : 5.114 dBm Delta1 : 36.553 MHz : 3.811 dB T1 : 5776.804 MHz : -0.225 dBm T2 : 5813.196 MHz : 0.052 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-40, Channel: 5795.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.643 MHz : -3.682 dBm M2 : 5789.950 MHz : 5.856 dBm Delta1 : 36.553 MHz : 4.907 dB T1 : 5776.804 MHz : 0.538 dBm T2 : 5813.196 MHz : 1.226 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-40, Channel: 5795.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.643 MHz : -3.771 dBm M2 : 5789.950 MHz : 5.476 dBm Delta1 : 36.553 MHz : 5.074 dB T1 : 5776.804 MHz : 0.398 dBm T2 : 5813.196 MHz : 1.303 dBm OBW : 36.393 MHz	Measured 6 dB Bandwidth: 36.553 MHz Limit: $\geq 0.5$ MHz Margin: -36.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.683 MHz : -4.973 dBm M2 : 5778.687 MHz : 1.457 dBm Delta1 : 76.313 MHz : 1.306 dB T1 : 5737.004 MHz : -4.038 dBm T2 : 5812.996 MHz : -3.668 dBm OBW : 75.992 MHz	Measured 6 dB Bandwidth: 76.313 MHz Limit: $\geq 0.5$ MHz Margin: -75.81 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5737.004 MHz : -3.623 dBm M2 : 5775.160 MHz : 2.952 dBm Delta1 : 76.313 MHz : 0.807 dB T1 : 5737.004 MHz : -3.623 dBm T2 : 5812.996 MHz : -3.080 dBm OBW : 75.992 MHz	Measured 6 dB Bandwidth: 76.313 MHz Limit: $\geq 0.5$ MHz Margin: -75.81 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### 6 dB & 99% BANDWIDTH

Variant: 802.11ac-80, Channel: 5775.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5737.004 MHz : -4.005 dBm M2 : 5789.910 MHz : 2.309 dBm Delta1 : 76.313 MHz : 1.676 dB T1 : 5737.325 MHz : 0.270 dBm T2 : 5812.996 MHz : -2.051 dBm OBW : 75.671 MHz	Measured 6 dB Bandwidth: 76.313 MHz Limit: $\geq 0.5$ MHz Margin: -75.81 MHz

[Back to the Matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### A.1.2. Peak Output Power



#### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2404.004 MHz : -9.031 dBm M2 : 2413.503 MHz : 11.954 dBm Delta1 : 15.992 MHz : 1.226 dB	Channel Power: 20.97 dBm Limit: 25.23 dBm Margin: -4.26 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2412.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2404.124 MHz : -7.182 dBm M2 : 2413.503 MHz : 12.873 dBm Delta1 : 15.872 MHz : 0.334 dB	Channel Power: 21.73 dBm Limit: 25.23 dBm Margin: -3.50 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2412.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2404.004 MHz : -9.358 dBm M2 : 2413.022 MHz : 11.850 dBm Delta1 : 15.992 MHz : 1.605 dB	Channel Power: 20.77 dBm Limit: 25.23 dBm Margin: -4.46 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2429.004 MHz : -9.482 dBm M2 : 2435.617 MHz : 11.783 dBm Delta1 : 15.992 MHz : 1.599 dB	Channel Power: 20.80 dBm Limit: 25.23 dBm Margin: -4.43 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2437.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2429.004 MHz : -8.736 dBm M2 : 2435.497 MHz : 12.641 dBm Delta1 : 15.992 MHz : 1.517 dB	Channel Power: 21.56 dBm Limit: 25.23 dBm Margin: -3.67 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2437.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2429.124 MHz : -8.384 dBm M2 : 2435.497 MHz : 11.736 dBm Delta1 : 15.872 MHz : 0.484 dB	Channel Power: 20.68 dBm Limit: 25.23 dBm Margin: -4.55 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2454.124 MHz : -8.014 dBm M2 : 2460.617 MHz : 12.033 dBm Delta1 : 15.752 MHz : 1.204 dB	Channel Power: 20.90 dBm Limit: 25.23 dBm Margin: -4.33 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2462.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2454.124 MHz : -7.644 dBm M2 : 2463.503 MHz : 12.602 dBm Delta1 : 15.872 MHz : 0.755 dB	Channel Power: 21.53 dBm Limit: 25.23 dBm Margin: -3.70 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11b, Channel: 2462.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2454.004 MHz : -9.246 dBm M2 : 2460.617 MHz : 11.935 dBm Delta1 : 15.992 MHz : 1.336 dB	Channel Power: 20.92 dBm Limit: 25.23 dBm Margin: -4.31 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.719 MHz : -6.722 dBm M2 : 2411.579 MHz : 13.501 dBm Delta1 : 20.561 MHz : 1.538 dB	Channel Power: 23.79 dBm Limit: 25.23 dBm Margin: -1.44 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2412.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.960 MHz : -5.673 dBm M2 : 2412.180 MHz : 14.518 dBm Delta1 : 20.321 MHz : 0.708 dB	Channel Power: 24.53 dBm Limit: 25.23 dBm Margin: -0.70 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2412.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.840 MHz : -7.115 dBm M2 : 2411.940 MHz : 14.073 dBm Delta1 : 20.561 MHz : 1.725 dB	Channel Power: 24.44 dBm Limit: 25.23 dBm Margin: -0.79 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.719 MHz : -7.182 dBm M2 : 2436.459 MHz : 13.330 dBm Delta1 : 20.681 MHz : 0.767 dB	Channel Power: 23.74 dBm Limit: 25.23 dBm Margin: -1.49 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2437.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.840 MHz : -6.806 dBm M2 : 2437.180 MHz : 14.193 dBm Delta1 : 20.441 MHz : 1.690 dB	Channel Power: 24.47 dBm Limit: 25.23 dBm Margin: -0.76 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2437.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.960 MHz : -6.273 dBm M2 : 2437.060 MHz : 13.837 dBm Delta1 : 20.561 MHz : 0.228 dB	Channel Power: 24.35 dBm Limit: 25.23 dBm Margin: -0.88 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.719 MHz : -7.526 dBm M2 : 2461.579 MHz : 13.568 dBm Delta1 : 20.681 MHz : 1.438 dB	Channel Power: 23.82 dBm Limit: 25.23 dBm Margin: -1.41 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2462.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.960 MHz : -5.655 dBm M2 : 2462.301 MHz : 14.427 dBm Delta1 : 20.321 MHz : 0.891 dB	Channel Power: 24.55 dBm Limit: 25.23 dBm Margin: -0.68 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11g, Channel: 2462.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.840 MHz : -7.357 dBm M2 : 2462.060 MHz : 13.936 dBm Delta1 : 20.561 MHz : 1.735 dB	Channel Power: 24.35 dBm Limit: 25.23 dBm Margin: -0.88 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.719 MHz : -6.924 dBm M2 : 2411.579 MHz : 13.265 dBm Delta1 : 20.561 MHz : 1.515 dB	Channel Power: 23.62 dBm Limit: 25.23 dBm Margin: -1.61 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.840 MHz : -6.781 dBm M2 : 2412.180 MHz : 14.390 dBm Delta1 : 20.441 MHz : 1.952 dB	Channel Power: 24.55 dBm Limit: 25.23 dBm Margin: -0.68 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.840 MHz : -7.099 dBm M2 : 2412.060 MHz : 13.747 dBm Delta1 : 20.561 MHz : 1.836 dB	Channel Power: 24.27 dBm Limit: 25.23 dBm Margin: -0.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.719 MHz : -7.300 dBm M2 : 2436.459 MHz : 13.265 dBm Delta1 : 20.681 MHz : 0.797 dB	Channel Power: 23.72 dBm Limit: 25.23 dBm Margin: -1.51 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.960 MHz : -5.571 dBm M2 : 2437.180 MHz : 14.463 dBm Delta1 : 20.321 MHz : 0.181 dB	Channel Power: 24.48 dBm Limit: 25.23 dBm Margin: -0.75 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2426.960 MHz : -6.039 dBm M2 : 2437.060 MHz : 13.989 dBm Delta1 : 20.441 MHz : 1.068 dB	Channel Power: 24.34 dBm Limit: 25.23 dBm Margin: -0.89 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.719 MHz : -7.349 dBm M2 : 2461.339 MHz : 13.495 dBm Delta1 : 20.561 MHz : 1.849 dB	Channel Power: 23.76 dBm Limit: 25.23 dBm Margin: -1.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.840 MHz : -7.015 dBm M2 : 2462.301 MHz : 14.063 dBm Delta1 : 20.441 MHz : 1.775 dB	Channel Power: 24.36 dBm Limit: 25.23 dBm Margin: -0.87 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2451.840 MHz : -7.229 dBm M2 : 2461.940 MHz : 13.662 dBm Delta1 : 20.561 MHz : 1.462 dB	Channel Power: 24.28 dBm Limit: 25.23 dBm Margin: -0.95 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2402.160 MHz : -9.433 dBm M2 : 2429.094 MHz : 10.981 dBm Delta1 : 39.920 MHz : 0.510 dB	Channel Power: 24.36 dBm Limit: 25.23 dBm Margin: -0.87 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2402.401 MHz : -7.477 dBm M2 : 2426.449 MHz : 12.572 dBm Delta1 : 39.439 MHz : 0.997 dB	Channel Power: 25.77 dBm Limit: 25.23 dBm Margin: 0.54 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2402.160 MHz : -9.021 dBm M2 : 2435.347 MHz : 11.996 dBm Delta1 : 39.679 MHz : 1.930 dB	Channel Power: 25.35 dBm Limit: 25.23 dBm Margin: 0.12 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2417.160 MHz : -9.458 dBm M2 : 2442.170 MHz : 11.038 dBm Delta1 : 39.920 MHz : 1.826 dB	Channel Power: 24.17 dBm Limit: 25.23 dBm Margin: -1.06 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2417.160 MHz : -10.214 dBm M2 : 2433.032 MHz : 11.974 dBm Delta1 : 39.679 MHz : 2.803 dB	Channel Power: 25.55 dBm Limit: 25.23 dBm Margin: 0.32 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2417.160 MHz : -8.801 dBm M2 : 2432.551 MHz : 11.734 dBm Delta1 : 39.679 MHz : 1.511 dB	Channel Power: 25.13 dBm Limit: 25.23 dBm Margin: -0.10 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2431.920 MHz : -11.605 dBm M2 : 2445.868 MHz : 11.018 dBm Delta1 : 39.920 MHz : 4.214 dB	Channel Power: 24.30 dBm Limit: 25.23 dBm Margin: -0.93 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2432.160 MHz : -8.870 dBm M2 : 2452.120 MHz : 12.102 dBm Delta1 : 39.679 MHz : 2.520 dB	Channel Power: 25.60 dBm Limit: 25.23 dBm Margin: 0.37 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2432.160 MHz : -10.011 dBm M2 : 2448.032 MHz : 11.856 dBm Delta1 : 39.679 MHz : 2.359 dB	Channel Power: 25.06 dBm Limit: 25.23 dBm Margin: -0.17 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5734.479 MHz : -7.306 dBm M2 : 5744.820 MHz : 12.706 dBm Delta1 : 21.162 MHz : 0.659 dB	Channel Power: 23.05 dBm Limit: 25.23 dBm Margin: -2.18 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5745.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5734.479 MHz : -6.704 dBm M2 : 5743.136 MHz : 14.408 dBm Delta1 : 21.042 MHz : 1.454 dB	Channel Power: 25.16 dBm Limit: 25.23 dBm Margin: -0.07 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5745.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5734.599 MHz : -6.743 dBm M2 : 5750.230 MHz : 13.334 dBm Delta1 : 20.922 MHz : 0.775 dB	Channel Power: 23.98 dBm Limit: 25.23 dBm Margin: -1.25 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5774.359 MHz : -8.443 dBm M2 : 5783.136 MHz : 12.747 dBm Delta1 : 21.283 MHz : 1.456 dB	Channel Power: 23.26 dBm Limit: 25.23 dBm Margin: -1.97 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5785.00 MHz, Chain b, Temp: Ambient, Voltage: 12 Vdc




Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5774.479 MHz : -6.584 dBm M2 : 5784.218 MHz : 14.471 dBm Delta1 : 20.922 MHz : 2.394 dB	Channel Power: 24.99 dBm Limit: 25.23 dBm Margin: -0.24 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5785.00 MHz, Chain c, Temp: Ambient, Voltage: 12 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5774.479 MHz : -6.629 dBm M2 : 5784.459 MHz : 13.818 dBm Delta1 : 21.042 MHz : 0.948 dB	Channel Power: 24.42 dBm Limit: 25.23 dBm Margin: -0.81 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.